

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 447 214 A8

(12)

CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 54,72

(51) Int Cl.7: **B32B 15/08**, H05K 1/03,
C08G 73/10

(48) Corrigendum issued on:

02.03.2005 Bulletin 2005/09

(86) International application number:

PCT/JP2002/011333

(43) Date of publication:

18.08.2004 Bulletin 2004/34

(87) International publication number:

WO 2003/037620 (08.05.2003 Gazette 2003/19)

(21) Application number: **02779957.6**

(22) Date of filing: **31.10.2002**

(84) Designated Contracting States:

BE DE ES LU

(30) Priority: **01.11.2001 JP 2001336053**

01.11.2001 JP 2001336062

04.06.2002 JP 2002162636

28.06.2002 JP 2002189252

26.07.2002 JP 2002218714

(71) Applicant: **Arakawa Chemical Industries, Ltd.**

Osaka-shi, Osaka 541-0046 (JP)

(72) Inventors:

- **GODA, Hideki,**
R & D Ctr. ARAKAWA Chem. Ind. Ltd.
Tsurumi-ku, Osaka-shi, Osaka 538 (JP)

- **FUJIWARA, Takayuki,**
R & D Ctr.ARAKAWA Chem.Ind.Ltd
Tsurumi-ku, Osaka-shi, Osaka 538 (JP)
- **TAKEUCHI, Takeshi,**
R & D Ctr.ARAKAWA Chem.Ind.Ltd.
Tsurumi-ku, Osaka-shi, Osaka 538 (JP)

(74) Representative: **Müller-Boré & Partner**

Patentanwälte

Grafinger Strasse 2

81671 München (DE)

(54) **POLYIMIDE-METAL LAYERED PRODUCTS AND POLYAMIDEIMIDE-METAL LAYERED PRODUCT**

(57) The present invention provides the following laminates:

(1) a polyimide-metal laminate which is obtainable by applying to one side of a metal foil a silane-modified polyimide resin composition (A) comprising alkoxy-containing silane-modified polyimide (a) and a polar solvent (b), drying and curing the composition;

(2) a polyamideimide-metal laminate which is obtainable by applying to one side of a metal foil a silane-modified polyamideimide resin composition

(C-1) comprising methoxy-containing silane-modified polyamideimide (d), a polar solvent (b) and an inorganic filler (c), drying and curing the composition; and

(3) a polyimide-metal laminate in which the cured film of the above composition (A) has a metal plated layer thereon.

EP 1 447 214 A8