

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 481 712 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

01.12.2004 Bulletin 2004/49

(51) Int Cl.7: **A63C 5/12**

(21) Application number: **03012021.6**

(22) Date of filing: **28.05.2003**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**

Designated Extension States:

AL LT LV MK

• **Cebocli, Aude**

73490 La Ravoire (FR)

• **Garcin, Pierre**

73410 Saint Ours (FR)

(71) Applicant: **IMS KUNSTSTOFF AG**

3076 Worb (CH)

(74) Representative: **Hepp, Dieter et al**

Hepp, Wenger & Ryffel AG,

Friedtalweg 5

9500 Wil (CH)

(72) Inventors:

• **Geissbühler, Urs**

3604 Thun (CH)

(54) **Running surface for a winter sports apparatus, winter sports apparatus comprising such running surface, material composition for production of such running surface, use of a material additive to such running surface and method of manufacture of such running surface**

(57) The invention concerns an improvement of gliding properties of running surfaces for winter sports apparatus, e.g. skis and snowboards. A running surface according to the invention contains a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof; especially preferred is an ultramarine as such mineral additive. Gliding prop-

erties are similar or improved in comparison to those obtainable with the addition of soot, carbon black or graphite. The mineral addition according to the invention can however be combined with the addition of soot, carbon black or graphite. The invention also opens up new possibilities in the coloration of running surfaces.

EP 1 481 712 A1

Description

[0001] The invention relates to a running surface for a winter sports apparatus, more precisely to the enhancement of the gliding properties of such a running surface.

[0002] Currently used running surfaces for winter sports apparatus, e.g. any types of skis (e.g. cross-country skis, alpine skis, telemark skis), snowboards, skiboards, sleds etc., in more general terms for any running surface intended for gliding on snow or ice are preferably made of hydrophobic plastics, e.g. polyethylene (PE). The mechanism of gliding of such running surfaces on snow and/or ice is yet not fully understood. However, it is believed that upon interaction of surface roughness and snow- or ice crystals a hydrodynamic lubricating effect upon melt water due to frictional heat is essentially involved.

[0003] At higher gliding speed, the locally formed melt water tends to spread all over the running surface, leading to an unwanted "suction effect" which may influence the gliding speed in a negative way. In order to overcome this phenomenon, additives such as soot, carbon black and graphite have been added to the polyethylene matrix (see e.g. CH 657 993 A and CH 660 018 A). These additives are supposed to diminish the "suction effect" due to their higher heat conductivity. The superior gliding properties of such modified running surfaces led to their preferential use today. However, these running surfaces are inevitably black due to the black color of soot, carbon black and graphite, thus hampering any alternative coloration of running surfaces. Moreover, there is a high need for further improved gliding properties of running surfaces, especially for sports competition purposes.

[0004] It is an object of the present invention to avoid the shortcomings of the known running surfaces and particularly to provide a running surface for winter sports apparatus with further improved gliding properties. It is an additional object of the invention, to provide a running surface for winter sports apparatus that allow for a non-black coloration. Such running surfaces need to be inexpensively and easy to produce and to apply. Moreover, the running surfaces have to meet the demands of high durability.

[0005] The above-mentioned objects are fulfilled by a running surface for a winter sports apparatus, a winter sports apparatus comprising such a running surface, a material composition for the production of such running surface and a method of manufacture such running surfaces according to the independent claims.

[0006] The invention concerns a running surface for a winter sports apparatus or the like, e.g. any types of skis (e.g. cross-country skis, alpine skis, telemark skis), snowboards, skiboards, sleds etc., in more general terms any types of running surfaces intended for gliding on snow or ice wherein the running surface contains a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof. Explicitly enclosed within the intention of the invention are also naturally and non-naturally occurring closely related structural and/or chemical analogues of these minerals, especially the derivatives obtainable by exchange of the cation(s) or anion(s). The nomenclature of these mineral additions is given according to the Strunz Classification System [Hugo Strunz; Ernest Nickel: Strunz Mineralogical Tables. Ninth Edition. 2001. ISBN 3-510-65188-X], where the sodalite group and tsaregorodtsevite-wadalite series is classified under VIII/J.11 (Tectosilicates). Typical members of this class are:

Tsaregorodtsevite, VIII/J. 11-05, $N(CH_3)_4[Si_2(Si_{0.5}Al_{0.5})O_6]_2$;
 Sodalite, VIII/J.11-10, $Na_4Al_3Si_3O_{12}Cl$;
 Nosean, VIII/J.11-20, $Na_8Al_6S_{16}O_{24}(SO_4)$;
 Hauyne, VIII/J.11-30, $(Na,Ca)_{4-8}[Al_6Si_6(O,S)_{24}](SO_4, Cl)_{1-2}$;
 Lazurite, VIII/J. 11-40, $(Na,Ca)_8(AlSiO_4)_6(S,SO_4,Cl)_{1-2}$;
 Tugtupite, VIII/J.11-50, $Na_4AlBeSi_4O_{12}Cl$;
 Kamaishilite, VIII/J.11-60, $Ca_2Al_2SiO_6(OH)_2$; and
 Bicchulite, VIII/J.11-70, $Ca_2Al_2SiO_6(OH)_2$.

[0007] It has now surprisingly been found that such a mineral addition further improves the gliding properties of running surfaces to a remarkable extent. In order to improve the gliding properties of running surfaces, soot, carbon black or graphite can be substituted with these mineral additions. Moreover, due to the color of these minerals, a non-black coloration of running surfaces is easily achievable. The running surfaces according to the invention are inexpensively and easy to produce, are easy to apply and fulfill the demands of durability. Of course, the running surface according to the invention may be used with or without a layer of wax for the purpose of gliding enhancement.

[0008] In a preferred embodiment, a running surface according to the invention is made of plastic, especially of polyethylene (PE). Preferentially, ultra high molecular weight (UHMW) polyethylene (PE) e.g. in the range of about 2×10^6 g/mol to about 12×10^6 g/mol of high density is used for this purpose and processed in a press-sintering process. However, the running surface according to the invention may also be produced by extrusion of high density polyethylene (PE) with a molecular weight in the range of about 2×10^5 g/mol to 8×10^5 g/mol. Of course, the invention is not limited to the use of a specific polymer matrix and can be carried out with any other preferably hydrophobic plastic material as well, that are useful for the production of such running surfaces.

[0009] In an especially preferred embodiment, the mineral addition contains an ultramarine; optionally, further especially mineral additions may be included in the running surface. Ultramarines such as the naturally occurring lazurite (Strunz ID: VIII/J. 11-40, the blue component of the gemstone lapis lazuli) are also known under the synonyms cyaneus, lasurite (of Brogger), Lasurstein, lazurite (of Dana), Sapphis (of Agricola). Beside their natural occurrence, ultramarines of the general formula $\text{Na}_4[\text{Al}_3\text{Si}_3\text{O}_{12}]\text{S}_3$ can be synthesized by fusing kaolin, sodium carbonate and sulfur, rendering them particularly useful for large-scale purposes for cost reasons. With ultramarines, especially advantageous gliding properties are obtainable, in some embodiments even exceeding the effect of soot, carbon black and graphite at comparable or less amounts to be added. Moreover, due to the strong coloration effect of ultramarines, new colorations of running surfaces are obtainable without a negative effect to the gliding properties. Besides a blue coloration (e.g. due to ultramarineblue, C.A.S. no. 57455-37-5), especially pink or violet (C.A.S. no. 12769-96-9) variations of ultramarines are of course also to be used in accordance with the invention in order to achieve more different colorations.

[0010] Most preferably, the mineral addition contains about 0.1% to about 40% by weight, preferably about 1% to about 30% by weight of an ultramarine. This range proved especially effective in enhancing the gliding properties without significantly altering stability, flexibility or other mechanical and/or physical properties of the running surface.

[0011] In accordance with yet another preferred embodiment of the invention, the running surface additionally contains soot and/or carbon black and/or graphite. Experimental results indicate that both these classes of additives can be synergistically incorporated into a running surface simultaneously, providing an especially advantageous influence on the gliding characteristic of the running surface.

[0012] According to an especially preferred embodiment of the invention, the running surface comprises about 75% to about 95% by weight, preferably about 85% by weight of polyethylene, 0% to about 20% by weight, preferably about 10% by weight of soot and/or carbon black and/or graphite and about 0.1% to about 40% by weight, preferably about 1% to about 30% by weight, most preferably about 5% by weight of a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a closely related structural and/or chemical analogue thereof, preferably an ultramarine. Compositions comprising these amounts of additives proved especially advantageous with respect to gliding properties, mechanical and handling properties and coloration.

[0013] A material composition for the production of a running surface comprises preferably polyethylene and a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a closely related structural and/or chemical analogue thereof, preferably an ultramarine. Optionally, soot, carbon black or graphite may be included. A material composition is here and henceforth to be understood including the still unprocessed mixture of crude materials as well as especially a press-sintered body produced from such mixture, from which a running surface can be peeled down.

[0014] Obviously, the use of a mineral chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof, especially an ultramarine as additive to a running surface of a winter sports apparatus is especially advantageous.

[0015] A running surface according to the invention can be produced in a sintering or extrusion process, comprising the step of adding a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof, especially an ultramarine.

[0016] The invention will now be exemplarily described by means of preferred embodiments; however, the invention is not to be limited to these embodiments.

Example 1 (for comparative purposes, state of the art)

[0017] A mixture of 15 parts by weight of carbon black (20nm particle size; oil necessity of 500%) and 85 parts by weight of the high density polyethylene Hostalen GUR 4170 (molecular weight $10,5 \times 10^6$ g/mol) is prepared in a mixing apparatus. The mixture is then press-sintered to a homogeneous cylindrical body according to standard procedures (e.g. such as those disclosed in the brochure of Hoechst, "Hostalen GUR" [HKR112-7089C12299/14]). After cooling down, the cylindrical body is peeled down to a band with the thickness of a running surface, e.g. 1,4 mm. The running surface is then roughened on one side and prepared for fixation on the ski body with an oxidizing flame. Of course, the running surface may also be prepared by an extrusion process. The general process of production is not essential to the invention, but rather the nature of the additive(s) to the running surface.

Example 2 (according to the invention)

[0018] Example 1 is repeated, but the composition of the starting mixture is altered to 100 parts by weight of the polyethylene component and 1 part by weight of ultramarine (C.A.S. no. 57455-37-5).

Example 3 (according to the invention)

[0019] Example 1 is repeated, but the composition of the starting mixture is altered to 85 parts by weight of the polyethylene component, 10 parts by weight of the carbon black component and 5 parts by weight of ultramarine (C. A.S. no. 57455-37-5).

Example 4 (according to the invention)

[0020] Example 1 is repeated, but the composition of the starting mixture is altered to 76 parts by weight of the polyethylene component, 4 parts by weight of the carbon black component and 20 parts by weight of ultramarine (C. A.S. no. 57455-37-5).

Measurements, physical properties

[0021] Running surfaces according to examples 1 to 4 were characterized by means of some of their physical characteristics (table 1). No outstanding differences were detected that might significantly contribute to a change of gliding properties.

Table 1:

physical characteristics of running surfaces according to examples 1 to 4.				
	Example 1	Example 2	Example 3	Example 4
density [g/cm ³]	1.002	0.948	1.011	1.062
min. melting point [°C]	139.7	141.0	139.3	140.0
melting enthalpy [J/g]	129	140	129	92

Gliding properties

[0022] Skis were prepared comprising running surfaces according to examples 1 to 4. For the gliding test purpose, skis were used that are built around a central core, comprising a supporting laminate structure on the top and bottom of the core, the gliding surface being fixed between lateral running edges. However, the running surface according to the invention may of course be used with any type of winter sports apparatus intended for gliding on snow or ice. Beside the different running surfaces, the skis were constructed equivalently. Skis comprising running surfaces according to the invention (examples 2 to 4) exhibited comparable or improved gliding properties in comparison to the ski comprising a running surface according to the prior art (example 1).

Claims

1. Running surface for a winter sports apparatus, wherein the running surface contains a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof.
2. Running surface according to claim 1, wherein the running surface is made of plastic, especially of polyethylene (PE).
3. Running surface according to claims 1 or 2, wherein the mineral addition contains an ultramarine.
4. Running surface according to one of claims 1 to 3, wherein the mineral addition contains about 0.1% to about 40% by weight, preferably about 1% to about 30% by weight of an ultramarine.
5. Running surface according to one of claims 1 to 4, wherein the running surface additionally contains soot and/or carbon black and/or graphite.

6. Running surface according to claim 5,
wherein the running surface comprises about 75% to about 95% by weight, preferably about 85% by weight of polyethylene, 0% to about 20% by weight, preferably about 10% by weight of soot and/or carbon black and/or graphite and about 0.1% to about 40% by weight, preferably about 1% to about 30% by weight, most preferably about 5% by weight of a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a closely related structural and/or chemical analogue thereof, preferably an ultramarine.
7. Winter sports apparatus, comprising a running surface according to one of claims 1 to 6.
8. Material composition for the production of a running surface according to one of claims 1 to 6, comprising polyethylene and a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a closely related structural and/or chemical analogue thereof, preferably an ultramarine.
9. Use of a mineral chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof, especially an ultramarine as additive to a running surface of a winter sports apparatus.
10. Method of manufacture of a running surface for a winter sports apparatus in a sintering or extrusion process, comprising the step of adding a mineral addition chosen from the sodalite group and tsaregorodtsevite-wadalite series or a mixture thereof, especially an ultramarine.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 01 2021

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	CH 657 993 A (IMS KUNSTSTOFF AG) 15 October 1986 (1986-10-15) * claims 1-5 *	1-10	A63C5/12
A	FR 2 719 050 A (PLASTINORD) 27 October 1995 (1995-10-27) * claim 1 *	1,9,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A63C
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
MUNICH		2 October 2003	Murer, M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 01 2021

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02-10-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
CH 657993	A	15-10-1986	CH	657993 A5	15-10-1986
FR 2719050	A	27-10-1995	FR	2719050 A1	27-10-1995