



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**12.01.2005 Bulletin 2005/02**

(51) Int Cl.7: **C11D 17/00**, C11D 3/20,  
C11D 1/722

(21) Application number: **04076634.7**

(22) Date of filing: **04.06.2004**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**  
Designated Extension States:  
**AL HR LT LV MK**

(72) Inventors:  
• **Van der Kooij, Felix Marco**  
**3133 AT Vlaardingen (NL)**  
• **Van de Pas, Johannes Cornelis**  
**3133 AT Vlaardingen (NL)**

(30) Priority: **10.07.2003 EP 03077186**

(74) Representative:  
**Rosen Jacobson, Frans Lucas M. et al**  
**Unilever N.V.**  
**Unilever Intellectual Property Group**  
**Olivier van Noortlaan 120**  
**3133 AT Vlaardingen (NL)**

(71) Applicants:  
• **UNILEVER N.V.**  
**3013 AL Rotterdam (NL)**  
Designated Contracting States:  
**AT BE BG CH CZ DE DK EE ES FI FR GR HU IT  
NL PL PT SE SI SK TR**  
• **UNILEVER PLC**  
**London EC4P 4BQ (GB)**  
Designated Contracting States:  
**CY GB IE**

(54) **Detergent compositions**

(57) A cleaning tablet which has a plurality of discrete regions with differing compositions, characterised in that at least one first region of the tablet comprises:

- (a) at least 50 wt% (based on the weight of said region) of nonionic surfactants;
- (b) from 1 to 20 wt% (based on the weight of said region) of structurant materials comprising soap; and
- (c) from 1 to 30 wt% (based on the weight of said

region) of diluent materials,

wherein said first region comprises more than 60 wt% of surfactants (based on the weight of said region).

**Description****Field of the invention**

5 [0001] This invention relates to cleaning compositions in the form of tablets for use in fabric washing or machine dishwashing.

**Background of the invention**

10 [0002] Detergent compositions in tablet form have advantages over powdered products in that they do not require measuring and are thus easier to handle and dispense into the wash load.

[0003] Tablets of a cleaning composition are generally made by compressing or compacting a quantity of the composition in particulate form.

15 [0004] Tablets comprising two or more separate regions have also been described. For example WO 01/42416 describes the production of multi-phase moulded bodies comprising a combination of core moulded bodies and a particulate premix. WO 00/61717 describes a detergent tablet which is characterised in that at least part of its outer surface is semi-solid. WO 00/04129 describes a multi-phase detergent tablet comprising a first phase in the form of a shaped body having at least one mould therein and a second phase in the form of a particulate solid compressed within said mould. WO 99/24549 describes a detergent tablet comprising a compressed solid body and a non-compressed gelatinous portion mounted in a mould of said body.

20 [0005] There have been a number of proposals for tablets which are subdivided into separate regions (e.g. layers) which differ in their composition.

[0006] WO 99/35225 relates to moulded bodies with two solid phases wherein one phase of no more than 40 vol% of the moulded body contains more than 80wt% of the total of an active substance contained in the moulded body with an ingredient from the group of surfactants.

25 [0007] The object of the present invention is to provide a multi-phase cleaning tablet, whereby at least one of the phases comprises a high level of nonionic surfactants and whereby said tablet can easily be prepared at relatively low costs and said tablet has good form retention and good dispersing and cleaning properties.

**Summary of invention**

30 [0008] According to the present invention there is provided a cleaning tablet which has a plurality of discrete regions with differing compositions, characterised in that at least one first region of the tablet comprises:

- 35 (a) At least 50 wt% (based on the weight of said region) of nonionic surfactants;  
 (b) from 1 to 20 wt% (based on the weight of said region) of structurant materials comprising soap; and  
 (c) from 1 to 30 wt% (based on the weight of said region) of diluent materials;

wherein said first region comprises more than 60 wt% of surfactants (based on the weight of said region).

40 [0009] Preferably said first region is either substantially free from non-soap anionic surfactant materials or comprises nonionic surfactants and non-soap anionic surfactant materials in a weight ratio of more than 10:1.

[0010] The regions of the tablet are preferably separate layers within a tablet, whereby each layer has substantially the same diameter and said layers are stacked to form a substantially cylindrical cleaning tablet. Preferably the first region has a weight of from 2 to 30 grammes, more preferred from 3 to 20 grammes. Preferably the remaining regions together have a weight of 10 to 50 grammes, more preferred 15 to 30 grammes.

**Detailed description of the invention****Composition of the cleaning tablet**

50 [0011] The first region of the tablet is comprises high levels of nonionic surfactants. Generally such high levels of nonionic surfactants tend to lead to the formation of a smooth region. Such smooth regions are preferred embodiments of the first region of the tablet. For the purpose of this invention the term smooth phase refers to compositions which are on the one hand solid enough to retain their shape at ambient temperature and on the other hand smooth in appearance. Smooth textures are generally of low or no porosity and have -at normal viewing distance- the appearance of a continuous phase for example as opposed to porous and particulate appearance of a compacted particulate material.

55 [0012] WO99/24549 describes the use of non-compressed gelatinous portions mounted in a mold as a smooth phase.

These tablets must be made with specific equipment to ensure the appropriate mold formation. Furthermore the compositions for the smooth phase as disclosed in this document contain very high levels of ingredients with a limited functionality in the wash such as dipropylene glycolbutylether or glyceroltriacetate.

**[0013]** WO 00/61717 describes (in the example) the preparation of a compressed particulate tablet on top of which a (non-compressed) layer was made by pouring a mixture of nonionic and PEG followed by hardening. This formulation and its method of preparation is disadvantageous because it requires a very long hardening step in the tablet mould, during which the tablet mould cannot be used for further production, therewith significantly increasing the cost of production.

**[0014]** Preferably the first region of the tablets is a smooth region and also a semi-solid region. For the purpose of this invention the term smooth region can refer to a phase which is smooth or - preferably- smooth and semi-solid. For the purpose of this invention the term semi-solid refers to compositions which are one the one hand solid enough to retain their shape at ambient temperature but which are neither completely solid.

**[0015]** A suitable test to check if a composition can be considered as semi-solid can be described with reference to the accompanying drawings which diagrammatically illustrate the testing of a cylindrical tablet:

**[0016]** A cylindrical tablet with a diameter of 45 mm and a height of 20 mm is compressed radially between the plates of a material testing machine until the tablet fractures. At the starting position, the plates contact the tablet but do not apply force to it. Force is applied, to compress the tablet, the vertical speed of the upper plate is 25 mm/minute. The testing machine measures the applied force (F), and also the displacement (x) of the plates towards each other as the tablet is compressed. The distance (y) between the plates before force is applied, which is the diameter of the tablet, is also known. At failure, the tablet cracks and the applied force needed to maintain the displacement drops. Measurement is discontinued when the applied force needed to maintain the displacement has dropped by 25% from its maximum value. The displacement at failure ( $x_f$ ) is also measured.

**[0017]** A graph of force (F) against displacement (x) is made. The maximum force is the force at failure ( $F_f$ ). The break energy is the area under the graph of force against displacement, up to the point of break. It is given by the equation:

$$E_b = \int_0^{x_f} F(x) dx$$

wherein  $E_b$  is the break energy in mJoules, x is the displacement in metres and F is the applied force in Newtons at displacement x and  $x_f$  is the displacement at failure.

**[0018]** Semi-solid compositions are characterised by a ratio of  $F_f$  to  $E_b$  of less than 1.0, more preferred from 0.1 to 0.9, most preferred from 0.2 to 0.6, while traditional tablets of compacted particulate materials are generally characterised by a ratio of  $F_f$  to  $E_b$  of more than 1, more generally more than 1.25 or even more than 1.5 up to say 6.

**[0019]** The first region is predominantly constituted by surfactants and comprises more than 60 wt%, preferably from 70 to 90 wt%, thereof. It has been found these high surfactant levels provide very good dispersing and cleaning properties to the tablet.

**[0020]** Preferably, the surfactants in the first region are either substantially free from non-soap anionic surfactants or comprise a combination of nonionic surfactants and non-soap anionic surfactants in a weight ratio of more than 10:1, more preferably from 11:1 to 50:1, most preferred from 12:1 to 30:1. Further surfactants, for example cationic surfactants may equally be present for example at a level of 0.1 to 10 wt% based on the weight of the first region. For the purpose of the present invention, soap is defined to mean a structurant material.

**[0021]** The first region also advantageously comprises 1 to 30 wt% of diluent materials, more preferred from 2 to 28 wt%, most preferred from 4 to 26 wt% based on the weight of the first region. Examples of suitable diluent materials include alcohols, ethers, polyethers, polyols, alkylamines, alkanol amines and fatty amines, alkyl (or fatty) amides and mono- and di- N-alkyl substituted derivatives thereof, alkyl (or fatty) carboxylic acid lower alkyl esters, ketones, aldehydes, and glycerides. Preferred diluent materials are selected from the group consisting of pentanediols, butanediols, propanediols, such as 1,3-propane diol, alkanol amines, di-alkyl ethers, polyethylene glycols, alkyl ketones (such as acetone) and glyceryl trialkylcarboxylates (such as glyceryl tri-acetate), glycerol, and sorbitol. Even more preferred are liquid diluent materials in particular butanediols, propanediols such as propylene glycol, and polyethylene glycols for example dipropylene glycol.

**[0022]** The first region also advantageously comprises from 1 to 20 wt% of structurant materials comprising soap, more preferably from 1 to 18 wt%, most preferred from 4 to 16 wt% based on the weight of the first region. These structuring materials are present for structuring said first region. Apart from soap, examples of suitable structurant

materials are low molecular organic substances having a molecular weight of less than 500.

**[0023]** Suitable organic materials are for example composed of combinations of one or more of O-H-C-N atoms; optionally the organic materials are organic salts with one or more cations. Preferably the organic material is water-soluble (e.g. having a solubility of more than 10 g/l, more preferred more than 100 g/l at 20°C). Also preferably the organic material is solid at ambient temperature. Especially preferably the organic material is meltable e.g. having a melting point of less than 100°C.

**[0024]** The organic material can for example be selected from the group of sugars for example glucose, fructose, lactose etc and citrates, more preferably the organic material has a molecular weight from 50 to 150, most preferably the organic material is selected from the group of urea, lactates and acetates or combinations thereof. Most preferred is the use of urea or acetates. Suitably water-soluble acetates will be used for example sodium acetate or potassium acetate. For the purpose of the invention molecular weight of materials is calculated excluding any crystal water that may be present.

**[0025]** The first region preferably comprises no or only low levels of water. Preferably the level of water is less than 20 wt % based on the weight of the semi-solid phase, more preferred less than 15 wt%, most preferred from 5 to 12 wt%. In most cases, the semi-solid phases are substantially free from water, which means that apart from low levels of moisture (e.g. for neutralisation or as crystal water) no additional added water is present. However, sometimes it may be preferable to add a small quantity of water to the surfactant rich material during manufacture.

**[0026]** Preferably the total weight of surfactants in the first region is from 2 to 20 grammes, more preferred from 3 to 10 grammes.

**[0027]** In a preferred embodiment of the invention the second region comprises no or only low levels of surfactants. Preferably the level of surfactants in the second region is less than 10 wt%(based on the total weight of the second region), more preferred from 0 to 9 wt%, most preferred from 1 to 8 wt%.

**[0028]** The second region of the tablet is preferably a solid region, for example this can be prepared by compression or melting. Preferably the second region is a compacted particulate composition.

**[0029]** The second region preferably comprises ingredients of the tablet other than surfactants. Examples of these ingredients are builders, bleach system, enzymes etc. Preferably the builders in the tablet are predominantly present in the second region. Preferably the bleach system is predominantly present in the second region. Preferably the enzymes are predominantly present in the second region. For the purpose of this invention the term "predominantly present" refers to a situation wherein at least 90 wt% of an ingredient is present in the second region, more preferred more than 98 wt%, most preferred substantially 100 wt%.

**[0030]** The above description of the tablet has been given with reference to a tablet constituted by two regions. It will however be understood that each of the regions may be composed of a limited number of discrete regions. For example the first region may be a single discrete part of the tablet but may also be a limited number (say 1-5) discrete parts. Preferably each of these parts are at least 1 gramme, also preferably each of these parts is substantially of the same composition. If reference is made to the composition or weight of the first region it is understood that this concerns the total weight and composition of these parts.

**[0031]** Similarly the solid second region may be composed of a limited number (say 1-5) of solid parts e.g. separate layers in the tablet. Preferably each of these parts has a weight of at least 10 grammes, also preferably each of the solid parts are substantially of the same composition. If reference is made to the composition or weight of the second region it is understood that this concerns the total weight and composition of these solid parts.

**[0032]** In addition to the first region and the solid second region the cleaning tablets of the invention may optionally comprise further regions, for example the tablet may be partly or wholly coated.

**[0033]** Cleaning tablets according to the invention are preferably manufactured by a process comprising the steps of

- (a) compression of particulate composition to form a pre-compressed tablet forming the second region
- (b) production of a surfactant rich tablet, preferably by casting or extrusion of a surfactant rich (for example a molten) material to form the first region
- (c) assembling the final tablet by combining the first region and the second region, preferably under the application of a mild co-compression force.

**[0034]** Preferably the pressure for preparing the pre-compressed tablet is from 0.1 to 20 kN/cm<sup>2</sup>. Preferably the pressure for preparing the smooth tablet is preferably from 0 to 5 kN/cm<sup>2</sup>, more preferred 0.01 to 5 kN/cm<sup>2</sup>.

**[0035]** One advantage of the preferred methods of the present invention is that the co-compression step of (c) leads to good adherence of the first region to the second region and may avoid the need of applying an adhesive material between the surfactant rich and solid region. Another advantage of the method of the invention is that it can be carried out in a normal tablet press without the need of adaptation of the shape of the pressing surfaces.

**[0036]** A tablet of this invention may be intended for use in machine dishwashing. Such a tablet is likely to contain surfactant in a low concentration such as 0.5 to 2 wt% based on the whole tablet, although higher concentrations

ranging up to 10 wt% may be used. Such will typically contain salts, such as over 60 wt%, often over 85 wt% of the tablet.

**[0037]** Water soluble salts typically used in machine dishwashing compositions are phosphates (including condensed phosphates) carbonates and silicates, generally as alkali metal salts. Water soluble alkali metal salts selected from phosphates, carbonates and silicates may provide 60 wt% or more of a dishwashing composition.

**[0038]** Another preferred possibility is that a tablet of this invention will be intended for fabric washing. In this event the tablet will be likely to contain at least 2 wt%, probably at least 5 wt%, up to 40 or 50 wt% surfactant based on the whole tablet, and from 5 to 80 wt% detergency builder, based on the whole tablet.


**[0039]** Materials which may be used in tablets of this invention will now be discussed in more detail.

#### Surfactant Compounds


**[0040]** Compositions which are used in tablets of the invention will contain one or more detergent surfactants. In a fabric washing composition, these preferably provide from 5 to 50% by weight of the overall tablet composition, more preferably from 5 to 40% by weight of the overall composition. Surfactant may be anionic, cationic, zwitterionic, amphoteric, nonionic or a combination of these.

**[0041]** Synthetic (i.e. non-soap) anionic surfactants are well known to those skilled in the art. Examples include alkylbenzene sulphonates, particularly sodium linear alkylbenzene sulphonates having an alkyl chain length of C<sub>8</sub>-C<sub>15</sub>; olefin sulphonates; alkane sulphonates; dialkyl sulphosuccinates; and fatty acid ester sulphonates.

**[0042]** Primary alkyl sulphate having the formula



in which R is an alkyl or alkenyl chain of 8 to 18 carbon atoms especially 10 to 14 carbon atoms and M<sup>+</sup> is a solubilising cation, is commercially significant as an anionic surfactant.



**[0043]** Linear alkyl benzene sulphonate of the formula

where R is linear alkyl of 8 to 15 carbon atoms and M<sup>+</sup> is a solubilising cation, especially sodium, is also a commercially significant anionic surfactant.

**[0044]** Frequently, such linear alkyl benzene sulphonate or primary alkyl sulphate of the formula above, or a mixture thereof will be the desired anionic surfactant and may provide 75 to 100 wt% of any anionic non-soap surfactant in the composition.

**[0045]** Suitable nonionic surfactant compounds which may be used include in particular the reaction products of compounds having a hydrophobic group and a reactive hydrogen atom, for example, aliphatic alcohols, acids, amides or alkyl phenols with alkylene oxides, especially ethylene oxide.

**[0046]** Specific nonionic surfactant compounds are alkyl (C<sub>8-22</sub>) phenol-ethylene oxide condensates, the condensation products of linear or branched aliphatic C<sub>8-20</sub> primary or secondary alcohols with ethylene oxide, and products made by condensation of ethylene oxide with the reaction products of propylene oxide and ethylene-diamine.

**[0047]** Especially preferred are the primary and secondary alcohol ethoxylates, especially the C<sub>9-11</sub> and C<sub>12-15</sub> primary and secondary alcohols ethoxylated with an average of from 5 to 20 moles of ethylene oxide per mole of alcohol.

**[0048]** In some fabric washing tablets of this invention, the amount of nonionic surfactant lies in a range from 4 to 40%, better 4 or 5 to 30% by weight of the whole tablet.

**[0049]** Many nonionic surfactants are liquids. These may be absorbed onto particles of the composition.


#### Detergency Builder

**[0050]** A composition which is used in tablets of the invention will contain from 5 to 80%, more usually 15 to 60% by weight of detergency builder. This may be provided wholly by water soluble materials, or may be provided in large part or even entirely by water-insoluble material with water-softening properties. Water-insoluble detergency builder may be present as 5 to 80 wt%, better 5 to 60 wt% of the composition.

**[0051]** Alkali metal aluminosilicates are strongly favoured as environmentally acceptable water-insoluble builders for

## EP 1 496 106 A1

fabric washing. Alkali metal (preferably sodium) aluminosilicates may be either crystalline or amorphous or mixtures thereof, having the general formula:



[0052] These materials contain some bound water (indicated as "xH<sub>2</sub>O") and are required to have a calcium ion exchange capacity of at least 50 mg CaO/g. The preferred sodium aluminosilicates contain 1.5-3.5 SiO<sub>2</sub> units (in the formula above). Both the amorphous and the crystalline materials can be prepared readily by reaction between sodium silicate and sodium aluminate, as amply described in the literature.

[0053] Suitable crystalline sodium aluminosilicate ion-exchange detergency builders are described, for example, in GB 1429143 (Procter & Gamble). The preferred sodium aluminosilicates of this type are the well known commercially available zeolites A and X, the novel zeolite P described and claimed in EP 384070 (Unilever) and mixtures thereof.

[0054] Conceivably a water-insoluble detergency builder could be a layered sodium silicate as described in US 4664839.

NaSKS-6 is the trademark for a crystalline layered silicate marketed by Hoechst (commonly abbreviated as "SKS-6"). NaSKS-6 has the delta-Na<sub>2</sub>SiO<sub>5</sub> morphology form of layered silicate. It can be prepared by methods such as described in DE-A-3,417,649 and DE-A-3,742,043. Other such layered silicates, such as those having the general formula NaMSi<sub>x</sub>O<sub>2x+1</sub>·yH<sub>2</sub>O wherein M is sodium or hydrogen, x is a number from 1.9 to 4, preferably 2, and y is a number from 0 to 20, preferably 0 can be used.

[0055] Water-soluble phosphorous-containing inorganic detergency builders, include the alkali-metal orthophosphates, metaphosphates, pyrophosphates and polyphosphates. Specific examples of inorganic phosphate builders include sodium and potassium tripolyphosphates, orthophosphates and hexametaphosphates.

[0056] Non-phosphorous water-soluble builders may be organic or inorganic. Inorganic builders that may be present include alkali metal (generally sodium) carbonate; while organic builders include polycarboxylate polymers, such as polyacrylates, acrylic/maleic copolymers, and acrylic phosphonates, monomeric polycarboxylates such as citrates, gluconates, oxydisuccinates, glycerol mono- di- and trisuccinates, carboxymethyloxysuccinates, carboxymethyloxymalonates, dipicolinates and hydroxyethyliminodiacetates.

[0057] At least one region (preferably the second region) of a fabric washing tablet preferably include polycarboxylate polymers, more especially polyacrylates and acrylic/maleic copolymers which can function as builders and also inhibit unwanted deposition onto fabric from the wash liquor.

### Bleach System

[0058] Tablets according to the invention may contain a bleach system in at least one region of a tablet, preferably in the second region. This preferably comprises one or more peroxy bleach compounds, for example, inorganic persalts or organic peroxyacids, which may be employed in conjunction with activators to improve bleaching action at low wash temperatures. If any peroxygen compound is present, the amount is likely to lie in a range from 10 to 25% by weight of the composition.

[0059] Preferred inorganic persalts are sodium perborate monohydrate and tetrahydrate, and sodium percarbonate, advantageously employed together with an activator. Bleach activators, also referred to as bleach precursors, have been widely disclosed in the art. Preferred examples include peracetic acid precursors, for example, tetraacetylethylene diamine (TAED), now in widespread commercial use in conjunction with sodium perborate; and perbenzoic acid precursors. The quaternary ammonium and phosphonium bleach activators disclosed in US 4751015 and US 4818426 (Lever Brothers Company) are also of interest. Another type of bleach activator which may be used, but which is not a bleach precursor, is a transition metal catalyst as disclosed in EP-A-458397, EP-A-458398 and EP-A-549272. A bleach system may also include a bleach stabiliser (heavy metal sequestrant) such as ethylenediamine tetramethylene phosphonate and diethylenetriamine pentamethylene phosphonate.

[0060] As indicated above, if a bleach is present and is a water-soluble inorganic peroxygen bleach, the amount may well be from 10% to 25% by weight of the composition.

### Other Detergent Ingredients

[0061] The detergent tablets of the invention may also contain (preferably in the second region) one of the detergency enzymes well known in the art for their ability to degrade and aid in the removal of various soils and stains. Suitable enzymes include the various proteases, cellulases, lipases, amylases, and mixtures thereof, which are designed to remove a variety of soils and stains from fabrics. Examples of suitable proteases are Maxatase (Trade Mark), as supplied by Gist-Brocades N.V., Delft, Holland, and Alcalase (Trade Mark), and Savinase (Trade Mark), as supplied

by Novo Industri A/S, Copenhagen, Denmark. Detergency enzymes are commonly employed in the form of granules or marumes, optionally with a protective coating, in amount of from about 0.1% to about 3.0% by weight of the composition; and these granules or marumes present no problems with respect to compaction to form a tablet.

**[0062]** The detergent tablets of the invention may also contain (preferably in the second region) a fluorescer (optical brightener), for example, Tinopal (Trade Mark) DMS or Tinopal CBS available from Ciba-Geigy AG, Basel, Switzerland. Tinopal DMS is disodium 4,4'-bis-(2-morpholino-4-anilino-s-triazin-6-ylamino) stilbene disulphonate; and Tinopal CBS is disodium 2,2'-bis-(phenyl-styryl) disulphonate.

**[0063]** An antifoam material is advantageously included (preferably in the second region), especially if a detergent tablet is primarily intended for use in front-loading drum-type automatic washing machines. Suitable antifoam materials are usually in granular form, such as those described in EP 266863A (Unilever). Such antifoam granules typically comprise a mixture of silicone oil, petroleum jelly, hydrophobic silica and alkyl phosphate as antifoam active material, absorbed onto a porous absorbed water-soluble carbonate-based inorganic carrier material. Antifoam granules may be present in an amount up to 5% by weight of the composition.

**[0064]** It may also be desirable that a detergent tablet of the invention includes an amount of an alkali metal silicate, particularly sodium ortho-, meta- or disilicate. The presence of such alkali metal silicates at levels, for example, of 0.1 to 10 wt%, may be advantageous in providing protection against the corrosion of metal parts in washing machines, besides providing some measure of building and giving processing benefits in manufacture of the particulate material which is compacted into tablets.

**[0065]** A tablet for fabric washing will generally not contain more than 15 wt% silicate. A tablet for machine dishwashing will often contain more than 20 wt% silicate. Preferably the silicate is present in the second region of the tablet.

**[0066]** Further ingredients which can optionally be employed in a region of a fabric washing detergent of the invention tablet (preferably the second region) include anti-redeposition agents such as sodium carboxymethylcellulose, straight-chain polyvinyl pyrrolidone and the cellulose ethers such as methyl cellulose and ethyl hydroxyethyl cellulose, fabric-softening agents; heavy metal sequestrants such as EDTA; perfumes; and colorants or coloured speckles.

**[0067]** Further ingredients which can optionally be used in tablets of the invention, preferably in the second region are dispersing aids. Examples of suitable dispersing aids are water-swelling polymers, highly soluble materials (e.g. sodium citrate, potassium carbonate or sodium acetate) or sodium tripolyphosphate with preferably at least 40% of the anhydrous phase I form.

### Particle Size and Distribution

**[0068]** The second region of a detergent tablet of this invention, is a preferably a matrix of compacted particles.

**[0069]** Preferably the particulate composition has an average particle size in the range from 200 to 2000  $\mu\text{m}$ , more preferably from 250 to 1400  $\mu\text{m}$ . Fine particles, smaller than 180  $\mu\text{m}$  or 200  $\mu\text{m}$  may be eliminated by sieving before tableting, if desired, although we have observed that this is not always essential.

**[0070]** While the starting particulate composition may in principle have any bulk density, the present invention is especially relevant to tablets made by compacting powders of relatively high bulk density, because of their greater tendency to exhibit disintegration and dispersion problems. Such tablets have the advantage that, as compared with a tablet derived from a low bulk density powder, a given dose of composition can be presented as a smaller tablet.

**[0071]** Thus the starting particulate composition may suitably have a bulk density of at least 400 g/litre, preferably at least 500 g/litre, and perhaps at least 600 g/litre.

**[0072]** Tableting machinery able to carry out the manufacture of tablets of the invention is known, for example suitable tablet presses are available from Fette and from Korch.

**[0073]** Tableting may be carried out at ambient temperature or at a temperature above ambient which may allow adequate strength to be achieved with less applied pressure during compaction. In order to carry out the tableting at a temperature which is above ambient, the particulate composition is preferably supplied to the tableting machinery at an elevated temperature. This will of course supply heat to the tableting machinery, but the machinery may be heated in some other way also.

**[0074]** The size of a tablet will suitably range from 10 to 160 grams, preferably from 15 to 60 g, depending on the conditions of intended use, and whether it represents a dose for an average load in a fabric washing or dishwashing machine or a fractional part of such a dose. The tablets may be of any shape. However, for ease of packaging they are preferably blocks of substantially uniform cross-section, such as cylinders or cuboids. The overall density of a tablet preferably lies in a range from 1040 or 1050 gm/litre up to 1600 gm/litre.

**[0075]** The invention is illustrated by the following non-limiting examples.

### Example 1

**[0076]** A detergent powder was made of the following composition by pregranulating the granule ingredients, followed

EP 1 496 106 A1

by post-dosing the rest of the ingredients.

5  
10  
15  
20  
25

<i>Ingredient</i>	<i>Parts by weight</i>
<b>granules</b>	
Linear alkyl benzene sulphonate, sodium salt	1.1
Alcohol ethoxylate nonionic, 7EO	0.5
Soap (C16-C18)	0.1
Zeolite A24	2.4
Sodium acetate	0.3
Sodium carbonate	0.4
Sodiumcarboxymethyl cellulose,	0.1
Moisture/minors	0.4
<b>Post-dose</b>	
Antifoam adjunct	3.0
Fluorescent whitening agent adjunct	2.2
Sodium tripolyphosphate	62.3
Na silicate	3.8
Tetraacetyldiethylenediamine TAED)	4.3
Sodium percarbonate	16.9
Phosphonate sequestrant	1.9
Minors/enzymes/colour	to 100

[0077] Smooth parts were prepared having the following compositions:

30  
35  
40

	<i>Composition A</i>	<i>Composition B</i>	<i>Composition C</i>	<i>Composition D</i>
<i>Ingredient</i>	<i>% by weight</i>	<i>% by weight</i>	<i>% by weight</i>	<i>% by weight</i>
Alcohol ethoxylate nonionic, 7EO	72	70	82.5	62
Lauryldimethylhydroxy-Ethylammonium chloride	-	-	-	10
Sodium soap (C12)	-	-	7.3	-
Sodium soap (C16-C18)	8.5	8.5	-	8.5
propylene glycol	18	17.5	10.2	18
Water*	balance	balance	balance	balance

\*Water in the composition may result from the raw materials, from reaction water, or small amounts of water may be added during manufacture.

[0078] The mixture was heated to 80°C and cast into moulds and cooled to 20°C to form firm, 5 grammes smooth and semi-solid parts of 45mm diameter and 6mm high.

[0079] The tablets were made as follows:

45

[0080] 25 grammes of the powder were inserted into a 45 mm die of a tableting machine. The tableting machine had a flat upper punch which was used for pre-compressing tablets. Each of the above-described surfactant-rich smooth parts was then applied onto the pre-compressed tablets by gently pressing, thus forming two-layer tablets. The thus-formed two-layer tablets were found to show good form retention as well as good cleaning properties.

**Comparative example A**

50  
55

[0081] A detergent powder was made having the same composition as that of example 1, by pre-granulating the granule ingredients, followed by post-dosing the rest of the ingredients. Subsequently, a smooth part was prepared having the following composition:

	<i>% by weight</i>
7EO Alcohol ethoxylate	80



(continued)

	% by weight
Polyethylene glycol (PEG4000)	20

5

**[0082]** This mixture was heated to 80°C and cast into a mould and cooled to 20°C to form a smooth and semi-solid part of 45 mm diameter and 6 mm high and having a weight of 5 grammes.

10

**[0083]** Using this semi-solid part a two-layer tablet was made by applying the same procedure as that of example 1. The semi-solid phase of the resulting tablet was found to be fragile and susceptible to breakage. As a consequence, the form retention of the resulting tablet was found to be poor.

### Claims

15

1. A cleaning tablet which has a plurality of discrete regions with differing compositions, **characterised in that** at least one first region of the tablet comprises:

20

- (a) at least 50 wt% (based on the weight of said region) of nonionic surfactants;
- (b) from 1 to 20 wt% (based on the weight of said region) of structurant materials comprising soap; and
- (c) from 1 to 30 wt% (based on the weight of said region) of diluent materials,

wherein said first region comprises more than 60 wt % of surfactants (based on the weight of said region).

25

2. A cleaning tablet according to claim 1, wherein said first region comprises from 70 to 90 wt% of surfactants.

3. A cleaning tablet according to claim 1 or claim 2, wherein said first region is either substantially free from non-soap anionic surfactant materials or comprises nonionic surfactants and non-soap anionic surfactant materials in a weight ratio of more than 10:1.

30

4. A cleaning tablet according to claim 1, wherein the first region is a smooth region.

5. A cleaning tablet according to claim 1 or claim 2, comprising a second region of compacted particulate material.

35

40

45

50

55



European Patent  
Office

EUROPEAN SEARCH REPORT

Application Number  
EP 04 07 6634

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	DE 199 57 504 A (HENKEL KGAA) 1 March 2001 (2001-03-01) * examples *	1-5	C11D17/00 C11D3/20 C11D1/722
X,D	WO 00/61717 A (PROCTER & GAMBLE (US)) 19 October 2000 (2000-10-19) * examples *	1-5	
A	DE 100 48 058 A (HENKEL KGAA) 18 April 2002 (2002-04-18) * claims *	1-5	
A	WO 01/49815 A (RECKITT BENCKISER N.V.) 12 July 2001 (2001-07-12) * examples *	1-5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			C11D
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
Munich		18 October 2004	Miller, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 04 07 6634

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19957504	A	01-03-2001	DE 19957504 A1	01-03-2001
			AU 7648000 A	26-03-2001
			CA 2317182 A1	28-02-2001
			WO 0116283 A1	08-03-2001
-----				
WO 0061717	A	19-10-2000	EP 1043390 A1	11-10-2000
			AU 3571400 A	14-11-2000
			EP 1169426 A1	09-01-2002
			WO 0061717 A1	19-10-2000
-----				
DE 10048058	A	18-04-2002	DE 10048058 A1	18-04-2002
			AU 8989401 A	08-04-2002
			DE 10108153 A1	24-10-2002
			WO 0226926 A1	04-04-2002
			EP 1322743 A1	02-07-2003
			US 2003186828 A1	02-10-2003
-----				
WO 0149815	A	12-07-2001	DE 19963569 A1	26-07-2001
			AU 3164401 A	16-07-2001
			BR 0016836 A	10-09-2002
			CA 2395870 A1	12-07-2001
			CN 1415010 T	30-04-2003
			WO 0149815 A2	12-07-2001
			EP 1242573 A2	25-09-2002
			PL 356058 A1	14-06-2004
			US 2003060393 A1	27-03-2003
			ZA 200205662 A	03-10-2003
-----				