(11) EP 1 559 545 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

03.08.2005 Bulletin 2005/31

(51) Int Cl.7: **B41C 1/14**

(21) Application number: 04030789.4

(22) Date of filing: 27.12.2004

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR Designated Extension States:

AL BA HR LV MK YU

(30) Priority: 29.01.2004 IT MI20040137

(71) Applicant: SAATIPRINT SpA
22070 Appiano Gentile (CO) (IT)

(72) Inventor: Fracas, Paolo 22070 Appiano Gentile-Como (IT)

(74) Representative: Cicogna, Franco
Ufficio Internazionale Brevetti
Dott.Prof. Franco Cicogna
Via Visconti di Modrone, 14/A
20122 Milano (IT)

(54) Automatic machine for photoengraving screen printing plates for screen printing high quality compact discs

(57) The present invention relates to an automatic machine for photoengraving or photoetching screen printing plates for screen-printing high quality compact discs or CD's, comprising a central control unit (1) op-

eratively coupled to a photoengraving station (3), including a frame or plate conveyor to convey printing frames or plates under a frame photoengraving assembly (3) adapted to scan, by a polygonal mirror and a flat field lens, a laser light beam.




FIG1

20

35

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to an automatic machine for photoengraving or photoetching screen printing plates for screen printing high quality CD's.

[0002] Prior screen printing plate or frame photoengraving machines have a comparatively large size and, moreover, they require a continuous presence of an operator for setting the screen printing operations or procedures.

[0003] Another drawback of prior screen printing plate or frame photoengraving machines is that said machines are not reliable in operation, since they include a comparatively large number of movable parts which are subjected to wear phenomena, requiring the machine to be frequently stopped.

SUMMARY OF THE INVENTION

[0004] Accordingly, the aim of the present invention is to overcome the above mentioned drawbacks, by providing an automatic machine for photoengraving or photoetching screen printing plates or frames for printing high quality CD's, which is adapted to operate according to a continuous cycle, through the 24 hours of a day, without requiring any operators and with an exposure time within a minute.

[0005] Within the scope of the above mentioned aim, a main object of the present invention is to provide such an automatic machine allowing to provide high definition and resolution engraved or etched images, and this in an apparatus including a very small number of movable elements.

[0006] Another object of the present invention is to provide such an automatic machine which, owing to its specifically designed features, is very reliable and safe in operation.

[0007] Yet another object of the present invention is to provide such an automatic machine which can be easily made starting from easily available elements and materials and which, moreover, is very competitive from a mere economic standpoint.

[0008] According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by an automatic machine for photoengraving screen printing plates for screen printing high quality CD's, characterized in that said automatic machine comprises a central control unit, operatively coupled to a photoengraving station including a printing frame conveyor, to convey printing frames under a photoengraving assembly for photoengraving said printing frames, said photoengraving assembly being adapted to scan, by a polygonal mirror and a flat-field lens, a laser light beam.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Further characteristics and advantages of the present invention will become more apparent hereinafter from the following detailed disclosure of a preferred, thought not exclusive, embodiment of an automatic machine for photoengraving screen printing plates or frames for screen-printing high quality CD's, which is illustrated, by way of an indicative but not limitative example, in the accompanying drawings, where:

Figure 1 is a schematic view illustrating the automatic machine according to the present invention; Figure 2 schematically illustrates the operation principle of the photoengraving or photoetching assembly included in the automatic machine according to the present invention;

Figure 3 is a front view illustrating the photoengraving or photoetching assembly;

Figure 4 is a partially cross-sectioned side elevation view illustrating the photoengraving assembly;

Figure 5 is a front elevation view illustrating the automatic machine with a screw conveyor;

Figure 6 is a top plan view illustrating the subject automatic machine:

Figure 7 is a side elevation view illustrating the subject automatic machine;

Figure 8 is a further front elevation view illustrating the automatic machine according to the present invention including a belt conveyor;

Figure 9 is a top plan view illustrating the automatic machine shown in figure 8, and

Figure 10 is a further side elevation view illustrating the automatic machine shown in figure 8.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0010] With reference to the number references of the above mentioned figures, the automatic machine for photoengraving or photoetching screen printing plates or frames for screen printing high quality CD's, according to the present invention, comprises a central control unit including, for example, a computer, indicated by 1, which is operatively coupled to a photoengraving station, generally indicated by the reference number 2.

[0011] The photoengraving or photoetching station 2 comprises a photoengraving assembly, generally indicated by the reference number 3, which will be disclosed in a more detailed manner hereinafter, and which is arranged near a magazine 4 for feeding and properly arranging screen printing plates or frames 10, a further photoengraved or photoetched screen printing frame or plate unloading magazine 5 being moreover provided.

[0012] Said magazines 4 and 5 provide, in actual practice, loading and unloading units for respectively loading and unloading the screen printing plates or frames, allowing to remove frames from a vertical magazine, locate the removed frames under the photoen-

graving assembly and then transfer the photoengraved frames to the unloading magazine, thereby allowing the machine to operate without any operators.

[0013] The subject photoengraving machine or system can be easily started and operated, since it does not require setting operations; actually, it operates as a desk printing unit, and the photoengraving operation can be started by a simple "click" of a mouse.

[0014] Thus, the subject photoengraving assembly provides all the advantages of the digital technology.

[0015] This will allow to store the screen printing files in an electronic type of pattern, to allow a great reduction of the cost and time necessary for making the screen printing plate or frames.

[0016] Moreover, the screen printing frames or plates can be produced in a flexible manner, since it is possible to easily set a photoengraving procedure for different images for each printing frame.

[0017] As is clearly shown in figure 2, the central control unit 1 is operatively coupled to a synchronizer 11, driving an encoder 12 controlling a polygonal mirror, which will be disclosed hereinafter, and an encoder 13 related to the screen printing frame or plate position.

[0018] More specifically, said synchronizer 11 is coupled to a modulator 14 controlling a power supply source 15 for a laser 16 adapted to emit a light beam to be sent on the screen printing frame.

[0019] To that end, as is shown in figure 3, the beam provided by the laser 16 will impinge on a flat fixed mirror 17, in turn sending the beam to a rotary mirror 20, controlled by said encoder 12, so as to synchronize the displacement thereof with that of the frame 10 on the working plane of the photoengraving assembly.

[0020] The laser beam, sent by the rotary mirror to a flat field lens, generally indicated by the reference number 30, will pass through a first flat-concave lens, indicated by the reference number 31, a second concave-convex lens, indicated by the reference number 32 and a third flat-convex lens, indicated by the reference number 33.

[0021] The above optical assembly will operate to emit a modulated beam, adapted to provide a very high image definition accuracy.

[0022] In this connection it should be pointed out that the movement of the rotary mirror 20 is synchronized or timed with the movement of the screen printing frame 10 conveyor, in turn controlled by the mentioned encoder 13.

[0023] The screen printing frames or plates can be driven, as shown in figures 5 to 7, by a screw system, provided for alternatively displacing or driving centering pegs 41.

[0024] The latter will convey or entrain the screen printing frame from their loading station under the photoengraving assembly and then to the unloading magazine.

[0025] Then, said centering pegs will return to their starting position, for taking up a further screen printing

frame.

[0026] Optionally, the screen printing frame, as shown in figures 8 to 10, can comprise a belt conveyor, generally indicated by the reference number 50, which is rotatively driven by an operating assembly, indicated by the reference number 51, designed for conveying the printing frame in a synchronized or timed manner.

[0027] On the screen printing frame, a screen printing plate including a photosensitive film is provided, said screen printing plate being affected by a laser light source, having a wavelength of 405 nm.

[0028] In particular, the laser light is emitted, as stated, by the laser source and passes through the above disclosed optic chain, and, as driven by the polygonal mirror, will impinge on the frame photosensitive film.

[0029] More specifically, the polygonal mirror will direct the point-like light beam to the photosensitive film, thereby causing the photosensitive film layer to cure at set points, since the flat field lens will linearize the light beam, thereby preventing any beam distortion and aberration phenomena from occurring.

[0030] In particular, the photosensitive film portion not affected by the light beam can be solubilized, by using water or any other suitable solutions.

[0031] From the above disclosure, it should be apparent that the invention fully achieves the intended aim and objects.

[0032] In fact, the invention provides a fully automatic machine allowing to photoengrave, in a continuous operation cycle, screen printing plates for screen printing high quality CD's, which machine can be easily controlled, owing to the provision of the disclosed central control unit.

[0033] Said central control unit, in particular, will control the laser beam, by modulating it depending on the signals coming from the above disclosed encoders controlling both the conveyor and the rotary polygonal mirror, which is designed for displacing the light beam.

[0034] The invention, as disclosed, is susceptible to several modifications and variations, all of which will come within the inventive idea.

[0035] Moreover, all the constructional details can be replaced by other technically equivalent elements.

[0036] In practicing the invention, the used materials, as well as the contingent size and shapes can be any, depending on requirements.

Claims

50

1. An automatic machine for photoengraving screen printing plates for screen printing high quality CD's, characterized in that said automatic machine comprises a central control unit operatively coupled to a photoengraving station including a screen printing frame conveyor for conveying screen printing frames under a screen printing photoengraving assembly adapted to scan a laser beam by a polygonal mirror and a flat-field lens.

2. An automatic machine, according to the preceding claim, characterized in that said automatic machine comprises moreover a screen printing frame loading station arranged upstream a photoengraving station and a screen printing unloading station arranged downstream of said photoengraving sta-

3. An automatic machine, according to claim 1, characterized in that said polygonal mirror is a rotary polygonal mirror.

4. An automatic machine, according to claim 1, characterized in that said central control unit is operatively coupled to a synchronizer and a modulator, driven by said synchronizer, which is operatively coupled to a control encoder for controlling said po-

lygonal mirror and a further control encoder for controlling a position of said screen printing frame on said conveyor.

5. An automatic machine, according to claim 4, characterized in that said modulator drives a laser supply source, said laser being designed for emitting a laser beam deflected by a fixed mirror to said polygonal mirror, the beam of said polygonal mirror being sent to said flat field lens.


6. An automatic machine, according to claim 1, characterized in that said conveyor comprises a longitudinal extending conveyor screw, including removable coupling means for removably coupling said screening frames and being controlled by a screen-

ing frame position controlling encoder.

- 7. An automatic machine, according to claim 1, characterized in that said screen printing frame conveyor comprises an endless conveyor belt driven 40 by a driving assembly in turn controlled by said screen printing frame position controlling encoder.
- 8. An automatic machine, according to claim 5, characterized in that said flat field lens comprises a first flat-concave lens, a second concave-convex lens and a third flat-convex lens.

50

55










FIG 3











EUROPEAN SEARCH REPORT

Application Number EP 04 03 0789

	Citation of document with in	dication, where appropriate,	Relevant	CLASSIFICATION OF THE	
Category	of relevant passaç		to claim	APPLICATION (Int.Cl.7)	
Υ	US 5 201 027 A (M.S 6 April 1993 (1993- * the whole documen		1	B41C1/14	
Υ	EP 1 004 435 A (ASA KABUSHIKI KAISHA) 3 * the whole documen	1 May 2000 (2000-05-31)	1		
				TECHNICAL FIELDS SEARCHED (Int.Cl.7)	
				B41C	
	The present search report has b	een drawn up for all claims			
	Place of search	Date of completion of the search		Examiner	
	The Hague	31 March 2005	Loncke, J		
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		E : earlier patent do after the filing dat er D : document cited i L : document cited fi	T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document		

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 04 03 0789

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-03-2005

cited in search report		Publication date		Patent family member(s)	Publication date
US 5201027	A	06-04-1993	IT DE FR GB	1246734 B 4142887 A1 2670922 A1 2253112 A ,B	26-11-1994 25-06-1992 26-06-1992 26-08-1992
EP 1004435	Α	31-05-2000	CA EP JP US WO	2301029 A1 1004435 A1 3226552 B2 6305284 B1 9908872 A1	25-02-1999 31-05-2000 05-11-2000 23-10-2000 25-02-1999
			WO	990072 AI	25-02-139;

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82