



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
31.08.2005 Bulletin 2005/35

(51) Int Cl.7: **F01N 1/16, F01N 1/08**

(21) Application number: **05011547.6**

(22) Date of filing: **23.10.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**

(30) Priority: **24.10.2002 US 420825 P**
21.10.2003 US 690130

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
03256721.6 / 1 413 717

(71) Applicant: **Barnes Group, Inc.**
Connecticut 06010-0489 (US)

(72) Inventor: **Sageman, Robert J.**
Rochester Hills, MI 48306 (US)

(74) Representative: **Price, Nigel John King**
J.A. KEMP & CO.
14 South Square
Gray's Inn
London WC1R 5JJ (GB)


Remarks:

This application was filed on 27 - 05 - 2005 as a
divisional application to the application mentioned
under INID code 62.

(54) **Flapper finger valve**

(57) A flapper finger valve assembly for use in an
exhaust system. The flapper finger valve assembly in-
cludes a tube (24) having a plurality of orifices (22)
therethrough. The flapper finger valve (12) assembly al-
so includes a plurality of flapper finger valves (12) ge-
nerally having a C-shape wherein the flapper finger
valves (12) are arranged on an outside surface of the
tube (24). The flapper finger valves (12) are capable of

radial movement with respect to the tube (24). A plurality
of retainers (28) generally having a C-shape are ar-
ranged around the flapper finger valve (12). These re-
tainers will define a maximum radial movement for such
flapper finger valves (12) on the tube (24). The flapper
finger valve assembly also includes a fastener (36)
which will secure the flapper finger valves (12) between
a tube (24) and retainers (36) in the flapper finger valve
assembly.



Description

[0001] The invention broadly relates to exhaust systems and mufflers, and more particularly relates to a flapper finger valve and a flapper finger valve assembly that will be used in an automotive exhaust system to define a flow path for exhaust gasses that are released under high pressure and high flow conditions.

[0002] It is well known in the art to use mufflers on automotive vehicles to silence exhaust noise and to control the back pressure on the power train. Generally, mufflers are stamped from typically known steel, aluminum or the like and will use multiple internal baffles and tubes to silence the exhaust noise from the power train. In prior art mufflers exhaust enters one end of a muffler and is moved through a series of baffles and tubes in the interior of the muffler, to an exhaust tube and then on to a tailpipe. The design of the baffles, the number of baffles, the holes in the baffles, and any piping within the muffler all relate to the pressure and flow conditions through the muffler and exhaust system of the automotive vehicle. The size of the prior art muffler and exhaust systems of automotive vehicles is rather large in order to accomplish the baffling and noise reduction required by the muffler systems. The size of the exhaust systems require a lot of the packaging room available on the undercarriage of the chassis system of the automotive vehicles. The tuning and control of other characteristics of the muffler also can increase the performance and other associated characteristics of the automotive vehicle depending on the design of the baffles and the amount of pressure allowed to be released and at what flow rate the pressure is released through the exhaust system. Therefore, the performance characteristics of the vehicle that are effected by the release of pressure through the exhaust system in many prior art vehicles is fixed once the exhaust system is installed. Hence, the size of the muffler had to be large to correctly tune and dampen noise as required by the exhaust muffler system.

[0003] Therefore, there is a need in the art for a low cost exhaust system that reduces the package size of the muffler for the underbody of the chassis. There also is a need for an exhaust system that can be tuned or controlled without changing the size of the muffler and the number of baffles or tubes within the muffler system.

[0004] An aim of the present invention is to provide a low cost flapper finger valve and flapper finger valve assembly which defines a flow path for the exhaust gasses of an exhaust system to be released under high pressure or high flow conditions.

[0005] Another aim of the present invention is to provide an exhaust system that is capable of a variety of configurations to control and/or fine tune the exhaust system per application requirements of the motor vehicle characteristics.

[0006] Still another aim of the present invention is to provide an exhaust system that includes a muffler with a smaller package thus reducing the amount of room

used on the chassis underbody.

[0007] Still another aim of the present invention is to provide flapper finger valve assembly that can independently operate or operate within an existing muffler to regulate the flow path for exhaust gasses in an exhaust system of an automotive vehicle.

[0008] In one aspect of the present invention, the foregoing and other aims are obtained by a novel design for a flapper finger valve assembly for use in an automotive exhaust system. The flapper finger valve assembly would either be an independent mechanism or integrated into an assembly for a muffler or exhaust system to create and regulate flow through a path for exhaust gasses to be released under high pressure and high flow conditions in the exhaust system. The flapper finger valve assembly includes at least one flapper finger valve connected to an exhaust tube and an exhaust pressure relief valve retainer or backer.

[0009] One advantage of the above aspect of the present invention is an improved exhaust or muffler system.

[0010] Still another advantage of the above aspect of the present invention is to create an escape path for exhaust gases to be released under high pressure and flow conditions.

[0011] Still another advantage of the above aspect of the present invention is the reduction in overall size and packaging requirements for the exhaust system of an automotive vehicle.

[0012] Yet another advantage of the above aspect of the present invention is the reduction in weight of the exhaust system for the vehicle.

[0013] Still another advantage of the above aspect of the present invention is the tuneability and variability of the exhaust system by changing design requirements of the flapper finger valves.

[0014] The invention provides an exhaust system, said system including:

a muffler; and
a flapper finger valve assembly arranged within said muffler.

[0015] The invention also provides, a muffler for use in an exhaust system, said muffler including:

a body; and
a flapper finger valve assembly arranged within said body.

[0016] Preferably, said flapper finger valve assembly has a tube.

[0017] Preferably, said tube has a plurality of orifices therethrough.

[0018] Preferably, said flapper finger valve assembly system has at least one flapper finger valve, said flapper finger valve having a generally C-shape.

[0019] Preferably, said flapper finger valve is ar-

ranged around said tube, said flapper finger valve covers said orifices when said flapper finger valve is in a closed position.

[0020] Preferably, said flapper finger valve has a predetermined spring coefficient.

[0021] Preferably, said flapper finger valve moves in a radially outward direction when exposed to a predetermined pressure.

[0022] Preferably, said flapper finger valve is capable of being tuned to specific exhaust system characteristics.

[0023] Preferably, said flapper finger valve has predetermined angled bends, thicknesses and widths.

[0024] Preferably, said flapper finger valve assembly system has at least one relief valve retainer, said relief valve retainer generally having a C-shape.

[0025] Preferably, said flapper finger valve assembly is electronically controlled and tunable.

[0026] Preferably, the flapper finger valve assembly has a plurality of flapper finger valves arranged around an outer surface of said tube, said flapper finger valves covering said orifices when said flapper finger valve assembly is in a closed position.

[0027] Preferably, the flapper finger valve assembly has a plurality of relief backers arranged around said flapper finger valves to control a maximum distance of radial movement in an outward direction for said flapper finger valve.

[0028] Preferably, the flapper finger valves and said relief backers are secured to an outer surface of said tube.

[0029] Preferably, the flapper finger valves having a predetermined thickness and spring coefficient, said flapper finger valves being arranged to open or move radially away from said tube at predetermined exhaust pressures.

[0030] Preferably, the flapper finger valves are electronically controllable or tunable.

[0031] Preferably, a plurality of said flapper finger valve assemblies are arranged within a reduced size muffler in parallel or series.

[0032] The invention also provides a flapper finger valve assembly for use in an exhaust system, said assembly including:

a tube, said tube having a plurality of orifices there-through;

a plurality of flapper finger valves generally having a C-shape, said flapper finger valves arranged on an outside surface of said tube, said flapper finger valves align with said orifices such that said orifices are covered by said flapper finger valves when the assembly is in a closed or equilibrium position;

a plurality of retainers generally having a C-shape, said retainers arranged around said flapper finger valves, said retainers having a fixed radius and deforming a maximum limit of radial movement for said flapper finger valves when said flapper finger

valves are in an open position; and
a fastener for securing said flapper finger valves and said retainers to said tube.

[0033] Embodiments of apparatus in accordance with the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figures 1A - 1E show a flapper finger valve assembly according to the present invention.

Figures 2A - 2C show a flapper finger valve assembly according to the present invention.

Figures 3A- 3H show an exhaust pressure relief valve backer according to the present invention.

Figures 4A - 4D show an exhaust pressure relief valve assembly in its open and closed positions.

Figures 5A - 5B show an exhaust pressure relief valve assembly in a series configuration.

Figures 6A - 6C show an exhaust pressure tube according to the present invention.

Figure 7 shows a side view of an exhaust pressure tube according to the present invention.

Figure 8 shows a side view of an alternate embodiment of an exhaust pressure tube according to the present invention.

Figure 9 shows an end view of an exhaust tube with a flapper valve in a closed position.

Figure 10 shows an end view of a flapper valve assembly with the flapper valve in its open position.

Figure 11 shows a side view of a flapper valve according to the present invention.

Figure 12 shows a side view of the flapper valve according to the present invention.

Figure 13 shows a top view of the flapper valve according to the present invention.

Figure 14 shows a cross section of a muffler or exhaust system having a flapper finger valve assembly according to the present invention.

Figure 15 shows an alternate embodiment of a flapper finger valve assembly according to the present invention.

[0034] Referring to the drawings, Figs. 1 through 14 show the flapper finger valve assembly 10 according to the present invention. The flapper finger valve assembly 10 will be for use on a muffler or exhaust system component 38 and/or as a stand alone unit that will allow for the propagation of the exhaust gasses through a predetermined path for release under high pressure and high flow conditions. The use of the flapper finger valve assembly 10 will allow for a reduction in the packaging size of the muffler 38 thus increasing available space on the undercarriage of the chassis of an automotive vehicle. Furthermore the reduction in size will also reduce the weight and manufacturing costs of the muffler or exhaust system 38. It should further be noted that the flapper finger valve assembly 10 will be available in a variety

of configurations and will also allow for a variable control or fine tuning of the exhaust system and power train of the vehicle.

[0035] Fig. 1 shows the exhaust pressure flapper finger valve or relief valve 12 according to the present invention. Generally, the flapper finger valve 12 has an overall C-shape. The valve 12 has an orifice 14 through a surface thereof at or near a top point thereof. Fig. 1 shows the valve in a closed position 16 and in an open position 18. It should be noted that generally the flapper finger valve 12 will be made of a steel material that will have a predetermined spring coefficient. It should be noted that any other type of metal, ceramic, plastic, composite or any other type of material may be used for the flapper finger valve 12. As shown in Fig. 1 the flapper finger valve 12 also includes, on both ends thereof, a predetermined bend 20 at a predetermined angle which will be used to cover and seal a predetermined orifice 22 in the exhaust system. The flapper finger valve 12 is designed such that it controls the release of the exhaust pressure and flow of the exhaust in a predetermined manner. The steel will have a predetermined spring coefficient that in one embodiment will be in the closed position in its equilibrium position. Then when a predetermined pressure from the exhaust is placed upon an inner surface of the flapper finger valve 12, the flapper finger valve 12 will be urged in an outer direction thus increasing the size of the C and bending the finger valve 12 outward in a radial direction. The flapper finger valve 12 must have the proper spring characteristics and the ability to open and close at various pressures and within predetermined time constraints. It should further be noted that the profile or predetermined bend 20 in each of the flapper finger valves 12 may vary depending on the relief orifices 22 in the exhaust tube 24. It should further be noted that the finger valve has a predetermined thickness which will also affect the characteristics of the exhaust system. The thickness of the material will be matched to the pressure and noise reduction requirements of the exhaust system. The thicker the material the more pressure and the greater flow needed to open the valve 12. Therefore, the thinner the material the quicker the valve 12 will open, thus releasing exhaust pressure through the muffler system. It should be noted that the flapper finger valve 12 can be placed on the outer circumference of an exhaust tube 24 or on an inner circumference of an exhaust tube 24 depending on the design requirements and flow direction needed for the exhaust. Furthermore, a bridge 26, as shown in Fig. 1, will reduce the width of the flapper finger valve 12 at predetermined positions based on the pressure and flow requirements needed along with the response time in the exhaust system. Therefore, all of the variables discussed above can be changed on the flapper finger valve 12 to fine tune and/or configure the exhaust system to predetermined specifications.

[0036] Fig. 2 shows the exhaust pressure relief valve backer or retainer 28 for use in the present invention.

The retainer 28 generally has a rectangular shape if viewed flat. However, in its operational mode the retainer 28 generally has a C-shape. The retainer 28 will control the maximum amount of radial travel for the flapper finger valve 12. Therefore, the effective radius of the retainer 28 is a predetermined length that will allow the flapper finger valve 12 to open to a predetermined position or close to a predetermined position depending on the operating requirements of the exhaust system. It should be noted that in one embodiment the retainer 28 is made of a steel material but that it should be noted that any other metal material, plastic, ceramic, composite or any other known material capable of withstanding the pressure and heat of an automotive exhaust system may be used. The exhaust pressure relief valve backer 28 also includes an orifice 30 at a top portion through a surface thereof. This orifice 30 will mate and align with the orifice 14 located on the flapper finger valve 12 and will allow for connection of the retainer 28 and flapper finger valve 12 to an exhaust tube 24. In one embodiment the retainer 28 will be placed and arranged such that an outer surface of the flapper finger valve 12 engages with an inner surface of the retainer 28. The retainer 28 has a fixed radius and does not have the spring coefficient shown in the flapper finger valve 12 and therefore is designed to set an upper limit on the amount of radial movement for the flapper finger valve 12. The exhaust pressure relief valve backer 28 also may include a predetermined bend 32 on both ends thereof. This bend will match with any bend found in the flapper finger valve 12.

[0037] Figs. 5 and 6 show an exhaust pressure tube 24 for use with the flapper finger valve 12 and retainer 28 as discussed above. The exhaust pressure tube 24 will restrict the exhaust flow volume to a predetermined amount to produce the control and fine tuning of the exhaust system for the application required. It should be noted that the exhaust tube 24 generally has a tubular cross section and includes a plurality of orifices. A mounting orifice 34 through one surface thereof will mate with the orifices 14, 30 on the flapper finger valve 12 and retainer 28 to allow for connection of the flapper finger valve 12 and retainer 28 to the exhaust tube 24. A first and second relief orifice 22 are located equal distance from each other through the surface of the exhaust tube 24 opposite from the mounting orifice 34. The size of the relief orifices 22 will determine the amount of flow through the exhaust pressure tube 24 and flapper finger valve 12. It should be noted that in one embodiment the exhaust pressure tube 24 is made of a steel material but that any other known metal, plastic, ceramic, composite or other material capable of withstanding the pressure and heat may also be used for the exhaust pressure tube 24. The exhaust pressure tube 24 will be designed to mate with and align with any known tube within an exhaust system/muffler 38. The relief orifices 22 generally are circular but any other shape may be used depending on the requirements and noise reduc-

tion capabilities of any other design. The size of the relief orifices 22 also will be tuned to the specific pressure requirements and flow variations of the flapper finger valve assembly 10. This will allow for multiple pressure and flow control variables depending on the size and/or shape of the flow relief orifices 22.

[0038] Figs. 3, 4 and 6 show the flapper finger valve assembly 10 completely assembled. As shown the exhaust tube 24 is placed within a muffler system 38 or in an tube within an exhaust system at predetermined intervals or at predetermined areas therein. A flapper finger valve 12 is placed directly in contact with the exhaust tube 24 on an outside surface of the exhaust tube 24 and then an inside surface of the retainer 28 is placed in direct contact with an outer surface of the flapper finger valve 12. The orifices 14, 30 on the flapper finger valve 12 and retainer 28 are aligned with the mounting orifice 34 on the exhaust tube 24 and any known fastener or connection method 36 is used to connect the three components to one another, such as but not limited to screws, rivets, inserts, welding or any other mechanical or chemical bonding means. At an equilibrium position the flapper finger valve 12 will engage the entire outer circumference of the exhaust tube 24 and cover the relief orifices 22. During operation once the exhaust pressure increases and the flow increases the valve 12 will open in a radial direction, away from the outer surface of the exhaust tube 24 and allow for flow of the exhaust through the relief orifices 22 and on through the muffler or the exhaust system 38. It should be noted that the flapper finger valve assembly 10 can be placed in parallel or series as shown in Figs. 4 and 6 or placed anywhere within the exhaust system to achieve the desired tuning and control characteristics of the exhaust system. Therefore, it can be placed in a tube at the beginning of the muffler 38, at the end of the muffler 38 or in a separate independent unit separate from the muffler. The amount of noise reduction and tuning characteristics will depend on the design requirements of the vehicle.

[0039] It should further be noted that it is contemplated to have a flapper finger valve assembly 10 that is electronically controlled that will allow the user of the motor vehicle to dial in a specific tuning for the exhaust system. This assembly could use electric solenoids or the like to control how far the finger valves 12 open and which finger valves 12 will even be capable of opening. Furthermore, a plurality of different size and tuned valves 12 may be placed in the same muffler with only specific valves 12 becoming operational at predetermined times depending on the characteristics selected by the motor vehicle operator. It should also be noted that pneumatic, electro-mechanical, hydraulic or pure mechanical systems are contemplated to control the flapper finger valve assembly 10 in any known contemplated exhaust systems for a vehicle.

[0040] Figure 15 shows an alternate embodiment for an exhaust pressure flapper finger valve or relief valve

120 according to the present invention. Generally, the flapper finger valve 120 has an overall C-shape. The valve 120 has a connecting orifice 140 through a surface thereof at or near a top thereof. It should be noted that generally the flapper finger valve 120 will be made of a steel material that will have a predetermined spring coefficient. It should be noted that any other type of metal, ceramic, plastic, composite, fabric, or any other type of material may be used for the flapper finger valve 120. As shown in Figure 15, the flapper finger valve 120 also includes a plurality of predefined orifices 127 arranged around the connecting orifice 140. The orifices 127 may either be a circular orifice or any other shaped orifice depending on the environment and design requirements of the flapper finger valve 120. The diameter of the orifices 127 are arranged and placed at predetermined positions based on the pressure and flow requirements needed along with the response time in the exhaust system. The large diameter orifices 127 will require less pressure from the exhaust system to open the flapper valve 120 to its open position while smaller diameter orifices 127 will require greater pressure to open the flapper valve 120, thus allowing for release of the exhaust pressure through the muffler system. Therefore, the orifices 127 work in the same manner as the bridges as shown in Figure 1. Therefore, all of the variables discussed including the shape, size and location of the orifices 127 can be changed on the flapper finger valve 120 to fine tune and/or configure the exhaust system to predetermined specifications.

[0041] While it may be apparent that the preferred embodiments of the invention disclosed are well calculated to fill benefits, objects or advantages of the invention, it will be appreciated that the invention is susceptible to modifications, variations and change within departing from the proper scope of the invention as shown. Therefore, within the scope of the appended claims, the present invention may be practiced otherwise than is specifically described.


Claims









1. A flapper valve for controlling axial leakage through openings in an exhaust system tube, said flapper valve comprising a generally flat strip of spring material having first and second ends with a first portion including said first end, and a second portion including said second end and extending in a first direction from said first end, said second portion being cantilevered with respect to said first portion with first and second portions forming a continuous arcuate structure extending along an arc of at least about 90 degrees.
2. The flapper valve of claim 1, further comprising a third end and a third portion including said third end and extending in a second opposite direction from








said first portion, said third portion being cantilevered with respect to said first portion, said first, second, and third portions forming a continuous arcuate structure extending along an arc of at least about 180 degrees, and said first portion being intermediate said second and third portions. 5



through a surface thereof for connection of said flapper valve to an exhaust tube.


3. The flapper valve of claim 1 or 2, wherein said first portion comprises an orifice through a surface thereof for connection of said flapper valve to an exhaust tube. 10
4. The flapper valve of any one of the preceding claims, wherein said flapper valve has a generally C-shape. 15
5. A flapper valve for controlling axial leakage through openings in an exhaust system tube, said flapper valve comprising a generally flat strip of spring material having first and second ends with a first portion including said first end, and a second portion including said second end and extending in a first direction from said first end, said second portion being cantilevered with respect to said first portion with first and second portions forming a continuous C-shaped structure. 20 25
6. The flapper valve of claim 5, further comprising a third end and a third portion including said third end and extending in a second opposite direction from said first portion, said third portion being cantilevered with respect to said first portion, said first, second, and third portions forming a continuous C-shaped structure. 30 35
7. The flapper valve of claim 5, wherein said C-shaped flapper valve structure extends along an arc greater than about 90 degrees.
8. The flapper valve of claim 6, wherein said C-shaped flapper valve structure extends along an arc greater than about 180 degrees. 40
9. The flapper valve of any one of claims 5 to 8, wherein said first portion comprises an orifice through a surface thereof for connection of said flapper valve to an exhaust tube. 45
10. A flapper valve for controlling axial leakage through openings in an exhaust system tube, said flapper valve comprising a generally C-shaped strip of spring material having first and second ends and comprising a bend adjacent each end, each bend having a predetermined angle for covering an orifice in the exhaust system. 50 55
11. The flapper valve of claim 10 wherein said C-shaped strip comprises an orifice at a top portion



















FIG. 15.