

Europäisches Patentamt European Patent Office Office européen des brevets



(11) **EP 1 578 026 A8**

(12) CORRECTED EUROPEAN PATENT APPLICATION

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A2)

Remarks

(48) Corrigendum issued on:

21.12.2005 Bulletin 2005/51

(43) Date of publication:

21.09.2005 Bulletin 2005/38

(21) Application number: 05012686.1

(22) Date of filing: 02.05.1995

(84) Designated Contracting States:

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

(30) Priority: 06.05.1994 JP 11763694

06.05.1994 JP 11763794 06.05.1994 JP 11763894 06.05.1994 JP 11763994

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 95917502.7 / 0 708 535

- (71) Applicant: NTT MOBILE COMMUNICATIONS NETWORK INC.
 Minato-ku, Tokyo 105-8436 (JP)
- (72) Inventors:
 - Kawahara, Toshiro c/o Int. Prop. Dept., NTT DoCoMo Chiyoda-ku, Tokyo 100-6150 (JP)

(51) Int CI.7: **H04B 3/20**, H04B 3/23

- Ohya, Tomoyuki c/o Int. Prop. Dept., NTT DoCoMo Chiyoda-ku, Tokyo 100-6150 (JP)
- Saigusa, Masahito c/o Int. Prop. Dept., NTT DoCoMo Chiyoda-ku, Tokyo 100-6150 (JP)
- Naka, Nobuhiko c/o Int. Prop. Dept., NTT DoCoMo Chiyoda-ku, Tokyo 100-6150 (JP)
- (74) Representative:

Winter, Brandl, Fürniss, Hübner Röss, Kaiser, Polte Partnerschaft Patent- und Rechtsanwaltskanzlei Alois-Steinecker-Strasse 22 85354 Freising (DE)

Remarks:

This application was filed on 13-06-2005 as a divisional application to the application mentioned under INID code 62.

(54) Double talk detecting method, double talk detecting apparatus, and echo canceler

(57) This invention relates to a double talk detecting method suited to be used for an echo canceler, and more particularly to a method for correctly detecting whether or not the double talk is present, even in the case where a speech transmitting level difference between a far-end talker and a near-end talker is comparatively large. What is assumed in the present invention is an echo canceler which can be employed in a telephone line network for transmitting a speech of a farend talker sent through a digital line and a speech of a near-end talker sent through an analog line. A double talk detecting method applicable to the echo canceler here extracts predetermined analyzed parameters re-

spectively from a first speech signal corresponding to the speech of the far-end talker sent from the echo canceler to a hybrid circuit and the speech of the near-end talker input to the echo canceler through the hybrid circuit. The analyzed parameters herein used are frequency components, of each of the speech signals. In this invention, the analyzed parameters themselves or correlation values of the fluctuations of the analyzed parameters, etc. are calculated and a detection is made as to whether or not the double talk is present, based on the result of calculation.

FIG.8
FOURTH EMBODIMENT

