



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 72

(51) Int Cl.:

B60R 22/48 (1985.01)

(48) Corrigendum issued on:

24.05.2006 Bulletin 2006/21

(86) International application number:

PCT/JP2004/000295

(43) Date of publication:

19.10.2005 Bulletin 2005/42

(87) International publication number:

WO 2004/069615 (19.08.2004 Gazette 2004/34)

(21) Application number: **04702803.0**

(22) Date of filing: **16.01.2004**

(84) Designated Contracting States:

DE FR GB

(30) Priority: **24.01.2003 JP 2003016312**

07.07.2003 JP 2003192935

(71) Applicant: **HONDA MOTOR CO., Ltd.**

Tokyo 107-8556 (JP)

(72) Inventors:

- **AKABA, Hiroshi,**
c/o K.K. Hon-da Gijutsu Kenkyusho
Wako-shi,
Saitama 351-0193 (JP)

- **KAMIJI, Koichi,**
c/o K.K. Hon-da Gijutsu Kenkyusho
Wako-shi,
Saitama 351-0193 (JP)
- **SUGAMATA, Yoshihisa,**
c/o K.K. Hon-da Gijutsu
Wako-shi,
Saitama 351-0193 (JP)

(74) Representative: **Prechtel, Jörg et al**

Weickmann & Weickmann,
Patentanwälte,
Postfach 860 820
81635 München (DE)

(54) **TRAVEL SAFETY DEVICE FOR MOTOR VEHICLE**

(57) A travel safety device for a vehicle comprises: an object detecting unit (114) for detecting an object existing in the traveling direction of the vehicle (100); a correlation calculating unit (39) for calculating a correlation involving the distance between the vehicle (100) and the object on the basis of a detection result of the corresponding object detecting unit (114); an automatic brake unit (120) for automatically decelerating the vehicle (100); a safety device (122) including a seatbelt device (15) for automatically tightening the seatbelt (14) and releasing the tightening thereof; and safety device operation control units (38, 39, 43) for determining a possibility of a contact between the vehicle (100) and the object on the basis of the correlation calculated by the correlation calculating unit (39) and for controlling the operation of the safety device (122) where it is predicted that there is a possibility of a contact; wherein the safety device operation control units (38, 39, 43) simultaneously actuate the automatic brake unit (120) and seatbelt device (15) where it is predicted that there is a possibility of a contact.

FIG. 3

