(11) **EP 1 596 618 A8** 

(12)

## **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1) INID code(s) 74

(48) Corrigendum issued on: 17.05.2006 Bulletin 2006/20

(43) Date of publication: **16.11.2005 Bulletin 2005/46** 

(21) Application number: 04702827.9

(22) Date of filing: 16.01.2004

(51) Int Cl.: H04Q 7/36 (1995.01)

(86) International application number: PCT/JP2004/000307

(87) International publication number: WO 2004/068883 (12.08.2004 Gazette 2004/33)

(84) Designated Contracting States: **DE FI GB SE** 

(30) Priority: 29.01.2003 JP 2003019606

(71) Applicant: NEC CORPORATION Minato-ku,
Tokyo 108-8001 (JP)

(72) Inventor: TAKAI, Kenichi; Tokyo; 1088001 (JP)

(74) Representative: Wenzel & Kalkoff
Patentanwälte
Postfach 73 04 66
D-22124 Hamburg (DE)

## (54) RADIO COMMUNICATION SYSTEM, BASE STATION APPARATUS, AND DOWNSTREAM TRANSMISSION DIRECTING CHARACTERISTIC CONTROL METHOD USED THEREFOR

(57) A communication bit rate computing unit (24) computes the cumulative bit rate of downlink communication data, at which a base station communicates with a terminal, and totalizes the bit rates for each sector area. A amplitude/phase control unit (23) checks whether the cumulative bit rate for each sector area, reported from the communication bit rate computing unit (24), is higher than a first threshold or lower than a second threshold.

If the cumulative bit rate is higher than the first threshold, the amplitude/phase control unit (23) performs directing characteristic control so as to narrow the area range of the corresponding sector area to a range smaller than a standard area range. If the cumulative bit rate is lower than the second threshold, the amplitude/phase control unit (23) performs directing characteristic control so as to widen the area range of the corresponding sector area to a range larger than the standard area range.

