



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 617 014 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
18.01.2006 Bulletin 2006/03

(51) Int Cl.:
E04G 23/02 (2006.01)

(21) Application number: **05254265.1**

(22) Date of filing: **07.07.2005**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**
Designated Extension States:
AL BA HR MK YU

(30) Priority: **13.07.2004 GB 0415594**
18.05.2005 GB 0510126

(71) Applicant: **Patrick, Alan John**
Kilsyth, Glasgow
G65 9DE (GB)

(72) Inventor: **Patrick, Alan John**
Kilsyth, Glasgow
G65 9DE (GB)

(74) Representative: **Atkinson, Ralph et al**
Atkinson Burrington Ltd
28 President Buildings
President Way
Sheffield S4 7UR (GB)

(54) Building panel repair

(57) Building panel repair apparatus (201) comprising a substantially planar backplate (202) for insertion through a hole in a building panel to be repaired. A front face (204) of the backplate is provided with adhesive for mounting the backplate to the rear side of a building panel. At least one flap (210) is defined in the backplate movable between an open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel; and a closed position providing a substrate surface for hole repair material. A method of building panel repair using the apparatus. A method of manufacture of the apparatus.




Figure 9

EP 1 617 014 A1

Description

Background of the Invention

1. Field of the Invention

[0001] The present invention relates to building panel repair, in particular to apparatus for use in building panel repair, a method of building panel repair and a method of manufacture of apparatus for use in building panel repair.

2. Description of the Related Art

[0002] A first technique for repairing a hole in a building panel, such as a wallboard or drywall, involves filling the hole with crunched up paper or a piece of wood and applying layers of plaster until the repair is considered to be satisfactory.

[0003] A problem with this technique is the unpredictability of the integrity of the repair. The technique involves an irregular distribution of plaster throughout the restoration area. A differential cure rate across the repair, due to different depths of plaster within the filled hole or fluctuations in temperature and humidity, is a contributing factor towards cracking. In addition, during curing, plaster contracts and the application of an insufficient quantity of plaster in an area can also lead to cracking. The technique also involves the use of a porous fill material, and absorption of water from the plaster by the fill material can lead to dehydration cracking. The potential quality of the repair is deteriorated during curing by interacting factors contributing towards cracking, often leading to a repair of unsatisfactory quality requiring patching.

[0004] A second technique for repairing a hole in a hollow building panel described in Patent number US 4 193 243 involves the insertion of a perforated sheet through the hole and is then mounted to the building panel using a tool and rod arrangement inserted through the perforated sheet. A problem with this technique is that the tool and rod arrangement may become lost or broken in a building environment and is inconvenient to use. Following mounting of the perforated sheet, the outer portion of the rod must be broken off and the tool removed. This is inconvenient in practice and may weaken the quality of the mounting of the perforated sheet to the building panel. In addition, the apparatus used in the repair presents an obstruction to subsequent mounting of an object to the repaired area of the building panel.

[0005] A third technique for repairing a hole in a building panel involves applying a mesh patch to the front surface of the building panel to cover over the hole and to which plaster or other compound is then applied. When dry, the plaster or other compound is sanded down. A disadvantage with this technique is that in most cases, a bump is left on the building panel surface. Such a bump may present an obstacle if tiling over the repair. Furthermore, a relatively small amount of plaster or other com-

pound is used to complete the repair. This characteristic of the repair renders the repair susceptible to damage, for example in the event an object strikes the building panel in the area of the repair, and also reduces the ability of the building panel to support fixings in the area of the repair.

Brief Summary of the Invention

[0006] According to a first aspect of the present invention there is provided apparatus for use in building panel repair comprising a substantially planar backplate for insertion through a hole in a building panel to be repaired, a front face of the backplate being provided with adhesive for mounting the backplate to the rear side of a building panel; wherein at least one flap is defined in said backplate movable between a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel; and a second closed position providing a substrate surface for hole repair material.

[0007] According to a second aspect of the present invention there is provided a method of building panel repair using apparatus comprising a substantially planar backplate for insertion through a hole in a building panel to be repaired, a front face of the backplate being provided with adhesive for mounting the backplate to a rear face of a building panel; wherein at least one flap is defined in said backplate movable between a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel and a second closed position providing a substrate surface for hole repair material, said method comprising the steps of a) inserting the backplate through a hole in a building panel; b) with a flap in said first open position, positioning the front face of said backplate to face the rear face of said building panel; c) with the adhesive provided on the front face of the backplate exposed, pulling the front face of the backplate against the rear face of the building panel to mount said backplate; d) moving said flap into said second closed position; and e) applying hole repair material to the exposed surface of the mounted backplate.

[0008] According to a third aspect of the present invention there is provided a method of manufacturing apparatus comprising a substantially planar backplate for insertion through a hole in a building panel to be repaired, a front face of the backplate being provided with adhesive for mounting the backplate to a rear face of a building panel; wherein at least one flap is defined in said backplate movable between a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel and a second closed position providing a substrate surface for hole repair material, said method comprising the steps of: a) adhering one side of two-sided adhesive tape to one side of a backplate sheet; and b) cutting through said backplate sheet to define at least one flap.

Brief Description of the Several Views of the Drawings

[0009]

Figure 1 shows apparatus for use in building panel repair and a building panel to be repaired;
 Figure 2 shows repair apparatus for use in repairing a hole in a building panel;
 Figure 3 shows a first preparation step in using the apparatus of Figure 2;
 Figure 4 shows a second preparation step in using the apparatus of Figure 2;
 Figure 5 shows a third step in using the apparatus of Figure 2 in which the backplate is inserted through a hole in a building panel to be repaired;
 Figure 6 shows a fourth step in using the apparatus of Figure 2 in which the backplate is mounted to the building panel being repaired;
 Figure 7 shows a cross-section view of the illustration of Figure 6;
 Figure 8 shows a fifth step in using the apparatus of Figure 2;
 Figure 9 shows a sixth step in using the apparatus of Figure 2 in which hole repair material is applied to the mounted backplate of Figure 8;
 Figure 10 shows a cross-section view of hole repair material being applied to the mounted backplate of Figures 8 and 9;
 Figure 11 shows a cross-section view of hole repair material being applied to a mounted backplate;
 Figure 12 shows a building panel following repair using the apparatus of Fig. 2;
 Figure 13 illustrates a second example of a repair using a repair apparatus;
 Figure 14 illustrates a third example of a repair using a repair apparatus;
 Figure 15 shows the apparatus of Figure 2 being divided into two smaller backplates;
 Figure 16 shows the apparatus of Figure 2 being trimmed;
 Figure 17 shows an aperture being made in a second area that overlaps a first area of a building panel that has been repaired using the apparatus of Figure 2;
 Figure 18 shows a cross-section view of a repair through which a mounting member has been located;
 Figure 19 shows a first step in the manufacture of the apparatus of Figure 2;
 Figure 20 shows a second step in the manufacture of the apparatus of Figure 2;
 Figure 21 shows a third step in the manufacture of the apparatus of Figure 2;
 Figure 22 shows a fourth step in the manufacture of the apparatus of Figure 2;
 Figure 23 shows a repair apparatus having a square rectangular shape;
 Figure 24 shows the repair apparatus of Figure 23

in further detail;

Figure 25 shows repair apparatus having flexed in response to manually applied pressure;

Figure 26 shows a repair apparatus having the perimeter of at least one region of the backplate delineated;

Figure 27 shows the repair apparatus of Figure 26 prepared for use in the repair of a building panel behind which an obstacle extends.

Written Description of the Best Mode for Carrying Out the Invention

Figure 1

[0010] Figure 1 shows repair apparatus 101 for use in building panel repair. A building panel 102 requires repair. In this example, an electrical fitting 103 has been removed from building panel 102 by building operative 104, leaving an unwanted aperture 105.

[0011] The repair apparatus comprises a substantially planar backplate for insertion through a hole in a building panel to be repaired. A front face of the backplate is provided with adhesive for mounting the backplate to the rear side of a building panel. At least one flap is defined in the backplate movable between a first open position, providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel, and a second closed position providing a substrate surface for hole repair material.

Figure 2

[0012] An enlarged view of a repair apparatus 201 is shown in Figure 2. Repair apparatus 201 comprises a substantially rectangular planar backplate 202. According to the present embodiment, backplate 202 is fabricated from plastic board having a twin wall structure. The structure comprises a first front wall 203, providing a front face 204, spaced apart from a second rear wall 205, providing a rear face 206, by a plurality of connecting members, known as flutes, extending between the walls 203, 205, for example connecting member 207.

[0013] The front face 204 of backplate 202 is provided with two-sided adhesive tape 208; having one side adhered to the front face 204 of backplate 202 and the opposite side provided with a removable backing 209. Substantially the whole of front face 204 is provided with adhesive.

[0014] According to the present embodiment, four flaps 210, 211, 212, 213 are defined in the backplate 202. The flaps 210, 211, 212, 213 are arranged in two pairs; a first pair comprising flap 210 and nearest adjacent flap 211 and a second pair comprising flap 212 and nearest adjacent flap 213. According to the shown arrangement, the flaps forming first pair 210, 211 and second pair 212, 213 open in the same direction as each other, however the flaps in the first pair 210, 211 open in a

different direction, the opposite direction, to the flaps of the second pair **212**, **213**.

[0015] In *Figure 2*, each of the flaps **210**, **211**, **212**, **213** is shown in a fully closed position, in which the flap lies flush in the plane of the backplate **202**. The flaps **210**, **211**, **212**, **213** open inwardly; the distal end of each flap **210**, **211**, **212**, **213** is rotatable from the fully closed position towards the centre of the backplate **202**. The distal end of an outwardly opening flap is rotatable from the fully closed position away from the centre of the backplate, towards an edge.

[0016] The repair apparatus may also feature at least one repair material aperture. According to the present embodiment, an array of repair material apertures **214** is defined in backplate **202**. In this example, the array of hole repair material apertures **214** is located substantially centrally of front face **204** with the first pair of flaps **210**, **211** located to one side of the array **214** and the second pair of flaps **212**, **213** located to the other side of the array **214**. Thus, in this example, the flaps **210**, **211**, **212**, **213** open inwardly towards the array of repair material apertures **214**.

Figure 3

[0017] *Figure 3* illustrates a first preparation step in using repair apparatus **201**. The front face **204** of the backplate **202** is prepared for mounting to a building panel.

[0018] An adhesive surface of adhesive tape **208** on the front face **204** of backplate **202** is exposed through removal of the removable backing **209**. As shown, a building operative **301** can achieve this by lifting a corner of the removable backing **209** up from a corner of the front face **204** of the backplate **202** and peeling it back across the front face **204**, as indicated by arrow **302**.

Figure 4

[0019] A second preparation step in using repair apparatus **201** is illustrated in *Figure 4*. The flaps **210**, **211**, **212**, **213** of the backplate **202** are recond to provide backplate positioning means.

[0020] Each of the flaps **210**, **211**, **212**, **213** is moved from the closed position shown in *Figure 2*, into an open position. When opened, each flap **210**, **211**, **212**, **213** is manually grippable, allowing an operative to grip a flap to gain hold of the backplate **202**. Furthermore, moving a flap **210**, **211**, **212**, **213** from the closed position into an open position leaves behind a flap aperture through the backplate **202**, for example flap aperture **401**, allowing an operative to hook a finger through to gain hold of the backplate. In this example, the flaps of each pair **210**, **211** and **212**, **213** open in the same direction as each other, for ease of use.

[0021] In *Figure 4*, each of the flaps **210**, **211**, **212**, **213** are shown in a forward open position in which the flap extends forwardly of front face **204**. Flaps **210**, **211**

and **212** are each shown in a forward open position in which the flap extends substantially normal to the front face **204** of the backplate **202**. As shown, a building operative **301** can achieve reconfiguration of the flaps **210**, **211**, **212**, **213** from the fully closed position into a forward open position by pushing the side of the flap flush with the rear face **206** of the backplate **202** forward through the backplate **202** to the front face **204** side.

[0022] The backplate positioning means presented following reconfiguration of the flaps **210**, **211**, **212**, **213** into an open position functions to assist an operative in positioning the backplate for mounting, and thus facilitates the mounting of the backplate to a building panel.

Figure 5

[0023] *Figure 5* illustrates a third step in using repair apparatus **201**. The backplate **202** is inserted through a hole **501** in a building panel **502** to be repaired. In this example, building panel **502** is an internal plasterboard wall.

[0024] The width and length dimensions of backplate **202** are greater than the corresponding dimensions of the hole **501** in the building panel **502**. However, the backplate **202** can be inserted through the hole **501** when oriented with a width edge **503** leading. As shown, a building operative **301** can achieve this by using one or both hands to grip one or more of the flaps **210**, **211**, **212**, **213** and, whilst holding the flap(s), orienting the backplate **202** for insertion into the hole **501** and then passing the backplate **202** from the front side of the building panel **502** through the hole **501** to the rear side of the building panel **502**, as indicated by arrow **504**. The backplate may be flexed to facilitate insertion through the hole.

[0025] As previously described, substantially the whole of front face **204** is provided with adhesive. With this arrangement, the front surface of each flap **210**, **211**, **212**, **213** is provided with adhesive. Each flap **210**, **211**, **212**, **213** presents an adhesive surface that will stick to a human finger. This feature functions to reduce the risk of the backplate dropping behind a building panel during positioning for mounting.

Figure 6

[0026] A fourth step in using repair apparatus **201** is illustrated in *Figure 6*. The backplate **202** is mounted to the building panel **502** to be repaired.

[0027] The front face **204** of the backplate **202** is adhered to the rear side of the building panel **502**. As shown, a building operative can achieve this by orienting front face **204** of backplate **202** to face the rear side of the building panel **502**, hooking a finger through a flap aperture, for example flap aperture **601**, and pulling backplate **202** forward into contact with the building panel **502**; as indicated by arrow **602**. Alternatively, the pulling action can be effected whilst holding the backplate **202** using the flaps **210**, **211**, **212**, **213**.

[0028] Dotted line boundary 603 indicates the position of the edges of the backplate 202 relative to the hole 501 in the building panel 502 following mounting.

Figure 7

[0029] A cross-section view of Figure 6 is shown in Figure 7. By hooking a finger 701 through a flap aperture, for example flap aperture 702, of backplate 202 building operative 301 can press the backplate 202 into contact with the rear side 703 of building panel 502 directly. This feature functions to increase the security of the mounting of the backplate to the building panel.

[0030] In addition, the feature of substantially the whole of front face 204 being provided with adhesive also functions to increase the security of the mounting by increasing the potential area of the backplate 202 adhered to the building panel during mounting. This adhesive arrangement is particularly useful in the instance that a dry patch of plasterboard can be inserted into the repair, with the repair being completed by a plaster skim around the edges. Such an adhesive arrangement is also useful in the instance that prior cleaning of the rear side of the building panel to which the backplate is to be mounted has not been performed, and the rear side of the building panel has dust or debris attached.

[0031] The backplate can also be fixed in position using screws, for example standard plasterboard screws. This feature is particularly useful in cases where the rear side of the building panel is damaged or damp. A screw fixing to secure the backplate to the building panel provides for a repair that is as effective as when the backplate is secured by adhesive only.

Figure 8

[0032] In Figure 8, a fifth step in using repair apparatus 201 is illustrated. Following installation, the flaps 210, 211, 212, 213 of backplate 202 are recond to provide a substrate surface for hole repair material. Each of the flaps 210, 211, 212, 213 is moved from the open position shown in Figure 4, into a closed position, preferably the fully closed position shown in Figure 2.

[0033] As shown, a building operative 301 can achieve reconfiguration of the flaps 210, 211, 212, 213 from the open position into the closed position by pushing the front of a flap 210, 211, 212, 213 from the front face side of the backplate 202 backwards into the plane of the front face 204 of backplate 202 to close the associated flap aperture.

[0034] As previously described, each flap 210, 211, 212, 213 presents an adhesive surface to which a human finger may stick. However, an operative may wish to prevent a finger sticking to a flap, for example to facilitate removal of the finger following flap closure. An operative can establish a dust barrier against the adhesive by drawing a fingertip along the chalky edge of the hole to be repaired or other dusty area.

[0035] The repair apparatus may also feature at least one flap with directional fold. According to the present embodiment, each of the flaps 210, 211, 212, 213 of repair apparatus 201 has directional fold, the flap being inhibited from being movable through the backplate 202. In particular, backplate 202 is cond to inhibit each flap 210, 211, 212, 213 from being movable from the closed position through to the rear face side of the backplate 202. This feature functions to facilitate the reconfiguration of each flap 210, 211, 212, 213 of the mounted backplate 202 into the closed position, by inhibiting movement beyond the fully closed position.

[0036] With the flaps 210, 211, 212, 213 in the closed position, the exposed area of the front face 204 is effectively substantially continuous, with the exception of the array of repair material apertures 214.

[0037] The mounted backplate functions to provide a stable surface to which curable hole repair material can be applied. The backplate serves to maintain the hole repair material in position until cured, and then to provide support for the cured hole repair material.

Figure 9

[0038] A sixth step in using the repair apparatus 201, in which curable hole repair material is applied to the mounted backplate of Figure 8, is illustrated in Figure 9. As shown, a building operative 301 can achieve this by loading hole repair material 901 onto a trowel 902 and then applying the hole repair material 901 to the exposed area of front face 204 of mounted backplate 202 using the trowel 902; as indicated by arrow 903. In this example, hole repair material 901 is plaster of paris.

Figure 10

[0039] Figure 10 shows a cross-section view of hole repair material being applied to the mounted backplate 202 of Figures 8 and 9. As shown, the repair material apertures of repair material aperture array 214, for example repair material aperture 1001, are each arranged to receive hole repair material 901.

[0040] As hole repair material 901 is applied to front face 204 of backplate 202, in addition to being received in repair material aperture 1001, hole repair material 901 may flow through the backplate 202 to the rear face 1002 of the backplate 202. It is then acted upon by gravity to a degree depending on the composition and consistency of the hole repair material, encouraging further flow. This feature functions to interlock the backplate with the hole repair material.

[0041] As previously described, backplate 202 has a twin wall structure. Backplate 202 has a substantially hollow construction allowing hole repair material 901 received in a repair material aperture 1001 to flow downwards between the walls 1003, 1004 under gravity. This feature functions to interlock backplate 202 with hole repair material 901. The arrangement of the connecting

members of the backplate may encourage downward flow of hole repair material. According to the example shown, the connecting members of backplate **202** are spaced apart substantially parallel with each other, in the orientation shown, extending substantially vertically.

Figure 11

[0042] *Figure 11* shows a cross-section view of hole repair material **901** being applied to mounted backplate **202** in an alternative scenario in which the flaps **210, 211, 212, 213** are not in the fully closed position. With the flaps **210, 211, 212, 213** extending in a different plane to that of backplate **202**, hole repair material **901** may flow into the gap between each flap **210, 211, 212, 213** and the backplate **202**. In addition, due to the twin wall construction of backplate **202**, hole repair material **901** may flow into the flaps **210, 211, 212, 213**. These features function to interlock backplate **202** with hole repair material **901**. Interlocking of the backplate with the hole repair material provides for a more secure repair.

Figure 12

[0043] *Figure 12* shows the repair **1201** in building panel **502**, using repair apparatus **201** and hole repair material **901** in accordance with the method as described with reference to *Figures 3* to *11*.

[0044] Dotted line boundary **603** indicates the position of the edges of the backplate **202** relative to the hole **501** in the building panel **502**. Line **1202** indicates the boundary of the applied hole repair material **901**. A sufficient quantity of hole repair material **901** has been applied to the backplate **202** to fill the cavity between the front face **204** of backplate **202** and the front side of the building panel **502**. Additional hole repair material **901** has been spread across the restored cavity, beyond the boundary of the hole **501** onto the front face of building panel **502** to seal the repair. A satisfactory repair can be attained using traditional plaster or patch compound. Typically, two coats of hole repair material will be expected to complete a satisfactory repair.

[0045] The adhesive on the front face **204** of backplate **202** provides a surface to which hole repair material may adhere more strongly than the surface of the backplate, depending upon the material composition the backplate, adhesive and hole repair material. This feature functions to facilitate the application of hole repair material to the backplate and functions to improve the uniformity of hole repair material distribution throughout the cavity. In this example, hole repair material **901** is plaster of paris, which will adhere well to the plaster of the side walls of the cavity being filled. This adhesion around the edges of the cavity is complemented by adhesion of the hole repair material **901** to the front face **204** of backplate **202**, helping to support the material during curing.

Figure 13

[0046] *Figure 13* illustrates a patch **1301** in a plaster board wall **1302** requiring repair. The patch **1301** defines an irregular shaped hole **1303**. In this example, the patch **1301** represents crush damage to the wall **1301**. Such damage may result from mishandling or impact, for example by a forklift truck. The paper covering of the wall **1302** has ripped, the edges of the hole **1303** are distressed and the inside face of the hole **1303** has partially collapsed around the edges. Thus, the damage has lessened the integrity of the wall strength.

[0047] To prepare the wall **1302** for repair using repair apparatus **201**, at least the whole damaged area is cut out from the wall **1302**. This leaves behind a larger hole, indicated by dotted line **1304**, around which the wall **1302** is undamaged. The repair apparatus **201** may then be installed as described with reference to *Figures 3* to *8*.

Figure 14

[0048] *Figure 14* illustrates a repair in an internal wall **1401**, using repair apparatus **201**. The size of the repaired hole **1402** in the wall is greater than that repairable by a single repair apparatus **201**. However, repair has been achieved by using a second additional repair apparatus **1403**. In this example repair apparatus **1403** is identical to repair apparatus **201**.

[0049] The backplates of the two repair apparatus **201, 1403** are mounted to the wall **1401** effectively by three sides each, and are positioned to lie alongside each other to provide a substantially continuous substrate surface.

[0050] Repair apparatus **201** is cond to be mounted to a wall effectively by only two sides of the backplate, allowing large holes in a building panel to be repaired using three or more repair apparatus. Such a hole may be left in a building panel following removal of, for example, an air vent or fusebox.

Figure 15

[0051] As shown in *Figures 2* and *15*, flaps **210, 211, 212, 213** of repair apparatus **201** are arranged substantially symmetrically about centreline **1501** of backplate **202**, with each pair of flaps **210, 211** and **212, 213** located substantially centrally of each half of the backplate **202**. Repair material aperture array **214** is located substantially symmetrically about centreline **1501**.

[0052] With this arrangement, halving backplate **202** along centreline **1501** produces two substantially identical smaller backplates, each having a pair of flaps and a plurality of repair material apertures.

[0053] For example, backplate **202** may be dimensioned for use in repairing a hole in a building panel made by the removal of a double electrical socket fitting, and when halved provides two backplates each dimensioned for use in repairing a hole in a building panel made by the removal of a single electrical socket fitting.

[0054] Preferably, the backplate of the repair apparatus can be manually cut with a domestic purpose tool. The construction of backplate **202** allows building operative **301** to cut the backplate using a pair of domestic purpose scissors **1502**, as shown.

[0055] To facilitate division, backplate **202** may be provided with one or more score lines, for example on the front face **204** along centreline **1501**.

[0056] As previously described, the twin wall structure of backplate **202** comprises two walls spaced apart by connecting members extending therebetween. The arrangement of the connecting members may facilitate cutting in a particular direction and/or hinder cutting in a particular direction along the backplate.

Figure 16

[0057] Alternatively, as illustrated in *Figure 16*, the backplate **202** of repair apparatus **201** can be cut with a knife. As described previously, substantially the whole of front face **204** is provided with adhesive. This feature enables the backplate **202** to be cut into any desired shape, and still be mountable to a building panel.

[0058] *Figure 16* illustrates a hole **1601** in a plasterboard wall **1602**. Plasterboard walls are typically constructed on a timber frame, known as studding. A hole requiring repair may be formed in the wall immediately adjacent to a studding member which may potentially interfere with the installation of repair apparatus.

[0059] In *Figure 16*, hole **1601** is immediately adjacent studding member **1602**. In this example, trimming of one side of repair apparatus **201** is required to enable installation. As shown, building operative **301** has sliced off a portion **1603** of the backplate of repair apparatus **201** to enable the repair apparatus to be mounted to the wall **1601** such that the array of repair material apertures **214** is located substantially centrally of the hole **1601**. As described with reference to *Figure 14*, repair apparatus **201** is constructed such that the mounting of the backplate following trimming is stable.

Figure 17

[0060] *Figure 17* shows a building panel **1701** having a prior repair **1702**, in which an aperture, indicated by dotted line **1703**, has been repaired using repair apparatus **201**, the mounted position of which is indicated by dotted line **1704**. A new aperture is required in the building panel **1701**, for example to allow fitting of an electrical socket. In this example, the boundary of the required new aperture, indicated by dotted line **1705**, overlaps the mounted backplate **202** of the prior repair **1702**. However, there is no problem in defining the new aperture since backplate **202** can be manually cut.

[0061] As shown, building operative **301** can create the required aperture in building panel **1701** by cutting out building panel portion **1706** bounded by hole perimeter line **1705**, in this example using a saw **1707** or similar

tool, and cutting off the overlapped portion **1708** of backplate **202**.

[0062] Thus, the repair apparatus allows an aperture in a building panel to be relocated from a first area to a second area that overlaps the first area, following repair of the first area using the repair apparatus.

Figure 18

[0063] *Figure 18* shows a cross-section view of repair **1201**. As shown, the repair **1201** allows a mounting member, such as screw **1801**, to be used in that area of the building panel. The hole repair material **901** allows penetration by a mounting member. The backplate **202** of the repair apparatus **201**, which is effectively incorporated into the building panel structure, may be punctured by a mounting member such that the backplate **202** does not present a blockade to the mounting member. The integrity of the repair **1201** is sufficient to withstand, for example, a picture being mounted on the wall **502** using a mounting member installed in the repair **1201**.

Figure 19

[0064] *Figure 19* shows a first step in the manufacture of a repair apparatus. A backplate sheet **1901** is positioned to receive visual graphics, thereafter applied to a rear face **1902** thereof. In this example, a plurality of backplates is produced from backplate sheet **1901**.

[0065] Preferably, the backplate sheet is fabricated from a material that is lightweight, to facilitate transport and manual handling of the resultant repair apparatus, and to reduce strain on the mounting of a backplate to a building panel.

[0066] Preferably, the backplate sheet material is relatively inflexible, to provide the repair apparatus with a backplate presenting in use a stable substrate surface for hole repair material. Preferably, however, the backplate sheet material can tolerate a degree of flexing, to reduce cracking of the resultant repair apparatus and to facilitate mounting of a backplate to a building panel.

[0067] Preferably, the backplate sheet material is water impermeable, to reduce the risk of water damage of the repair apparatus during transport or use. Furthermore, this feature functions to reduce dehydration of applied hole repair material, which can result in cracking in the cured hole repair material.

[0068] Preferably, the backplate sheet material allows the backplate to be manually cut using a domestic purpose tool. A suitable thickness of a backplate sheet to produce a backplate suitable for domestic use is in the range 3.5-6.5mm.

[0069] As previously described, backplate **202** of repair apparatus **201** is fabricated from twin wall plastic board. A suitable twin wall plastic board having a polypropylene component is available under the tradename Correx TM from D S Smith Plastics, England. This product displays preferred characteristics described above.

Polypropylene is resistant to water, dirt or chemical ingress. The high strength to weight ratio of polypropylene provides a board that is resistant to bending and deformation and is sufficiently robust to withstand conditions typically encountered in a building site environment. However, polypropylene based board is relatively easy to die cut and provides for cost effective small volume manufacture; at present die cutting process tooling is relatively inexpensive compared to plastic injection moulding tooling. Further, the use of polypropylene in the building industry is favoured due to the material being recyclable. Alternative suitable backplate materials include cardboard, laminated card and plywood.

[0070] The application of visual graphics, for example illustrated instructions for use, may be performed by a screenprinting process, a lithoprinting process or by the application of stickers or transfers. Alternatively, a flexoprinting process, which utilises rollers, may be used and at present this process is cheaper than screenprinting and lithoprinting processes. Polypropylene board is identified as being a workable material in surface printing applications.

Figure 20

[0071] Figure 20 shows a second step in the manufacture of a repair apparatus. Adhesive 2001 is applied to the front face 2002 of backplate sheet 1901; as indicated by arrow 2003. In this illustrated example, adhesive is distributed across substantially the whole of the front face 2002 of backplate sheet 1901, either as a substantially continuous or patterned layer. In accordance with the arrangement of adhesive of repair apparatus 201, substantially the whole of the front face of each backplate produced from backplate sheet 1901 will be provided with adhesive.

[0072] According to a first alternative arrangement of adhesive, the front face of a backplate is provided with adhesive along the edges only. According to a second alternative arrangement of adhesive, the front face of a backplate is provided with adhesive in each corner only.

[0073] As previously described, the front face 204 of backplate 202 is provided with two-sided adhesive tape. Suitable adhesive tape is available under the tradename 3M Scotch 300 LSE (low surface energy) high strength adhesive tape available from Parafix Tapes & Conversions Limited, United Kingdom and most major tape suppliers. Preferably, the depth and/or quality of the applied adhesive is sufficient to tolerate any dirt or debris on a mounting surface.

[0074] The adhesive applied to the backplate provides a bonding surface and provides a key for hole repair material. Additionally, hole repair material may adhere to the adhesive surface more strongly than to the surface of the backplate, depending upon the material composition the backplate, adhesive and hole repair material. For example, bonding between hole repair material and adhesive is stronger than bonding between hole repair ma-

terial and polypropylene. Thus, in embodiments utilising Correx TM board, the adhesive improves the integrity of the repair.

Figure 21

[0075] Figure 21 shows a third step in the manufacture of a repair apparatus. A plurality of backplates 2101, 2102, 2103, 2104 are defined in backplate sheet 1801. Each backplate 2101, 2102, 2103, 2104 has at least one flap, for example flap 2105, and additionally at least one repair material aperture, for example repair material aperture 2106.

[0076] Different arrangements of flaps to that illustrated in the accompanying figures are utilisable. For example, outwardly opening flaps may be defined in a backplate or flaps opening in different directions. The location of a flap or flaps defined in a backplate relative to another or edges of the backplate may also vary, and flaps of different sizes are utilisable.

[0077] Each of the defining cuts performed at this step may be achieved using a die cutting process. Cuts may be performed from either side of the backplate sheet. Cuts may be square through the backplate sheet, where the die cutting meets the board normal thereto or cuts may be made at an angle to the board to form a chamfered edge, for example to assist in the creation of flaps with directional fold. Alternatively, chamfered edges may be formed by a plastic injection moulding process.

[0078] Flaps with directional fold may be formed in a twin wall plastic backplate by the stamping of a crease on one side of the backplate only during the die cutting process, the blade of the die cutting tool deforming the material rather than cutting completely through it.

[0079] Preferably the diameter of a repair material aperture is in the range 4.5-8.5mm. An array of repair material apertures may be formed from apertures having different diameters. Suitable width and length dimensions for a backplate for use in repairing a hole in a building panel made by the removal of a double electrical socket fitting are approximately 120mm and 180mm respectively. To repair a hole in a building panel having width and length dimensions up to 0.1016m square, a backplate having width and length dimensions of 0.1524m square would be sufficient.

Figure 22

[0080] Figure 22 shows a fourth step in the manufacture of repair apparatus 201. The backplates 2101, 2102, 2103, 2104 are separated from backplate sheet 1901. This may be achieved using a suction or stamping process.

[0081] Removal of areas of a backplate, for example the removal of material to form a repair material aperture, may be performed using a suction or stamping process or may be performed manually. Thus, removal of backplate material may be performed prior to packaging or

retail or may be left for a building operative to remove prior to use.

Figure 23

[0082] A repair apparatus **2301** having a square rectangular shape is shown in *Figure 23*. In a similar scenario to that shown in *Figure 1*, a wall **2302** has a hole **2303** therein requiring repair.

Figure 24

[0083] *Figure 24* shows an enlarged view of repair apparatus **2301**. In this example, the repair apparatus has length and width dimensions of six inches (~0.1524m) square. This size of backplate is suitable for repairing aperture **2303**, which in this example has length and width dimensions of four inches (~0.1016m) square.

[0084] Repair apparatus **2301** defines repair material apertures including a plurality of repair material apertures aligned along a first axis such that said backplate is pre-disposed to bend along the first axis.

[0085] It can be seen from *Figure 24* that repair material apertures **2401**, **2402**, **2403** and **2404** each lie upon the same bend axis **2405** of backplate **2406**. In this example, first bend axis **2405** is a centreline of backplate **2406**. The provision of apertures aligned along an axis introduces a line of weakness to the backplate that renders the backplate less resistant to folding, to the effect that the backplate will tend to flex along the weakened axis.

[0086] A repair apparatus may be provided with apertures aligned to form more than one bend axis. For example, repair material apertures **2407**, **2408**, **2409** and **2410** of repair apparatus **2301** are aligned along second bend axis **2411** of backplate **2406**. Second bend axis **2411** extends in a direction perpendicular to bend axis **2405**, and the bend axes **2405** and **2411** intersect. In an alternative arrangement, a repair material aperture is provided at the point of intersection of bend axes. It is to be appreciated that different arrangements of apertures may be utilised to provide different arrangements of bend axes. For example, a repair apparatus may be provided with a plurality of bend axes that do not intersect.

Figure 25

[0087] *Figure 25* shows repair apparatus **2301** responding to manually applied pressure. Repair apparatus **2301** is being held in one hand **2501** only, gripped between the thumb **2502**, which is in contact with a first edge **2503** of the backplate **2407**, and the fingers **2504**, which are in contact with the opposite edge **2505** of the backplate **2407**. Under a squeezing action effected by hand **2501**, the backplate of the repair apparatus flexes to fold along bend axis **2406**, which extends between the opposite edges **2503**, **2505**.

[0088] In some situations, flexing of a repair apparatus

facilitates insertion of the repair apparatus through an aperture in a building panel. The provision of a bend axis, through the positioning of apertures in the backplate, confers control to an operative over the bending or flexing of the repair apparatus. This feature serves to add to the convenience of using the repair apparatus.

[0089] In the example of *Figure 25*, the bending of backplate **2407** enables the repair apparatus **2301** to be inserted through a circular aperture **2506** in a building panel **2507** that has a diameter which is less than the minimum measurement across the backplate **2407**. Thus, in some cases the bend axis feature of the repair apparatus serves to reduce the amount of preparation prior to performing repair of a building panel using the repair apparatus. The bend feature may obviate a necessity to either increase the size of an aperture to be repaired or reduce the size of the repair apparatus. This feature is particular useful when repairing apertures having an irregular shape.

Figure 26

[0090] In some circumstances it is desirable for an inner region of a repair apparatus to be removed, for example to accommodate a pipe or other obstacle extending behind the building panel being repaired. A repair apparatus may have the perimeter of at least one region of the backplate delineated to facilitate manual removal of that region from the backplate. The perimeter of a region of the backplate may be delineated by a visual representation, such as a continuous line, and/or by perforations and/or by scoring. The perimeter of a region may be marked out on the front face of the backplate, for example on the removable backing, or on the rear face of the backplate. The same or different outlines may be presented on the front and rear faces of the backplate.

[0091] *Figure 26* shows a repair apparatus **2601**. On the front face **2602** of the backplate **2603**, the perimeter of each of a plurality of concentric circular regions is delineated.

[0092] In this example, the smallest circle **2604** is substantially central of the backplate **2603** and the perimeter of each of some of the larger circles extend across repair material apertures defined in the backplate **2603**, for example the perimeter of circle **2605** extends across repair material aperture **2606**.

[0093] A line **2607** is also presented on the front face **2602** of the backplate **2603** that extends from an edge **2608** of the backplate **2603** to the smallest circle **2604**, indicating a cut line to facilitate cutting out of an inner region of the backplate.

[0094] It is to be appreciated that different repair apparatus may have different arrangements of regions outlined, including different shapes, sizes and overlapping of different outlines. The outlining of a cut line and inner region(s) of the backplate assists an operative in cutting out the desired shape neatly. An inner region may be cut using scissors, a knife or other cutting tool.

Figure 27

[0095] *Figure 27* shows repair apparatus **2601** prepared for use in the repair of an aperture **2701** in a building panel **2702** through which a utility pipe **2703** extends.

[0096] Preparation of the repair apparatus **2601** includes the steps of cutting along line **2607**, cutting out and removing an inner region **2704** of the backplate **2603** to leave behind an aperture **2705**, and exposing the adhesive on the front face **2602** of the backplate. With the inner region **2704** of the backplate **2603** removed, the backplate **2603** can be located behind the building panel **2702** around the utility pipe **2703**.

[0097] The backplate **2603** is shown folded along a bend axis **2706**, which extends through the aperture **2704**. Whilst bent, the repair apparatus **2601** can be inserted into the aperture **2701** in the building panel **2702** to one side of the utility pipe **2703**, in this illustrated example over the top of the pipe **2703**. The backplate **2603** can be then be located around the utility pipe **2703** by spreading out the parts of the backplate **2603** either side of the cut line **2607** and manipulating the backplate **2603** to bring these parts around either side of the pipe **2703**.

[0098] The repair apparatus **2601** may then be positioned against the rear surface of the building panel **2702** and secured as previously described. Dotted line **2707** around aperture **2701** in building panel **2702** indicates the finish position of the backplate **2603** relative to the aperture **2701**.

[0099] As illustrated in *Figure 1*, a plurality of repair apparatus may be joined together, for convenient transport and storage. A plurality of repair apparatus may be tied together by a cord or tie-wrap threaded through a flap aperture in each repair apparatus. A plurality of repair apparatus each defining at least one repair material aperture may be joined together on a cord or a tie-wrap threaded through a repair material aperture in each repair apparatus. Alternatively, a two-piece fastener may be used. Such a fastener may be an injection moulded polythene stud fastener having a male connecting part that releasably connects to a female connecting part. Using a fastener having a repeatedly separable/connectable part to group a plurality of repair apparatus together allows an operative to disconnect the part, remove a repair apparatus, and then group the remaining repair apparatus together using the same fastener, by reconnecting the part. A repair material aperture or flap aperture in a backplate may also be used to hang the repair apparatus in a retail or storage environment.

[0100] Thus, the repair apparatus is convenient for an operative to transport and store and is quick and easy to use. The simplicity of the construction of the repair apparatus and the quick and simple associated method of use is advantageous in poor light conditions and cluttered environments.

[0101] The repair apparatus functions to provide a substantially planar uniform substrate surface on which to apply hole repair material. This feature functions to pro-

vide the cavity to be filled with a uniform depth, to reduce cracking of applied hole repair material during curing caused by different curing rates within the cavity due to different depths of hole repair material within the cavity.

5 The uniformity of the substrate surface functions to facilitate the application of a regular distribution of hole repair material within the cavity. This feature provides the advantage that the quantity of hole repair material required to fill the hole can be more accurately determined prior to the repair being carried out.

10 [0102] The repair apparatus provides a relatively inflexible substrate surface to support hole repair material. It is desirable to reduce movement of the substrate surface that will result in cracking of applied hole repair material. For example, flexing of a mounted backplate may weaken the security of the mounting of the backplate to the building panel, which in turn may result in the repair being more susceptible to post repair damage caused by the repair failing under force applied thereto.

15 [0103] The building operative practised in the use of the repair apparatus will become knowledgeable regarding the time required to install the repair apparatus, the quantity of hole repair material required to complete a particular type of repair, the consistency of the hole repair material to be used for ease of application and to avoid cracking during curing, and the cure time of a particular type of building panel repair. Thus, the repair apparatus is cond to reduce variability in performing building panel repair and improve the reliability of the repair. This provides increased control over the duration to complete a repair, the quality of a repair and the cost per repair.

20 [0104] Preferably, the repair apparatus is manufactured to be applicable for use in providing a repair that would conform to one-hour fire rating regulations with a dry patch repair. To achieve this, a repair compound suitable for such purpose should be used.

Claims

40 1. Apparatus (**201**) for use in building panel repair comprising a substantially planar backplate (**202**) for insertion through a hole in a building panel to be repaired, a front face (**204**) of the backplate being provided with adhesive for mounting the backplate to the rear side of a building panel; **characterised in that** at least one flap (**210**) is defined in said backplate movable between:

50 a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel; and a second closed position providing a substrate surface for hole repair material.

55 2. Apparatus according to claim 1 configured to inhibit a flap from being movable from one side of said backplate through said backplate to the other side of said

backplate.

3. Apparatus according to claim 1 or claim 2 wherein a flap is defined on each side of a centreline of said backplate. 5
4. Apparatus according to claim 3 wherein said backplate defines a first pair of flaps on one side of said centreline of said backplate, and a second pair of flaps on the other side of said centreline, the flaps of each of said first pair and said second pair open in the same direction as each other, and the flaps of said first pair open in a different direction to the flaps of said second pair. 10
5. Apparatus according to claim 4 wherein said flaps open inwardly towards the centre of the backplate. 15
6. Apparatus according to any preceding claim wherein at least one repair material aperture (214) is defined in said backplate for receiving curable hole repair material. 20
7. Apparatus according to claim 6 wherein said backplate defines a plurality of repair material apertures aligned along a first axis such that said backplate is predisposed to bend along said first axis. 25
8. Apparatus according to any preceding claim wherein said backplate has a rectangular shape. 30
9. Apparatus according to any preceding claim wherein said adhesive comprises two-sided adhesive tape having one side adhered to the front face of said backplate and the opposite side for adhering to a building panel being provided with a removable backing. 35
10. Apparatus according to claim 1 wherein adhesive is distributed across substantially the whole of the front face of said backplate. 40
11. Apparatus according to any preceding claim wherein said backplate is fabricated from water impermeable material. 45
12. Apparatus according to any preceding claim wherein said backplate is fabricated from plastic.
13. Apparatus according to claim 12 wherein said backplate is fabricated from twin wall polypropylene board. 50
14. Apparatus according to any preceding claim wherein the perimeter of at least one region of said backplate is delineated by means of at least one of: a visual representation, perforations and a score line, to facilitate manual removal of said region from the back-

plate.

15. Apparatus according to claim 14 wherein the perimeter of each of a plurality of concentric circular regions of said backplate is delineated. 5
16. Apparatus according to any preceding claim having at least one score line across said backplate to facilitate division of said backplate.
17. A method of building panel repair using apparatus (201) comprising a substantially planar backplate (202) for insertion through a hole in a building panel to be repaired, a front face (204) of the backplate being provided with adhesive for mounting the backplate to a rear face of a building panel; wherein at least one flap (210) is defined in said backplate movable between a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel and a second closed position providing a substrate surface for hole repair material, said method **characterised** by the steps of:
 - a) inserting the backplate through a hole in a building panel;
 - b) with a flap in said first open position, positioning the front face of said backplate to face the rear face of said building panel;
 - c) with the adhesive provided on the front face of the backplate exposed, pulling the front face of the backplate against the rear face of the building panel to mount said backplate;
 - d) moving said flap into said second closed position; and
 - e) applying hole repair material to the exposed surface of the mounted backplate.
18. A method according to claim 17 wherein said adhesive comprises two-sided adhesive tape having one side adhered to the front face of said backplate and the opposite side for adhering to a building panel being provided with a removable backing, and said method further comprises the step of removing said removable backing.
19. A method according to claim 17 wherein said backplate defines a plurality of repair material apertures (214) aligned along a first axis such that said backplate is predisposed to bend along said first axis and said method further comprises the step of bending said backplate along said first axis to facilitate inserting the backplate through a hole in a building panel.
20. A method according to claim 17 wherein the perimeter of a region of said backplate is delineated to facilitate manual removal of said region from the backplate and said method further comprises the

step of removing said region from said backplate.

21. A method of manufacturing apparatus (201) comprising a substantially planar backplate (202) for insertion through a hole in a building panel to be repaired, a front face (204) of the backplate being provided with adhesive for mounting the backplate to a rear face of a building panel; wherein at least one flap (210) is defined in said backplate movable between a first open position providing an operative with backplate positioning means to facilitate mounting of the backplate to a building panel and a second closed position providing a substrate surface for hole repair material, said method **characterised by** the steps of:

- a) adhering one side of two-sided adhesive tape to one side of a backplate sheet; and
- b) cutting through said backplate sheet to define at least one flap.

22. A method according to claim 21 wherein a plurality of flaps are defined at step b) and said method further comprises the step of dividing the backplate sheet into a plurality of said apparatus.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26




Figure 27



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 05 25 4265

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	CA 1 319 236 C (MERIC INDUSTRIES, INC) 22 June 1993 (1993-06-22)	1,8,9,21	E04G23/02
Y	* pages 3-4; figure 4A *	12-15	

Y	US 4 285 183 A (CONDIT ET AL) 25 August 1981 (1981-08-25)	12	
	* column 2, lines 6-15; figure 2 *		

D,A	US 4 193 243 A (TINER, FRANCIS L) 18 March 1980 (1980-03-18)	1-22	
Y	* column 3, lines 63-67 *	13	

A	US 5 778 624 A (RUSSELL ET AL) 14 July 1998 (1998-07-14)	1,2,8,9, 17,18	
	* column 2, lines 26-35 *		
	* column 3, line 66 - column 4, line 5 *		

Y	US 4 083 258 A (HAMMETT ET AL) 11 April 1978 (1978-04-11)	14,15	
	* column 2, lines 33-57; figure 3 *		

			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			E04G
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 20 October 2005	Examiner Saretta, G
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

3

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 05 25 4265

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-10-2005

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
CA 1319236	C	22-06-1993	NONE	
US 4285183	A	25-08-1981	NONE	
US 4193243	A	18-03-1980	NONE	
US 5778624	A	14-07-1998	NONE	
US 4083258	A	11-04-1978	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82