

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 640 220 A8

(12)

CORRECTED EUROPEAN PATENT APPLICATION

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 72

(51) Int Cl.:

B60R 21/01 (2006.01)

(48) Corrigendum issued on:

02.08.2006 Bulletin 2006/31

(43) Date of publication:

29.03.2006 Bulletin 2006/13

(21) Application number: **05108666.8**

(22) Date of filing: **20.09.2005**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**

Designated Extension States:

AL BA HR MK YU

(30) Priority: **24.09.2004 JP 2004277697**

(71) Applicant: **Keihin Corporation**

Shinjuku-ku, Tokyo (JP)

(72) Inventors:

- Yuan, Fang,**
Keihin Corp., Tochigi R&D Dev. Ctr.
Takanezawa-machi, Shioya-gun, Tochigi-ken (JP)
- Oosaki, Tatsuji**
Keihin Corp., Tochigi R&D Dev. Ctr.
Takanezawa-machi, Shioya-gun, Tochigi-ken (JP)

(74) Representative: **Poulin, Gérard et al**

BREVALEX

3, rue du Docteur Lancereaux

75008 Paris (FR)

(54) Collision determining apparatus for a vehicle

(57) A collision determining apparatus for a vehicle includes: a first acceleration measuring device (12); a second acceleration measuring device (21); a first change in movement speed calculating device (26) which calculates a first change in movement speed; an interval integral value calculating device (29); a second change in movement speed calculating device (23); a first collision determining device (28); a continuation determining

device (31); a second collision determining device (25); a collision determination continuing device (32) which sets a collision continuation determining value to an ON state or OFF state based on the first change in movement speed and the interval integral value; and a control signal generating device (34) which generates a control signal instructing that an occupant protection apparatus be operated based on the collision continuation determining value and the second change in movement speed.

