



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 640 893 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A2)
INID code(s) 30

(51) Int Cl.:

G06K 19/077 (2006.01) **G06K 19/00** (2006.01)
H01Q 7/00 (2006.01) **H01Q 7/06** (2006.01)
H01Q 1/38 (2006.01) **H01Q 1/22** (2006.01)
H01Q 9/27 (2006.01)

(48) Corrigendum issued on:

07.06.2006 Bulletin 2006/23

(43) Date of publication:

29.03.2006 Bulletin 2006/13

(21) Application number: **05028729.1**

(22) Date of filing: **18.12.2001**

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

(30) Priority: **18.12.2000 JP 2000383102**

03.12.2001 JP 2001368241

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:

01271675.9 / 1 347 533

(71) Applicant: **MITSUBISHI MATERIALS**
CORPORATION

Chiyoda-ku,
Tokyo 100-8117 (JP)

(72) Inventors:

- **Endo, Takanori,**
c/o Mitsubishi Materials Corp.
Bunkyo-ku,
Tokyo (JP)

- **Yonezawa, Tadashi,**
c/o Mitsubishi Materials Corp.
Bunkyo-ku,
Tokyo (JP)
- **Yahata, Seiro,**
c/o Mitsubishi Materials Corp.
Bunkyo-ku,
Tokyo (JP)

(74) Representative: **HOFFMANN EITLE**
Patent- und Rechtsanwälte
Arabellastrasse 4
81925 München (DE)

Remarks:

This application was filed on 30 - 12 - 2005 as a
divisional application to the application mentioned
under INID code 62.

(54) **Antenna for RFID tag**

(57) An antenna for RFID tag which can be mounted
directly on the surface of a management object without
using a spacer whatever material the surface of the object
might be made of. This antenna for RFID tag (34) is elec-
trically connected with an IC chip and mounted on an
article (11). The antenna for RFID tag (34) comprises a
soft magnetic member (26) formed into a flat plate and

mounted on the article (11) at its back and a coil body
(14b) fixed directly or with a predetermined spacing on
the soft magnetic member, spirally wound and having
such a number of turns or a diameter that it has a pre-
determined characteristics value in the wound state.

EP 1 640 893 A8

FIG. 6

