



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 653 565 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:

**Corrected version no 1 (W1 A2)**  
**Remarks**

(51) Int Cl.:

**H01R 13/629 (2006.01)**

(48) Corrigendum issued on:

**13.12.2006 Bulletin 2006/50**

(43) Date of publication:

**03.05.2006 Bulletin 2006/18**

(21) Application number: **06101282.9**

(22) Date of filing: **26.03.2002**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE TR**

Designated Extension States:

**AL BA HR MK YU**

• **Pizzarelli, Rocco**

**10036, SETTIMO TORINESE (IT)**

• **Girard, Fausto**

**10152, TORINO (IT)**

(30) Priority: **27.03.2001 IT TO20010290**

(62) Document number(s) of the earlier application(s) in  
accordance with Art. 76 EPC:

**02735181.6 / 1 396 052**

(71) Applicant: **FCI**

**78000 Versailles (FR)**

(74) Representative: **Jorio, Paolo et al**

**Studio Torta S.r.l.**

**Via Viotti, 9**

**10121 Torino (IT)**

(72) Inventors:

• **Stella, Gianni**


**10141, TORINO (IT)**

Remarks:

This application was filed on 03 - 02 - 2006 as a  
divisional application to the application mentioned  
under INID code 62.

(54) **ELECTRIC CONNECTOR**

(57) An electric connector (2') adapted to be coupled to a complementary connector (3) along a first direction (A) and comprising an insulating casing (4) having cavities for electric terminals, a slide (16) fitted to the casing (4) to slide in a second direction (B) perpendicular to the first direction (A), and having cam grooves (22) for receiving respective engaging members (23) on the complementary connector (3) to produce a coupling movement of the connectors (2'; 3) in the first direction (A) upon movement of the slide (16) in the second direction (B) into a fully assembled position, and at least one elastically flexible member (71) which projects from the slide (16), cooperates with an interacting portion (72) of the casing (4) to prevent the slide (16) from moving into the fully assembled position, and is releasable from the interacting portion (72) in a deformed configuration set by correct coupling among the grooves and the engaging members (22, 23).



EP 1 653 565 A8