(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

16.08.2006 Bulletin 2006/33

(51) Int Cl.:

A63B 21/062 (2006.01)

(21) Application number: 05002681.4

(22) Date of filing: 09.02.2005

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

Designated Extension States:

AL BA HR LV MK YU

(71) Applicant: Kuo, Hai Pin Tainan City (TW) (72) Inventor: Kuo, Hai Pin Tainan City (TW)

(74) Representative: Casalonga, Axel et al Bureau Casalonga & Josse Bayerstrasse 71/73 80335 München (DE)

(54) Counterweight exercise machine

A counterweight exercise machine has a frame. The frame comprises two main guide rods; two sub-guide rods; a passive rod parallel to the two main guide rods; at least one main weight; a selector; a base having a lower substrate and an upper substrate; and two sleeves connected to the lower substrate and the upper substrate; at least one pin capable of passing through the round holes of the front sheet and the rear sheet and the passive rod; and at least one sub-weight. By above mentioned components, the selector serves to lock a predetermined number of main weights and the pin inserts into the sub-weight so as to increase the total weight. A force applied unit serves to drive the passive rod to drive the main weight and the sub-weight to operate along the main guide rods and sub-guide rods to achieve the object of training the muscle.




FIG. 2

EP 1 690 568 A1

10

15

20

25

40

45

50

FIELD OF THE INVENTION

[0001] The present invention relates to exercise machines, and in particular to a counterweight exercise machine which has main weights and sub-weights. The sub-weights are fixed by at least one pin so as to be operated on two sets of guide rods with the main weights. Different weights can be assembled to have a desire weight for training the muscles of the users according to the physical condition and the willingness of the user.

1

BACKGROUND OF THE INVENTION

[0002] The current counterweight exercise machine has a frame for supporting a plurality of weights. The user assembles a predetermined number of weights for training the hands or legs of the user in vertical direction. Users can train his (or her) muscle by applying a force to balance the weight of the weights. In some improve designs, some sub-weights are used with the main weights to cause that the user can assemble some weights to have a desire weight. However the sub-weights are directly added to the main weights, it is inconvenient as the user detaches the sub-weights from the main weights.

SUMMARY OF THE INVENTION

[0003] Accordingly, the primary object of the present invention is to provide a counterweight exercise machine which have main weights and sub-weights. The sub-weights are fixed by at least one pin so as to be operated on two sets of guide rods with the main weights.

[0004] A counterweight exercise machine has a frame. The frame comprises two main guide rods; two sub-guide rods; a passive rod parallel to the two main guide rods; at least one main weight; a selector; base having a lower substrate and an upper substrate; and two sleeves connected to the lower substrate and the upper substrate; at least one pin capable of passing through the round holes of the front sheet and the rear sheet and the passive rod; at least one sub-weight. By above mentioned components, the selector serves to lock a predetermined number of main weights and the pin inserts into the subweight so as to increase the total weight. A force applied unit serves to drive the passive rod so as to drive the main weight and the sub-weight to operate along the main guide rods and sub-guide rods to achieve the object of training the muscle.

[0005] The various objects and advantages of the present invention will be more readily understood from the following detailed description when read in conjunction with the appended drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006]

Fig. 1 is a perspective view of the present invention. Fig. 2 is a perspective view about the frame and the weights of the present invention.

Fig. 3 is a schematic perspective view bout the main weights and the sub-weights of the present invention.

Fig. 4 is a cross sectional view about the combination of the upper pin, the lower pin and the sub-weights.

Fig. 5 shows the operation according to Fig. 4.

Fig. 6 is a structural view of the Fig. 2.

Fig. 7 is another structural view of Fig. 2.

DETAILED DESCRIPTION OF THE INVENTION

[0007] In order that those skilled in the art can further understand the present invention, a description will be described in the following in details. However, these descriptions and the appended drawings are only used to cause those skilled in the art to understand the objects, features, and characteristics of the present invention, but not to be used to confine the scope and spirit of the present invention defined in the appended claims.

[0008] Referring to Figs. 1 and 2, the counterweight exercise machine of the present invention is illustrated. The counterweight exercise machine has a frame 10 which can steadily stand on the floor. The frame 10 is formed by a straight rod 11, two cambered rods 12, and a transversal rod 13. The frame 10 is sufficient to support a weight unit applied thereon. The weight unit is formed by a plurality of predetermined main weights 3. The main weights 3 are installed to two main guide rods 18 and a passive rod 17. The main weights 3 are placed into a gap 30 below the passive rod 17. The number of the main weights 3 is determined by a selector 5. The selector 5 is engaged to an annular groove 170 of the passive rod 17. Thereby, a plurality of main weights 3 are locked to the passive rod 17. A shaft 140 extends from the cambered rods 12 so as to fix a rotating wheel 14 and an eccentric wheel 15. Thereby the rotating wheel 14 and the eccentric wheel 15 rotate synchronously. The eccentric wheel 15 is connected to the passive rod 17 by using a belt 173. A linkage rod 14 extending from the rotating wheel 14 is connected to a force applying unit 16 through a post 142. When the force applied unit 16 is driven by a force from a user, the heel of the user applies a force so as to lift the force applied unit 16 and thus the rotating wheel 14 and the eccentric wheel 15 rotates synchronously along clockwise direction. Since the heel of the user serves to balance the weight of the main weights 3 so that the muscle of user is trained. Likewise, the force applying unit 16 can be used to train the hand of the user. By the same effect, in the present invention, when the leg and heel are used as above described, a seat 161 can be installed aside the counterweight exercise machines of present invention and the user can sit on the seat 161 so that the leg can lift the force applied unit 16. [0009] Each main weight 3 has the same predetermined weight. Thereby the total weight is the integral times of the weight of each main weight 3. To have other selections to the assembly of the main weights 3, subweights are designed. The weight of each sub-weight is a part of the main weight 3. Referring to Figs. 2 and 3, a base 2 has a lower substrate 23 and an upper substrate 24 and two sleeves 21, 22 between the lower substrate 23 and the upper substrate 24. The sleeves 21, 22 enclose the two main guide rods 18. A center section of the base 2 is fixed to an upper section of the passive rod 17. A front sheet 41 and a rear sheet 42 are fixed to the lower substrate 23. The front sheet 41 has an upper round hole 410 and a lower round hole 411. The rear sheet 42 has an upper round hole 420 and lower round hole 421. Referring to Fig. 4, an upper pin 8 and a lower pin 9 pass through the front sheet 41, the rear sheet 42, the upper round holes 410, 411, the lower round holes 420, 421, an upper round hole 171 and a lower round hole 172 of the passive rod 17. Each the upper pin 8 and the lower pin 9 have a force applying portion. Namely, the distal end of the upper pin has magnetic seats 81, 82 and the distal end of the lower pin has magnetic seats 91, 92 corresponding to magnetic seats 81, 82. The magnetic seats 81, 82, 91, 92 stand aside the front sheet 41. If the upper pin 8 and the lower pin 9 are inserted into the round holes 420, 421 of the rear sheet 42, the magnetic seat 81, 91 will absorb the iron front sheet 41. On the contrary, when the upper pin 8 and lower pin 9 are released from the round holes 420, 421 of the rear sheet 42, the magnetic seats 81, 91 are absorbed to the inner lateral surface of the front seat 41. By the magnetic seats 81, 82, 91, 92, the upper pin 8. and lower pin 9 are stable and thus they are difficult to release out.

[0010] In the present invention, there are at least one sub-weight 6. In this embodiment, two sub-weights 6, 7 are used in description. The two sub-weights 6, 7 may be same weights or different weights, but they are smaller than that of the main weight 3. One side of the sub-weight 6 has a vertically penetrating round hole 60 and one side of the sub-weight 7 has a vertically penetrating round hole 70, as shown in Fig. 3. The round holes 60, 70 are engaged to two vertical sub-guide rods 19 of the frame 10, and the middle sections of the sub-weights 6, 7 have via holes 61, 71 which are aligned to the round holes 410, 420, 411 and 421 in a same horizontal line. Upper ends of the via holes 61, 71 of the sub-weights 6, 7 have notches 62, 72.

[0011] As above mentioned, the selector 5 can fix a plurality of weights 3 less than desired one. Then some sub-weights are added. The upper pin 8 can pass through the via hole 61 of the sub-weight 6. The sub-weight 7 does not be locked by the lower pin 9. When the passive rod 17 is lifted upwards, other than the main weights 3 are lifted along the main guide rods 18, the sub-weight 6 will be lifted along the sub-guide rod 19 (referring to

Fig. 5). Thus, as shown in Fig. 4, a larger weight can be added for training. When the main weights 3 and the subweights 6, 7 are locked, as shown in Figs. 6 and 7, the user only needs to apply a force to lift the passive rod 17 for balancing the main weights and the sub-weights, the user can achieve the object of training.

[0012] In the present invention, the magnetic seats 81, 82, 91, 92 serve to fix the upper pin 8 and the lower pin 6 to the front sheet 41. If the upper pin 8 and the lower pin 9 are not used to lock the sub-weights 6, 7 and the magnetic seats 81, 91 are absorbed to the front sheet 41, when the passive rod 17 descends in an elevation of the sub-weight 6, the foremost ends of the upper pin 8 and the lower pin 9 will be pushed away due to the notches 62 of the sub-weight 6. Not only the pins 8, 9 will not cut, but also the magnetic seats 82, 92 are absorbed to the front sheet 41 so as to be retained in a safety state. [0013] In summary, in the present invention, the frame 10 is installed with main guide rods 18 and sub-guide rods 19. The main guide rods 18 have a plurality of main weights 3. The sub-guide rods 19 have at least one subweight 6. The selector 5 serves to lock the main weights 3. The upper pin 8 and the lower pin 9 serve to lock the sub-weights 6, 7. Thereby the user can select a desire weight for training.

[0014] The present invention is thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the present invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

Claims

40

45

50

 A counterweight exercise machine having a frame capable of standing on a floor steadily; the frame comprising:

two main guide rods;

two sub-guide rods;

a passive rod parallel to the two main guide rods; at least one main weight having a predetermined weight; the main weight being installed to the two main guide rods;

a selector capable of being inserted into two adjacent main weights and to be engaged to the passive rod;

a base having a lower substrate and an upper substrate; and two sleeves connected to the lower substrate and the upper substrate; the two sleeves enclosing the two main guide rods; the base being engaged to the passive rod to be as an integral body; the lower substrate having a front sheet and a rear sheet; each of the front sheet and rear sheet having at least one round hole: at least one pin capable of passing through the round holes of the front sheet and the rear sheet and the passive rod;

at least one sub-weight having a weight smaller than that of the main weight; two opposite sides of the sub-weight having vertically penetrating round holes so as to be engaged to the two sub-guide rods vertically; a center of the sub-weight having a via hole for receiving one end of the pin; wherein by above mentioned components, the selector serves to lock a predetermined number of main weights and the pin inserts into the sub-weight so as to increase the total weight; a force applied unit serves to drive the passive rod so as to drive the main weight and the sub-weight to operate along the main guide rods and subguide rods to achieve the object of training.

)] -

10

15

2. The counterweight exercise machine as claimed in claim 1, wherein each pin has two magnetic seats which are spaced with a predetermined distance; the two magnetic seats are located at two lateral sides of the front sheet; when the sub-weight is locked or unlocked, the front sheet is absorbed so that the pin will not release.

20

3. The counterweight exercise machine as claimed in claim 1, wherein an upper end of the via hole of the sub-weight has a notch for pushing away the end of the pin to prevent the pin from being cut.

25

30

35

40

45

50

55




FIG. 1




FIG. 2






FIG. 3








FIG. 6




FIG. 7



EUROPEAN SEARCH REPORT

Application Number EP 05 00 2681

Category	Citation of document with ir of relevant passa	ndication, where appropriate, ges	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
X Y	EP 1 132 116 A (TEC 12 September 2001 (* paragraphs [0001] [0017], [0018] *	CHNOGYM S.R.L) (2001-09-12) , [0012] - [0015],	1 2	A63B21/062
	* column 3, line 21 * columns 4,6 * * claims 2-4 * * figures 1-4,6a *	line 26 *		
Υ	WO 88/06909 A (ASH, 22 September 1988 (* abstract * * page 3, paragraph * figures 3a,3b *	(1988-09-22)	2	
Α	WO 2005/009547 A (M 3 February 2005 (20 * figures 5-9 * * page 15, line 13 * page 16, paragrap * page 16, line 25	005-02-03) - line 37 * oh 1 *	1,2	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	* claim 14 *			A63B
Α	US 6 719 672 B1 (EL AL) 13 April 2004 (* figure 3 *	1		
Α	US 4 627 615 A (NUF 9 December 1986 (19 * figure 1 *	1		
Α	US 3 746 338 A (PRO 17 July 1973 (1973- * figure 7 *	OCTOR R,US) -07-17)	1	
	The present search report has	been drawn up for all claims		
	Place of search	Date of completion of the search		Examiner
	The Hague	24 August 2005	Te,	jada Biarge, D
X : part Y : part docu	ATEGORY OF CITED DOCUMENTS icularly relevant if taken alone icularly relevant if combined with anot iment of the same category inological background	E : earlier patent after the filing ; her D : document cite L : document cite	ed in the application d for other reasons	ished on, or

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 05 00 2681

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-08-2005

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 1132116	A	12-09-2001	IT EP US	B020000059 1132116 2001014641	A1	13-08-200 12-09-200 16-08-200
WO 8806909	Α	22-09-1988	WO GB	8806909 2202601		22-09-1988 28-09-1988
WO 2005009547	Α	03-02-2005	AU WO	2003267752 2005009547		14-02-2009 03-02-2009
US 6719672	B1	13-04-2004	NONE			
US 4627615	Α	09-12-1986	NONE			
US 3746338	 A	17-07-1973	NONE			

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82