



(11) **EP 1 713 042 B9**

(12) **CORRECTED EUROPEAN PATENT SPECIFICATION**

(15) Correction information:
Corrected version no 1 (W1 B1)
Corrections, see
Description Paragraph(s) 8, 10, 16

(51) Int Cl.:
G08B 3/10 (2006.01) **G08B 13/22** (2006.01)
G08B 25/00 (2006.01)

(48) Corrigendum issued on:
22.02.2012 Bulletin 2012/08

(45) Date of publication and mention
of the grant of the patent:
24.08.2011 Bulletin 2011/34

(21) Application number: **06006990.3**

(22) Date of filing: **31.03.2006**

(54) **Method and apparatus for providing graduated annunciation of an impending alarm in a security system**

System und Verfahren zur Bereitstellung der graduellen Ankündigung eines bevorstehenden Alarms in einem Sicherheitssystem

Procédé et appareil pour mettre à disposition l'annonce progressive d'une alarme imminente dans un système de sécurité

(84) Designated Contracting States:
BE DE FR GB

(30) Priority: **11.04.2005 US 103175**

(43) Date of publication of application:
18.10.2006 Bulletin 2006/42

(73) Proprietor: **ROBERT BOSCH GMBH**
70442 Stuttgart (DE)

(72) Inventors:
• **Petricoin, Dennis**
NY 14466 Hemlock (US)
• **Markham, Steven A.**
NY 14607 Rochester (US)
• **Hayden, Craig A.**
NY 14624 Rochester (US)
• **Caler, Dennis M.**
NY 14505 Marion (US)

(74) Representative: **Knapp, Thomas**
Dreiss Patentanwälte
Postfach 10 37 62
70032 Stuttgart (DE)

(56) References cited:
JP-A- 2002 014 721 US-A- 5 574 425
US-A- 5 774 051 US-A- 5 877 683

- **HONEYWELL: "Galaxy 16, 16 plus user's guide"[Online] 2003, XP002440981 USA**
Retrieved from the Internet: URL: http://www.pr-alarms.co.uk/images/gala_xy16userguide.pdf
[retrieved on 2007-07-03]
- **SECURITY HOUSE: "Galaxy 16 en 16 plus"**
SALES BROCHURE, February 2001 (2001-02),
XP002440982 the Netherlands

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Field of the Invention

[0001] The present invention relates to surveillance systems that issue alarm signals, and, more particularly, to reducing the issuance of false alarm signals by such surveillance systems.

Description of the Related Art

[0002] Surveillance systems, also known as security systems, include security devices such as motion detectors for monitoring interior portions of a secured area of space, and door sensors and window sensors for monitoring perimeter portions of the secured area of space. When one of these sensors detects motion and/or the opening of a monitored door or window, the security system may issue an alarm signal that causes a siren to produce an audible alarm, and that is electronically communicated to a security company. The security company typically notifies the police, who may then visit the secured area of space in order to investigate.

[0003] A problem is that many of the alarm signals issued by a security system are what are known as "false alarms". False alarms are not the result of a genuinely dangerous condition, such as the presence of an intruder, but rather are a result of a resident of the building moving within the secured area of space and inadvertently causing an alarm signal to be issued. For example, a person returning home through their garage may enter through a side entry door of the garage that is monitored by the security system, or may open the side entry door to go outside after having driven into the garage through a garage door. Even if there is some time period provided by the security system to allow the resident to enter a passcode to thereby abort an alarm signal, the resident may not know, or may have forgotten, that the alarm system has been activated, and thus will not enter a passcode in time to prevent the occurrence of a false alarm. As another example, a resident may, without knowing or remembering that the alarm system has been activated, open a door in order to let a dog outside, or walk into a ground floor area that is monitored while the residents sleep on an upper floor. Again, even if the security system provides some audible or visual indication that a passcode needs to be provided in order to abort an alarm signal, the indication may not be of high enough intensity to get the attention of the resident, who may not be fully awake. The resulting audible alarm produced by a siren as a result of a false alarm often wakes many sleeping people needlessly. Moreover, investigations of the false alarms by the police are a waste of community resources and may result in the owners of the security system being monetarily fined.

[0004] An approach to reducing the false alarm problem is known as "entry delay", in which some time period is provided by the security system to allow the resident

to enter a passcode to thereby abort an alarm signal, as mentioned above. Most security systems employ an entry delay period which begins when the initial entry door is violated. The user needs to disarm the system within a programmed time period in order to avoid a false alarm. That is, if the system is not disarmed within the given time period, an alarm response will begin.

[0005] Another approach is known as "dialer delay", which delays the sending of an alarm signal to a monitoring station for a predetermined time period. This gives the homeowner time to cancel the alarm before emergency service personnel are dispatched. The delay period begins when an alarm condition has been detected. The security system will delay the sending of an alarm signal to the central station for a programmed period of time. If the alarm condition is not acknowledged within the given time period, the security system will send a report to a central station.

[0006] A problem with both the entry delay and the dialer delay approach is that the resident of the secured building may not be aware that an alarm response is forthcoming, and that he needs to enter a passcode or take some other measure to prevent the alarm. A reason the resident may be unaware of the forthcoming alarm response is that he does not see or hear any indication from the security system that he needs to take action in order to avoid the alarm. Even if he does see and/or hear such an indication, the indication may not be of sufficient intensity to capture his attention and cause him to take action. Moreover, even if he does see and/or hear the indication, and it captures his attention, he may be too distracted, or may not be thinking clear enough, to comprehend the meaning or significance of the indication that he perceives.

[0007] A further problem is that even if the resident does see and/or hear an indication from the security system, the indication succeeds in capturing his attention, and he perceives its meaning, the indication does not inform the resident of how much time he has remaining to enter a passcode before it is too late to prevent an alarm response. Thus, it sometimes occurs that a resident overestimates an amount of time remaining to enter a passcode, and hence fails to enter the passcode within the allotted time, which results in a false alarm.

[0008] US-A-5 574 425 relates to a anti-hijacking safety system for a vehicle and its driver. The Honeywell user guide to the Galaxy 16 System describes the handling of an intruder system, whereby, when unsettling the system, the keypad buzzer begins to pulse rapidly after 75% of the entry time has expired. When setting the system, the keypad displays exit time count down blocks.

[0009] What is needed in the art is a security system, and method of operation therefor, that is capable of capturing a user's attention, regardless of where he is on the premises, and making the user aware that he needs to enter a passcode in order to prevent an alarm signal from being issued. What is also needed is a security system, and method of operation therefor, that provides a user

with some indication of how much time is available for him to enter a passcode and thereby avoid the issuance of an alarm signal.

SUMMARY OF THE INTENTION

[0010] The present invention provides a security system that visually and in a preferred embodiment, also audibly, gives a user some indication of how much time is remaining for him to enter a passcode and thereby abort an alarm signal. The visual and, optionally, audible indications increase in intensity with time in order to ensure that the attention of the user is captured, regardless of where he is on the premises. The security system provides audible, spoken word instructions for the user to enter a passcode, thereby ensuring that the user will comprehend the meaning of the indications regardless of his state of mind.

[0011] The invention comprises, in one form thereof, a method of operating a security system, including sensing a security breach, and providing an indication to a user that an alarm signal will be issued in response to the sensing of the security breach. The indication perceptibly changes with time.

[0012] The invention comprises, in another form thereof, a security system according to claim 1 including a sensor for sensing a security breach and transmit a detection signal dependent thereon. An indicating device provides an indication to a user that an alarm signal will be issued in response to the detection signal. The indication perceptibly changes with time.

[0013] The invention comprises, in yet another form thereof, a method of operating a security system, according to claim 6, including sensing a security breach, and providing an indication to a user that an alarm signal will be issued in response to the sensing of the security breach. The indication perceptibly changes with time to thereby indicate to the user a period of time before the alarm signal will be issued.

[0014] An advantage of the present invention is that a user is provided with some indication of how much time is remaining before an alarm response will occur. Thus, the user can make sure that he enters his passcode in time to avoid a false alarm.

[0015] Another advantage is that the visual and, optionally, audible indications provided by the security system increase in intensity with time to thereby ensure that the attention of the user is captured, regardless of where the user is on the premises.

[0016] Yet another advantage is that audible, spoken word instructions for the user to enter a passcode are provided, thereby ensuring that the user will comprehend the meaning of the indications and what course of action he should take, regardless of his state of mind.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The above mentioned and other features and

objects of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

Figure 1 is a block diagram of one embodiment of a security system of the present invention.

Figure 2 is a plan view of one embodiment of the user interface of Figure 1.

Figure 3 is a timing diagram of one embodiment of a method of the present invention for operating the security system of Figure 1.

Figure 4 is a flow chart of another embodiment of a method of the present invention for operating the security system of Figure 1.

[0018] Corresponding reference characters indicate corresponding parts throughout the several views. Although the exemplification set out herein illustrates embodiments of the invention, in several forms, the embodiments disclosed below are not intended to be exhaustive or to be construed as limiting the scope of the invention to the precise forms disclosed.

DESCRIPTION OF THE PRESENT INVENTION

[0019] Referring now to the drawings and particularly to Figure 1, there is shown one embodiment of a security system 10 of the present invention for a structure 12 such as a building. However, system 10 may be used to secure other spaces, such as outdoor areas, subterranean rooms and passages, and zones of air space. System 10 includes a system controller 14, security sensors 16₁ through 16_n, and a user interface 18.

[0020] System controller 14 includes a control device in the form of a control panel 20 electrically connected via an option bus 22 to a wireless sensor network (WSN) hub 24. Control panel 20 may include a processor 26, a memory device 28 and a telephone interface 30. Processor 26 may coordinate communication with the various system components including WSN hub 24 and an audible alarm 36 associated with building 12. Memory 28 may include software for interpreting signals from sensor devices 16 and user interface 18, and deciding based thereon whether to initiate an alarm signal from control panel 20. The alarm signal may be used to activate audible alarm 36, or to notify a central station receiver (CSR) (not shown) such as a security company, fire station, or police station, for example, via public telephone network 32. After control panel 20 initiates an alarm signal, the alarm signal may be transmitted immediately to alarm 36 and/or to the CSR. Alternatively, after control panel 20 initiates an alarm signal, there may be a delay before the alarm signal is transmitted in order to provide the user

time to abort the alarm signal transmission by entering a passcode in user interface 18 or by waving an identification token 38 (Figure 2) near user interface 18. Memory 28 may also store identification information for sensors 16 such that control panel 20 may determine by analyzing a received signal which of sensors 16 transmitted the signal.

[0021] WSN hub 24 may include an antenna element 34 for transmitting and receiving air-borne signals, such as radio frequency signals. The radio frequency signals may be received by and transmitted from, i.e., exchanged with, sensors 16 and user interface 18. Information from sensors 16 and user interface 18 may be passed by WSN hub 24 to control panel 20 via option bus 22. Control panel 20 may pass information to WSN hub 24 via option bus 22 for transmission to sensors 16 and user interface 18 as necessary. WSN hub 24 may include a processor 40 and memory 42 for storing software and identification information associated with sensors 16 and user interface 18.

[0022] Sensors 16 may be in the form of any number or combination of perimeter sensors, such as window sensors and door sensors, and interior sensors, such as motion detectors. The window sensors may detect the opening and/or closing of a corresponding window (not shown) of building 12. The door sensors may detect the opening and/or closing of a corresponding door (not shown) of building 12. Door sensors are traditionally treated as "delay" sensors in that, after the door sensor detects that the corresponding door has been opened, there is a delay before the alarm signal is transmitted in order to provide the user time to abort the alarm signal transmission by entering a passcode in user interface 18 or by waving identification token 38 near user interface 18, as mentioned above. Conversely, window sensors are traditionally treated as "instant" sensors in that, after the window sensor detects that the corresponding window has been opened, the alarm signal is transmitted immediately. However, it is also possible within the scope of the present invention for window sensors to be treated as "delay" sensors. The motion sensors may each detect movement within a corresponding interior zone of the secured area, and are traditionally treated as "instant" sensors. However, again, it is possible for motion sensors to be treated as "delay" sensors.

[0023] Each sensor 16 may be wireless and may include a respective antenna element 52 for transmitting and receiving air-borne signals, such as radio frequency signals. The radio frequency signals may be received by and transmitted from, i.e., exchanged with, WSN hub 24. For example, each sensor 16 may send a detection signal to control panel 20 via hub 24 each time the sensor senses a security breach.

[0024] User interface 18 may be wireless and may include an antenna element 50 for exchanging air-borne signals with WSN hub 24. As shown in Figure 2, user interface 18 may include a speaker 44, a visual display such as liquid crystal diode (LCD) display 46, and a key-

pad 48 or some other input that enables the user to select a mode of operation and otherwise program security system 10.

[0025] Speaker 44 may be capable of producing audible tones and audible spoken words that are intended to be heard by a user of security system 10. The content of the audio communications may be transmitted by control panel 20 to user interface 18 for broadcast by speaker 44.

[0026] Display 46 includes twelve segments 54a-1 arranged in a circle, a lock icon 56, and a person icon 58. Each of segments 54 is individually selectively displayable. Lock icon 56 may be selectively displayable. More particularly, lock icon 56 may be displayed as shown when security system 10 is armed, and may not be displayed when security system 10 is not armed. Person icon 58 may be displayed as shown within the circle formed by segments 54 when system 10 is armed in the Stay mode; may be displayed outside the circle in area 60 when system 10 is armed in the Away mode; and may not be displayed at all when system 10 is not armed. Each of segments 54 and icons 56, 58 may be grey in color in contrast to a background 62 that has a selectable color. The color of background 62 may be selected to be either green, amber or red, for example, under the control of control panel 20.

[0027] Keypad 48 may include pushbuttons 64a-f. Pushbuttons 64a-e correspond to numbers 1-5, respectively, and may be depressed by the user to thereby enter a passcode having multiple digits. Pushbutton 64e may be used by the user, e.g., may be depressed multiple times, to set a volume level of the sounds produced by speaker 44. Pushbutton 64f may be depressed by the user in order to cause speaker 44 and/or display 46 to respectively produce audible and visible information and/or instructions for the benefit of the user.

[0028] One embodiment of a method of the present invention for operating security system 10 is illustrated in Figure 3. Figure 3 is a timing diagram of an entry delay period that begins at time to when a security breach is sensed by sensors 16. The security breach may be, for example, the opening of a door of building 12 by an intruder or by a user of system 10, who may be a resident of building 12. In the illustrated embodiment, an alarm signal will be issued at time to + 36 seconds unless a passcode is entered into keypad 48 or token 38 is placed near user display 18 sometime during the 36 second entry delay time period. The issuance of the alarm signal may cause audible alarm 36 to be activated and/or the CSR to be notified via telephone network 32. If the security breach was caused by a user of system 10 or a resident of building 12, then the issuance of the alarm signal would be considered a false alarm.

[0029] The duration of the entry delay period is arbitrarily illustrated as being 36 seconds. It is to be understood that the entry delay period may have any duration selected by the user and/or made available by the manufacturer of security system 10. The time duration of the entry delay period may typically be approximately be-

tween 20 seconds and 90 seconds.

[0030] During the entry delay period, indicating devices including siren 36, speaker 44 and display 46 generally provide indications to the user that an alarm signal will be issued in response to a detection signal from one or more of sensors 16. The indications perceptibly change with time during the entry delay period. For example, the intensity of the indications may generally increase with time to thereby provide an indication to the user of how much time remains in which the user may abort the alarm signal, i.e., prevent the issuance of the alarm signal.

[0031] In the embodiment of Figure 3, at time to when the security breach is sensed by one or more of sensors 16, the backlighting of display 46 turns an amber color, i.e., the color of background 62 turns amber. Further, padlock icon 56 remains ON, i.e., is displayed; person icon 58 begins flashing ON and OFF with a frequency on the order of one cycle per second; and all twelve segments 54 are turned ON, i.e., are displayed. Also at time to, speaker 44 begins to broadcast an audible tone referenced with the number 66 in Figure 3. In one embodiment, the tone has a frequency of 3000 Hz and repetitively cycles ON for 30 milliseconds and OFF for 300 milliseconds.

[0032] Under display heading 68 in Figure 3, it is illustrated when each of segments 54a-1 turns off during the entry delay period. Segments 54 may turn OFF sequentially in a counterclockwise direction starting at the top of the circle. For example, segment 54i turns OFF at time to + 2 seconds, segment 54k turns OFF at time to + 5 seconds, segment 54j turns OFF at time to + 8 seconds, etc. The final segment 54a turns OFF at time to + 35 seconds, approximately one second before the entry delay period ends and the alarm signal is issued. The sequential turning OFF of segments 54 provides a quantitative visual indication and a spatial representation of both a period of time elapsed since the security breach was sensed at time to, and a period of time remaining before the alarm signal will be issued at time to + 36 seconds.

[0033] At time to + 18 seconds, halfway through the entry delay period, the color of the backlighting, i.e., the color of background 62, changes from amber to red. Thus, the perceptible changing of the color of background 62 with time is another visual indication to the user that an alarm signal will be issued in response to the sensing of the security breach. The changing color of background 62 provides a qualitative visual indication of both a period of time elapsed since the security breach was sensed at time to, i.e., eighteen seconds, and a period of time remaining before the alarm signal will be issued at time to + 36 seconds, i.e., also eighteen seconds.

[0034] Also at time to + 18 seconds, an audio indication in the form of a single sound pulse 70 is produced for two seconds. For example, siren 36 may be activated for the two second time period between to + 18 seconds and to + 20 seconds. Thus, the sound pulse begins a period of time, i.e., eighteen seconds, after the security breach was

sensed, and a period of time, i.e., eighteen seconds, before the alarm signal will be issued. Moreover, the sound pulse ends a period of time, i.e., twenty seconds, after the security breach was sensed, and a period of time, i.e., sixteen seconds, before the alarm signal will be issued.

[0035] Siren 36 may be loud enough to be easily heard by a user regardless of where he is located on the premises, either inside building 12 or outside building 12. Thus, even if the user is too far away from user interface 18 to see display 46 or to hear the tone from speaker 44, the sound pulse from siren 36 will capture his attention.

[0036] With the user's attention captured, user interface 18 then, as referenced with number 72 in Figure 3 at time to + 20 seconds, audibly provides spoken word information to the user to explain the significance of the audible siren pulse and/or the visual indication of display 46. The spoken word information may also direct the user as to what action he should take. This spoken word information may be helpful in avoiding false alarms in situations in which the user is confused, only vaguely familiar with the security system, or in a state of mind that does not enable him to comprehend that he must enter his passcode or place his token 38 near user interface 18. For example, a spoken word announcement from speaker 44 may state, "To turn off your system, present your token or enter your passcode". As referenced at 74 in Figure 3, the audio tone 66 may be suspended during announcement 72.

[0037] At time to + 27 seconds, three-quarters through the entry delay period, another audio indication in the form of a pair of sound pulses are produced. A first pulse 76 has a two second duration, ending at time to + 29 seconds. After a one second respite, a second pulse 78 also has a two second duration, beginning at time to + 30 seconds and to + 32 seconds. As with sound pulse 70, pulses 76, 78 may each be in the form of an activation of siren 36. The double pulse activation of siren 36 may be, even to a greater degree than single pulse 70, loud enough and long enough to be easily heard by a user regardless of where he is located on the premises, either inside building 12 or outside building 12.

[0038] User interface 18 then, as referenced with number 80 in Figure 3 at time to + 32 seconds, audibly provides another spoken word announcement similar or identical to announcement 72. As referenced at 82 in Figure 3, the audio tone 66 may again be suspended during announcement 80.

[0039] Finally, if the user has not entered his passcode or presented a token 38 by time to + 36 seconds, then an alarm signal is issued. That is, siren 36 may be activated for a longer period, such as several minutes or more, and a CSR may be notified via telephone network 32.

[0040] The time duration of each of announcements 72, 80 is shown as two seconds in Figure 3. However, it is to be understood that the lengths of announcements 72, 80 may be three or more seconds. Moreover, the

starting times of announcements 72, 80, as well as the starting times and durations of sound pulses 70, 76, 78, may be other than as shown in Figure 3 within the scope of the invention.

[0041] Another embodiment of a method 400 of the present invention for operating security system 10 is illustrated in Figure 4. In a first step S402, a security breach is sensed. For example, one of sensors 16 may detect the opening of a door or window of building 12. As another example, one or more of sensors 16 may detect movement within building 12. The sensor sensing the security breach may transmit to control panel 20 a detection signal that is dependent upon the sensed security breach.

[0042] In a second step S404, an indication is provided to a user that an alarm signal will be issued, the indication perceptibly changing with time. The embodiment discussed above with reference to Figure 3 discloses several types of indications, including both visual indications and audio indications, that an alarm signal will be issued. These indications perceptibly change with time. As an example of a visual indication, the backlighting color of background 62 may change to amber when a security breach is sensed, and then may change to red halfway through the entry delay time period. The sequential turning OFF or extinguishing of the twelve segments 54 over the course of the entry delay time period is another alarm signal issuance indication that visually and perceptibly changes with time.

[0043] An example of an audio indication of an impending alarm signal is the spoken word announcement from speaker 44. The spoken word announcement changes with time in that it is silent or nonexistent during the first half of the entry delay time period, and is broadcast only in the third and fourth quarters of the entry delay time period. Another example of an audio indication of the impending alarm signal that perceptibly changes with time is entry delay tone pattern 66. Tone pattern 66 is broadcast consistently throughout the entry delay time period with the exception that it ceases or is suspended during announcements 72, 80 in the third and fourth quarters, respectively, of the entry delay time period. A third example of an audio indication of the impending alarm signal that perceptibly changes with time is the activation of audible alarm 36. This siren sound pulse changes with time in that it is silent or nonexistent during the first half of the entry delay time period, and is broadcast only in the third and fourth quarters of the entry delay time period. Another aspect of the changes of the siren broadcast is that only one sound pulse is provided in the third quarter of the entry delay time period, and two pulses are provided in the fourth quarter.

Claims

1. A method of operating a security system (10) in a building (12), said method comprising the steps of:

sensing a security breach (S402) in the building (12);

and providing an indication to a user that an alarm signal will be issued in response to said sensing step, the indication perceptibly changing with time (S404), **characterized in that** the indication comprises a visual indication comprising a spatial representation of a period of time before the alarm signal will be issued.

2. The method of one of the preceding Claims wherein the changing of the indication comprises a changing of a color of the visual indication.
3. The method of one of the preceding Claims wherein the indication comprises an audio indication.
4. The method of Claim 3 wherein the audio indication includes spoken words beginning at a period of time before the alarm signal will be issued.
5. The method of one of Claims 3 and 4 wherein the audio indication includes a sound pulse (70) beginning at a period of time before the alarm signal will be issued.
6. A security system (10) operating in a building (12) comprising: a sensor (16) configured to sense a security breach in the building (12) and transmit a detection signal dependent thereon; and an indicating device configured to provide an indication to a user that an alarm signal will be issued in response to the detection signal, the indication perceptibly changing with time, **characterized in that** the indication comprises a visual indication comprising a spatial representation of a period of time before the alarm signal will be issued.
7. The security system (10) of Claim 6 wherein the changing of the indication comprises a changing of a color of the visual indication.
8. The security system (10) of one of Claims 6 to 7 wherein the indication comprises an audio indication.
9. The security system (10) of Claim 8 wherein the audio indication includes spoken words beginning at least a period of time before the alarm signal will be issued.
10. The security system (10) of one of Claims 8 and 9 wherein the audio indication includes a sound pulse (70) beginning at a period of time before the alarm signal will be issued.

Patentansprüche

1. Verfahren zum Betreiben eines Sicherheitssystems (10) in einem Gebäude (12), wobei das Verfahren die folgenden Schritte umfasst:

Erfassen einer Sicherheitsverletzung (S402) in dem Gebäude (12); und Bereitstellen eines Hinweises für einen Anwender, dass ein Alarmsignal ausgegeben wird, in Reaktion auf den Erfassungsschritt, wobei sich der Hinweis im Lauf der Zeit wahrnehmbar verändert (S404), **dadurch gekennzeichnet, dass** der Hinweis einen visuellen Hinweis enthält, der eine räumliche Darstellung einer Zeitdauer enthält, bevor das Alarmsignal ausgegeben wird.

2. Verfahren nach einem der vorhergehenden Ansprüche, wobei die Änderung des Hinweises eine Änderung einer Farbe des visuellen Hinweises umfasst.
3. Verfahren nach einem der vorhergehenden Ansprüche, wobei der Hinweis einen Audiohinweis umfasst.
4. Verfahren nach Anspruch 3, wobei der Audiohinweis gesprochene Wörter enthält, die bei einer Zeitperiode vor der Ausgabe des Alarmsignals beginnen.
5. Verfahren nach einem der Ansprüche 3 und 4, wobei der Audiohinweis einen Tonimpuls (70) enthält, der bei einer Zeitperiode vor der Ausgabe des Alarmsignals beginnt.
6. Sicherheitssystem (10), das in einem Gebäude (12) arbeitet und umfasst: einen Sensor (16), der konfiguriert ist, um eine Sicherheitsverletzung in dem Gebäude (12) zu erfassen und um ein davon abhängiges Detektionssignal zu senden; und eine Hinweisvorrichtung, die konfiguriert ist, um für einen Anwender einen Hinweis bereitzustellen, dass ein Alarmsignal ausgegeben wird, in Reaktion auf das Detektionssignal, wobei sich der Hinweis im Lauf der Zeit wahrnehmbar verändert, **dadurch gekennzeichnet, dass** der Hinweis einen visuellen Hinweis enthält, der eine räumliche Darstellung einer Zeitdauer vor der Ausgabe des Alarms enthält.
7. Sicherheitssystem (10) nach Anspruch 6, wobei die Änderung des Hinweises eine Änderung einer Farbe des visuellen Hinweises enthält.
8. Sicherheitssystem (10) nach einem der Ansprüche 6 bis 7, wobei der Hinweis einen Audiohinweis enthält.
9. Sicherheitssystem (10) nach Anspruch 8, wobei der Audiohinweis gesprochene Wörter enthält, die wenigstens bei einer Zeitperiode vor der Ausgabe des

Alarmsignals beginnen.

10. Sicherheitssystem (10) nach einem der Ansprüche 8 und 9, wobei das Audiosignal einen Tonimpuls (70) enthält, der bei einer Zeitperiode vor der Ausgabe des Alarmsignals beginnt.

Revendications

1. Procédé d'exploitation d'un système de sécurité (10) dans un bâtiment (12), ledit procédé comprenant les étapes consistant à : détecter une violation de la sécurité (S402) dans le bâtiment (12) ; et fournir une indication à un utilisateur qu'un signal d'alarme va être généré en réponse à ladite étape de détection, l'indication changeant de façon perceptible avec le temps (S404), **caractérisé en ce que** l'indication comprend une indication visuelle comprenant une représentation spatiale d'une période de temps avant que le signal d'alarme soit généré.
2. Procédé selon l'une des revendications précédentes, dans lequel le changement de l'indication comprend un changement d'une couleur de l'indication visuelle.
3. Procédé selon l'une des revendications précédentes, dans lequel l'indication comprend une indication audio.
4. Procédé selon la revendication 3, dans lequel l'indication audio comprend du texte parlé commençant à une période de temps avant que le signal d'alarme soit généré.
5. Procédé selon l'une des revendications 3 et 4, dans lequel l'indication audio comprend une impulsion sonore (70) commençant à une période de temps avant que le signal d'alarme soit généré.
6. Système de sécurité (10) fonctionnant dans un bâtiment (12) comprenant : un détecteur (16) conçu pour détecter une violation de la sécurité dans le bâtiment (12) et transmettre un signal de détection dépendant de celui-ci ; et un dispositif indicateur conçu pour fournir une indication à un utilisateur qu'un signal d'alarme va être généré en réponse au signal de détection, l'indication changeant de façon perceptible avec le temps, **caractérisé en ce que** l'indication comprend une indication visuelle comprenant une représentation spatiale d'une période de temps avant que le signal d'alarme soit généré.
7. Système de sécurité (10) selon la revendication 6, dans lequel le changement de l'indication comprend un changement d'une couleur de l'indication visuelle.

8. Système de sécurité (10) selon l'une des revendications 6 à 7, dans lequel l'indication comprend une indication audio.
9. Système de sécurité (10) selon la revendication 8, dans lequel l'indication audio comprend du texte parlé commençant à une période de temps avant que le signal d'alarme soit généré. 5
10. Système de sécurité (10) selon l'une des revendications 8 et 9, dans lequel l'indication audio comprend une impulsion sonore (70) commençant à une période de temps avant que le signal d'alarme soit généré. 10

15

20

25

30

35

40

45

50

55




Fig. 1




Fig. 2




Fig. 3




Fig. 4

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5574425 A [0008]