



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 71

(51) Int Cl.:

B60R 21/0136^(2006.01)

(48) Corrigendum issued on:

24.01.2007 Bulletin 2007/04

(43) Date of publication:

02.11.2006 Bulletin 2006/44

(21) Application number: **06008450.6**

(22) Date of filing: **24.04.2006**

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated Extension States:

AL BA HR MK YU

(30) Priority: **25.04.2005 JP 2005126840**

(71) Applicants:

- **DENSO CORPORATION**
Kariya-city,
Aichi-pref. 448-8661 (JP)
- **HITACHI CABLE, LTD.**
Tokyo 101-8971 (JP)

(72) Inventors:

- **Takafuji, Tetsuya**
Kariya-city
Aichi-pref., 448-8661 (JP)
- **Kachu, Ryotaro**
Toyota-shi,
Aichi-ken 471-8571 (JP)
- **Fujita, Koichi**
Toyota-shi,
Aichi-ken 471-8571 (JP)
- **Kobayashi, Yoji**
Tokyo 101-8971 (JP)

(74) Representative: **Kuhnen & Wacker**

Intellectual Property Law Firm
Prinz-Ludwig-Strasse 40A
85354 Freising (DE)

(54) **Vehicle collision detection system**

(57) A vehicle collision detection system includes: a load transferring member (25) that is placed at a front part of a vehicle body and transfers rearward a collision load (F) applied when a vehicle collision occurs; a reinforcing member (20) placed behind the load transferring member; and mechanical collision sensors (30) that are placed between the load transferring member and the reinforcing member and detect a collision. The collision sensors are mounted to the load transferring member by snap locks. In a vehicle collision detection system, collision sensors can be mounted with ease and reliability.

FIG. 1

