



(11) **EP 1 734 646 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A2)
INID code(s) 22

(51) Int Cl.:

H02K 37/14 (2006.01) H02K 37/18 (2006.01)

(48) Corrigendum issued on:

21.02.2007 Bulletin 2007/08

(43) Date of publication:

20.12.2006 Bulletin 2006/51

(21) Application number: **06076429.7**

(22) Date of filing: **24.07.2002**

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **24.07.2001 JP 2001223010**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:

02255182.4 / 1 280 262

(71) Applicant: **JAPAN SERVO CO. LTD.**

Chiyoda-Ku,
Tokyo 101 (JP)

(72) Inventor: **Sakamoto, Masafumi,**

Japan Servo Co., Ltd.

Kiryu-shi,
Gunma (JP)

(74) Representative: **Powell, Timothy John et al**

Eric Potter Clarkson LLP

Park View House

58 The Ropewalk

Nottingham NG1 5DD (GB)

Remarks:

This application was filed on 14 - 07 - 2006 as a divisional application to the application mentioned under INID code 62.

(54) **Permanent magnet type three-phase stepping motor**

(57) In a permanent magnet type three-phase stepping motor having a stator (1) having 3L pieces of stator pole and a rotor (2) having a permanent magnet (4, 9) magnetized so as to form a plurality (Nr) of N and S pole pairs, wherein a condition of $0.3 \leq \{Nr / \pi\} (Ws + Wr) / (Ds + Dr) \leq 0.5$ is established, where L is an integer not less than 1, Nr is $L(3n \pm 1)$, n is an integer not less than 1, Ds is an inner diameter of the stator (1), Dr is an outer diameter of the rotor (2), Ws is a width of the stator pole tooth, and Wr is a width of the rotor tooth.

FIG. 1A

