



(11) **EP 1 742 503 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 71

(51) Int Cl.:

H04R 9/02 (2006.01) H04M 1/03 (2006.01)

(48) Corrigendum issued on:

21.02.2007 Bulletin 2007/08

(86) International application number:

PCT/JP2005/008448

(43) Date of publication:

10.01.2007 Bulletin 2007/02

(87) International publication number:

WO 2005/107317 (10.11.2005 Gazette 2005/45)

(21) Application number: **05738748.2**

(22) Date of filing: **27.04.2005**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR**

(30) Priority: **28.04.2004 JP 2004133117**

(71) Applicant: **Matsushita Electric Industrial Co., Ltd.**

**Kadoma-shi
Osaka 571-8501 (JP)**

(72) Inventors:

- **HONDA, Kazuki**
c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)
- **SANO, Koji**
c/o Mat. Elec. Ind. Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)
- **KUBO, Kazutaka**
c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)
- **YAMASAKI, Kazuya**
c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **YANO, Hiroshi**

c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **SHIMOKAWATOKO, Takeshi**

c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **FUKUYAMA, Takanori**

c/o Mat.Elec.Ind. Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **TOMOEDA, Shigeru**

c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **ENOMOTO, Mitsutaka**

c/o Mat. Elec. Ind. Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

• **SUMIYAMA, Masahide**

c/o Mat.Elec.Ind.Co., Ltd.
Osaka-shi, Osaka 540-6319 (JP)

(74) Representative: **Grünecker, Kinkeldey,**

**Stockmair & Schwanhäusser
Anwaltssozietät
Maximilianstrasse 58
80538 München (DE)**

(54) **ELECTRIC ACOUSTIC CONVERTER AND ELECTRONIC DEVICE USING THE SAME**

(57) An electro-acoustic transducer wherein a stopper of a terminal is composed of an elastic body having an impulsive-force resistance and an excellent resilience. The stopper is mounted on the yoke or lower plate of magnetic circuit, which is made of a metallic material

having an impulsive-force resistance. In this way, the stopper can restrict the terminal within the reversibility limit value of the spring force of the metallic material, and hence can enhance the reliability.

EP 1 742 503 A8

FIG. 1

