



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
14.03.2007 Bulletin 2007/11

(51) Int Cl.:
A61B 17/16 (2006.01) A61F 2/40 (2006.01)

(21) Application number: **06254732.8**

(22) Date of filing: **12.09.2006**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**
Designated Extension States:
AL BA HR MK YU

• **Warren, Dr. Russel**
Connecticut (US)
• **Lee, Dr. Don**
Nashville
Tennessee 37215 (US)

(30) Priority: **13.09.2005 US 225645**

(71) Applicant: **Biomet Manufacturing Corp.**
Warsaw, IN 46581-0587 (US)

(74) Representative: **Giles, Ashley Simon**
HASELTINE LAKE
Imperial House
15-19 Kingsway
London WC2B 6UD (GB)

(72) Inventors:
• **Winslow, Nathan A.**
Warsaw
Indiana 46582 (US)

(54) **Modular humeral head resurfacing system**

(57) A two piece humeral component for use in joint arthroplasty which is adapted to be implanted into a joint and engaged by a socket component of the joint. The joint component includes a body having a first articulating surface and a second medial surface opposite the first articulating surface. The first articulating surface is adapted to be engaged by the socket and the second medial

surface is adapted to be secured to mounting portion. The mounting portion has a first surface and a second medial surface. The first surface is adapted to be fixably engaged to the second mounting portion of the humeral component. The second medial surface is adapted to be secured to the humerus. A peg which has a first end adapted to engage a cavity found in the humerus is disposed on the mounting portion's second medial surface.




FIG. 1

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part application of United States Patent Application No. 10/930,044 filed on August 30, 2004, which is a continuation-in-part application of United States Patent Application No. 10/205,386 filed July 25, 2002 and issued August 31, 2004 as U.S. Patent No. 6,783,549, which claims the benefit of U.S. Provisional Application No. 60/308,340, filed on July 27, 2001. The disclosure of the above applications is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field Of The Invention

[0002] This invention relates generally to an apparatus and method for shoulder arthroplasty and, more particularly, to a humeral component and other associated surgical components and instruments for use in shoulder arthroplasty.

2. Discussion of the Related Art

[0003] A natural shoulder joint may undergo degenerative changes due to a variety of etiologies. When these degenerative changes become so far advanced and irreversible, it may ultimately become necessary to replace a natural shoulder joint with a prosthetic shoulder joint. When implantation of such a shoulder joint prosthesis becomes necessary, the natural head portion of the humerus is resected and a cavity is created in the intramedullary canal of the host humerus for accepting a humeral component. The humeral component includes a head portion used to replace the natural head of the humerus. Once the humeral component has been implanted, the humeral cavity positioned at the scapula socket may also be resurfaced and shaped to accept a glenoid component. The humeral component generally includes an articulating surface which engages and articulates with the socket portion of the glenoid component.

[0004] It is generally known in the art to provide a shoulder joint prosthesis having a humeral component, as discussed above. However, current prior art humeral components along with the associated surgical components and instruments utilized during shoulder arthroplasty suffer from many disadvantages.

[0005] For example, since the humeral component is subject to various types of loading by the glenoid component, the humeral component must offer a stable and secure articulating surface. To achieve this, some humeral components provide a post or stem attached to a lateral surface of the prosthetic humeral head. These humeral components are generally a single piece system with a single stem, which is inserted and cemented into a hole bored deeply into the intramedullary cavity. However, such existing humeral components also exhibit several disadvantages. For example, these types of stemmed humeral components utilize a large stem to sta-

bilize and secure the humeral component to the humerus. Such humeral components increase the amount of bone tissue removed, while also increasing the labor and complexity of the shoulder arthroplasty. Other stemmed humeral components may offer a larger diameter stem. However, the larger diameter stem also requires excess bone tissue to be removed which may not be practical in some patients.

[0006] Other prior art humeral components, such as that disclosed in WO 01/67988 A2 sets out a stemless humeral component or head that provides an integral cruciform shape that includes two planar intersecting fins. While this type of humeral component addresses the amount of bone tissue removed, this type of system provides little versatility or adjustments to a surgeon performing the shoulder arthroplasty. Moreover, this type of system does not provide additional enhanced fixation other than the planar intersecting fins.

[0007] Additionally, most prior art humeral components only rely on the stem to secure the humeral component into the intramedullary canal, via a cement mantle or bone attachment. The stem may also include grooves or holes, which act as an anchor, once the stem is cemented within the intramedullary canal. The medial surface of most humeral components are thus generally overlooked to enhance cement fixation and are therefore generally smooth. Although some humeral components may include a few longitudinal grooves and others may include both grooves and depressions on the medial surface, such surface enhancements only utilize or texture a portion of the medial surface, thereby not advantageously using the entire medial surface.

[0008] What is needed then is a modular humeral component and associated surgical components for use in shoulder arthroplasty which do not suffer from the above-mentioned disadvantages. This in turn, will provide a humeral component which is stable and secure, reduces the overall amount of bone tissue required to be removed, increases a surgeon's available components utilizing a single sized post, reduces the overall surgical time and complexity, increases overall medial surface area, enhances and increases post strength without increasing overall post diameter, provides a fully enhanced or textured medial surface for enhanced cement fixation or bone fixation and increased overall stability, provides for a uniform cement mantle, and provides increased tensile and shear strength. It is, therefore, an object of the present invention to provide such a humeral component and associated surgical components for use in shoulder arthroplasty.

SUMMARY OF THE INVENTION

[0009] In accordance with the teachings of the present invention, an apparatus and method for shoulder arthroplasty is disclosed. The apparatus and method employs a modular humeral component and other associated surgical components for use in the shoulder arthroplasty. In

this regard, the modular humeral component is adapted to be implanted into a humerus and engaged by a glenoid portion of a scapular component.

[0010] In one preferred embodiment, a modular humeral component is used for shoulder arthroplasty such that the humeral component is adapted to be implanted into a humerus and engage a glenoid component. The humeral component includes a head member having a first articulating surface and a second fixation surface, which is opposite to the first articulating surface. The first articulating surface is adapted to engage the articulating surface of the glenoid component and the second fixation surface is adapted to engage a fixation component. The fixation component has a first surface adapted to be secured to the head member and a second surface that is generally opposite the first surface. The second surface includes a fixation member adapted to be secured to the humerus.

[0011] Use of the present invention provides an apparatus and method for shoulder arthroplasty, and specifically, a modular humeral component and associated surgical components for use in shoulder arthroplasty. As a result, the aforementioned disadvantages associated with the currently available humeral components and associated surgical components for shoulder arthroplasty have been substantially reduced or eliminated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Still other advantages of the present invention will become apparent to those skilled in the art after reading the following specification and by reference to the drawings in which:

[0013] Figure 1 is a perspective view of the humeral component according to the teachings of the preferred embodiment of the invention shown implanted in a skeletal structure;

[0014] Figures 2a-2c are views of the fixation member of humeral component of Figure 1;

[0015] Figures 3a-9 are alternate embodiments for the fixation member of the humeral component of the present invention;

[0016] Figures 10-12 represent alternate peg configurations for the fixation member of the humeral component of the present invention;

[0017] Figures 13 and 14 represent alternate texturing, which is usable in the humeral components of the present invention;

[0018] Figures 15 and 16 represent cross-sectional views of implanted humeral components of the present invention;

[0019] Figures 17 through 22 depict an alternate embodiment of the present invention having an insert member disposed between the head and the base member;

[0020] Figures 23a-23e depict another alternate embodiment of the present invention having flanges disposed on a shelfless base member;

[0021] Figures 24-26b illustrate a method for preparing

the humerus implantation of the humeral component using associated surgical components according to the teachings of the preferred embodiment of the present invention;

[0022] Figures 27-28 further illustrate methods for implanting the humeral components into the prepared humerus according to the teachings of the preferred embodiment of the present invention;

[0023] Figures 29a-c represent side and perspective views of an alternate fixation member having a through stem fixation bore;

[0024] Figures 30a-c represent side and perspective views of an alternate fixation member having a male Morse taper with through stem fixation bore;

[0025] Figures 31a-c represent side and perspective views of an alternate fixation member having a female Morse taper with through stem fixation bore;

[0026] Figures 32a-c represent side and perspective views of an alternate fixation member

[0027] Figure 33 represents a perspective view of an alternate fixation member;

[0028] Figure 34 represents a cross-sectional view of the fixation member shown in figure 33;

[0029] Figure 35 represents a cross-sectional view of an alternate fixation member;

[0030] Figures 36a and 36b represent an alternate fixation component having a fixation member;

[0031] Figure 37 represents the coupling of a bone engagement member to a fixation shelf;

[0032] Figure 38 represents a fixation member having a concave shelf member;

[0033] Figure 39a-39b represents the intention of a fixation member;

[0034] Figure 40 represents a prosthetic according to another embodiment to the invention;

[0035] Figures 41 and 42 are side views of the prosthetic shown in Figure 40;

[0036] Figure 43 represents a perspective view of the implantation of the coupling member shown in Figure 40; and

[0037] Figures 44 and 45 represent side views of the implantation of a humeral prosthetic head into the coupling member shown in Figures 43 and 42.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0038] The following description of the preferred embodiments concerning an apparatus and method for shoulder arthroplasty is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

[0039] Figure 1 depicts the components used in the shoulder arthroplasty of the current invention. As shown, the modular humeral component 31 has a base member 32 and a head member 33. The base member 32 has a fixation peg 34, which is used to attach the humeral component to the resected portion 36 of the humerus 38. If

a total shoulder arthroplasty is performed, a glenoid component 40 is first implanted into the scapula 42 using techniques well known in the art. The glenoid component 40 is preferably of the type disclosed in U.S. Patent No. 5,800,551, which is hereby incorporated by reference, or other suitable conventional glenoid components. The humeral component 31 is designed to allow rotational and transitional movement of the head member 33 with respect to the glenoid component 40.

[0040] Figures 2a-2c depict the base member 32 of one embodiment of the current invention. The base member 32 is defined by a shelf member 44, which may have a plurality of through holes 46. The shelf member 44 can have at least one mating member 48 for engaging the head member 33 of the humeral component 31. It is preferred that the mating member 48 be a defined Morse taper or other suitable attaching mechanism. In addition to the mating member 48, each base member 32 has a fixation peg 34 disposed on the lower lateral surface 50 of shelf member 44. The fixation peg 34 is generally perpendicular to the shelf member for its entire length of the fixation peg 34. As depicted in Figures 2a-3, the shelf member 44 of the base member 32 can define flat lower lateral surface 50 and flat generally parallel upper surfaces 51. Figure 3a shows the second embodiment of the current invention, which has a cavity 52 defined in the shelf member 44. The cavity 52 is preferably the female side of a Morse taper, which would engage a male Morse taper on the head member 33.

[0041] Figure 3b shows the head member 33 which mates with the base member 32 of Figure 3a. It should be noted that a surgical kit of the components would contain numerous head members 33, each having a varied radius of curvature, diameter, and height to allow a surgeon to optimize joint movement. Additionally, a surgical kit would contain the instruments needed for implantation (shown later).

[0042] The head member 33 and base member 32 must be made of bio-compatible materials such as, without limitation, titanium, titanium alloys, surgical alloys, stainless steels, bio-compatible ceramics, and cobalt alloys. Optionally, the base member 32 can additionally be made of materials such as biocompatible ceramics and resorbable and non-resorbable polymers and other anticipated bio-compatible metallic or polymeric materials. Should the base member 32 be made of non-metallic components, a fastener would be needed to couple the head 33 to the base 32.

[0043] As shown in Figures 4-7, the shelf members 44 need not to be planar. Figures 4 and 5 show the base member 32 and having an interior concave surface 56 and a convex medial surface 58. Base members, as disclosed in Figures 4 and 5 would be used in situations where maximum bone removal in the humerus 38 is required. In each situation, the head member 33 would have a convex medial surface 59 for engaging the concave surface 56. It is envisioned as with all of the embodiments that the base members 32 and head member

33 can be coupled using the mating member 48, i.e., Morse taper. The use of the convex-concave interface provides a coupling interface which is self centering under a multitude of loading conditions. The interface reduces the occurrence of micro-motions which can disrupt the normal functioning of the joint prosthesis as well as lead to premature component failures. Any loads applied to the articulating surface of the head member 33, are transferred as a perpendicular force into the base member 32 of the modular humeral component 31 through the non-planar shelf member 44.

[0044] Figures 6 and 7 define base members 32 having the shelf member 60 having a convex outer surface 62. Additionally shown is a concave inner surface 64 for mating with a resected head 36 of the humerus 38. The base members as depicted in Figures 6 and 7 can be used when minimal bone removal is possible and will generally encapsulate the hemispheric shape cut into the humerus 38 as described later. As with the base members as shown in figures 4 and 5, any loads applied to the articulating surface of the head member 33, are transferred as a perpendicular force into the base member 32 of the modular humeral component 31.

[0045] Figures 8 and 9 disclose alternate embodiments of the base member 32 for the humeral component 31. Figure 8 depicts the base member 32 having a convex outer surface 66 and a flat lateral surface 68. The base members as depicted in Figures 2a-3 and 8 can be utilized when a moderate amount of bone material must be removed from the resected head 36 of the humerus 38. Figure 9 depicts the base member 32 having a flat upper surface 51 and a convex lateral surface 58. This base member would readily utilize the head member 33 as used with the base member as depicted in Figure 2a. It is envisioned that either base member can have a defined male or female mating member 48 in the form of a Morse taper.

[0046] Figures 10-12 depict possible configurations for the fixation peg 34. Figure 10 shows the fixation peg 34 defining a plurality of flutes 70 therein. As can be seen, the modular system does not need a shelf member 44. Without the shelf member 44, the base can have either a male or female Morse taper. Figures 11 and 12 depict the fixation peg 34 being at a tapered prism with the base of the prism coupled to the lower lateral surface 50 of the shelf member 44.

[0047] Figures 13 and 14 depict possible surface treatments for the lower lateral surface 50 of the shelf member 44 and fixation peg 34. All of the possible fixation pegs 34 can have a porous coated region 72, which will assist in the fixation of the component to the humerus 38. Additionally, all of the lower lateral surfaces 50 of the shelf member 44 can define a waffle, pattern 74 to assist in the incorporation of bone cement. Each fixation peg 34 extends from the lower lateral surface 50 to define or fill in a coupling region 75 having a diameter of about 0.50 inches. Each coupling region 75 also includes a sidewall 77 formed with and from the lower lateral surface 50. The

coupling region 75 provides a smooth flat surface for which the fixation peg 34 extends out, and reduces or eliminates any stress risers about each fixation peg 34, which could be caused by positioning the lower lateral surface 50 immediately adjacent the fixation peg 34.

[0048] The fixation peg 34 includes a first end 79, which is inserted into or engages a cavity or hole formed within a cavity in the humerus and a second end 81, which extends from or is integral with the shelf member 44. The first end 79 is semi-spherical and the second end has a 0.25 inch radius about the circumference of the second end 81 of the peg, which blends into a flat or smooth portion of the coupling region 75 to decrease the overall shear stress of the fixation peg 34. Optionally, should the fixation peg be non-metallic, embedded within the first end of each fixation peg 34 is a tantalum ball 83. The tantalum ball 83 enables the humeral component 31 to be easily identified in an x-ray.

[0049] Figures 15 and 16 depict cross-sectional views of various embodiments of the current invention implanted into resected head 36 of humerus 38. As depicted in Figure 16, when a large amount of bone mass must be removed during the arthroplasty, the base member 32 as depicted in Figure 9 can be used. As is shown, the base member 32 is fixed to the humerus 38 using a plurality of screws 85. The lateral surface 59 of the head member 33 defines a cavity 52 for receiving the mating member 48 or Morse taper post.

[0050] As with the base member depicted in Figure 15, the base member 32 is held to the humerus 38 by use of screws 85 disposed through the holes 46. Figure 16 discloses the use of the base member 32 as depicted in Figure 3a which is similarly held in place by use of fixation screws 85 to the humerus 38.

[0051] Figures 17 through 18 show an alternate embodiment of the humeral component 109. Base member 110 is shown having a modified Morse taper cavity 116. The humeral component 109 further has a head portion 112 with a male Morse taper portion 121. Disposed between the head portion 112 and the base member 110 is a coupling member 114. Coupling member 114 has an outer surface 118 which acts as the male portion of a Morse taper to bond with the cavity 116 of the base member 110. Coupling member 114 further defines a female portion 120 of a Morse taper which corresponds to the male portion 121 of the Morse taper of the head portion 112. The coupling portion 114 functions to move the center of curvature of the head portion 112 a fixed distance 123 from the center line of the base member 110. This functions to effectively change the centering location of the head portion 112 with respect to the humerus 138, thus allowing the surgeon more flexibility.

[0052] Figure 17a shows the alternate humeral component 109 in its assembled configuration. Figure 18 shows an exploded view of the alternate humeral component 109, coupling member 114, and base member 110. Rotation of coupling member 114 allows for translation of the head portion 112 on the base member 110.

Figures 19 through 19b depict a head portion 112 having a female Morse taper cavity 116 which engages a male Morse taper 115 on alternate coupling member 114. Figure 19a depicts an assembled view of the alternate humeral component 109.

[0053] Figures 21 through 21b depict an alternate embodiment of the humeral component 122. Shown is the base member 124 which has a modified female cavity defining a Morse taper 116. The head portion 126 has a coupling male Morse taper 132 disposed on the medial surface of the head component 126. Disposed between the head portion 126 and the base portion 124 is the coupling member 128. The coupling member 128 defines an outer surface 118 which functions as the male portion of the Morse taper and couples to the female portion 116 of the base member 124. The coupling member 128 further defines an interior cavity 130 which functions as a female Morse taper for the male Morse taper 132 of the head 126. The interior cavity 130 of the coupling member has an offset angle 134, which functions to rotate the center of curvature of the head portion 126 with respect to the base member 124. Similarly, shown in Figure 21b is a coupling member 114 having a male Morse taper 115 being angled.

[0054] Figures 20 and 22 show the alternate humeral components 122 inserted into a resected humerus. As with the other humeral components, the base member is fixed to the head of the humerus using fasteners.

[0055] Figures 23a-23e depict another alternate embodiment of the present invention. Shown is a shelfless base member 232 which is formed by a fixation peg 234. Each fixation peg 234 has three evenly spaced triangular fins 236 disposed thereon. The triangular fins 236 have an edge 239 which is coplanar to a top surface 238 of fixation peg 234. Incorporated into a top surface 238 of the fixation peg 234 is a fixing mechanism 240.

[0056] Figures 23a and 23b disclose fixing mechanism 240 in the form of a female Morse taper as the fixation which functions to couple the head 30 onto the base member 232 (see Figure 23d). As can be seen Figure 23e, the top surface 238 alternately can have a fixing mechanism 240 in the form of a male Morse taper disposed thereon. It is envisioned that a head member 30 being used in this embodiment can have a lower surface 244 which has a porous coat, plasma spray, grit blast, or smooth surface to facilitate the coupling to the bone.

[0057] When the base member 240 is coupled to head member 30, there is a defined gap between the lower surface 244 of the head 30 and the upper surface 238 of the base member 232. After implantation, the lower surface 244 of head member 30 rests upon the resected bone, not the top surface 238 of the base member 232.

[0058] The method for implanting the humeral component 31, along with associate surgical components utilized will now be described with reference to Figures 24a-28. The head of the humerus 38 is resected using a saw, chisel then planed flat or with a concavity. With the resected head 36 of the humerus 38 exposed, an alignment

or guide hole 90 is first drilled substantially through the center of resected head 36 of the humerus 38 using a quick release drill bit 96 and driver 98. Optionally, the resected head 36 of humerus 38 can be resected to provide a flat surface during the drilling of pilot hole 90.

[0059] Once the guide hole 90 is drilled, the resected head 36 of humerus 38 is optionally reamed using a concave spherical reamer shaft 102 with the driver 98. The concave reamer 102 includes a guide pin 104 and a roughened spherical surface 106 substantially corresponding to the spherical shape of the lower medial surface of the shelf member 44 of base member 32. An optional convex reamer surface 108 permits rasping or drilling of tight humeral cavities (see Figures 26a and 26b). Upon rotating the surface of the reamer, the bone of the resected head 36 of the humerus 38 is prepared to mate or conform to the shape of the lower lateral surface 50 of the shelf member 44 of the base member 32. As depicted in Figures 25a and 26b, the reamer 102 can have a convex shape or alternatively a flat shape, which reams a concave shape into the resected head 36 of the humerus 38. Determining which reamer is used is a function of the preoperative degenerative changes in the humerus 38.

[0060] With reference to Figures 27-28, which depict the insertion of the humeral components 30, once the surface of the resected head 36 of the humerus 38 has been resected, the base member 32 is inserted into the guide hole 90. It is envisioned that fixation peg 34 of the base member 32 can be forced into the guide hole 90 to displace the bone material around the intramedullary canal. Optionally, the guide hole 90 can also be reamed to a larger interior diameter to accept the base member 32 without displacement of the bone material by the fixation peg 34.

[0061] Once the base member 32 has been inserted into the guide hole 90, the optional screws 85 are disposed through the holes 46 to couple the base member 32 to the humerus 38. At this point, a surgeon may use any number of test head portions and/or adapter portions to determine the proper size needed to mate with the glenoid component. Once a proper head member 33 size has been determined, the final head member 33 can be fixed to the shelf member 44 of the base member 32.

[0062] Figures 26 and 27 show the use of the base member 32 as depicted in Figure 3. As can be seen, the base member of Figure 3 is utilized when a minimal amount of bone is required to be removed.

[0063] Figures 29a-c represent side and perspective views of an alternate fixation member 246 defining a through member fixation bore 248. The shelf member 250 can have at least one mating member 252 for engaging the head member of the humeral component. The mating member 252 can be a defined female Morse taper 254 or other suitable attaching mechanism. In addition to the mating member 252, each fixation member 246 has a fixation peg 256 disposed on the lower lateral surface 258 of shelf member 250. The fixation peg 256 may

be perpendicular to the shelf member for the entire length of the fixation peg 256. As depicted in Figures 29a-c, the shelf member 250 of the fixation member 246 can define a convex spherical lower lateral surface 258 and concave spherical upper lateral surface 260. Figure 29a shows hidden lines representing the through member fixation bore 248. As shown, the female Morse taper 254 is optionally co-linear or concentric with both the through member fixation bore 248 and the fixation peg 256. Adjacent to the bottom 262 of the female Morse taper is a defined conical portion 264 which is configured to accept a head of a bone coupling screw.

[0064] Figures 30a-c represent side and perspective views of an alternate fixation member 266 having a mating member 268 in the form of a male Morse taper with a through stem fixation bore 270 for engaging the head member of the humeral component. In addition to the mating member 268, the fixation member 266 has a fixation peg 272 disposed on the lower lateral surface 274 of shelf member 276. The shelf member 276 can define convex spherical lower lateral surface 258 and concave spherical upper lateral surface 260. Figure 30a shows hidden lines representing the through member fixation bore 270. As shown, the mating member 268, in the form of a Morse taper, is optionally co-linear with both the through member fixation bore 270 and the fixation peg 272. Disposed through the top 278 of the fixation member 268 is a defined conical portion 280 which is configured to accept a tapered head of a bone coupling screw.

[0065] Figures 31a-c and 32a-c represent side and perspective views of an alternate fixation members 282a and 282b. The members 282a and 282b have a shelf member 280 with mating features 284a and 284b for engaging the head member of the humeral component. The shelf member 280 of the fixation members 282a and 282b define a flat lower lateral surface 286 and convex spherical upper lateral surface 288. Figures 31a and 32a show hidden lines representing the through member fixation bore 290. The mating features 284a and 284b in the form of a Morse tapers are optionally co-linear with both the through member fixation bore 290 and a fixation peg 292. Disposed through the top 278 of the mating features 284a and 284b and fully through the fixation members 282a and 282b is a defined fixation bore 248 having a conical screw head supporting portion 298 which is configured to accept a tapered head of a bone coupling screw. This bone coupling screw can be positioned into or extended through the resected bone.

[0066] The fixation members depicted in figures 29a through 32c are generally implanted as described above. Generally, a portion of the head of the joint is resected using a rasp or other appropriate cutting tool. A bore is then formed in the resected head. The fixation member is then fixed to the prepared surface. A fastener such as a bone screw then disposed through the fixation bore 290 to fasten the fixation member to the resected bone. At this point, an articulating head (shown in figures 1 or 15 through 22) is coupled to the fixation member. While

specific fixation members are shown in figures 29-32c, the through bore feature is equally applicable to the fixation members shown in figure 1-14.

[0067] The modular nature of the humeral component 31 of the present invention allow a set of various types of both replacement base members 32 and head members 33 to be formed. In using such a set, a surgeon can interoperably choose the appropriate base member depending on the patient's particular degenerative condition. Additionally, the surgeon can then choose from a set of head members 33, which both have the proper articulating surface radius and a proper coupling to the base member 32.

[0068] Figures 33 and 34 represents a perspective and cross sectional views of an alternate fixation member 300. The fixation member 300 is formed of two components, a generally circular shelf member 302, and a bone engaging member 304. As described below, after an articulating surface is resected, an appropriate shelf member 302 is positioned against the resected surface. The bone engagement member 304 is then coupled to and through the shelf member 302 into the resected bone. An articulating head (not shown) is coupled to the bone fixation member to form a prosthetic with an articulating surface.

[0069] The bone engaging member 304 has a head engagement portion 306 and a threaded bone engagement portion 308. The bone engagement member 304 additionally has a shelf member engagement region 310 and drive feature 312. The shelf engagement region 310 functions to distribute and translate forces from the articulating head into the resected bone. It is envisioned that the shelf engagement region 310 can be an annular engagement flange 318 or textured cylindrical interface surface. The drive feature 312 can be an aperture having at least one defined flat drive surface, such as a hex aperture. The head engagement portion 306 can be a defined male 314 or female 316 Morse taper.

[0070] The shelf member 302 can be generally flat or curved. As described in previous embodiments, the shelf member 302 has upper and lower surfaces 320 and 322 which can be flat, concave or convex. The shelf members can additionally define a plurality of through apertures 324 that are configured to accept bone engaging screws to prevent rotation of the shelf member 302 during the insertion of the bone engaging member.

[0071] Figure 34 shows the annular engagement flange 318 is positioned on upper surface 320 of the annular shelf member 302. The shelf member 302 defines an aperture which annularly supports the bone engaging member 304. It is envisioned that the male Morse taper 316 can be used to couple the fixation member to an articulating head (see Figures 15-21).

[0072] Figure 35 represents a cross-sectional view of an alternate fixation member 302. Shown is the bone engaging member 304 having a head engagement portion 306 which is generally located below the shelf member 302. The head engagement portion 306 is shown as

a female Morse taper 316. The annular engagement flange 318 is disposed within an annular coupling groove 326 which is formed about the aperture 328 of the shelf member 302. Defined in the bottom of the Female Morse taper 316 is the drive mechanism 312. It is envisioned that the annular coupling groove 326 can take the form of a tapered countersink.

[0073] Figures 36a and 36b represent an alternate fixation component having a bone fixation member 304. The upper surface 320 of the shelf member 302 is shown being concave as previously described. The shelf member has an annular coupling groove 326 which mates with the annular flange 318 of the bone engaging member 304.

[0074] Figure 37 represents a cross-sectional view of an alternate fixation member. Shown is the bone engaging member 304 having a head engagement portion 306 which is generally located below the shelf member 302. The head engagement portion 306 is shown as a female Morse taper 316. The annular engagement flange 318 is disposed on the upper surface 320 about the aperture 328 of the shelf member 302. Defined in the bottom of the Female Morse taper 316 is the drive mechanism 312.

[0075] Figure 38 shows the bone engagement member 304 with annular engagement flange 318. The annular engagement flange 318 is positioned on the convex upper surface 320 of the annular shelf member 302. The shelf member 302 defines an annular engagement groove adjacent the aperture which annularly supports the male Morse taper of the bone engaging member 304.

[0076] Figure 39a-39b represents the implantation of a fixation member. Once the surface of the resected head 36 of the humerus 38 has been resected, the shelf member 302 positioned adjacent to the resected head 36. The bone engagement member 304 is inserted into the guide hole 90. It is envisioned that the bone engagement member 302 can be forced into the guide hole 90 to displace the bone material around the intramedullary canal.

[0077] Once the bone engagement member 302 has been inserted into the guide hole 90, the bone engagement member 302 is rotated until the annular engagement flange 318 engages the upper surface 320 of the annular shelf member 302. Optional screws 85 are disposed through the holes 324 to couple the base member 302 to the humerus 38. At this point, a surgeon may use any number of test head portions and/or adapter portions to determine the proper size needed to mate with the glenoid component. Once a proper head member size has been determined, the final head member 330 can be fixed to the head engagement portion 306 of the bone engaging member 302.

[0078] Figure 40 represents a humeral implant 400 according to another embodiment. Shown is a coupling member 402 and a humeral head 403. The coupling member 402 has a generally cylindrical body portion 404 with an exterior coupling surface 406. The coupling surface 406 can be tapered or can be cylindrical. The exterior coupling surface 406 further has at least one bone en-

gaging thread 407 which is configured to couple the cylindrical body portion to a hole defined within the receptive humerus as previously described. Appended to the proximal end 408 of the body portion 404 is a pair of linearly aligned coupling flanges 410 and 412, which define a pair of fastening member coupling apertures 414. The body portion 404 defines a female Morse taper 416 which is used to couple the head 403 to the coupling member 402. The coupling member 402 is configured to allow the fixation of the head without relying on the head seating on the resection for stability.

[0079] The head portion 403 is shown with an axially centered fixation stem 418. It is envisioned the stem 418 can take the form of an offset male Morse taper as is shown in Figures 17-22. Additionally, the head has an exterior articulation surface 405 which is configured to articulate with a natural or prosthetic glenoid (not shown).

[0080] Figures 41 and 42 represent side views of the prosthetic shown in Figures 40. The coupling flanges 410 and 412 have a coupling surface 420 which is configured to be mated to a resected humerus 422. As shown in Figures 44 and 45, the resected humerus 422 can be prepared as previously described to have a flat 424 or convex surface 426. The body 404 is inserted into a hole within the resected humerus 422. In this regard, the body 404 is rotated in a hole formed in the resected humerus to engage the threads with the humeral head and neck bone.

[0081] A pair of fasteners 434 are positioned through the coupling apertures 414 in the coupling flanges, 410 and 412. As seen in Figures 43 and 45, a coupling surface 420 of the flanges 410 and 412 can have a predefined concave coupling surface. Additionally, the concave surface can be formed by a physician bending the flanges 410 and 412 in the operating room prior to the insertion of the coupling fasteners 434 into the apertures 414.

[0082] After the coupling member 402 is inserted into the humerus, a trialing head 60' is optionally used to determine the proper size and orientation of the humeral head 403. The humeral head 403 is then coupled to the coupling member as previously described.

[0083] The description of the invention is merely exemplary embodiments in the present invention. One skilled in the art would readily recognize from such discussion and from accompanying drawings and claims that various changes, modifications, variations may be made therein without departing from the spirit and scope of the invention.

Claims

1. A modular joint component for use in a joint arthroplasty, said modular joint component adapted to be implanted into a joint having a head and a neck to engage an articulating surface of the joint, said modular joint component comprising:

a head member having a first articulating surface and a second fixation surface opposite said first articulating surface, said first articulating surface operable to engage the articulating surface of the joint and said second fixation surface being adapted to be secured to a fixation component; and

said fixation component having a first surface adapted to be secured to said second fixation surface of said head member and a second surface which is generally opposite the first surface, said second surface having a fixation member adapted to be secured within at least one of the head and the head and neck of the joint, said fixation component defining a pair of coupling flanges.

2. The modular joint component as defined in Claim 1 wherein said fixation component first surface comprises a locking taper.
3. The modular joint component as defined in Claim 1 wherein said coupling flanges of said fixation element has a spherical convex shape.
4. The modular joint component as defined in Claim 1 wherein the locking taper is a female locking taper.
5. The modular joint component as defined in Claim 1 wherein the fixation member defines an exterior bone engaging thread.
6. The modular joint component as defined in Claim 1 wherein said second surface of said fixation element is at least one of a generally flat shape and a generally spherical shape.
7. The modular joint component as defined in Claim 1 wherein said coupling flanges are configured to be deformed into a spherical concave shape.
8. The modular joint component as defined in Claim 1 wherein said head fixation surface defines an offset fixation component.
9. A modular joint component for use in a joint arthroplasty, said modular joint component adapted to be implanted into a joint having a head and a neck to engage an articulating surface of the joint, said modular joint component comprising:

a head member having a first articulating surface and a second fixation surface opposite said first articulating surface, said first articulating surface operable to engage the articulating surface of the joint and said second fixation surface being adapted to be secured to a head fixation portion of a bone fixation component; and

- the bone fixation component adapted to be secured within a fixation member accepting aperture, said fixation component defining a bone engaging member, a head fixation portion, and a linear coupling flange.
10. The modular joint component as defined in Claim 9 wherein said head fixation portion comprises a locking taper.
11. The modular joint component as defined in Claim 10 wherein the locking taper is a female locking taper.
12. The modular joint component as defined in Claim 10 wherein said coupling flange has a spherical convex shape.
13. The modular joint component as defined in Claim 10 wherein the linear coupling flange defines an aperture.
14. The modular joint component as defined in Claim 10 wherein said coupling flange has a first surface that is generally opposite the coupling surface that is at least one of a generally flat shape and a generally spherical shape.
15. A method for implanting a humeral component during shoulder arthroplasty, said method comprising:
- resecting at least a portion of the head of a humerus;
- preparing a hole in the head or neck of the humerus;
- providing a fixation component having a plurality of coupling flanges that define a plurality of bone screw holes and a generally cylindrical fixation member extending from the shelf;
- implanting the fixation component onto the humerus by inserting the fixation member into the hole prepared in the humerus;
- inserting at least one bone screw in at least one hole defined by the coupling flanges;
- providing a head member having a first articulating surface and a second fixation surface opposite the first articulating surface; and
- securing the head member to the fixation component.
16. The method as defined in Claim 15 further comprising reaming a spherical surface into the humerus.
17. The method as defined in Claim 15 further comprising reaming a spherical convex surface into the humerus.
18. The method as defined in Claim 15 wherein securing the head member to the fixation component includes
- attaching the head member to the fixation component by way of a locking taper.
19. The method as defined in Claim 15 wherein the fixation member defines a bone engaging thread.
20. The method as defined in Claim 15 further comprising rotatably adjusting the head member relative to the fixation component by way of the coupling member.
21. The method as defined in Claim 15 further comprising bending the coupling flanges in the operating room.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 17A




FIG. 18




FIG. 19




FIG. 19A




FIG. 19B




FIG. 21




FIG. 21A




FIG. 21B




FIG. 20




FIG. 22




FIG. 23B




FIG. 23A




FIG. 23C




FIG. 23D










FIG. 23E






FIG. 27




FIG. 28




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 30A




FIG. 30B




FIG. 30C




FIG. 31A




FIG. 31B




FIG. 31C




FIG. 32A




FIG. 32B




FIG. 32C




FIG. 36B




FIG. 36A




FIG. 37




FIG. 38




FIG. 33




FIG. 34













FIG. 35





REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 10930044 B [0001]
- US 10205386 B [0001]
- US 6783549 B [0001]
- US 30834001 P [0001]
- WO 0167988 A2 [0006]
- US 5800551 A [0039]