



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 86

(51) Int Cl.:

H01M 4/02 ^(2006.01) **H01M 10/40** ^(2006.01)

(48) Corrigendum issued on:

04.07.2007 Bulletin 2007/27

(86) International application number:

PCT/JP2006/306459

(43) Date of publication:

28.03.2007 Bulletin 2007/13

(87) International publication number:

WO 2006/106731 (12.10.2006 Gazette 2006/41)

(21) Application number: **06730407.1**

(22) Date of filing: **29.03.2006**

(84) Designated Contracting States:

DE FR GB

(30) Priority: **04.04.2005 JP 2005107253**

(71) Applicant: **Matsusita Electric Industrial Co., Ltd.**
Kadoma-shi, Osaka 571-8501 (JP)

(72) Inventors:

- **FUJIKAWA, Masato,**
Chuo-ku, Osaka-shi, Osaka 540-6319, (JP)

• **SUZUKI, Kohei,**

Chuo-ku, Osaka-shi, Osaka 540-6319, (JP)

• **INOUE, Kaoru**

Chuo-ku, Osaka-shi, Osaka 540-6319, (JP)

• **SHIMADA, Mikinari**

Chuo-ku, Osaka-shi, Osaka 540-6319, (JP)

(74) Representative: **TBK-Patent**

Bavariaring 4-6

80336 München (DE)

(54) **CYLINDRICAL LITHIUM SECONDARY BATTERY**

(57) A cylindrical lithium secondary battery that is excellent in resistance to short-circuits, is capable of preventing a capacity loss due to dropping, and has a good balance in battery characteristics. The cylindrical lithium secondary battery includes: a cylindrical battery can; an electrode assembly; and a non-aqueous electrolyte. The electrode assembly has a porous heat-resistant layer that is interposed between the positive electrode and the negative electrode. The electrode assembly has a central cavity into which a hollow mandrel is inserted. The hollow mandrel has a slit that extends along the entire length thereof. The outer diameter A of the hollow mandrel and the width B of the slit satisfy the relation: $0.1 \leq B/A \leq 0.6$.

FIG. 1

