



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**09.05.2007 Bulletin 2007/19**

(51) Int Cl.:  
**F02M 61/08 (2006.01) F02M 61/10 (2006.01)**  
**F02M 51/06 (2006.01)**

(21) Application number: **06251832.9**

(22) Date of filing: **31.03.2006**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR**  
Designated Extension States:  
**AL BA HR MK YU**

(71) Applicant: **Delphi Technologies, Inc.**  
**Troy, Michigan 48007 (US)**

(72) Inventor: **Hoffman, Guy**  
**5240 Sandweiler (LU)**

(74) Representative: **Waller, Stephen**  
**Murgitroyd & Company,**  
**165-169 Scotland Street**  
**Glasgow G5 8PL (GB)**


(30) Priority: **02.11.2005 EP 05256794**

(54) **Improved control valve arrangement**

(57) A fuel injector has a body (10) and a pintle (12) axially movable with respect to the body in upper (18) and lower (20) guides, and limited by an end stop (26). The guides (18,20) are mounted in a support (30) spaced

from the body (10) and immersed, in use, in fuel. Differential expansion of the pintle (112) with respect to the spacing between the spray aperture (16) and the end stop (26) is minimised.

Fig. 2



## Description

[0001] This invention relates to fuel injectors for internal combustion engines, and in particular outwardly opening solenoid actuated fuel injectors for direct injection of gasoline.

[0002] One known type of fuel injector is that having an outwardly opening pintle, biased towards the closed position by a spring and opened by an actuator such as a solenoid or piezo-stack. The pintle is typically slidable within upper and lower guides, and its opening is limited by an end stop which is typically the top surface of the upper guide.

[0003] Due to packaging constraints of the injector tip, the pintle has to be relatively long. During engine operation the injector housing heats up and expands. The pintle however is cooled by the flow of fuel around it and does not show a similar expansion. The difference in expansion leads to a decrease in stroke, which shifts the fuel delivery characteristic in the lean direction. During engine operation the pintle is typically cooled to the fuel temperature of approximately 50°C, while the injector housing can be heated to a temperature of over 100°C. This temperature difference between the injector housing and the pintle can cause a reduction in pintle stroke of more than 20µm.

[0004] Figure 1 shows diagrammatically a prior art approach to dealing with this problem. The injector has a body 10 and a pintle 12 having an external head 14 which is sealingly engageable with a spray aperture 16 of the body 10. The pintle 12 is axially movable in upper and lower guides 18 and 20 by an actuator 22 such as the armature of a solenoid. A return spring 24 biases the pintle 12 to the closed position. An end stop 26 on the pintle 12 cooperates with the upper surface of the upper guide 18 to limit extension of the pintle 12.

[0005] In order to ameliorate the temperature differential between the body 10 and the pintle 12, a swirler (not seen in Figure 1) is placed in the fuel flow path so as to induce swirling of the fuel, as indicated at 28. This promotes heat transfer between the body 10 and the pintle 12 and thus reduces the temperature differential discussed above.

[0006] However, in this prior art injector the largest part of the available fuel pressure is dissipated in the swirler and is not available in the valve group for spray atomisation.

[0007] The present invention provides a fuel injector comprising an injector body having a tip portion defining a spray aperture; a pintle extending within the tip portion; guide means within the tip portion guiding the pintle for axial movement between an extended and a retracted position, the pintle having an external head engageable with the spray aperture in said retracted position to seal the spray aperture; resilient means biasing the pintle to said retracted position; actuating means for selectively moving the pintle into said extended position; and an end stop engageable with the pintle to limit the extension of

the pintle;

and is characterised in that the end stop is mounted on a support extending within the housing from a location adjacent the spray aperture and spaced from the housing so as to be, in use, substantially surrounded by fuel.

[0008] Preferred features and advantages of the invention will be apparent from the claims and from the following description.

[0009] An embodiment of the invention will now be described, by way of example only, with reference to the drawings, in which:

Figure 1 is a cross-section of a prior art fuel injector, as discussed above; and

Figure 2 is a cross section of a fuel injector forming one embodiment of the present invention.

[0010] In Figure 2, parts which are similar to those of Figure 1 are denoted by like reference numerals and will not be further described. A support 30 in the form of a tube extends from a location adjacent the spray aperture 16 axially within the body 10. The upper and lower pintle guides 18, 20 are secured to the support 30. The support 30 is cooled by flow of fuel around it with the result that the support 30 and the pintle 12 are at approximately the same temperature. Thus, the spacing between the supports 18, 20 is affected by approximately the same thermal expansion and contraction as the pintle 12, and a reduction in pintle stroke is avoided.

[0011] The support 30 may be provided with apertures 32 above the lower pintle guide 20 to permit fuel to flow both around and inside the support 30. Alternatively, the apertures 32 may be omitted, and apertures (not shown in Figure 2) may be provided below the lower pintle guide 20 to permit fuel to flow as indicated at 34 to the spray aperture 16.

[0012] Having the support 30 in the form of a tube is preferred for reasons of simplicity and ease of manufacture. However, other forms of internal support for the pintle guides could be used. Other modifications may be made to the foregoing embodiment within the scope of the claims.

## Claims

1. A fuel injector comprising an injector body (10) having a tip portion defining a spray aperture (16); a pintle (12) extending within the tip portion; guide means (18,20) within the tip portion guiding the pintle (12) for axial movement between an extended and a retracted position, the pintle (12) having an external head (14) engageable with the spray aperture (16) in said retracted position to seal the spray aperture (16); resilient means (24) biasing the pintle (12) to said retracted position; actuating means (22) for selectively moving the pintle (12) into said extended position; and an end stop (26) engageable with the

pintle (12) to limit the extension of the pintle (12);  
**characterised in that** the end stop (26) is mounted  
on a support (30) extending within the housing (10)  
from a location adjacent the spray aperture (16) and  
spaced from the housing (10) so as to be, in use, 5  
substantially surrounded by fuel.

2. A fuel injector according to claim 1, in which the guide  
means comprises upper (18) and lower (20) guides  
mounted on said support (30). 10
3. A fuel injector according to claim 2, in which the end  
stop (26) is formed by an upper surface of the upper  
guide (18). 15
4. A fuel injector according to claim 2 or claim 3, in  
which the support comprises a tube (30) extending  
coaxially within the body (10).
5. A fuel injector according to claim 4, in which said 20  
tube is (30) apertured (32) between the upper (18)  
and lower (20) guides to form a flow path for fuel.
6. A fuel injector according to claim 4, in which said 25  
tube (30) is apertured below the lower guide (20) to  
form a flow path for fuel.

30

35

40

45

50

55




Fig. 1




Fig. 2



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 06 25 1832

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2001/030248 A1 (POPP ROGER C ET AL) 18 October 2001 (2001-10-18) * page 3, paragraph 29-31; figure 1 * -----	1-6	INV. F02M61/08 F02M61/10 F02M51/06
X	US 4 653 720 A (KNAPP ET AL) 31 March 1987 (1987-03-31) * column 2, lines 22-52; figure 1 * -----	1,2,4,5	
X	US 3 156 414 A (DRESSLER THOMAS M) 10 November 1964 (1964-11-10) * column 2, line 67 - column 3, line 18; figure 2 * -----	1,2,4,5	
X	US 5 190 223 A (MESENICH ET AL) 2 March 1993 (1993-03-02) * column 11, lines 1-15; figure 7 * -----	1,2,4,5	
X	US 3 791 589 A (PAGDIN B,GB) 12 February 1974 (1974-02-12) * column 3, lines 20-48; figure 1 * -----	1,4	
A	US 3 249 308 A (CADIOU JEAN GEORGES) 3 May 1966 (1966-05-03) * column 4, lines 5-18; figure 1 * -----	1	TECHNICAL FIELDS SEARCHED (IPC) F02M
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 7 June 2006	Examiner Etschmann, G
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

2  
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 06 25 1832

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-06-2006

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001030248 A1	18-10-2001	CA 2330226 A1	12-07-2001
		US 6270024 B1	07-08-2001
		US 2001038043 A1	08-11-2001
-----			
US 4653720 A	31-03-1987	AU 569653 B2	11-02-1988
		AU 5276986 A	04-09-1986
		DE 3507443 A1	04-09-1986
		FR 2578295 A1	05-09-1986
		GB 2171758 A	03-09-1986
		JP 61201879 A	06-09-1986
		KR 9312229 B1	24-12-1993
-----			
US 3156414 A	10-11-1964	NONE	
-----			
US 5190223 A	02-03-1993	NONE	
-----			
US 3791589 A	12-02-1974	AU 474906 B2	05-08-1976
		AU 5255273 A	29-08-1974
		CA 967444 A1	13-05-1975
		DE 2310326 A1	13-09-1973
		FR 2174993 A1	19-10-1973
		GB 1417702 A	17-12-1975
		IT 977956 B	20-09-1974
		JP 1179232 C	30-11-1983
		JP 48103920 A	26-12-1973
		JP 57049751 B	23-10-1982
		ZA 7301189 A	28-11-1973
-----			
US 3249308 A	03-05-1966	ES 290499 A1	01-12-1963
		FR 1344917 A	06-12-1963
		GB 1051842 A	
		LU 44126 A1	31-10-1963
-----			