



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
27.06.2007 Bulletin 2007/26

(51) Int Cl.:
B65D 88/06 (2006.01) **B65D 88/76 (2006.01)**
B65D 90/10 (2006.01) **B65D 88/02 (2006.01)**

(21) Application number: **06126843.9**

(22) Date of filing: **21.12.2006**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR
 Designated Extension States:
AL BA HR MK YU

(72) Inventors:
 • **Tast, Niila**
15270 Kukkila (FI)
 • **Forssell, Fredrik**
513 96 Fristad (SE)
 • **Strand, Johan**
513 35 Fristad (SE)

(30) Priority: **23.12.2005 FI 20055700**

(71) Applicant: **Uponor Suomi Oy**
15560 Nastola (FI)

(74) Representative: **Huhtanen, Ossi Jaakko**
Kolster Oy AB,
Iso Roobertinkatu 23,
P.O. Box 148
00121 Helsinki (FI)

(54) **Container for underground installation**

(57) A container comprises a body (1) that is configured for underground installation. It may also comprise an ascending tube (2). The ascending tube may be detachable from the body and it may comprise a tube part

(3) and a base whose outer dimensions are larger than the tube part (3) seen in the axial direction of the tube part. On the exterior of the body (1), at least on one side thereof, it is possible to arrange transport mounts (13).




FIG. 1

Description

BACKGROUND OF THE INVENTION

[0001] The invention relates to a container having a body that is configured for underground installation, and an ascending tube.

[0002] The invention further relates to a container having a body that is configured for underground installation.

[0003] There are known containers, such as depositing tanks, which have a body and an ascending tube. It is known to configure the container body such that the container is intended for installation in the ground. Thus, typically only a part of the ascending tube will remain visible on the ground. It is relatively cumbersome to transport these containers. Because of the ascending tube it is practically impossible to stack the containers one on top of the other. There are also known containers comprising a hole for the ascending tube, and during transport the body and the tube are kept apart. An ascending tube that is separate from the body may be transported independently of the body, whereby it may get damaged or disappear during transport. Solutions have been proposed, in which the tube is connected outside the container body for transport, but this requires extra arrangements and it is not a completely reliable solution either in view of keeping the ascending tube intact and safe in transport. A solution is also known, in which the ascending tube is of telescopic type. In that case its length is adjustable and for transport the tube parts are fitted one inside the other. The telescopic structure is very complex, however, and therefore very difficult and expensive to manufacture. It also requires carefulness to make sure that it remains intact in transport. For the duration of transport it may be necessary to place the container on a pallet so that it can be handled with a forklift truck and/or a hand pallet truck. It is possible to avoid using a pallet in a solution, in which the container bottom comprises transport mounts. The transport mounts of the container raise the rest of the container body up such that the fork of a forklift truck or a hand pallet truck may be fitted under the container. Installation of a container like this, however, poses a problem that on preparing the final installation base for the container a recess should be provided for the mounts in order for the bottom of the container to be completely supported against the ground. This is relatively difficult, however, and unsupported areas easily remain underneath the container with the mounts.

BRIEF DESCRIPTION OF THE INVENTION

[0004] The object of the present invention is to provide a novel container.

[0005] The container of the invention is characterized by what is stated in the independent claims.

[0006] A container comprises a body that is intended for underground installation and an ascending tube. The ascending tube is detachable from the body. The ascend-

ing tube comprises a tube part and a base, which base is larger in the outer dimensions than the tube part seen in the axial direction of the tube part. For transport it is possible to stack containers one on top of the other. As the base of the ascending tube is larger than the tube part of the ascending tube, it is possible to produce a relatively large hole in the container body, whereby the interior of the container may be utilized extremely well for transport of parts or accessories relating to the container. This solution facilitates transport and reduces a risk that the parts and accessories would be damaged in transport. The container may be divided into chambers with partition walls. The chambers are serviced through the ascending tube, and advantageously, the ascending tube is so large and arranged such that two or more chambers, preferably all chambers, may be serviced through one ascending tube. As the base of the ascending tube is larger than the tube part it is possible to make the hole in the body so large that the tube part of the ascending tube or some other part or accessory relating to the container may be placed through the hole in one of the chambers for transport, i.e. in such a manner that the partition walls do not hinder the placement of the ascending tube or another part or accessory inside the container body for transport. Advantageously, the tube part of the ascending tube is arranged eccentrically to the base of the ascending tube, which enables the placement of the tube part of the ascending tube in one of the chambers for transport even better.

[0007] Further, a container comprises a body that is intended for underground installation. Transport mounts are arranged in the body on at least one side thereof. In that case it is possible to transport the container lying on the side. Hence, the container may be moved during transport with a forklift or a hand pallet truck, i.e. the fork of the forklift truck or the hand pallet truck fits under the container lying on the side. When the container is installed, the foundation on which the container is to be mounted can be packed and levelled to be even. The bottom of the container is flat, i.e. no air will remain beneath the container and the container will not stand on its legs alone. In accordance with one embodiment, the transport mounts are arranged on at least two opposing sides of the container. Thus, containers lying on their sides may be superimposed for transport. The superimposed containers support on the transport mounts of one another. Thus, the transport mounts on one side of the container may be made concave and those on the other side of the container may be made convex. In that case in transport the container is placed with the concave transport mounts downwardly and the convex transport mounts upwardly and on top of a first container there is placed a second container such that the concave transport mounts of the second container fit against the convex transport mounts of the container below. Thus the containers will be precisely aligned and firmly in place during transport.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The invention will be described in greater detail in the attached drawings, wherein

Figure 1 shows schematically a depositing tank seen obliquely from above,
 Figure 2 shows the tank of Figure 1 with an ascending tube in transport position,
 Figure 3 shows a schematic cross-sectional side view of the depositing tank,
 Figure 4 shows a cross-sectional side view of the tank of Figure 3 with the ascending tube in transport position,
 Figure 5 shows a top view of the container of Figure 3, and
 Figure 6 shows a top view of the depositing tank in the situation of Figure 4.

[0009] For the sake of clarity, in the figures some embodiments of the invention are shown in a simplified form. Like reference numerals refer to like parts in the figures.

DETAILED DESCRIPTION OF SOME EMBODIMENTS OF THE INVENTION

[0010] Figure 1 shows a depositing tank. The depositing tank comprises a body 1, which is configured for allowing the container to be buried in the ground. Preferably the body 1 is made of plastic, such as polyethylene PE or polypropylene PP or some other suitable plastic material.

[0011] The container further comprises an ascending tube 2 arranged in the body 1. The ascending tube 2 includes a tube part 3, which extends above the ground when the container is in use. The ascending tube 2 further includes a base 4 that is integral with the tube part 3.

[0012] The ascending tube 2 is configured to be detachable from the body 1, whereby the ascending tube may be arranged partly inside the body 1 during the transport of the container in a manner shown in Figure 2.

[0013] The base 4 of the ascending tube 2 comprises a flange 5, and when the container is in use the ascending tube 2 is attached to the body 1, to a connecting end 6 provided in the body 1. The flange 5 is thus set over the connecting end 6. The connecting end 6 is a vertical collar that surrounds the hole in the upper part of the body 1. A seal is arranged between the flange 5 and the connecting end 6 such that the body 1 and the ascending tube 2 will be tightly fitted and the joint concerned will not leak. The flange 5 thus constitutes a sleeve that is arranged over the connecting end 6. The ascending tube 2 and the body 1 may also be interconnected with screws or bolts, whereby the base 4 may be designed to conform to the outer surface of the hole in the body 1 and a suitable seal is arranged between the base 4 and the body 1. Between the tube part 3 and the base 4 of the ascending tube 2 there is further provided a stiffening rib 7. The

stiffening rib 7 reinforces the structure of the ascending tube 2.

[0014] Figure 3 also illustrates how the ascending tube 2 is arranged in connection with the body 1.

[0015] Thus, the attaching figures show a depositing tank, in which there is a partition wall 8 or a plurality of partition walls 8 inside the container body 1. The partition walls 8 divide the interior of the container into chambers. As it appears from Figure 5, the tube part 3 of the ascending tube 2 is arranged such that all chambers inside the container may be serviced through the ascending tube 3.

[0016] Figures 4 and 6, in turn, illustrate how the eccentric placement of the tube part 3 of the ascending tube in the base 4 enables the tube part of the ascending tube being arranged in a chamber of the container during transport without the partition walls 8 preventing the tube part from being placed inside the container. In Figure 6, partition walls 8 that remain invisible behind the ascending tube 2 and the container body 1 are indicated by broken lines.

[0017] If the hole in the container body 1 is arranged to be sufficiently large, and correspondingly, the base 4 of the ascending tube 2 is sufficiently large and the tube part 3 is sufficiently small, the tube part 3 may also be arranged in a centralized manner in relation to the base 4, but nevertheless the tube part could be placed inside a container chamber. When the tube part 3 is arranged eccentrically to the base 4, a hole to be made in the body 1 need not be large as a whole, and yet it is possible to place the tube part inside the chamber. In addition, eccentricity makes it possible that during transport the base 4 is supported throughout to the rims of the hole in the container 1.

[0018] The container 1 is still further provided with lugs 9, by means of which the ascending tube 2 may be secured firmly into place for transport. Said lugs may also be utilized for holding the ascending tube 2 in place, when the container is in normal use. It is possible to connect to the lugs 9 a strap, a rope or a binding line by which the ascending tube 2 is held in place.

[0019] There may be one, two or more lugs 9 for securing the ascending tube 2.

[0020] The container body 1 is further provided with a recess 10. The recess 10 may be arranged at the end of the body 1 and it is intended for accommodating a distribution well during transport. Namely, subsequent to the depositing tank there is typically arranged a separate distribution well. The distribution well to be transported to the installation site together with the depositing tank can be transported attached to the recess 10. The container further comprises a dowel pin 11. The dowel pin is designed in size and shape to correspond to a pipe that is inserted in an inlet of the distribution well. Thus, the distribution well inlet may be arranged in the dowel pin 11. The container body 1 further comprises lugs 12. Thus, the distribution well may be firmly attached to the body 1 by means of the dowel pin 11 and the lugs 12 for trans-

port. Thanks to the dowel pin 11, two lugs 12, to which the strap, the rope or the connecting line are to be connected, will typically suffice for securing the distribution well.

[0021] Instead of the dowel pin 11, it is possible to use another aligning element, such as a rib, a notch or another suitable structural element. In that case the aligning element is not necessarily supported to the inlet of the distribution well, but it may be supported to some other shape in the distribution well.

[0022] On at least one side, i.e. flank, of the container body 1 there are arranged transport mounts 13. In a normal use position the container is naturally in a position shown in Figure 1, i.e. the ascending tube 2 points upwardly. When the transport mounts 13 have been arranged on the side of the body 1, the container is transported to the installation site on its side, i.e. the transport mounts pointing downwardly.

[0023] The transport mounts 13 may be arranged on the first side and additionally to a second side opposite to the first side. This allows a plurality of containers being superimposed during transport.

[0024] The transport mounts 13 may be provided such that on the first side of the container the transport mounts are concave. It is thus advantageous to transport the container with these concave mounts downwardly. The transport mounts 13 on the other side of the container are convex. Then, the convex transport mounts 13 point upwardly during transport. It will be relatively easy to place another container with concave downwardly pointing transport mounts on top of the convex transport mounts 13. Consequently, the concave transport mounts 13 of the upper container will fit smoothly and firmly against the convex transport mounts 13 of the lower container.

[0025] In some cases the features set forth in this application may be used as such, irrespective of other features. On the other hand, features set forth in this application may be combined, where necessary, to provide various combinations.

[0026] The drawings and the relating description are only intended to illustrate the inventive idea. The details of the invention may vary within the scope of the claims.

[0027] So, the container to which the presented features are applied, may be, for instance, a depositing tank as indicated in the attached drawings. Also, the container may be another container intended for installation in the ground, such as a sewage tank or any other liquid tank, a well, such as a distribution well, or a corresponding container or well. Further, if the container comprises partition walls, the container may be a depositing tank or a small-scale purifying plant or another corresponding container having two or more chambers inside the body. In addition to or instead of the ascending tube or a section thereof it is possible to transport inside the body also other parts or accessories relating to the container completely or such that part of them is located inside the body. These parts or accessories may include inlet and outlet

connections, inlet and outlet pipes, filter bed pipes, joints and branches, etc. During transport the ascending tube may also be mounted in its use position, and then the ascending tube will not be at all inside the body during transport. If the container body 1 is sufficiently large, it is possible to make the hole for the ascending tube base 4 in the body 1 so large that relatively large pieces may be transported in the interior of the body 1. The capacity of the body 1 may vary, for instance, between 500 and 5000 litres. If the capacity of the body 1 is sufficient, it is possible to transport a distribution well inside it, for instance.

Claims

1. A container having a body (1) that is configured for underground installation, and an ascending tube (2), **characterized in that** the ascending tube (2) is detachable from the body (1) and that the ascending tube (2) comprises a tube part (3) and a base (4), which base is larger in the outer dimensions than the tube part seen in the axial direction of the tube part (3), whereby the container body (1) comprises a hole that is larger than the outer measurement of the tube part (3) seen in the axial direction in order to enable utilization of the interior of the body (1) for transporting parts and accessories relating to the container.
2. The container of claim 1, **characterized in that** the tube part of the ascending tube (2) is arranged eccentrically to the base (4) of the ascending tube (2).
3. The container of claim 1 or 2, **characterized in that** inside the body (1) there is at least one partition wall (8) such that the container comprises at least two chambers, that the ascending tube (2) is arranged such that at least two chambers can be serviced therethrough and that at least one chamber may be utilized for transporting parts or accessories relating to the container.
4. The container of any one of the preceding claims, **characterized in that** the ascending tube (2) may be arranged at least partly inside the body (1) for the duration of transport.
5. The container of any one of the preceding claims, **characterized in that** on the exterior of the body (1) there is arranged at least one lug (9) for securing the ascending tube (2).
6. The container of any one of the preceding claims, **characterized in that** in the body (1), on the exterior thereof, there is provided a recess (10) for transporting a distribution well in connection with the container.

7. The container of claim 6, **characterized in that** in connection with the recess (10) there is an aligning element (11) that may be utilized for supporting the distribution well during transport.
8. The container of claim 7, **characterized in that** the aligning element is a dowel pin (11) that is designed in size and shape to correspond to a pipe that is to be inserted in an inlet of the distribution well.
9. The container of any one of the preceding claims, **characterized in that** a distribution well may be arranged inside the body (1) for transport.
10. The container of any one of the preceding claims, **characterized in that** on the exterior of the body (1), at least on one side thereof, there are arranged transport mounts (13).
11. The container of claim 10, **characterized in that** the transport mounts (13) are arranged on two opposing sides of the body (1).
12. The container of claim 11, **characterized in that** the transport mounts (13) on the first side of the body (1) are concave and the transport mounts (13) on the second side of the body (1) are convex.
13. The container having a body (1) that is configured for underground installation, **characterized in that** on the exterior of the body (1), at least on one side thereof, there are arranged transport mounts (13).
14. The container of claim 13, **characterized in that** the transport mounts (13) are arranged on two opposing sides of the body (1).
15. The container of claim 14, **characterized in that** the transport mounts (13) on the first side of the body (1) are concave and the transport mounts (13) on the second side of the body (1) are convex.
16. The container of any one of claims 13 to 15, **characterized in that** the container comprises an ascending tube (2) that is detachable from the body (1).
17. The container of claim 16, **characterized in that** the ascending tube (2) comprises a tube part (3) and a base (4) whose outer dimensions seen in axial direction of the tube part (3) are larger than those of the tube part (3).
18. The container of claim 17, **characterized in that** the tube part (3) of the ascending tube (2) is arranged eccentrically to the base (4) of the ascending tube (2).
19. The container of claim 17 or 18, **characterized in that** inside the body (1) there is at least one partition wall (8) such that the container comprises at least two chambers, that the ascending tube (2) is arranged such that at least two chambers may be serviced therethrough and that at least one chamber may be utilized for transport of parts or accessories relating to the container.
20. The container of any one of claims 16 to 19, **characterized in that** on the exterior of the body (1) there is arranged at least one lug (9) for securing the ascending tube (2).
21. The container of any one of claims 13 to 20, **characterized in that** in the body (1), on the exterior thereof, there is provided a recess (10) for transporting a distribution well in connection with the container.
22. The container of claim 21, **characterized in that** in connection with the recess (10) there is an aligning element that may be utilized for supporting the distribution well during transport.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 06 12 6843

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	DE 199 11 009 A1 (FUSION KUNSTSTOFF GMBH [DE]) 14 September 2000 (2000-09-14)	1,4,10,13,16,17	INV. B65D88/06 B65D88/76 B65D90/10 B65D88/02
Y	* column 1, lines 51-66 *	6-9,11,21,22	
	* figure 1 *		
X	US 6 024 242 A1 (STEVENSON SCOTT JAE [US]) 15 February 2000 (2000-02-15)	1,4,10,13,16,17	
	* abstract; figures 1,2 *		
X	DE 91 15 953 U1 (ABS PUMPEN AG, 5204 LOHMAR, DE) 27 February 1992 (1992-02-27)	13,14	
Y	* page 6, paragraph 1 *	11	
	* figures 1,2 *		
X	JP 2000 136540 A (SHIKOKU SANYU KASEI KK) 16 May 2000 (2000-05-16)	13	
A	* abstract; figure 1 *	1	
X	BE 1 013 186 A6 (TANK SHOP JAN VERBEECK B V B A [BE]) 2 October 2001 (2001-10-02)	13	
A	* figures 1,3 *	5,20	TECHNICAL FIELDS SEARCHED (IPC)
Y	US 2004/188447 A1 (BOLZER TODD [US]) 30 September 2004 (2004-09-30)	6-9,21,22	B65D
	* page 4, paragraph 40 *		
	* figure 1 *		
A	JP 2002 309631 A (ISHIKAWAJIMA KENZAI KOGYO KK) 23 October 2002 (2002-10-23)	1	
	* abstract; figures 1-5 *		
A	JP 11 105977 A (HITACHI CHEMICAL CO LTD) 20 April 1999 (1999-04-20)	1	
	* abstract; figure 1 *		
	-/-		
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 9 May 2007	Examiner Piolat, Olivier
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

6

EPO FORM 1503 03.82 (P04C01)



DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	JP 10 174985 A (SEKISUI CHEMICAL CO LTD) 30 June 1998 (1998-06-30) * abstract; figure 1 *	3,19	
A	US 2003/136789 A1 (BOLZER TODD [US] ET AL) 24 July 2003 (2003-07-24) * page 3, paragraph 23 * * figures 1,2 *	7,8,22	
A	AU 26840 71 A (RHEEM AUSTRALIA LIMITED) 28 September 1972 (1972-09-28) * page 4, lines 12-19 * * figure 4 *	11,14	
A	DE 20 2004 008058 U1 (VTG LEHNKERING REEDEREI GMBH [DE]) 22 July 2004 (2004-07-22) * page 2, paragraph 14 * * figures 2,3 *	12,15	
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 9 May 2007	Examiner Piolat, Olivier
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**CLAIMS INCURRING FEES**

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

**LACK OF UNITY OF INVENTION
SHEET B**

Application Number
EP 06 12 6843

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. claims: 1, 2-5, 16-20

Container with a detachable ascending tube

2. claims: 1, 6-9, 21-22

Container with a recess

3. claims: 13, 14-15, 10-12

Container with transport mounts

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 06 12 6843

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-05-2007

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19911009	A1	14-09-2000	NONE	
US 6024242	A1		NONE	
DE 9115953	U1	27-02-1992	NONE	
JP 2000136540	A	16-05-2000	NONE	
BE 1013186	A6	02-10-2001	NONE	
US 2004188447	A1	30-09-2004	NONE	
JP 2002309631	A	23-10-2002	NONE	
JP 11105977	A	20-04-1999	NONE	
JP 10174985	A	30-06-1998	NONE	
US 2003136789	A1	24-07-2003	US 2005077301 A1	14-04-2005
AU 2684071	A	28-09-1972	NONE	
DE 202004008058	U1	22-07-2004	EP 1598287 A1	23-11-2005