



(11) **EP 1 809 133 B9**

(12) **CORRECTED EUROPEAN PATENT SPECIFICATION**

(15) Correction information:
Corrected version no 1 (W1 B1)
Corrections, see
Description Paragraph(s) 60
Claims EN 1, 2, 6, 8, 12, 13

(51) Int Cl.:
A43B 3/26 *(2006.01)* **A43B 13/12** *(2006.01)*
A43B 3/10 *(2006.01)*

(86) International application number:
PCT/IL2005/001117

(48) Corrigendum issued on:
15.04.2015 Bulletin 2015/16

(87) International publication number:
WO 2006/046241 (04.05.2006 Gazette 2006/18)

(45) Date of publication and mention
of the grant of the patent:
02.07.2014 Bulletin 2014/27

(21) Application number: **05799424.6**

(22) Date of filing: **26.10.2005**

(54) **PERSONALLY ADJUSTABLE FOOTWEAR**

PERSÖNLICH VERSTELLBARE FUSSBEKLEIDUNG

CHAUSSURE ADAPTABLE INDIVIDUELLEMENT

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**

(30) Priority: **27.10.2004 IL 16485304**

(43) Date of publication of application:
25.07.2007 Bulletin 2007/30

(73) Proprietor: **Peeerfect Fit LLC**
New York NY 10036 (US)

(72) Inventors:
• **TVOUA, Ofer**
75240 Rishon Lezion (IL)

• **TVOUA, Amir**
75240 Rishon Lezion (IL)
• **CANFI, Ofer**
85338 Lehavim (IL)

(74) Representative: **Lotti, Giorgio et al**
Barzanò & Zanardo Milano S.p.A.
Via Borgonuovo, 10
20121 Milano (IT)

(56) References cited:
BE-A- 531 033 US-A- 2 211 509
US-A- 4 727 662 US-A- 4 944 099
US-A- 5 966 840 US-A- 6 138 385
US-A- 6 138 385 US-B1- 6 237 255
US-B1- 6 237 255

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

FIELD AND BACKGROUND OF THE INVENTION

[0001] This invention relates to footwear, particularly footwear whose size is adjustable.

[0002] The term "footwear" when used herein, is to be taken in its broadest sense and denotes shoes, sneakers, sandals, clogs, boots, skates, sportswear for the foot, etc.; and any of these terms may be substituted herein for the term "footwear".

[0003] There is known in the art shoes whose longitudinal dimension is adjustable by a variety of ways.

[0004] US 524,946 (Kregel) discloses a shoe intended for fitting to a deceased person for viewing and interment. Adjustability is achieved using an elastic band extending between a heel portion and toe portion designed to draw the heel portion forward to snugly fit to the foot of the deceased.

[0005] US 641,642 (Gunn) discloses a shoe, being adjustable length-wise and widthwise, the sole of which comprises a frame part at the shoe's heel and a shank at the middle/front of the sole. The frame part and shank are slidable with respect to one another to the extent of a slot in the shank. Upon adjusting to a desired length, the length of the sole is fixed by tightening a screw. The shoe comprises an upper, or top portion, designed to accommodate inserts on the right and left sides thereof, which can be folded to allow adjustment of the top portion of the shoe. The insert is secured by a lacing cord which passes between two vertical rows of eyelets. A similar arrangement is used to adjust the width of the shoe, with laterally arranged slots.

[0006] US 2,009,684 (Affronte) describes a shoe, having a similar length adjusting means wherein the shank has a tongue being slidable within a receiving portion of the heel section of the sole. The tongue has a plurality of holes for allowing a screw to pass and fix the tongue to the heel section at a hole corresponding to the desired shoe length.

[0007] US 2,497,175 (Mantos) provides a shoe formed of two main sections designed to be joined together by workmen in the shop of a shoe dealer whereby the size of the shoe can be adjusted to a given size prior to completing assembly of the shoe. A metal shank projecting from the toe section of the sole comprises an integral fork aligned with a metal sheath or plate mounted in the heel portion of the sole. The fork has tines with triangularly shaped lugs along their edges corresponding to receiving members on the sheath to allow the toe and heel sections of the shoe to be securely attached to produce a shoe having any number of discrete lengths.

[0008] US 3,389,481 (England) shows an expandable shoe having a mid-section of bellows-like material permitting longitudinal expansion and contraction along a sliding guide having a locking mechanism to secure the fit at a desired length. The locking mechanism comprises a metal shank having two sliding plates, one of which

has a transverse slot for receiving a detent formed in the other plate. A screw assembly extending up through the heel is removed to allow the plates to slide over one another, and then it is reinserted to retain the shoe in the newly extended position.

[0009] US 3,997,985 (Shina) discloses a stretchable shoe, particularly suitable for a growing child, comprising a front member and a rear member which may be adjusted in length. The front member and the rear member are separable and inter-connected by a screw which passes through one hole of the front member and one of a plurality of holes of the rear member. The front member is composed of an upper, an insole, a middle plate and a bottom plate, and the rear member is composed of a sole, an upper and a heel.

[0010] US 5,659,980 (Lin) discloses an adjustable shoe which has a heel, a toecap and an insole. The front portion of an instep has a plurality of positioning protrusions. First and second fastening pads are disposed on two outer sides of the heel. First and second ball buttons are disposed on the rear surface of the heel. An adjustable pad with positioning holes therein is disposed on the toecap from which two flaps extend. The inner surface of the flap has a fastening element. The first and second positioning plates are extended from the back of the outsole. The first positioning plate holds the first socket button and the second positioning plate holds the second socket button.

[0011] US 6,138,385 (Jungkind) describes a shoe sole having a jointed middle section located between toe and heel portions of the sole. The middle section is made of an elastically flexible of springy material configured as a wavy or folded web with crests and troughs. A spindle runs from the heel to the toe portions and has a head located inboard of the rear edge of the heel portion. The spindle is rotatable/screwable into a nut whereby the shoe can be adjusted in length.

[0012] Document US 6,237,255 discloses a device for personally adjusting the length of a shoe that comprises a front portion, a rear portion and a region of elongation interposed between the front portion and the rear portion. The region of elongation permits the variation of the length of the shoe sole. The described device further includes a retention mechanism for blocking in position the shoe sole length once it has been adjusted.

[0013] It would therefore be advantageous to provide footwear whose size can be adjusted by the wearer. It would also be advantageous to provide such adjustable footwear which is personalizable and easily and quickly re-adjustable.

SUMMARY OF THE INVENTION

[0014] The present invention relates to footwear whose size can be conveniently and easily adjusted without any need for tools.

[0015] Such footwear typically comprises a toe portion (hereinafter "toe"), a heel portion (hereinafter "heel"),

composing a sole and may also include a top portion or so-called upper.

[0016] According to the teachings of the present invention there is provided a personally adjustable footwear comprising the features of claim 1.

[0017] According to a further feature of the present invention, the toe portion, the heel portion and the intermediate portion are all integrally formed from a uniform composition.

[0018] According to a further feature of the present invention, the at least one sole layer has an upper surface providing a foot support, wherein the plurality of openings are configured to have a maximum open longitudinal dimension no greater than about 2.5 centimeters so as to provide near-continuous foot support

[0019] According to a further feature of the present invention, the at least one sole layer is implemented as at least two sole layers including a lower sole layer having a bottom surface configured for ground engagement and an upper sole layer including an upper surface for supporting a foot.

[0020] According to a further feature of the present invention, the upper sole layer is formed from a material softer than the lower sole layer.

[0021] According to a further feature of the present invention, the lower sole layer and the upper sole layer are shaped to define therebetween at least one longitudinal channel extending longitudinally between the toe portions and the heel portions, and wherein the retention mechanism includes an element deployed within the channel, the element being anchored to a first of the toe portion and the heel portion and being displaceable relative to the second of the toe portion and the heel portion.

[0022] According to a further feature of the present invention, the sole layer forms at least part of a sole arrangement, the sole arrangement including at least one longitudinal channel extending longitudinally between the toe portion and the heel portion, and wherein the retention mechanism includes an element deployed within the channel, the element being anchored to a first of the toe portion and the heel portion and being displaceable relative to the second of the toe portion and the heel portion.

[0023] According to a further feature of the present invention, the retention mechanism further includes a stepped resistance arrangement associated with the element and the second of the toe portion and the heel portion, the stepped resistance arrangement providing a resistive force opposing relative displacement of the toe portion and the heel portion between a plurality of predefined relative positions corresponding to a plurality of different lengths of the sole arrangement, such that a length of the sole arrangement is manually adjustable by manual application of force to overcome the resistive force, and such that, in the absence of manually applied force, the toe portion and the heel portion are retained in one of the predefined relative positions.

[0024] According to a further feature of the present in-

vention, the intermediate portion is resiliently biased to separate the toe portion and the heel portion to a predefined relative position corresponding to a maximum length of the sole arrangement, and wherein the retention mechanism further includes: (a) a flexible strap associated with the element and extending from the sole arrangement such that tension applied to the flexible strap relative to the second of the toe and the heel portions draws together the toe portion and the heel portion, thereby shortening the length of the sole arrangement; and (b) a locking arrangement for locking the flexible strap in a plurality of positions, thereby retaining the sole arrangement at a desired length.

[0025] According to a further feature of the present invention, the locking arrangement includes a first part of a hook-and-loop fastener associated with an end portion of the flexible strap and a complementary part of a hook-and-loop fastener associated with an upward-facing surface of the sole arrangement such that the flexible strap is folded onto the upward-facing surface to lock the sole arrangement at a desired length.

[0026] According to a further feature of the present invention, the retention mechanism further includes a manually releasable and manually engageable locking mechanism for locking a position of the element relative to the second of the toe portion and the heel portion.

[0027] According to a further feature of the present invention, the retention mechanism includes a manually releasable and manually engageable locking mechanism for locking a relative position of the toe portion and the heel portion.

[0028] Thus, the present invention provides footwear whose size can be conveniently and easily adjusted without any need for tools, possibly by a wearer thereof. The footwear according to embodiments of the invention is readjustable, thus it can be adjusted to a variety of lengths at any time.

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] In order to understand the invention and to see how it may be carried out in practice, embodiments will now be described, by way of non-limiting examples only, with reference to the accompanying drawings, in which:

Fig. 1 is a perspective view of an adjustable footwear not forming part of the present invention;

Fig. 2 is an exploded view of the footwear shown in Fig. 1;

Fig. 3A is a longitudinal sectional view along line III-III in Fig. 1;

Fig. 3B is a sectional side view of a modification of the footwear of Figs. 1-3;

Fig. 4 is a longitudinal sectional view showing another modification to the footwear shown in Fig. 1;

Fig. 5A is a perspective view of a segment usable in any of the embodiments of Figs. 1-4;

Figs. 5B-5J are perspective views of segments for

use in further embodiments of adjustable footwear, not forming part of the present invention;

Fig. 6 is a perspective view of an embodiment not forming part of the present invention;

Fig. 7 is a longitudinal sectional view of the embodiment shown in Fig. 6;

Fig. 8 is a top perspective view of a further adjustable footwear not forming part of the present invention;

Fig. 9A is a sectional view taken through plane IX-IX of Fig. 8;

Fig. 9B is a sectional view analogous to that of Fig. 9A illustrating an exemplary modification of the embodiment shown in Fig. 8;

Fig. 10 is a bottom perspective view of the embodiment shown in Fig. 8;

Fig. 11 is a bottom view of a modification of the embodiment of Fig. 1, not forming part of the present invention;

Fig. 12A-12C are side views of exemplary segments for use in the embodiment of Fig. 11;

Figs. 13A and 13B are upper and lower exploded isometric views, respectively, of a first variant, according to the invention, of the embodiment of Figs. 6 and 7;

Figs. 13C and 13D are upper and lower exploded isometric views of a slight variant of the implementation of Figs. 13A and 13B;

Figs. 14A and 14B are isometric views of a second variant, according to the invention, of the embodiment of Figs. 6 and 7, shown in an elongated and shortened state, respectively;

Fig. 14C is a partial exploded view of the implementation of Fig. 14A;

Fig. 15A is a partially cut-away lower isometric view of a third variant, according to the invention, of the embodiment of Figs. 6 and 7;

Fig. 15B is a longitudinal cross-sectional view taken through the implementation of Fig. 15A;

Fig. 16A is an isometric view of a fourth variant, according to the invention, of the embodiment of Figs. 6 and 7;

Fig. 16B is an isometric view of a retention mechanism from the implementation of Fig. 16A;

Figs. 17A and 17B are isometric views illustrating a further optional form of openings for rendering an intermediate sole portion flexible for implementation of the present invention; and

Fig. 18 is an isometric view of deployment of a set of size indicating indices for use in the above-referenced implementations according to a further feature of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0030] Referring to Figs. 1-5, an embodiment, including particular modifications, of an article of footwear, generally designated as **10**, is *illustrated*. The footwear **10** comprises a toe portion **12** (hereinafter "*toe*") and a heel

portion **14** (hereinafter "*heel*") and a plurality of segments **16** disposed therebetween. Extending from the toe **12** toward the heel **14** is at least one (and typically more than one) segment holding member in the form of a rod-like member - for example, four rods **18** as illustrated in Fig. 2.

[0031] The segments **16** typically have a geometry wherein they have a length and a width, the length being longer than the width - in other words an aspect ratio greater than one. The segments **16** may comprise an indication of their size, in particular the dimension affecting the length of the footwear **10**. Such an indication may be a numeral thereon indicating its dimension, or a color, shape, decoration, etc., corresponding to a dimension. However, the segments **16** may be of various shapes, colors, etc., merely for decorative purposes. The segments **16** may also be made of different materials for functional (e.g. wear-strength, comfort) and/or decorative purposes.

[0032] The segments **16** have essentially horizontal holes or bores **20** (best seen in Fig. 4) adapted so that the rods **18** can pass therethrough. For this purpose, at least some of the segment's bores **20** are alignable with each other. In this manner, the segments **16**, which constitute a middle portion of the sole of the footwear, can be incorporated into the sole or removed therefrom whereby the size of the footwear **10** is adjustable.

[0033] The heel **14** also has holes or bores **24** being alignable with the rods **18** and thus alignable with at least some of the bores **20** in the segments **16**. The heel's bores **24** are adapted to receive the rods **18** (i.e. free ends **22** thereof). The rods **18** extend into the heel **14** where they are fixed in place by a locking mechanism **26**.

[0034] The locking mechanism **26** comprises, for example, a top portion **28** and a bottom portion **30**, at least one or the other of the portions adapted to hold or clamp the rods **18** in place. Typically, the portions **28** and **30** are designed to be engageable with each other, in any known manner. For this purpose, the portions **28** and **30** may have engagement members **28a** and **30a**, respectively.

[0035] In order to adjust the size of the footwear **10**, the locking mechanism **26** is disengaged allowing the heel **14** to be slid back away from the toe **12** whereby it is removed from the rods **18**. Then, segments **16** are added or removed to increase or decrease the length of the footwear **10**. The heel **14** is then replaced, and then the locking mechanism **26** is reaffixed.

[0036] To further accommodate such adjustment, if the footwear **10** is a sandal or "flip-flop" or "thong" type, wherein it typically incorporates a toe-strap **32**, the positioning of said toe-strap **32** may be altered. For this purpose, at least some of the segments **16** may further comprise (essentially) vertical bores **34** (Figs. 3A, 3B and 4) adapted to receive attachment projections **36** of the toe-strap **32** which can be attached (fixed in place) by any known means.

[0037] As understood from the exploded view of the

footwear **10** in Fig. 2, the toe **12** can be composed of layers, for example an outsole layer **121**, an insole layer **122** and an intermediate layer **123**. Such a design may be convenient for manufacturing and allow for portions/layers of different characteristics. For example, the outsole layer **121** may be made of a wear resistant material for increasing the life of the footwear **10** and the insole layer **122** may be made of a relatively soft or compliant material for comfort of a wearer.

[0038] Fig. 4 illustrates an article of footwear **10** being a modification of that described with reference to the preceding figures. Here, the footwear **10** comprises at least some segments **16a** having at least one transverse bore **38**; best seen in Fig. 5A. A segment **16b** shown in Fig. 5A illustrates the possibility of the segment having both bores like bores **20** and like bore **38**; thereby providing different options for achieving a given footwear length as well as a particular aesthetic aspect (e.g. different colors on each face of the segment) or flexibility thereto.

[0039] Additionally, the segments **16b** could include bores **20a** essentially perpendicular to bores **20** such that the segment could be incorporated in the footwear **10** rotated a quarter turn/rotation to that shown in Fig. 5A. This feature could have advantages in situations, for example, where any of the segments **16b** have designs thereon or are shaped in a way that the overall design of the footwear can be changed (by turning/rotating segments), thereby giving the wearer the option to "self-design" the footwear to his/her taste. Bore **38** also provides flexibility in this regard.

[0040] It should be understood that the heel **14** could be designed in a manner analogous to that just described with respect to the toe **12**, and vice versa. In other words, referring now to Fig. 3B, there may be footwear **10'** wherein the rods **18** extend from a heel **14'** toward a toe **12'** and being locked in place by a locking mechanism **26'** at the toe **12'**, *mutatis mutandis*.

[0041] It should also be noted that rather than providing several extension segments **16**, there may be provided one or more segments, the length of which may be predetermined or be set to suit an individual's foot size, e.g. by trimming the length of such segments.

[0042] Figs. 5B-5I illustrate various examples of segments which may be used in adjustable footwear according to further embodiments not forming part of the present invention. The segments shown in these figures do not require a segment holding member (rod, tongue, cable, elastic, etc.) rather instead they comprise inter-engaging or inter-corresponding members, typically male-female type engagement elements.

[0043] In Fig. 5B there is shown a segment **116** having a "Lego™-type" configuration. Thus, it has projections **118** (only one is seen) and indentations **120** which are designed to correspond to indentations and projections of other similarly configured segments. Naturally, a toe and heel of footwear used in an embodiment shown in Fig. 5B would also have corresponding projections or indentations, as the case may be, so that the segments

116 could be suitably joined thereto. It should be understood that this latter situation is the same for all of the segments described in Figs. 5B-5I, and therefore this fact shall not be repeated.

5 [0044] In Fig. 5C there is shown a segment **216** being similar to segment **116** of Fig. 5B, however it comprises an elongated projection **218** and a slotted indentation **220** - again, designed to correspond to an indentation and projection of other similarly configured segments.

10 [0045] In Fig. 5D there is shown a segment **316** comprising a wide hook-shaped projection **318** and a rod **320**. For illustration purposes, the segment **316** is shown with a partial cutaway in the area of the rod **320** and typically the rod **320** would be attached to the rest of the segment at both its ends to provide strong support. To join such segments **316** with each other, one segment is angled to allow the hook-shaped projection **318** to be slid under the slotted indentation **320** of another segment, and then it is arranged to be flush to that other segment.

20 [0046] Fig. 5E presents a segment **416** being similar to segment **316** of Fig. 5D, however it comprises a pair of resilient projections **418** that can inter-engage with a rod **420**. Again, for illustration purposes, the segment **416** is shown with a partial cutaway in the area of rod **420**.

25 To join such segments **416** with each other, one segment is pushed toward another segment causing the projections **418** to first open when nubs **422** of the projections **418** contact the rod **420** of another segment, and then to close around the backside of the rod **420** in a snap-fit manner.

30 [0047] Fig. 5F shows another segment **516** connectable to like segments; as above. Here, the segment **516** comprises a screw-like projection **518** that can inter-engage with a threaded indentation **520**. To join such segments **516** with each other, one segment is simply turned so that its screw-like projection **518** screws into the threaded indentation **520** of another segment.

35 [0048] Fig. 5G shows yet another example of a segment **616** connectable to like segments. Here, the segment **616** comprises a projection, for example an L-shaped projection **618** that can inter-engage with a corresponding indentation **620**. The indentation **620** comprises a slot **622** and the projection comprises an arm **624**, the slot having a length dimension d1 typically being a bit longer than a length dimension d2 of the arm **624** of the L-shaped projection **618**.

40 [0049] To join such segments **616** with each other, a first segment is turned 90° so that its L-shaped projection **618** fits into the slot **622** of the other segment, then the first segment is pushed flush to the other segment, and lastly it is turned 90° so that the arm **624** enters an arm-receiving cavity **626** of the indentation **620**.

45 [0050] Fig. 5H shows yet a further example of a segment **716** connectable to like segments. Here, the segment **716** is a puzzle-like piece and comprises a projection **718** adapted to fit into an indentation **720** by either sliding transversely or by a pressure/snap fitting method.

[0051] Fig. 5I provides an embodiment showing another

er example wherein segments are inter-connected. Here, segments **816** (only one shown) have hook and loop fasteners (Velcro™) **818** and **820** adhered to their sides whereby they can attach one to the next.

[0052] Fig. 5J illustrates another embodiment wherein segments are inter-connected. However, in this case there are segments **916** that remain connected while being movable in relation to each other in that they can be spaced apart, to various degrees, or be positioned adjacent each other. This option can be accomplished, for example, as seen in Fig. 5I.

[0053] The segments **916** have segment connecting members **918**, for example nail-shaped members having a head **920** and a stem **922**. The segments **916** comprise cavities **924** (shown with dashed lines) within which the heads **920** and a portion of the stems **922** are located; these also being shown with dashed lines where they are internal to the segments **916**. The cavities **924** are shaped such that the connecting members **918** can be slid back and forth whereby the segments **916** may be positioned closer or farther from each other.

[0054] To fix the distance, the cavities **924** are adapted to fairly snugly hold the connecting members **918**, or the segments **916** may be held in place by one of several alternate methods (e.g. such as described below).

[0055] Figs. 6 and 7 illustrate an embodiment not forming part of the present invention, providing an article of footwear, generally designated as **100**. Here, disposed between a toe **12a** and a heel **14a** is a flexible bellows-like intermediate portion **50** which connects the toe and heel and provides size flexibility to the footwear **100**. More specifically, as illustrated in Figures 6 and 7, footwear **100** includes at least one sole layer including: toe portion **12a**, heel portion **14a**, and intermediate portion **50**, the intermediate portion being integrally formed with both the toe portion and the heel portion, preferably from a uniform composition. It is a particularly preferred feature of this embodiment, and of the variants of this embodiment described below, that intermediate portion **50** features a plurality of openings passing substantially vertically through the sole layer so that intermediate portion **50** is elastically flexible to allow relative longitudinal displacement of the toe portion and the heel portion to vary a length of the layer without significant variation in a thickness of the layer. In this context, the term "vertically" is used to refer to a direction generally perpendicular to the ground-engaging surface and/or foot supporting surface of the footwear.

[0056] Footwear **100** also features a retention mechanism associated with both toe portion **12a** and heel portion **14a** and configured for retaining any of a plurality of relative positions between the toe portion and the heel portion. Preferably, the sole arrangement includes at least one longitudinal channel (also referred to as a "passage") extending longitudinally between the toe portion and the heel portion, and the retention mechanism includes an element (in this case, a tongue **52**) deployed within the channel. The element is anchored to either toe

portion **12a** or heel portion **14a** and is displaceable relative to the other portion (heel portion **14a** or toe portion **12a**, respectively).

[0057] Thus, in the example illustrated in Figures 6 and 7, the toe **12a** has a tongue **52**, which may be integral therewith or attached thereto, adapted to be slidable through a passage (not seen) in the intermediate portion **50**. The tongue **52** comprises a plurality of through-holes **54** being collinear and typically equally spaced apart. The heel **14a** comprises a tongue receptacle **56** having depressions **58** corresponding, and similarly spaced, to holes **54**.

[0058] The heel **14a** comprises a top portion **60** adapted to be upwardly bendable, exposing the tongue receptacle **56**. The top portion **60** includes at least one downwardly projecting peg-like member **62**, arranged, and of a size, to pass through the tongue's holes **54** and be engagedly receivable in the depressions **58** of the tongue receptacle **56**, for example, in a snap-fit type manner.

[0059] To adjust the size of the footwear **100**, the heel's top portion **60** is lifted (illustrated by dashed lines in Fig. 7), thereby decoupling the peg-like members **62** from the depressions **58** and lifting them out from the holes **54**. The toe **12a** and the heel **14a** are then slid toward or away from each other to respectively decrease or increase the length of the footwear **100**. This may entail compressing or expanding the intermediate portion **50** for which purpose it is made of a flexible, resilient material.

[0060] When a desired length is achieved, within the tolerance of the distance between the spaced-apart holes **54**, the size of the footwear **100** can be fixed. This is accomplished by aligning the tongue's holes **54** with the tongue receptacle depressions **58** and closing the heel's top portion **60** downward to recouple the peg-like members **62** with the depressions **58**.

[0061] Optionally, there may be provided a marker **64**, such as an arrow or projection, associated with the tongue **52**, along with indicia **66** adjacent the tongue receptacle **56**, for indicating a shoe size. This marker/indicia arrangement may also be useful for making it easier to align the tongue's holes **54** with tongue receptacle's depressions **58**; for example, by means of a projection/socket (male/female component) arrangement for ensuring alignment.

[0062] It should be understood that the function provided by the heel's top portion **60** could alternatively be provided by a bottom portion thereof or even by a top or bottom portion of the toe **12a**, *mutatis mutandis*.

[0063] Turning now to Figures 13A-18, these illustrate a number of variant implementations based upon the concept of footwear **100**, and more specifically, wherein a sole arrangement includes at least one layer formed with a flexible intermediate portion for allowing elongation and contraction of a length of the sole arrangement. These variant implementations differ from footwear **100** described above primarily in: (a) the shape of the vertical openings through the layers used to impart flexibility to

the intermediate portion; and (b) the implementations of the retention mechanism.

[0064] Turning now specifically to Figures 13A and 13B, these show an implementation of personally adjustable footwear **1000**, constructed and operative according to the teachings of the present invention. Footwear **1000** has a sole arrangement assembled primarily from an upper sole layer **1002** and a lower sole layer **1004**, and which form between them a channel **1006** (Fig. 13B) which receives a tongue **1008**. At least one, and preferably both, of upper and lower sole layers **1002** and **1004** is formed with a toe portion **1012** and a heel portion **1014** interconnected by an intermediate portion **1010** which features a pattern of vertical openings **1016**.

[0065] Openings **1016** are deployed to provide a latticework pattern as viewed from above, i.e., a pattern of crisscross strips with roughly parallelogram openings between them, thereby imbuing the intermediate portion with greatly enhanced facility to accommodate longitudinal extension and/or compression while keeping the dimensions of the individual openings relatively small so that the upper surface of upper layer **1002** provides comfortable near-continuous support for the foot of a user. The term "foot support" in this context is used to refer to an element or surface which provides the primary mechanical support to the underside of the foot, but need not be in direct contact with the foot. Thus, the "foot support" may be overlaid by one or more layers of padding or other functional or aesthetic layers. In order to provide the aforementioned near-continuous support for the foot, the plurality of openings are preferably configured to have a maximum open longitudinal dimension no greater than about 2.5 centimeters.

[0066] It should be noted that the use of substantially vertical openings to provide the required flexibility has profound advantages over the various solutions proposed by the aforementioned prior art documents. Firstly, since each layer is integrally formed, the production processes required are simple and cost effective, thereby rendering the footwear suitable for large scale production. Secondly, since flexing occurs primarily within the plane of the sole layer, the thickness of the layer remains substantially unchanged during elongation or shortening of the footwear, thereby allowing the upper surface of the upper sole layer to be used directly as a foot support surface without requiring complicated arrangements of overlapping and sliding rigid insoles or the like.

[0067] It should be noted that the subdivision of the sole layers into toe portion, heel portion and intermediate portion does not simply any particular relative dimensions between the portions, and that there is no lower limit to the size of the toe portion and heel portion. Thus, one or both of the toe portion and heel portion may optionally be implemented as end portions of the sole layers so that the adjustable-length intermediate layer with its vertical openings occupies a major portion, or even substantially the entirety, of the length of the sole.

[0068] As mentioned, the entirety of each layer **1002**

and **1004** is preferably formed integrally from material of substantially uniform composition, the varying mechanical properties being provided by the geometrical form of the layer. The separate layers, on the other hand, may be produced from different materials to provide particular desired footwear characteristics. Thus, by way of non-limiting example, upper sole layer **1002** may be formed of relatively soft resilient material to increase wearing comfort while lower sole layer **1004** may be formed of relatively harder abrasion resistant material offering a hard-wearing ground-engaging surface. Suitable materials for providing the required mechanical properties, and suitable associated manufacturing techniques, are well known in the art and will not be addressed here in detail.

[0069] As mentioned above, lower sole layer **1002** and upper sole layer **1004** are shaped to define therebetween at least one longitudinal channel **1006** extending longitudinally between toe portions **1012** and heel portions **1014**. Tongue **1008**, which is deployed within channel **1006**, is anchored to either the toe portions **1012** or the heel portions **1014** and is displaceable relative to the other. In the case shown here, tongue **1008** is anchored to toe portions **1012** by a shaped head portion with a central hole which engages a corresponding socket and projecting tab formed in the underside of upper sole layer **1012**.

[0070] The implementation of Figures 13A and 13B is preferably formed with intermediate portion **1010** resiliently biased to separate the toe portion and the heel portion to a predefined relative position corresponding to a maximum length of the sole arrangement. This simplifies the mechanical requirements on the retention mechanism which then needs only act to limit the length of the footwear to a desired length against the inherent elasticity of the sole arrangement. In this case, the retention mechanism further includes a flexible strap **1018** associated with tongue **1008** and extending from the sole arrangement such that tension applied to the flexible strap relative to heel portion **1014** draws together toe portion **1012** and heel portion **1014**, thereby shortening a length of the sole arrangement. A low friction slide strip **1019** is optionally provided to help ensure free longitudinal movement of the strap **1018** at its relative thick point of attachment to tongue **1008**. A locking arrangement is also provided for locking the flexible strap in a plurality of positions, thereby retraining the sole arrangement at a desired length.

[0071] In the particularly preferred implementation illustrated here, the locking arrangement includes a first part of a hook-and-loop fastener **1020**, such as the fastener type typically referred to by the name Velcro™, associated with an end portion of flexible strap **1018** and a complementary part of a hook-and-loop fastener **1022** associated with an upward-facing surface of the sole arrangement such that the flexible strap is folded onto the upward-facing surface to lock the sole arrangement at a desired length. Although the hook-and-loop fastener is a particularly preferred option due to its convenience and

continuous adjustability, it should be noted that alternative fasteners are also within the scope of the invention. Example include, but are not limited to, snap-in-studs, various plug-and-socket arrangements, and various types of pins or hooks. In all cases, the fastener is preferably chosen to be a manually operated fastener which does not require any tools or any difficult manipulation to perform.

[0072] For simplicity of presentation, the implementation shown here is a sandal of the "thong" type, having an aperture **1024**, slits **1026** and clips **1028** for retaining the straps in the required positions. As before, the principles of the present invention are equally applicable to all types of footwear, as will be clear to one ordinarily skilled in the art.

[0073] Turning now briefly to Figures 13C and 13D, these show an implementation closely analogous to that of Figures 13A and 13B, differing primarily in that channel **1006** and the socket and tab for accommodating tongue **1008** are formed primarily in the upper surface of lower sole layer **1004**. In all other respects, the implementation of Figures 13C and 13D may be fully understood with reference to the description of Figures 13A and 13B. It should further be noted that other configurations, including but not limited to, implementations where the sole arrangement is formed from a single unitary layer with a suitable channel formed therethrough, or where the channel passes along the upper or lower surface of the sole arrangement, also fall within the scope of the present invention.

[0074] Referring briefly to Figure 18, it should be noted that implementations of the present invention employing straps folded onto the surface of the sole arrangement may also be provided with arrangements of indices indicating the corresponding shoe size to which the footwear is adjusted. In this case, the indices preferably appear on an upward facing surface of the sole arrangement and are aligned with a corresponding mark, tab or cut-out window formed in the flexible strap **1018**.

[0075] Turning now to Figures 14A-14C, these show a further implementations of footwear, generally designated **1050**, constructed and operative according to the teachings of the present invention. Footwear **1050** is generally similar to footwear **1000**, and equivalent elements are labeled similarly. Footwear **1050** differs from footwear **1000** primarily by the inclusion of an additional stepped resistance arrangement.

[0076] Specifically, the retention mechanism of footwear **1050** includes a stepped resistance arrangement, associated with tongue **1008** and heel portion **1014**, configured to provide a resistive force opposing relative displacement of the toe portion and the heel portion between a plurality of predefined relative positions corresponding to a plurality of different lengths of the sole arrangement. As a result, a length of the sole arrangement is manually adjustable by manual application of force to overcome the resistive force, while in the absence of manually applied force, the toe portion and the heel portion are re-

tained in one of the predefined relative positions. In other words, when flexible strap **1018** is not fastened, the sole arrangement can be taken in two hands by a user and the toe and heel either pulled apart or pushed together, passing through a plurality of states each defined by a positive "click" position. Then, when the desired length of the footwear is achieved, flexible strap **1018** is fastened as described above to provide supplemental fixing of the desired length.

[0077] One preferred example of an implementation of the stepped resistance arrangement is visible in the partial exploded view of Figure 14C. In this case, tongue **1008** is formed with a pair of resilient outwardly-biased tabs **1052** which engage a sequence of V-shaped notches **1054** formed along sides of channel **1006** within heel portion **1014**. The resilience of tabs **1052** and the angle of notches **1054** are chosen to ensure that the sole arrangement can be manually and non-destructively adjusted by application of axial compression or tension while providing sufficient resistive forces to retain a current length in the absence of significant externally applied forces.

[0078] The combination of the stepped resistance arrangement together with the flexible strap fastening arrangement is considered particularly advantageous since it combined the convenience of temporary fixing of the length prior to attachment of the strap fastening with the positive fastening effect of the strap arrangement. Nevertheless, it should be appreciated that both the strap fastening arrangement and the stepped resistance arrangement are each considered to be individually useful as freestanding products in their own right.

[0079] Turning now to Figures 15A and 15B, it should be noted that many other arrangements may be used to implement the aforementioned stepped resistance arrangement. By way of a further non-limiting example, Figures 15A and 15B illustrate a stepped resistance arrangement wherein the lateral engagement of the previous implementation is replaced with a vertically undulating arrangement. Specifically, this implementation of an item of footwear **1060** employs a tongue **1008** having a vertically undulating tail portion **1062** which passes over and/or under corresponding undulating configurations formed in the overlying surface of the upper sole layer and/or upper surface of the lower sole layer. This arrangement provides a similar stepped resistance effect to the notched arrangement described above.

[0080] Turning now to Figures 16A and 16B, there is shown a further variation of footwear, generally designated **1070**, constructed and operative according to the teachings of the present invention, in which the retention mechanism includes a manually releasable and manually engageable locking mechanism for locking a relative position of the toe portion and the heel portion. In this case, a central tongue **1072** incorporated in the heel portion is formed with a bilateral series of recesses **1074** and a complementary fork **1076** incorporated in the toe portion is formed with outwardly flexible arms which bear

engagement features 1078 for engaging the recesses. This arrangement provides manually operated positive locking of the length of the sole arrangement. This allows the use of an intermediate portion of the sole arrangement which is biased to either an intermediate length state or even the shortest length state, the sole arrangement being locked in a state with a desired degree of longitudinal extension (stretching) by the retention mechanism.

[0081] Referring briefly to Figures 17A and 17B, there is shown one example of an arrangement of vertical openings for the intermediate portion of the sole arrangement particularly suitable for implementations which are initially biased to their shortest state. Specifically, in this case, the sole arrangement is formed from one or more layers which initially assumes an unstressed state having a series of staggered transverse slits in its intermediate portion (Figure 17A). When stretched longitudinally, the material of the intermediate portion opens up to form a latticework pattern as illustrated in Figure 17B.

[0082] A further embodiment, not forming part of the present invention, is illustrated in Figs. 8-10, wherein there is an article of footwear 200 comprising elongated projections 70 extending from a heel 14b toward a toe 12b thereof. The profile of the projections 70 (Fig. 9A) corresponds to channels 72 in an elongated projection receiving portion 74 projecting from the toe 12b.

[0083] The heel's projections 70 are slidable toward and apart from the receiving portion 74. It should be noted however that the profile of the projection 70, in combination with the shape of the receiving portions channels 72, are of a geometry whereby the members are prevented from significantly sliding with respect to each other in the vertical direction. This is a much preferred situation for since it would otherwise be potentially inconvenient or uncomfortable to the wearer. It should be understood that many other profile/shape combinations are possible which would prevent such unwanted vertical displacement.

[0084] Fig. 9B illustrates one example of the many alternative interacting configurations for elongated projections and corresponding channels of a projection receiving portion. In this example, the projections are inverted T-shaped elongated projections 270, which are engageable in correspondingly shaped channels 272 with a projection receiving portion 274. It should be understood that such projections may be any of a variety of profiles in addition to those described above, e.g. L-shaped, bulb-shaped, J-shaped, Y-shaped, anchor-shaped, cross-shaped, and the like.

[0085] Appropriate design of the exemplary projections 70, 270 and channels 72, 272, respectively, can allow the footwear 200 to be adjusted to a desired length and remain at such while it is worn, for example, via a pressure or friction inter-fitting of the projections and receiving portions. However, the footwear 200 typically will include an auxiliary locking arrangement, such as that now described.

[0086] An example of such a locking arrangement is shown in Fig. 10, wherein extending from the toe 12b toward the heel 14b is a tongue 76 which comprises at least one peg-like member projecting therefrom. The peg-like member is not visible, however it can be of a form similar to that described above with reference to Figs. 6 and 7. The heel 14b comprises a tongue receptacle 78 comprising a plurality of depressions 80 which are adapted to receive the at least one peg-like member.

[0087] The size of the shoe can be adjusted by removing the tongue 76 from the tongue receptacle 78, sliding the toe and the heel apart or together - corresponding to the desired footwear size - and then reengaging the tongue 76 and the tongue receptacle 78 (i.e. pressing the peg-like structure into a/the depression(s)).

[0088] Once again, it should be understood that heel/toe (i.e. projections/receiving portion) could be arranged conversely and that the tongue could be disposed at either of the top or bottom of the sole of the footwear and could alternatively extend from the heel 14b, *mutatis mutandis*.

[0089] Fig. 11 shows a modification of the embodiment of Fig. 1 where there is footwear 110 wherein extending between a toe 112 and a heel 114 is at least one, typically more than one, segment holding member in the form of a stretchable member or elastic member 117 (two shown) running through segments 119 (therefore shown by dashed lines). The segments 119 can be added or removed upon pulling the toe 112 and heel 114 apart and the segment(s) is then fitted on the elastic member 117 or removed therefrom, respectively.

[0090] Figs. 12A - 12C provide some examples of segments which are suitable for use in the embodiment of Fig. 11. As such, Fig. 12A shows a segment 121 with one or more slits 123 adapted to allow the elastic member 117 to slide therealong the slits having a cavity 125 for holding the elastic member when the footwear 110 is assembled.

[0091] Fig. 12B shows a segment 131 having a transverse slit 133, the segment adapted to spread open whereby the elastic member 117 can be inserted or removed for adding or removing a segment, respectively.

[0092] Fig. 12C shows a segment 141 comprising two portions 143 and 145 held adjacent to each other by a hinge 147 at one end thereof and having a latch arrangement 149 at the other end thereof. To allow adding the segment 141 to the footwear 110, the segment can be opened by unlatching the latch arrangement 149 and pivoting the portions 143, 145 at the hinge 147 and fitting the segment around the elastic member 117. The reverse procedure is used to remove the segment 141 from the footwear 110.

[0093] It should be understood that segments such as segments 121, 31 and 141, and the like, can also be used in connection with the embodiment of Fig. 1.

[0094] It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown by the exemplary embodiments

described hereinabove. Thus, it should be understood that numerous additional embodiments are within the scope of the invention.

[0095] Further, the invention has been illustrated in relation to sandal type (i.e. so-called flip-flops or thongs), however, the invention also can embody footwear such as more conventional shoes and the like by incorporating known means for allowing the expansion/contraction of a footwear's upper portion (e.g. that described in the above-mentioned prior art).

[0096] In addition, it should be understood that modifications may be made. For example, any embodiments may incorporate locking mechanisms such as described with reference to Fig. 6.

[0097] It will be appreciated that the above descriptions are intended only to serve as examples, and that many other embodiments are possible within the scope of the present invention as defined in the appended claims.

Claims

1. Personally adjustable footwear (100,1000) comprising:

(a) at least one sole layer including: a toe portion (12a,1012), a heel portion (14a,1014), and an intermediate portion (50,1010), said intermediate portion (50,1010) being integrally formed with both said toe portion (12a,1012) and said heel portion (14a,1014), said intermediate portion (50,1010) having a plurality of openings passing substantially vertically through said layer so that said intermediate portion (50,1010) is elastically flexible to allow relative longitudinal displacement of said toe portion (12a,1012) and said heel portion (14a,1014) to vary a length of said layer without significant variation in a thickness of said layer; and

(b) a retention mechanism associated with both said toe portion (12a,1012) and said heel portion (14a,1014), said retention mechanism being configured for retaining any of a plurality of relative positions between said toe portion (12a,1012) and said heel portion (14a,1014) **characterized in that** said plurality of openings are deployed to provide a latticework pattern as viewed from above.

2. The footwear (100,1000) of claim 1, wherein said toe portion (12a,1012), said heel portion (14a,1014) and said intermediate portion (50,1010) are all integrally formed from a uniform composition.

3. The footwear (100,1000) of claim 1, wherein said at least one sole layer has an upper surface providing a foot support, wherein said plurality of openings are configured to have a maximum open longitudinal di-

mension no greater than about 2.5 centimeters so as to provide near-continuous foot support.

4. The footwear (1000) of claim 1, wherein said at least one sole layer is implemented as at least two sole layers including a lower sole layer (1004) having a bottom surface configured for ground engagement and an upper sole layer (1002) including an upper surface for supporting a foot.

5. The footwear (1000) of claim 4, wherein said upper sole layer (1002) is formed from a material softer than said lower sole layer (1004).

6. The footwear (1000) of claim 4, wherein said lower sole layer (1004) and said upper sole layer (1002) are shaped to define therebetween at least one longitudinal channel (1006) extending longitudinally between said toe portions (1012) and said heel portions (1014) and wherein said retention mechanism includes an element deployed within said channel, said element being anchored to a first of said toe portion (1012) and said heel portion (1014) and being displaceable relative to the second of said toe portion (1012) and said heel portion (1014).

7. The footwear (1000) of claim 1, wherein said sole layer forms at least part of a sole arrangement, said sole arrangement including at least one longitudinal channel (1006) extending longitudinally between said toe portion (1012) and said heel portion (1014), and wherein said retention mechanism includes an element deployed within said channel, said element being anchored to a first of said toe portion (1012) and said heel portion (1014) and being displaceable relative to the second of said toe portion (1012) and said heel portion (1014).

8. The footwear (1000) of claim 7, wherein said retention mechanism further includes a stepped resistance arrangement associated with said element and said second of said toe portion (1012) and said heel portion (1014), said stepped resistance arrangement providing a resistive force opposing relative displacement of said toe portion (1012) and said heel portion (1014) between a plurality of predefined relative positions corresponding to a plurality of different lengths of said sole arrangement such that a length of said sole arrangement is manually adjustable by manual application of force to overcome said resistive force, and such that, in the absence of manually applied force, said toe portion (1012) and said heel portion (1014) are retained in one of said predefined relative positions.

9. The footwear (1000) of claim 8, wherein said intermediate portion (1010) is resiliently biased to separate said toe portion (1012) and said heel portion

(1014) to a predefined relative position corresponding to a maximum length of said sole arrangement, and wherein said retention mechanism further includes:

- (a) a flexible strap (1018) associated with said element and extending from said sole arrangement such that tension applied to said flexible strap (1018) relative to said second of said toe (1012) and said heel (1014) portions draws together said toe portion (1012) and said heel portion (1014) thereby shortening said length of said sole arrangement; and
- (b) a locking arrangement for locking said flexible strap (1018) in a plurality of positions, thereby retaining said sole arrangement at a desired length.

10. The footwear (1000) of claim 7, wherein said intermediate portion (1010) is resiliently biased to separate said toe portion (1012) and said heel portion (1014) to a predefined relative position corresponding to a maximum length of said sole arrangement and wherein said retention mechanism further includes:

- (a) a flexible strap (1018) associated with said element and extending from said sole arrangement such that tension applied to said flexible strap (1018) relative to said second of said toe (1012) and said heel (1014) portions draws together said toe portion (1012) and said heel portion (1014), thereby shortening a length of said sole arrangement; and
- (b) a locking arrangement for locking said flexible strap (1018) in a plurality of positions, thereby retaining said sole arrangement at a desired length.

11. The footwear (1000) of claim 10, wherein said locking arrangement includes a first part of a hook-and-loop fastener (1020) associated with an end portion of said flexible strap (1018) and a complementary part of a hook-and-loop fastener (1022) associated with an upward-facing surface of said sole arrangement such that said flexible strap (1018) is folded onto said upward-facing surface to lock said sole arrangement at a desired length.

12. The footwear (1000) of claim 7, wherein said retention mechanism further includes a manually releasable and manually engageable locking mechanism for locking a position of said element relative to said second of said toe portion (1012) and said heel portion (1014).

13. The footwear (100,1000) of claim 1, wherein said retention mechanism includes a manually releasable

and manually engageable locking mechanism for locking a relative position of said toe portion (12a,1012) and said heel portion (14a,1014).

5

Patentansprüche

1. Persönlich einstellbares Schuhwerk (100, 1000), umfassend:

10

(a) mindestens eine Sohlenlage, die Folgendes umfasst: einen Zehenbereich (12a, 1012), einen Fersenbereich (14a, 1014) und einen Zwischenbereich (50, 1010), wobei dieser Zwischenbereich (50, 1010) integral mit sowohl dem Zehenbereich (12a, 1012) als auch dem Fersenbereich (14a, 1014) ausgebildet ist, wobei dieser Zwischenbereich (50, 1010) eine Vielzahl von Öffnungen aufweist, die im Wesentlichen senkrecht durch die Lage verlaufen, so dass dieser Zwischenbereich (50, 1010) elastisch flexibel ist, um eine relative Längsverschiebung des Zehenbereichs (12a, 1012) und des Fersenbereichs (14a, 1014) zu ermöglichen, um eine Länge dieser Lage ohne erhebliche Änderung einer Dicke dieser Lage zu ändern; und

25

(b) einen Haltemechanismus, der mit sowohl dem Zehenbereich (12a, 1012) als auch dem Fersenbereich (14a, 1014) verbunden ist, wobei dieser Rückhaltemechanismus gestaltet ist, um jede einer Vielzahl von Relativlagen zwischen dem Zehenbereich (12a, 1012) und dem Fersenbereich (14a, 1014) beizubehalten, **dadurch gekennzeichnet, dass** diese vielen Öffnungen so verteilt sind, dass sie in der Draufsicht ein Gitter bereitstellen.

30

35

2. Schuhwerk (100, 1000) nach Anspruch 1, wobei der Zehenbereich (12a, 1012), der Fersenbereich (14a, 1014) und der Zwischenbereich (50, 1010) alle integral aus einer einheitlichen Zusammensetzung ausgebildet sind.

40

3. Schuhwerk (100, 1000) nach Anspruch 1, wobei die mindestens eine Sohlenlage eine Oberseite aufweist, die eine Fußauflage bereitstellt, wobei die vielen Öffnungen so gestaltet sind, dass sie eine maximale offene Längsabmessung von nicht mehr als ungefähr 2,5 Zentimetern haben, um eine nahezu durchgehende Fußauflage bereitzustellen.

45

4. Schuhwerk (1000) nach Anspruch 1, wobei die mindestens eine Sohlenlage als mindestens zwei Sohlenlagen ausgeführt ist, die eine untere Sohlenlage (1004) mit einer Unterseite, die gestaltet ist, um am Boden anzugreifen, und eine obere Sohlenlage (1002) umfassen, die eine Oberseite zum Tragen eines Fußes umfasst.

50

55

5. Schuhwerk (1000) nach Anspruch 4, wobei die obere Sohlenlage (1002) aus einem weicherem Material als die untere Sohlenlage (1004) ausgebildet ist.
6. Schuhwerk (1000) nach Anspruch 4, wobei die untere Sohlenlage (1004) und die obere Sohlenlage (1002) so geformt sind, dass sie dazwischen mindestens einen Längskanal (1006) definieren, der sich in Längsrichtung zwischen den Zehenbereichen (1012) und den Fersenbereichen (1014) erstreckt, und wobei der Haltemechanismus ein in diesem Kanal angeordnetes Element umfasst, wobei dieses Element an einem ersten von dem Zehenbereich (1012) und dem Fersenbereich (1014) verankert und relativ zu dem zweiten von dem Zehenbereich (1012) und dem Fersenbereich (1014) verschiebbar ist.
7. Schuhwerk (1000) nach Anspruch 1, wobei die Sohlenlage mindestens einen Teil einer Sohlenanordnung bildet, wobei diese Sohlenanordnung mindestens einen Längskanal (1006) umfasst, der sich in Längsrichtung zwischen dem Zehenbereich (1012) und dem Fersenbereich (1014) erstreckt, und wobei der Haltemechanismus ein in diesem Kanal angeordnetes Element umfasst, wobei dieses Element an einem ersten von dem Zehenbereich (1012) und dem Fersenbereich (1014) verankert und relativ zu dem zweiten von dem Zehenbereich (1012) und dem Fersenbereich (1014) verschiebbar ist.
8. Schuhwerk (1000) nach Anspruch 7, wobei der Haltemechanismus ferner eine abgestufte Widerstandsanordnung umfasst, die mit dem Element und dem zweiten von dem Zehenbereich (1012) und dem Fersenbereich (1014) verbunden ist, wobei diese abgestufte Widerstandsanordnung eine Widerstandskraft bereitstellt, die der Relativverschiebung des Zehenbereichs (1012) und des Fersenbereichs (1014) zwischen einer Vielzahl von vorbestimmten Relativlagen, die einer Vielzahl von verschiedenen Längen der Sohlenanordnung entsprechen, entgegenwirkt, so dass eine Länge dieser Sohlenanordnung von Hand durch manuelle Kraftaufwendung zum Überwinden dieser Widerstandskraft eingestellt werden kann und so dass in Abwesenheit einer von Hand aufgewandten Kraft der Zehenbereich (1012) und der Fersenbereich (1014) in einer der vorbestimmten Relativlagen gehalten werden.
9. Schuhwerk (1000) nach Anspruch 8, wobei der Zwischenbereich (1010) elastisch vorgespannt ist, um den Zehenbereich (1012) und den Fersenbereich (1014) in einer vorbestimmten Relativlage zu trennen, die einer maximalen Länge der Sohlenanordnung entspricht, und wobei der Haltemechanismus ferner Folgendes umfasst:
- (a) ein flexibles Band (1018), das mit dem Element verbunden ist und sich derart von der Sohlenanordnung erstreckt, dass eine auf dieses flexible Band (1018) relativ zu dem zweiten von den Zehen- (1012) und den Fersenbereichen (1014) ausgeübte Zugspannung den Zehenbereich (1012) und den Fersenbereich (1014) zusammenzieht und dadurch die Länge der Sohlenanordnung verkürzt; und
- (b) eine Arretieranordnung zum Arretieren des flexiblen Bands (1018) in einer Vielzahl von Positionen, wodurch die Sohlenanordnung in einer gewünschten Länge gehalten wird.
10. Schuhwerk (1000) nach Anspruch 7, wobei der Zwischenbereich (1010) elastisch vorgespannt ist, um den Zehenbereich (1012) und den Fersenbereich (1014) in einer vorbestimmten Relativlage zu trennen, die einer maximalen Länge der Sohlenanordnung entspricht, und wobei der Haltemechanismus ferner Folgendes umfasst:
- (a) ein flexibles Band (1018), das mit dem Element verbunden ist und sich derart von der Sohlenanordnung erstreckt, dass eine auf dieses flexible Band (1018) relativ zu dem zweiten von den Zehen- (1012) und den Fersenbereichen (1014) ausgeübte Zugspannung den Zehenbereich (1012) und den Fersenbereich (1014) zusammenzieht und dadurch eine Länge der Sohlenanordnung verkürzt; und
- (b) eine Arretieranordnung zum Arretieren des flexiblen Bands (1018) in einer Vielzahl von Positionen, wodurch die Sohlenanordnung in einer gewünschten Länge gehalten wird.
11. Schuhwerk (1000) nach Anspruch 10, wobei die Arretieranordnung einen ersten Teil eines Klettverschlusses (1020), der mit einem Endabschnitt des flexiblen Bands (1018) verbunden ist, und einen komplementären Teil eines Klettverschlusses (1022) umfasst, der mit einer nach oben gerichteten Oberfläche der Sohlenanordnung verbunden ist, so dass das flexible Band (1018) auf diese nach oben gerichtete Oberfläche gefaltet ist, um die Sohlenanordnung in einer gewünschten Länge zu arretieren.
12. Schuhwerk (1000) nach Anspruch 7, wobei der Haltemechanismus ferner einen von Hand lösbaren und von Hand einrastbaren Fixiermechanismus zum Fixieren einer Position des Elements relativ zum zweiten von dem Zehenbereich (1012) und dem Fersenbereich (1014) umfasst.
13. Schuhwerk (100, 1000) nach Anspruch 1, wobei der Haltemechanismus einen von Hand lösbaren und von Hand einrastbaren Fixiermechanismus zum Fixieren einer Relativlage des Zehenbereichs (12a,

1012) und des Fersenbereichs (14a, 1014) umfasst.

Revendications

1. Chaussure réglable individuellement (100, 1000) comprenant :

(a) au moins une couche de semelle comprenant : une partie de pointe (12a, 1012), une partie de talon (14a, 1014) et une partie intermédiaire (50, 1010), ladite partie intermédiaire (50, 1010) étant formée de façon intégrale à la fois avec ladite partie de pointe (12a, 1012) et ladite partie de talon (14a, 1014), ladite partie intermédiaire (50, 1010) ayant une pluralité d'ouvertures passant sensiblement verticalement à travers ladite couche de manière que ladite partie intermédiaire (50, 1010) soit flexible élastiquement pour permettre un déplacement longitudinal relatif de ladite partie de pointe (12a, 1012) et ladite partie de talon (14a, 1014) pour faire varier une longueur de ladite couche sans variation significative d'une épaisseur de ladite couche ; et

(b) un mécanisme de retenue associé à la fois à ladite partie de pointe (12a, 1012) et à ladite partie de talon (14a, 1014), ledit mécanisme de retenue étant configuré pour maintenir l'une quelconque d'une pluralité de positions relatives entre ladite partie de pointe (12a, 1012) et ladite partie de talon (14a, 1014) ;

caractérisée en ce que ladite pluralité d'ouvertures est déployée pour fournir un motif en treillis tel que vu de dessus.

2. Chaussure (100, 1000) selon la revendication 1, dans laquelle ladite partie de pointe (12a, 1012), ladite partie de talon (14a, 1014) et ladite partie intermédiaire (50, 1010) sont toutes formées d'une seule pièce à partir d'une composition uniforme.
3. Chaussure (100, 1000) selon la revendication 1, dans laquelle ladite au moins une couche de semelle a une surface supérieure fournissant un support du pied, dans laquelle ladite pluralité d'ouvertures est configurée pour avoir une dimension longitudinale ouverte maximale non supérieure à environ 2,5 centimètres de manière à fournir un support du pied presque continu.
4. Chaussure (1000) selon la revendication 1, dans laquelle ladite au moins une couche de semelle est réalisée comme au moins deux couches de semelle comprenant une couche de semelle inférieure (1004) ayant une surface inférieure configurée pour un engagement avec le sol et une couche de semelle

supérieure (1002) ayant une surface supérieure pour supporter un pied.

5. Chaussure (1000) selon la revendication 4, dans laquelle ladite couche de semelle supérieure (1002) est formée à partir d'un matériau plus tendre que ladite couche de semelle inférieure (1004).
6. Chaussure (1000) selon la revendication 4, dans laquelle ladite couche de semelle inférieure (1004) et ladite couche de semelle supérieure (1002) sont profilées pour définir entre elles au moins un canal longitudinal (1006) s'étendant longitudinalement entre lesdites parties de pointe (1012) et lesdites parties de talon (1014) et dans laquelle ledit mécanisme de retenue comprend un élément déployé à l'intérieur dudit canal, ledit élément étant ancré à une première de ladite partie de pointe (1012) et ladite partie de talon (1014) et étant déplaçable par rapport à la deuxième de ladite partie de pointe (1012) et ladite partie de talon (1014).
7. Chaussure (1000) selon la revendication 1, dans laquelle ladite couche de semelle forme au moins partie d'un agencement de semelle, ledit agencement de semelle comprenant au moins un canal longitudinal (1006) s'étendant longitudinalement entre ladite partie de pointe (1012) et ladite partie de talon (1014) et dans laquelle ledit mécanisme de retenue comprend un élément déployé à l'intérieur dudit canal, ledit élément étant ancré à une première de ladite partie de pointe (1012) et ladite partie de talon (1014) et étant déplaçable par rapport à la deuxième de ladite partie de pointe (1012) et ladite partie de talon (1014).
8. Chaussure (1000) selon la revendication 7, dans laquelle ledit mécanisme de retenue comprend en outre un agencement de résistance à échelons associé audit élément et à ladite deuxième de ladite partie de pointe (1012) et ladite partie de talon (1014), ledit agencement de résistance à échelons fournissant une force de résistance s'opposant au déplacement relatif de ladite partie de pointe (1012) et ladite partie de talon (1014) entre une pluralité de positions relatives prédéfinies correspondant à une pluralité de longueurs différentes dudit agencement de semelle, de manière qu'une longueur dudit agencement de semelle soit réglable manuellement par application de force manuelle pour surmonter ladite force de résistance et de manière que, en l'absence de force appliquée manuellement, ladite partie de pointe (1012) et ladite partie de talon (1014) soient retenues dans une desdites positions relatives prédéfinies.
9. Chaussure (1000) selon la revendication 8, dans laquelle ladite partie intermédiaire (1010) est sollicité

élastiquement pour séparer ladite partie de pointe (1012) et ladite partie de talon (1014) vers une position relative prédéfinie correspondant à une longueur maximale dudit agencement de semelle et dans laquelle ledit mécanisme de retenue comprend en outre .

(a) une bande flexible (1018) associée audit élément et s'étendant à partir dudit agencement de semelle de manière qu'une tension appliquée à ladite bande flexible (1018) par rapport à ladite deuxième desdites parties de pointe (1012) et de talon (1014) tire ensemble ladite partie de pointe (1012) et ladite partie de talon (1014) en raccourcissant ainsi ladite longueur dudit agencement de semelle ; et

(b) un agencement de blocage pour bloquer ladite bande flexible (1018) dans une pluralité de positions, en retenant ainsi ledit agencement de semelle à une longueur désirée.

10. Chaussure (1000) selon la revendication 7, dans laquelle ladite partie intermédiaire (1010) est sollicitée élastiquement pour séparer ladite partie de pointe (1012) et ladite partie de talon (1014) vers une position relative prédéfinie correspondant à une longueur maximale dudit agencement de semelle et dans laquelle ledit mécanisme de retenue comprend en outre .

(a) une bande flexible (1018) associée audit élément et s'étendant à partir dudit agencement de semelle de manière qu'une tension appliquée à ladite bande flexible (1018) par rapport à ladite deuxième desdites parties de pointe (1012) et de talon (1014) tire ensemble ladite partie de pointe (1012) et ladite partie de talon (1014) en raccourcissant ainsi une longueur dudit agencement de semelle ; et

(b) un agencement de blocage pour bloquer ladite bande flexible (1018) dans une pluralité de positions, en retenant ainsi ledit agencement de semelle à une longueur désirée.

11. Chaussure (1000) selon la revendication 10, dans laquelle ledit agencement de blocage comprend une première partie d'une attache à bouclettes et crochets (1020) associée à une partie d'extrémité de ladite bande flexible (1018) et une partie complémentaire d'une attache à bouclettes et crochets (1020) associée à une surface orientée vers le haut dudit agencement de semelle de manière que ladite bande flexible (1018) soit repliée sur ladite surface orientée vers le haut pour bloquer ledit agencement de semelle à une longueur désirée.

12. Chaussure (1000) selon la revendication 7, dans laquelle ledit mécanisme de retenue comprend en

outre un mécanisme de verrouillage engageable manuellement et libérable manuellement pour verrouiller une position dudit élément par rapport à ladite deuxième de ladite partie de pointe (1012) et ladite partie de talon (1014).

13. Chaussure (100, 1000) selon la revendication 1, dans laquelle ledit mécanisme de retenue comprend un mécanisme de verrouillage engageable manuellement et libérable manuellement pour verrouiller une position relative de ladite partie de pointe (12a, 1012) et ladite partie de talon (14a, 1014).




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 5H




FIG. 5I




FIG. 5J




FIG. 6








FIG. 7






FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 14B







FIG. 14A










FIG. 17B




FIG. 17A





FIG. 18



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 524946 A, Kregel [0004]
- US 641642 A, Gunn [0005]
- US 2009684 A, Affronte [0006]
- US 2497175 A, Mantos [0007]
- US 3389481 A, England [0008]
- US 3997985 A, Shina [0009]
- US 5659980 A, Lin [0010]
- US 6138385 A, Jungkind [0011]
- US 6237255 B [0012]