



(11) **EP 1 834 447 B2**

(12) **NEW EUROPEAN PATENT SPECIFICATION**
After opposition procedure

(45) Date of publication and mention
of the opposition decision:
30.09.2015 Bulletin 2015/40

(51) Int Cl.:
F15B 13/08 ^(2006.01) **H04L 12/403** ^(2006.01)
H04L 12/40 ^(2006.01) **H05K 7/14** ^(2006.01)

(45) Mention of the grant of the patent:
27.10.2010 Bulletin 2010/43

(86) International application number:
PCT/GB2005/005074

(21) Application number: **05821680.5**

(87) International publication number:
WO 2006/072770 (13.07.2006 Gazette 2006/28)

(22) Date of filing: **23.12.2005**

(54) **COMMUNICATION SYSTEM COMPRISING A CONTROLLER SYSTEM AND A MASTER CONTROL MEANS CONNECTED VIA A MULTIPOLE CONNECTION MEANS**

KOMMUNIKATIONSSYSTEM MIT EINEM STEUERUNGSSYSTEM UND EINEM MASTER-KONTROLLMITTEL, DIE DURCH EINEN MEHRPOLIGEN ANSCHLUSS VERBUNDEN SIND

SYSTEME DE COMMUNICATION COMPRENANT UN SYSTEME DE COMMANDE ET UN MOYEN DE COMMANDE MAITRE CONNECT VIA UN MOYEN DE CONNEXION MULTIPOLAIRE

(84) Designated Contracting States:
CH CZ DE FR GB IT LI

(74) Representative: **Vossius & Partner**
Patentanwälte Rechtsanwälte mbB
Siebertstrasse 3
81675 München (DE)

(30) Priority: **07.01.2005 GB 0500223**

(43) Date of publication of application:
19.09.2007 Bulletin 2007/38

(56) References cited:
EP-A- 0 871 130 WO-A-2004/070481
WO-A-2004/092895 WO-A-2005/001699
WO-A1-01/29431 WO-A1-94/04831
WO-A1-99/54632 DE-A- 10 327 013
DE-A1- 3 807 149 DE-A1- 3 829 034
DE-A1- 19 629 868 DE-U1- 29 821 410
JP-A- H07 042 865 US-A- 3 591 850
US-A1- 2004 117 537 US-A1- 2004 213 676

(60) Divisional application:
09165276.8 / 2 110 560

(73) Proprietor: **NORGREN LIMITED**
Lichfield
Staffordshire WS13 6SB (GB)

(72) Inventors:
• **DALBY, Michael,**
Cannock,
Staffordshire WS12 4PN (GB)
• **DENSLEY, Mark,**
Littleton, Colorado 80122 (US)

• **"FIELDBUS SYSTEMS" MACHINE DESIGN,**
PENTON MEDIA, CLEVELAND, OH, US, vol. 67,
no. 11, 15 June 1995 (1995-06-15), page 172,
XP000519401 ISSN: 0024-9114

EP 1 834 447 B2

Description

[0001] It is now commonplace in, for example, production machinery for all of the pneumatic or hydraulic equipment to be controlled by respective directional control valves that are usually mounted on one and the same 'valve island'. It will be appreciated that the term 'valve island' is intended to include devices such as 'valve manifolds' and the like. The valves in the valve islands are usually controlled by solenoids that receive electrical signals to cause them to actuate the associated valve. The valve islands are connected to a controller system, via a communication system, which sends the signals to control the operation of the valves on the valve island.

[0002] There are two main types of communication system in common usage; multipole and fieldbus. In a multipole communication system, each valve in the valve island has a separate communication line effectively connecting it directly to the controller system. Thus, a 25-pin or other common connector links the controller system and the valve island and each pin provides the control signal for a different valve on the valve island. Thus, the multipole system is easy to understand and use. However, as a separate line is required for each valve to be controlled a complex multipole-based system can be expensive with regard to the wiring requirements and the number of outputs at the controller system. Further, it can be confusing when attempting to identify faults.

[0003] The other type of communication system is an address-based fieldbus system. Here, the valve islands are connected together to form a network often using a two-wire medium. The controller system sends instructions that are addressed to a particular valve island and a control system on the island interprets the instructions and thus actuates the appropriate valve. Although the fieldbus control system provides more flexibility, it can appear complex due to the programming required to administer the system.

[0004] For example, DE 19,629,868 discloses an arrangement for transmission of binary data in an interface system such as AS-i consisting of at least a transmission system, a slave module, and a master module. The transmission includes a two-wire cable used to exchange data between the master module and the slave module. The master module is connected to a higher-level control and communicates with addressed slave modules through a four-digit bit pattern.

[0005] DE 38 07 149 discloses another arrangement utilizing self-addressed test package information. The self-addressed test package information is used in conjunction with a ring-shaped network to identify whether the addresses allocated to a specific subscriber device occur more than once in the ring-shaped network. Each subscriber device (TLN) transmits self-addressed address test packet information (ati). Because the subscriber devices are only capable of transmitting self-addressed test packages, DE 38 07 149 provides the flexibility associated with addressed signals, but lacks the

simplicity of programming offered by multipole connections.

[0006] JP 07-042865 discloses a solenoid valve control system wherein command parallel signals including information on the number of a receiving station and information on a drive command are sent to a communications control portion from a programmable controller, and are subjected to parallel-to-serial conversion to obtain serial signals including the information on the number of the station and the information on the command.

[0007] WO 94/04831 describes an electro-pneumatic control device which includes a valve station designed as a component assembly, the valve station including a fluid-distributor unit fitted with a multiplicity of valves and an electronic central control unit represented by a control block.

[0008] According to the present invention, a communication system as defined by independent claim 1 is provided.

[0009] This is advantageous as the system is easy to understand and set up, yet has the advantages of an addressable communication system such as the fieldbus system described above. In particular, the valves may be distributed over the "master" valve island and several "slave" valve islands (with the associated control means), and all of them can be controlled by the controller system via a single multipole connection means. Thus, the user can program the controller system as if the system is a multipole system, while the master control means interprets the instructions and can relay them to the appropriate slave valve island control means as required.

[0010] Preferably the controller system is a programmable logic controller (PLC).

[0011] The master and slave control means control fluid flow control valves. In particular, the master and slave control means are associated with valve islands and thus they control the solenoid operated valves thereon.

[0012] Preferably further slave control systems are connected to the communication system via addressable connection means in a chain-like manner.

[0013] The addressable connection means may be based on a Local Interconnect Network (LIN) standard. The LIN standard is a single wire communications standard between a master system and at least one slave system. Each slave system needs minimal configuration to operate which, when combined with the single wire medium, make it simple and cost efficient. Preferably, the addressable connection means is based on the Controller Area Network (CAN) standard. Most preferably, the addressable connection means is based on a RS485 standard. Thus, the master and slave control means may include transceiver means to enable them to communicate using the chosen protocol of the addressable connection means.

[0014] Preferably the multipole connection means comprises a 25-pin connector or a 44-pin connector. However, it will be appreciated that the multipole connector may be some other industrially accepted connec-

tor.

[0015] The master control means comprises a microprocessor. The slave control means may also comprise a microprocessor.

[0016] Preferably, the master control means includes a diode array that derives power for the master control means, and for the actuation of any devices that it controls, from the multipole input signal. Preferably, the slave control means derives power from the addressable connection means. The master control means preferably has signal conditioning means to ensure that the signals received from the multipole connection means are in a suitable form, and within a particular voltage range, for being received by the microprocessor of the control means.

[0017] Preferably the master and slave control means have output means for actuating the required valve. The output means may comprise an output array de-multiplexer. Alternatively, the output means may be adapted to use a serial signal from the control means to control the appropriate valve. This configuration of the output means forms the subject of the second aspect of the invention.

[0018] As the invention allows for various numbers of valves to be spread over a master valve island and several slave valve islands, for example, the system of the first aspect of the invention requires a flexible means of actuating specific valves. As the control means comprises a microprocessor it is advantageous if it can output a serial signal to actuate a valve on the valve island.

[0019] There now follows by way of example only a detailed description of the present invention with reference to the accompanying drawings in which;

Figure 1 is a diagram showing the arrangement of the communication system of the invention;

Figure 2 is a diagram of the master control means;

Figure 3 is a diagram of the slave control means; and

Figure 4 is a diagram of the output means.

[0020] A communication system 1 according to the invention is represented in Figure 1. The communication system 1 comprises a master control means 2 that receives control signals from a controller system (not shown) and a slave control means 3. The master control means 2 receives signals from the controller system via multipole connection means 4. The multipole connection means 4 shown in Figure 1 uses a 25-pin D-type connector 5. The master control means 2 is in communication with each slave control means 3 via addressable connection means in the form of a sub-bus, which operates in accordance with the RS485 standard/protocol. The master control means 2 has a master sub-bus connector 6 for connecting it, via a sub-bus cable 7, to a slave sub-bus connector 8 on the slave control means 3. Thus, the master control means 2 forms the master node on a sub-

bus (with the cable 7 forming part of the bus) and the slave control means 3 forms the slave node on the bus. The slave control system 3 has a further sub-bus connector 9 for connecting it to a further slave control means (not shown).

[0021] It will be appreciated that the addressable connection means may be based on a sub-bus that operates in accordance with other standards such as CAN or LIN depending upon the application of the system.

[0022] It will also be appreciated that additional slave control means may be added in a "chain-like" arrangement. The number of slave control means that may be added is limited by the electrical power that can be supplied via the multipole connection 4 or through subsequent connections, as it is the power received through the connection 4 that allows the subsequent control means to operate. However, the master or slave control means may be adapted to receive their own power supply.

[0023] The master control means 2 and the slave control means 3 are associated with valve islands (not shown). Thus, the control means 2, 3 control solenoid-actuated pneumatic valves mounted on the valve island. The pneumatic valves may be used to actuate production machinery or the like.

[0024] Figure 2 shows a block diagram of the master control means 2, which is represented by the dashed lines. The diagram shows how the multipole signal 4 is used and how the signals are output to the sub-bus connector 6. The multipole signal 4 received by the control means 2 comprises twenty-five pins that provide the control signals 10 and a common 0 volts 11, which provides a ground for the system. The control signals 10 are received by signal conditioning means 12, which prepares the signals 10 for being received by a microprocessor 15. In particular, the signal conditioning means 12 reduces the voltage of the signals from typically 24 volts to a voltage that can be reliably interpreted by the microprocessor 15.

[0025] The signal conditioning means outputs a signal 13 that is received by the microprocessor 15. The microprocessor 15 interprets the signal and determines whether the valve to be actuated (not shown) is located on the valve island with which the control means 2 is associated or with which the slave control means 3 is associated. If it is determined that the valve to be actuated is controlled by the slave control means 3, the microprocessor 15 prepares the appropriate addressed signal for transmission on the sub-bus 7 of the addressable connection means. The output signal 16 is a serial signal to a sub-bus transceiver 17.

[0026] The sub-bus transceiver 17 modifies the signal 16 in accordance with the protocol/standard of the sub-bus (RS485) and then outputs the addressed data signal for transit over the sub-bus at 26. The output 26 is connected to the sub-bus connector 6 for transmitting along the sub-bus cable 7.

[0027] The control signals 10 split as they enter the

control means 2 and as well as being received by the signal conditioning means 12, they are received by a diode array 18. The control signals 10 are used to provide power for the components 15, 17 of the master control means 2 and for transmission to the further slave control means 3, via the sub-bus cable 7. The outputs 14 are received by a diode array 18. The diode array 18 combines the control signals 10 in the nature of an OR-gate to a single 24 volt power output 19. The 24 volts output 19 branches into a first line 20 and a second line 21. The first line 20 connects to the sub-bus connector 6 to provide power for the subsequent slave control means 3. The second line 21 is received by a voltage regulator 22 that regulates the 24 volt input 21 to a voltage suitable for operating the logic of the microprocessor 15 and the sub-bus transceiver 17. Thus, the voltage regulator 22 has an output 23 that branches into separate lines 24, 25 to supply power to the microprocessor and sub-bus transceiver respectively.

[0028] The outputs from the master control means 2 are output via the sub-bus connector 6. Thus, there are three separate signals that are passed along cable 7; the 24 volt output 20 from the diode array 18, a common 0 volt output 27 derived from the input 11 and the data signal 26. Although only one pin is shown for the data signal 26, there will be as many pins as required by the communication standard used for the addressable connection means.

[0029] A diagram of the slave control means 3 is shown in Figure 3. The slave control means 3 receives the three signals 20, 26 and 27 via the cable 7 and connector 8. The data signal 26 is received by a sub-bus transceiver 28, which interprets the signal in accordance with the RS485 standard/protocol. The sub-bus transceiver 28 outputs the signal at 29, which is received by a microprocessor 30. The microprocessor interprets the signal and if required passes instructions 31 to output means 32. Thus, the microprocessor interprets the serial data signal 29 from the sub-bus transceiver 28 and, if required, outputs a signal 33 via the output array 32. The output 33 from the output means 32 controls the appropriate solenoid valve on the valve island with which the control means 3 is associated.

[0030] The 24 volts input 20 splits when it enters the slave control means 3, one line being received by a voltage regulator 34 and the other by the output means 32. The output means uses the 24 volts to actuate the solenoids on the valve island (not shown). The voltage regulator 34, as in the master control means 2, has outputs 35 and 36 to provide power for the sub-bus transceiver 28 and the microprocessor 30, respectively.

[0031] The microprocessor 30 of the slave control means 3 has two-way communication with the sub-bus transceiver 28 and thus further slave control means can be attached to data line 26 (the sub-bus) via the second sub-bus connector 9 (shown in Figure 1). The second sub-bus connector 9 is connected to the sub-bus transceiver 28.

[0032] In use, the controller system (not shown) passes a multipole signal 4 to the master control means 2 to actuate a specific valve on either of the valve islands associated with control means 2, 3. The signal conditioner 12 receives the multipole control signals 10 and outputs the conditioned signals 13. The microprocessor 15 of the master control means 2 receives power from the voltage regulator 22 and receives the signals 13. The microprocessor 15 then, in accordance with its program, determines whether the valve to be actuated is located on the valve island with which it is associated. If so, it passes the appropriate signal to output means (not shown). If the valve is determined to be associated with the slave control means 3, the microprocessor prepares an addressed signal 16 and passes it to the sub-bus transceiver 17. The sub-bus transceiver 17 transmits it along the sub-bus cable 7 to the slave control means 3 in accordance with the protocol of the sub-bus. The signal is received by the sub-bus transceiver 28 of the slave control means 3. The transceiver 28 interprets and then outputs signal 29 to the microprocessor 30 of the slave control means 3. The microprocessor 30 processes the signal 29 in accordance with its program to determine if the signal is addressed to it and thus if a valve connected to the slave control means 3 should be actuated. If so, the appropriate signal 31 is sent to the output means 32, which causes the appropriate valve to be actuated. If the microprocessor determines that the signal 29 is not addressed to it, it is ignored.

[0033] The signal 26 is also relayed to any subsequent slave control means 3 by the sub-bus transceiver 28, via the further sub-bus connector 9, and any further slaves (not shown) processes the signal as described above.

[0034] The microprocessors 15, 30 may be pre-programmed or the user, via a RS232 interface or Bluetooth, may set the program, for example. Thus, the user may be able to program which valve or combination of valves are actuated in response to each multipole input 10.

[0035] Thus, many valve islands can be controlled from a single 25-pin (or other standard connector) multipole based system. In practice, it is common for a single valve island not to include a complete quota of valves thereon and therefore not all of the pins would be in use. Thus, with a standard multipole system a user may require several valve islands each connected by separate multipole connectors. The present invention allows the valves to be spread over a master and several slave valve islands that are controlled via the master control means. This reduces the amount of cabling required and the number of outputs at the controller system. Therefore, the system of the invention has the simplicity and ease of use of a multipole system, while having the flexibility of a Fieldbus system.

[0036] An output means 40 (as shown in Figure 4) comprises actuation signal arrangement means 41, 41' and actuation means 42, 42'. Each pair 43, 44 of actuation signal arrangement means 41, 41' and actuation means 42, 42' are associated with a fluid flow control means in

the form of a solenoid operated valve (not shown). The actuation signal arrangement means 41, 41' comprise a "D" type flip-flop having a power supply line 45, an edge-triggered clock signal input 46, a pre-actuation signal data input 47, 48, a pre-actuation signal data output 49, 50 and a 0 volts line 51. The data outputs 49, 50 branch to connect to the associated actuation means 42, 42'.

[0037] The actuation means 42, 42' comprise a "D" type latch. Inputs 52 and 53 to the latches 42, 42' are from outputs 49 and 50 respectively. The latches 42, 42' also have a power supply line 45 and 0 volts line 51. The latches 42 and 42' are connected to the valves by output lines 54 and 55. The latches 42, 42' also have inputs 56 for receiving an actuation signal. Thus, the output means 40 is of the form of a 2-bit serial latch.

[0038] The clock signal input 46, the pre-actuation signal data input 47 and the edge-triggered actuation signal input 56 are all received from the master or slave microprocessor 15, 30. The above inputs are digital and thus take the form of either a "1" or a "0".

[0039] In use, the sequence in which the above signals are applied determines which valves are actuated. For example, to actuate the second valve in the chain a pre-actuation signal of "1" is applied to the input 47 at the same time as a clock pulse at input 46. As will be appreciated, this causes the pre-actuation signal of "1" to appear at output 49 and therefore form the input of the second flip-flop 41' at input 48. During the second clock cycle, the pre-actuation signal is "0". Thus, after the second clock pulse at input 46, there is a pre-actuation signal of "0" at output 49 and the pre-actuation signal of "1" now appears at output 50.

[0040] The microprocessor 15, 30 now outputs an actuation signal to input 56. As the outputs 49 and 50 form the inputs 52 and 53, after the actuation signal, a "0" will appear at valve output 54 and a "1" will appear at valve output 55. Thus, the first valve in the chain will not be actuated, as it will receive a "0" signal, while the second valve in the chain will be actuated, as it receives the pre-actuation signal of "1".

[0041] If another valve is added, the pre-actuation signal data input of the additional flip-flop/latch pair can be connected to the output 50. Further valves can be added in a similar manner. Thus, it will be appreciated that this method can be used to actuate any valve in the chain of valves or any combination thereof, as the pre-actuation signals are fed into the chain at input 47 and then "passed through" the flip-flops by the clock signal edge. Once the clock signal has cycled the required number of times and the pre-actuation signals form the input of the appropriate latch 42, 42', the actuation signal is applied to pass the signals to the appropriate valve.

[0042] This method may also be used in a configuration mode to allow the microprocessor to determine how many valves are connected to the valve island with which it is associated. At the end of the chain of flip-flop/latch pairs 43, 44 the output 50 returns to the microprocessor. Using the example as shown in Figure 4, during a con-

figuration mode a pre-actuation signal of "1" is applied at input 47 during the first clock cycle at input 46. After the first clock cycle the pre-actuation signal is kept as "0". The microprocessor 15, 30 then counts the number of clock cycles applied at inputs 46 until the pre-actuation signal of "1" returns to it. The number of valves can thus be determined by counting the number of clock pulses applied during this configuration mode.

[0043] Further, during the configuration mode the microprocessor 30 of each slave control means 3 may pass the information of the number of valves associated with it back to the master control means 2. Thus, the master control means can then determine which valve is attached to which slave control means 3 and therefore address the appropriate one in response to the multipole signals 10.

Claims

1. A communication system comprising a controller system, a master control means (2) and at least one slave control means (3), the master control means (2) and at least one slave control means (3) being arranged for controlling fluid flow control valves, the controller system and the master control means (2) being connected via a multipole connection means (4), the master control means (2) being adapted to receive a multipole signal via the multipole connection means (4) and outputting an addressed signal to the at least one slave control means (3) via addressable connection means in the form of a sub-bus (7, 17), wherein the master control means (2) comprises a microprocessor (15) arranged for interpreting the multipole signal, determining whether the valve to be actuated is located on a valve island with which the control means (2) is associated or with which the slave control means (3) is associated, and if it is determined that the valve to be actuated is controlled by the slave control means (3), preparing an appropriate addressed signal for transmission on the sub-bus (7) of the addressable connection means.
2. A communication system according to claim 1, in which the controller system is a programmable logic controller (PLC).
3. A communication system according to claim 1 or claim 2, in which the master and slave control means (2, 3) control fluid flow control valves.
4. A communication system according to any preceding claim, in which the master and slave control means (2, 3) are associated with valve islands and control solenoid operated valves located thereon.
5. A communication system according to any preced-

ing claim, in which further slave control means (3) are connected to the communication system via addressable connection means (7, 17) in a chain-like manner.

6. A communication system according to any preceding claim, in which the addressable connection means (7, 17) is based on a Local Interconnect Network (LIN) standard.
7. A communication system according to any of claims 1 to 5, in which the addressable connection means (7, 17) is based on the Controller Area Network (CAN) standard.
8. A communication system according to any of claims 1 to 5, in which the addressable connection means (7, 17) is based on a RS485 standard.
9. A communication system according to any preceding claim, in which the master and slave control means (2, 3) include transceiver means (28) to enable them to communicate using the protocol of the addressable connection means (7, 17).
10. A communication system according to any preceding claim, in which the multipole connection means (4) comprises a 25-pin connector.
11. A communication system according to any of claims 1 to 9, in which the multipole connection means (4) comprises a 44-pin connector.
12. A communication system according to any preceding claim, in which the master control means (2) comprises a microprocessor (15).
13. A communication system according to any preceding claim, in which the slave control means (3) comprises a microprocessor (30).
14. A communication system according to any preceding claim, in which the master control means (2) includes a diode array (18) that derives power for the master control means (2), and for the actuation of any devices that it controls, from the multipole input signal (10).
15. A communication system according to any preceding claim, in which the slave control means (3) derives power from the addressable connection means (7, 17).
16. A communication system according to any preceding claim, in which the master control means (2) has signal conditioning means (12) to ensure that the signals received from the multipole connection means (4) are in a suitable form for receipt by the

microprocessor (15) of the control means.

17. A communication system according to any preceding claim, in which the master and slave control means (2, 3) have output means (32) for actuating the required valve.
18. A communication system according to claim 17, in which the output means (32) comprises an output array de-multiplexer.
19. A communication system according to claim 17, in which the output means (32) is adapted to use a serial signal from the control means to control the appropriate valve.

Patentansprüche

1. Kommunikationssystem, umfassend ein Steuerungssystem, ein Master-Steuermittel (2) und mindestens ein Slave-Steuermittel (3), wobei das Master-Steuermittel (2) und mindestens ein Slave-Steuermittel (3) zum Steuern von Flüssigkeitsregelventilen angeordnet sind, wobei das Steuerungssystem und das Master-Steuermittel (2) über ein Multipolanschlussmittel (4) miteinander verbunden sind, wobei das Master-Steuermittel (2) angepasst ist, ein Multipolsignal über das Multipolanschlussmittel (4) zu empfangen und ein adressiertes Signal an das mindestens eine Slave-Steuermittel (3) über adressierbare Anschlussmittel in Form eines Sub-Busses (7, 17) auszugeben, wobei das Master-Steuermittel (2) einen Mikroprozessor (15) umfasst, der angeordnet ist, um das Multipolsignal zu interpretieren, zu bestimmen, ob das zu betätigende Ventil auf einer Ventilinsel angeordnet ist, mit der das Steuermittel (2) verknüpft ist oder mit der das Slave-Steuermittel (3) verknüpft ist, und, wenn bestimmt wird, dass das zu betätigende Ventil vom Slave-Steuermittel (3) gesteuert wird, ein geeignetes adressiertes Signal für die Übertragung auf dem Sub-Bus (7) des adressierbaren Verbindungsmittels zu erzeugen.
2. Kommunikationssystem nach Anspruch 1, bei dem das Steuerungssystem eine speicherprogrammierbare Steuerung (SPS) ist.
3. Kommunikationssystem nach Anspruch 1 oder Anspruch 2, bei dem die Master- und Slave-Steuermittel (2, 3) Flüssigkeitsregelventile steuern.
4. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem die Master- und Slave-Steuermittel (2, 3) mit Ventilinseln verknüpft sind und auf diesen angeordnete Solenoid-betriebene Ventile steuern.

5. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem ein weiteres Slave-Steuermittel (3) in kettenartiger Weise über adressierbare Anschlussmittel (7, 17) an das Kommunikationssystem angeschlossen ist. 5
6. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem die adressierbaren Anschlussmittel (7, 17) auf einem LIN-Standard (LIN = Local Interconnect Network) basieren. 10
7. Kommunikationssystem nach einem der Ansprüche 1 bis 5, bei dem die adressierbaren Anschlussmittel (7, 17) auf dem CAN-Standard (CAN = Controller Area Network) basieren. 15
8. Kommunikationssystem nach einem der Ansprüche 1 bis 5, bei dem die adressierbaren Anschlussmittel (7, 17) auf einem RS485 Standard basieren. 20
9. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem die Master- und Slave-Steuermittel (2, 3) ein Sendeempfängermittel (28) enthalten, um ihnen die Kommunikation unter Einsatz des Protokolls der adressierbaren Anschlußmittel (7, 17) zu ermöglichen. 25
10. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Multipolanschlussmittel (4) einen 25-poligen Stecker umfasst. 30
11. Kommunikationssystem nach einem der Ansprüche 1 bis 9, bei dem das Multipolanschlussmittel (4) einen 44-poligen Stecker umfasst. 35
12. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Master-Steuermittel (2) einen Mikroprozessor (15) umfasst. 40
13. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Slave-Steuermittel (3) einen Mikroprozessor (30) umfasst. 45
14. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Master-Steuermittel (2) eine Dipolanordnung (18) enthält, die Energie für das Master-Steuermittel (2) und für die Betätigung der von ihm gesteuerten Vorrichtungen von dem Multipol-Eingangssignal (10) ableitet. 50
15. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Slave-Steuermittel (3) Energie von den adressierbaren Anschlussmitteln (7, 17) ableitet. 55
16. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem das Master-Steuermittel (2) ein Signalkonditioniermittel (12) aufweist, um

sicherzustellen, dass die von dem Multipolanschlussmittel (4) empfangenen Signale eine für den Empfang der Steuermittel durch den Mikroprozessor (15) geeignete Form aufweisen.

17. Kommunikationssystem nach einem der vorhergehenden Ansprüche, bei dem die Master- und Slave-Steuermittel (2, 3) ein Ausgabemittel (32) zur Betätigung des benötigten Ventils aufweisen.
18. Kommunikationssystem nach Anspruch 17, bei dem das Ausgabemittel (32) einen Ausgabe-Array-Demultiplexer umfasst.
19. Kommunikationssystem nach Anspruch 17, bei dem das Ausgabemittel (32) angepasst ist, ein von den Steuermitteln kommendes serielles Signal zum Steuern des entsprechenden Ventils zu verwenden.

Revendications



1. Système de communication comprenant un système contrôleur, un moyen de contrôle maître (2) et au moins un moyen de contrôle esclave (3), le moyen de contrôle maître (2) et au moins un moyen de contrôle esclave (3) étant agencés pour commander des vannes de contrôle d'écoulement de fluide, le système contrôleur et le moyen de contrôle maître (2) étant connectés par l'intermédiaire d'un moyen de connexion multipôle (4), le moyen de contrôle maître (2) étant adapté à recevoir un signal multipôle par l'intermédiaire du moyen de connexion multipôle (4) et fournir un signal adressé audit au moins un moyen de contrôle esclave (3) par l'intermédiaire d'un moyen de connexion adressable sous la forme d'un sous-bus (7, 17), dans lequel le moyen de contrôle maître (2) comprend un microprocesseur (15) agencé pour interpréter le signal multipôle, déterminer si la vanne à actionner est située sur un îlot de vannes auquel le moyen de contrôle (2) est associé ou auquel le moyen de contrôle esclave (3) est associé, et si on détermine que la vanne à actionner est commandée par le moyen de contrôle esclave (3), préparer un signal adressé approprié pour transmission sur le sous-bus (7) du moyen de connexion adressable.
2. Système de communication selon la revendication 1, dans lequel le système contrôleur est un contrôleur logique programmable (PLC).
3. Système de communication selon la revendication 1 ou 2, dans lequel les moyens de contrôle maître et esclave (2, 3) commandent des vannes de contrôle d'écoulement de fluide.
4. Système de communication selon l'une quelconque

des revendications précédentes, dans lequel les moyens de contrôle maître et esclave (2, 3) sont associés à des îlots de vannes et commandent des vannes à commande électromécanique situées sur ces derniers.

5. Système de communication selon l'une quelconque des revendications précédentes, dans lequel d'autres moyens de contrôle esclaves (3) sont connectés en chaîne au système de communication par l'intermédiaire d'un moyen de connexion adressable (7, 17). 5
6. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de connexion adressable (7, 17) est basé sur une norme LIN (Local Interconnect Network). 10
7. Système de communication selon l'une quelconque des revendications 1 à 5, dans lequel le moyen de connexion adressable (7, 17) est basé sur la norme CAN (Controller Area Network). 15
8. Système de communication selon l'une quelconque des revendications 1 à 5, dans lequel le moyen de connexion adressable (7, 17) est basé sur une norme RS485. 20
9. Système de communication selon l'une quelconque des revendications précédentes, dans lequel les moyens de contrôle maître et esclave (2, 3) comprennent un moyen émetteur-récepteur (28) pour leur permettre de communiquer en utilisant le protocole du moyen de connexion adressable (7, 17). 25
10. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de connexion multipôle (4) comprend un connecteur à 25 broches. 30
11. Système de communication selon l'une quelconque des revendications 1 à 9, dans lequel le moyen de connexion multipôle (4) comprend un connecteur à 44 broches. 35
12. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de contrôle maître (2) comprend un microprocesseur (15). 40
13. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de contrôle esclave (3) comprend un microprocesseur (30). 45
14. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de contrôle maître (2) comprend un réseau 50

de diodes (18) qui dérive de l'énergie pour le moyen de contrôle maître (2), et pour l'actionnement de tous les dispositifs qu'il contrôle, à partir du signal d'entrée multipôle (10).

15. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de contrôle esclave (3) dérive de l'énergie du moyen de connexion adressable (7, 17). 55
16. Système de communication selon l'une quelconque des revendications précédentes, dans lequel le moyen de contrôle maître (2) comporte un moyen de conditionnement de signal (12) pour garantir que les signaux reçus du moyen de connexion multipôle (4) ont une forme appropriée pour être reçus par le microprocesseur (15) du moyen de contrôle. 60
17. Système de communication selon l'une quelconque des revendications précédentes, dans lequel les moyens de contrôle maître et esclave (2, 3) comportent un moyen de sortie (32) pour actionner la vanne requise. 65
18. Système de communication selon la revendication 17, dans lequel le moyen de sortie (32) comprend un démultiplexeur de réseau de sortie. 70
19. Système de communication selon la revendication 17, dans lequel le moyen de sortie (32) est adapté à utiliser un signal série provenant du moyen de contrôle pour commander la vanne appropriée. 75



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- DE 19629868 [0004]
- DE 3807149 [0005]
- JP 7042865 A [0006]
- WO 9404831 A [0007]