

EP 1 858 115 A1

(51) Int Cl.:
H01Q 5/00 (2006.01) **H01Q 9/46** (2006.01)
H01Q 1/24 (2006.01)

(22) Date of filing: 19.05.2006

(74) Representative: **Estreen, Lars J.F. et al**
Kransell & Wennborg KB
P.O. Box 27834
115 93 Stockholm (SE)

(54) **Antenna device and portable radio communication device comprising such an antenna device**

mon conductors can be selectively connected in and out with respect to radio frequency signals in order to adjust the total electrical length of the antenna device, thereby making it operable in four different frequency bands.




Fig. 2

Description

FIELD OF INVENTION

[0001] The present invention relates generally to antenna devices and more particularly to a controllable internal multi-band antenna device for use in portable radio communication devices, such as in mobile phones. The invention also relates to a portable radio communication device comprising such an antenna device.

BACKGROUND

[0002] Internal antennas have been used for some time in portable radio communication devices. There are a number of advantages connected with using internal antennas, of which can be mentioned that they are small and light, making them suitable for applications wherein size and weight are of importance, such as in mobile phones. A type of internal antenna that is often used in portable radio communication devices is the monopole antenna.

[0003] However, the monopole antenna is inherently resonant in one frequency band. If multi-band operation is required, wherein the antenna is adapted to operate in two or more spaced apart frequency bands, two monopole antennas with different resonance frequencies can be provided. In a typical dual band phone, the lower frequency band is centered on 900 MHz, the so-called GSM 900 band, whereas the upper frequency band is centered around 1800 or 1900 MHz, the DCS and PCS band, respectively. If the upper frequency band of the antenna device is made wide enough, covering both the 1800 and 1900 MHz bands, a phone operating in three different standard bands is obtained. However, with today's high demands on functionality, antenna devices operating four or even more different frequency bands are in demand. With the limitations regarding cost and size of antenna devices this quad band operation is difficult to achieve.

[0004] A problem in prior art antenna devices is thus to provide a multi-band antenna with a small size and volume and broad frequency bands which retains good performance.

SUMMARY OF THE INVENTION

[0005] An object of the present invention is to provide an antenna device of the kind initially mentioned wherein the frequency characteristics provides for four comparatively wide frequency bands while the overall size of the antenna device is small.

[0006] Another object is to provide an antenna device having better multi-band performance than prior art devices.

[0007] The invention is based on the realization that several frequency bands can be provided in an antenna device by arranging the antenna with two branches of

different lengths and a switch arrangement adjusting the electrical lengths of the branches to provide four different resonance frequencies.

[0008] According to a first aspect of the present invention there is provided an antenna device as defined in claim 1.

[0009] According to a second aspect of the present invention there is provided portable radio communication device as defined in claim 10.

[0010] Further preferred embodiments are defined in the dependent claims.

[0011] The invention provides an antenna device and a portable radio communication device wherein the problems in prior art devices are avoided or at least mitigated by means of providing a switch. Thus, there is provided a small sized low cost multi-band antenna device operable in at least four different frequency bands.

[0012] The switch is preferably a PIN diode, having good properties when operating as an electrically controlled RF switch.

BRIEF DESCRIPTION OF DRAWINGS

[0013] The invention is now described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is an overall view of a portable radio communication device comprising an antenna device according to the invention;

Fig. 2 shows a schematic diagram of a first embodiment of an antenna device according to the invention;

Fig. 3 is a frequency diagram of the operating modes of the antenna shown in Fig. 2;

Fig. 4 shows a schematic diagram of a second embodiment of an antenna device according to the invention;

Fig. 5 shows a schematic diagram of a third embodiment of an antenna device according to the invention including a parasitic element;

Fig. 6 shows a schematic diagram of a fourth embodiment of an antenna device according to the invention having an alternative switch position; and

Fig. 7 shows a schematic diagram of a fourth embodiment of an antenna device according to the invention comprising a PIFA.

DETAILED DESCRIPTION OF THE INVENTION

[0014] In the following, a detailed description of preferred embodiments of an antenna device according to

the invention will be given. In the description, for purposes of explanation and not limitation, specific details are set forth, such as particular hardware, applications, techniques etc. in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be utilized in other embodiments that depart from these specific details. In other instances, detailed descriptions of well-known methods, apparatuses, and circuits are omitted so as not to obscure the description of the present invention with unnecessary details.

[0015] Fig. 1 shows the outlines of a portable radio communication device 1, such as a mobile phone. An antenna device 10 is arranged at the top of the communication device, adjacent to a printed circuit board (PCB) 2, and being connected to RF feeding and grounding devices (not shown).

[0016] In fig. 2, there is shown the antenna device 10 comprising a first elongated monopole radiating element 12 made of an electrically conductive material, such as a flex film, as is conventional. A second elongated monopole radiating element 14 is provided in parallel with the first radiating element.

[0017] The first and second radiating elements 12, 14 are connected to a first common elongated conductor 18 at a junction point 16. The first common conductor is in turn connected to a source of radio frequency signals RF, such as RF circuitry in the portable radio communication device 1 shown in Fig. 1.

[0018] The first common conductor 18 and the first radiating element 12, which are connected in series, are together arranged to resonate in a first lower frequency band LB1, such as the GSM 850 band. Correspondingly, the first common conductor 18 and the second radiating element 14 are together arranged to resonate in a first higher frequency band HB1, such as the GSM 1800 band.

[0019] Thus, the combination of the two branches 12, 14 and the common conductor 18 operates as a dual-band antenna device.

[0020] A second common conductor 20 is connected in parallel with the first common conductor, the second common conductor being electrically shorter than the first common conductor. A switch element 22 is provided in series with this second common conductor, preferably close to the common junction point 16. This switch element is preferably a PIN diode, i.e., a silicon junction diode having a lightly doped intrinsic layer serving as a dielectric barrier between p and n layers. Ideally, a PIN diode switch is characterized as an open circuit with infinite isolation in open mode and as an short circuit without resistive losses in closed mode, making it suitable as an electronic switch. In reality the PIN diode switch is not ideal. In open mode the PIN diode switch has capacitive characteristic (0.1-0.4pF), which results in finite isolation (15-25dB @ 1GHz) and in closed mode the switch has resistive characteristic (0.5-3 ohm) which results in resistive losses (0.05-0.2dB).

[0021] A high pass filter 24 is also provided in series

with this second common conductor, the function of which will be explained below. Finally the second common conductor 20 is connected to ground via a low pass filter 26 arranged to block all radio frequency signals. The low pass filter 26 can be arranged either in the antenna device itself or in electronic circuitry arranged on the PCB 2.

[0022] Finally, a DC control input, designated V_{Switch} in the figures, for controlling the operation of the PIN diode 22 is connected to the RF input via a filter block 28 to not affect the RF characteristics of the antenna device. This means that the filter characteristics of the filter block 16 is designed so as to block all radio frequency signals. In the preferred embodiment, the filter block 28 comprises a low pass filter.

[0023] It is preferred that the interface to the antenna device is provided as indicated by the dash-dotted lines in the figures. This means that the filter block 28 is arranged in electronic circuitry arranged on the PCB 2 and that the signal provided to the antenna device is an RF signal being DC biased or not DC biased, depending on mode of operation, as will be explained below.

[0024] The antenna is preferably designed to 50 Ohms.

[0025] The switching of the antenna device functions as follows. The RF source and other electronic circuits of the communication device operate at a given voltage level, such as 1.5 Volts. The criterion is that the voltage level is high enough to create the necessary voltage drop across the PIN diode, i.e. about 1 Volt. This means that the control voltage V_{Switch} is switched between the two voltages "high" and "low", such as 1.5 and 0 Volts, respectively. When V_{Switch} is high, there is a DC current flowing from the DC control input, through the low pass filter 28, via the first common conductor 18, through the PIN diode 22 and part of the second common conductor 20, and finally through the low pass filter 26 and to ground. This DC current creates a voltage drop across the PIN diode 22 and a corresponding current there through of about 5-15 mA. This voltage drop makes the diode conductive, effectively making the second common conductor 20 conductive with respect to RF signals. With the control voltage V_{Switch} "low", there is an insufficient voltage drop across the PIN diode 22 to make it conductive, i.e., it is "open", effectively blocking any RF signals in the second common conductor 20.

[0026] With the switch closed, the electrical length of the the second common conductor 20, which is shorter than the first common conductor 18, will determine the total electrical length of the antenna device. Thus, the second common conductor 20 and the first radiating element 12, which are connected in series, are together arranged to resonate in a second lower frequency band LB2, such as the GSM 900 band. Correspondingly, the first common conductor 16 and the second radiating element 14 are together arranged to resonate in a second higher frequency band HB2, such as the GSM 1900 band.

[0027] In summary, the size and configuration of the

two elongated radiating elements 12, 14 and the two common conductors 18, 20 are chosen so as to obtain the desired resonance frequencies, such as the 850 and 1800 MHz bands with the switch open and the 900 and 1900 MHz bands with the switch closed.

[0028] This change of geometry of the effective radiating elements adjusts the resonance frequencies of antenna device. This is seen in Fig. 3, wherein the dashed curves correspond to the operating mode with the switch open, i.e., with V_{Switch} high, and the solid curves correspond to the operating mode with the switch closed, i.e., with V_{Switch} high. The means that an antenna device which can operate in four different frequency bands is obtained, such as the above mentioned 850/900/1800/1900 MHz bands.

[0029] The adjustment of the resonance frequencies shown in Fig. 3 can be used to an advantage in so-called fold phones. In this kind of communication devices, the resonance frequency of an internal antenna element tends to move downwards in frequency when the position of the phone is changed from folded to unfolded mode. With the inventive antenna device, when the phone is unfolded, the movement of the resonance frequencies can be counteracted by closing the switch 22. Thus, with the phone folded, the control voltage V_{switch2} is low and with the phone unfolded, the control voltage is high. The antenna device then operates as a dual band antenna with essentially constant resonance frequency irrespective of the operating mode of the communication device (folded/unfolded).

[0030] The adjustment of the resonance frequencies shown in Fig. 3 can also be used to an advantage in dual band bar phones. In the frequency bands used for mobile communication, the transmit (TX) and receive (RX) frequencies are separated by approximately 45-90 MHz. By using frequency adjustment, near optimum efficiency can be obtained by adjusting the frequencies to the TX and RX frequencies instead of the broader frequency band incorporating the TX and RX frequencies.

[0031] In Fig. 4 a second embodiment of an antenna device according to the invention is shown. This is in most aspects identical to the one described with reference to Fig. 2. However, there is a second switch element 30 in the form of an additional PIN diode provided between the high pass filter 24 and the first common conductor 18 at an end of the second common conductor opposite to where the first switch element 22 is provided. This improves the decoupling of the second common conductor 20 when operating with the switches open.

[0032] In Fig. 5 a third embodiment of an antenna device according to the invention is shown. This is in most aspects identical to the one described with reference to Fig. 2. However, there is a conductive elongated parasitic element 32 provided close to the first common conductor 18. This parasitic element, which is grounded in one end, provides a fifth frequency band of the antenna device, such as the Bluetooth frequency band operating around 2.4 GHz or around 3 GHz (WCDMA).

[0033] In Fig. 6 a fourth embodiment of an antenna device according to the invention is shown. This uses the same general concept as the one described with reference to Fig. 2. However, in this embodiment, the first common conductor 18 is shorter than the second common conductor 20.

[0034] In Fig. 7 a fifth embodiment of an antenna device according to the invention is shown. It uses the above described general concept of adjusting the length of the radiating element by switching in and out two parallel conductors of different lengths but in this case applied to a so-called planar inverted F antenna (PIFA). The PIFA comprises a generally planar conductive plate divided by a slot into a first branch 112 and a second branch 114. The first branch 112, functionally corresponding to the first radiating element 12 described above is longer than the second branch which functionally correspond to the above described second radiating element 114. There is also a grounding connection 116 provided between the conductive plate and ground.

[0035] The switching concept applied on monopole antennas is the same for this PIFA, thereby creating an antenna device operable in four different frequency bands.

[0036] Preferred embodiments of an antenna device according to the invention have been described. However, it will be appreciated that these can be varied within the scope of the appended claims. Thus, a PIN diode has been described as the switch element. It will be appreciated that other kinds of switch elements can be used as well.

[0037] Although a PIFA has been shown in Fig. 7, it will be appreciated that the inventive idea is applicable also on so-called IFA antennas.

Claims

1. An antenna device for a portable radio communication device operable in at least four different frequency bands, the antenna device comprising:

- a first electrically conductive radiating element (12; 112);
- a second electrically conductive radiating element (14; 114);
- a junction (16) connecting the first and second radiating elements;
- a first conductor (18) arranged between the junction point and a source of RF signals;

characterized by

- a second conductor (20) arranged between the junction point and the source of RF signals, wherein the second conductor has an electric length different from the electric length of the first conductor (18);

- a controllable switch element (22) provided in series with the second conductor, said switch being controllable by a current flowing through the switch; and
 - a first filter block (24) provided in series with the second conductor, said first filter block being arranged to block signals with a frequency lower than the at least four different frequency bands.
2. The antenna device according to claim 1, comprising a second filter block (26) arranged between the second conductor and ground, wherein the second filter is arranged to block signals in the at least four different frequency bands; and
 3. The antenna device according to claim 1, comprising a third filter block (28) arranged between the first conductor and a control voltage input (V_{switch}).
 4. The antenna device according to any of claims 1-3, wherein the controllable switch element (30; 130) comprises a PIN diode.
 5. The antenna device according to any of claims 1-4, wherein the first and second radiating elements (12, 14) are elongated monopole radiating elements.
 6. The antenna device according to any of claims 1-4, wherein the first and second radiating elements (112, 114) are parts of an inverted F antenna.
 7. The antenna device according to any of claims 1-6, wherein the second conductor (14; 114) is electrically shorter than the first conductor (12; 112).
 8. The antenna device according to any of claims 1-7, comprising a further controllable switch element (30) provided between the first filter block (24) and the first conductor (18) at an end of the second conductor opposite to where the controllable switch element (22) is provided.
 9. The antenna device according to any of claims 1-8, comprising a conductive elongated parasitic element (32) provided close to the first conductor (18).
 10. A portable radio communication device comprising an antenna device operable in at least four different frequency bands, the antenna device comprising:
 - a first electrically conductive radiating element (12; 112);
 - a second electrically conductive radiating element (14; 114);
 - a junction (16) connecting the first and second radiating elements;
 - a first conductor (18) arranged between the junction point and a source of RF signals;

characterized by

- a second conductor (20) arranged between the junction point and the source of RF signals, wherein the second conductor has an electric length different from the electric length of the first conductor (18);
- a controllable switch element (22) provided in series with the second conductor, said switch being controllable by a current flowing through the switch;
- a first filter block (24) provided in series with the second conductor, said first filter block being arranged to block signals with a frequency lower than the at least four different frequency bands;
- a second filter block (26) arranged between the second conductor and ground, wherein the first filter is arranged to block signals in the at least four different frequency bands; and
- a third filter block (28) arranged between the first conductor and a control voltage input (V_{Switch}).




Fig. 1




Fig. 2





Fig. 3






Fig. 5




Fig. 6




Fig. 7



DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
Y	WO 01/28038 A (SIEMENS AG [DE]; BOLLENBECK JAN [DE]; PFANN PETER [DE]) 19 April 2001 (2001-04-19) * page 2, lines 28,29; figure 1 *	1-10	INV. H01Q5/00 H01Q9/46 H01Q1/24
Y	WO 99/22420 A (ERICSSON TELEFON AB L M [SE]) 6 May 1999 (1999-05-06) * page 3, line 23 - page 4, line 10; figure 1 *	1-10	
Y	EP 1 367 671 A2 (NGK SPARK PLUG CO [JP]) 3 December 2003 (2003-12-03) * paragraphs [0021] - [0025]; figure 1 *	1-10	
X	WO 01/29927 A (SIEMENS AG [DE]; SCHREIBER MICHAEL [DE]; HUBER STEFAN [DE]) 26 April 2001 (2001-04-26) * figure 2b *	1	
A	WO 02/078123 A (ERICSSON TELEFON AB L M [SE]; BOLIN THOMAS [SE]; YING ZHINONG [CN]; AN) 3 October 2002 (2002-10-03) * claim 1 *	1-10	TECHNICAL FIELDS SEARCHED (IPC)
A	WO 2005/048403 A (AMC CENTURION AB [SE]; THORNELL-PERS ANDERS [SE]) 26 May 2005 (2005-05-26) * figure 1 *	1-10	H01Q
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 3 November 2006	Examiner Van Dooren, Gerardus
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 06 44 5028

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-11-2006

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0128038	A	19-04-2001	NONE	
WO 9922420	A	06-05-1999	AU 9657998 A	17-05-1999
			CN 1290412 A	04-04-2001
			EP 1025613 A1	09-08-2000
			JP 2001522152 T	13-11-2001
			TW 392376 B	01-06-2000
EP 1367671	A2	03-12-2003	CN 2671143 Y	12-01-2005
			JP 2003347827 A	05-12-2003
			US 2004001031 A1	01-01-2004
WO 0129927	A	26-04-2001	NONE	
WO 02078123	A	03-10-2002	EP 1378021 A1	07-01-2004
WO 2005048403	A	26-05-2005	EP 1683232 A1	26-07-2006