



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A2)

Bibliography INID code(s) 54

(51) Int Cl.:

H04N 1/60 (2006.01)

(48) Corrigendum issued on:

23.04.2008 Bulletin 2008/17

(43) Date of publication:

30.01.2008 Bulletin 2008/05

(21) Application number: **07013106.5**

(22) Date of filing: **04.07.2007**

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated Extension States:

AL BA HR MK RS

(30) Priority: **25.07.2006 JP 2006202091**

(71) Applicant: **Brother Kogyo Kabushiki Kaisha**

Nagoya-shi, Aichi-ken 467-8561 (JP)

(72) Inventors:

- **Yamanaka, Tsuyoshi**
c/o Brother Kogyo Kabushiki Kaisha
Nagoya-shi
Aichi-ken 467-8561 (JP)
- **Miyata, Yuji**
c/o Brother Kogyo Kabushiki Kaisha
Nagoya-shi
Aichi-ken 467-8561 (JP)

(74) Representative: **Kuhnen & Wacker**

Patent- und Rechtsanwaltsbüro
Prinz-Ludwig-Strasse 40A
85354 Freising (DE)

(54) **Image data output device, printing device, printing system, image data output program and its installation program**

(57) An image data output device includes, a setting part that can set adjustment values, an adjusting part that can adjust the image quality of image data based on the adjustment values, a choosing part that can choose the image data, a display part that can display an image to preview adjustment effects for the image data chosen by the choosing part, the image quality has been adjusted by said adjusting part, and a data outputting part that can output the image data to be a print target to the printing device, wherein the image quality of the image data has been adjusted by said adjusting part.

FIG.8

