(11) **EP 1 944 638 A8**

(12) CORRECTED EUROPEAN PATENT APPLICATION

(15) Correction information:

Corrected version no 1 (W1 A2)
Remarks

(51) Int Cl.: **G02B** 6/44 (2006.01)

(48) Corrigendum issued on:

15.10.2008 Bulletin 2008/42

(43) Date of publication:

16.07.2008 Bulletin 2008/29

(21) Application number: 08000259.5

(22) Date of filing: 18.09.2003

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR Designated Extension States:

AL LT LV MK

(30) Priority: 18.09.2002 US 246007 30.12.2002 US 331900 31.03.2003 US 404196 08.04.2003 US 408953

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 03759283.9 / 1 552 330

01.07.2003 US 611513

(71) Applicant: Neptco JV LLC Pawtucket, RI 02861 (US)

(72) Inventors:

Hager, Thomas, P.
 Westerville, OH 43082 (US)

 Lehman, Richard, N. Newark, OH 43055 (US)

Priest, James, R.
 Nashport, OH 43830 (US)

(74) Representative: Bevan, Emma et al Mintz, Levin, Cohn, Ferris, Glovsky & Popeo Intellectual Property LLP The Rectory 9 Ironmonger Lane London EC2V 8EY (GB)

Remarks:

This application was filed on 08.01.2008 as a divisional application to the application mentioned under INID code 62.

(54) Low cost, high performance, flexible reinforcement for communications cable

(57) A flexible reinforcement member 30 for a communications cable comprising:

a plurality of high modulus fibers 32, said plurality of high modulus fibers comprises a plurality of glass fiber strands, wherein said plurality of glass fiber strands 32 comprises a plurality of sized glass fiber strands selected from the group consisting of a plurality of sized or unsized E-type glass fiber strands and a plurality of sized or un-

sized ECR-type glass fibers; and

a primary saturant 36 coupled to said plurality of high modulus fibers 32, said primary saturant 36 having a melting point below approximately 300 degrees Celsius and a melt viscosity of less than approximately 1000 centipoise.

EP 1 944 638 A8

