

(19)



(11)

EP 1 950 365 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

30.07.2008 Bulletin 2008/31

(51) Int Cl.:

E05B 29/06 (2006.01)

(21) Application number: **07101043.3**

(22) Date of filing: **23.01.2007**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**

Designated Extension States:

AL BA HR MK RS

(71) Applicant: **Porter Lock Co. Ltd.**

Zhonghe City, Taipei County (TW)

(72) Inventor: **Fan, Tso-Pin**

Zhonghe City, Taipei County, (TW)

(74) Representative: **Kewitz, Ansgar**

**2K Patentanwälte Kewitz & Kollegen
Partnerschaft**

Corneliusstrasse 18

60325 Frankfurt am Main (DE)

(54) **Lock core structure**

(57) The present invention provides a lock core structure including a housing (7), a lock core (1), at least two latch elements (2) and plural lock piece sets. Each lock piece set includes a division plate (5) and a first lock piece (4) and a second lock piece (3), wherein the first lock piece (4) and the second lock piece (3) are embedded in two sliding tracks (51) on the division plate (5), and an

elastic element (6) is mounted between the first lock piece (4) and the second lock piece (3) for interlocking the first and the second lock pieces (4, 3). Through the interlocked structure between the first lock piece (4) and the second lock piece (3), it will be harder for the theft to break the lock core (1).

EP 1 950 365 A1

Description

FIELD OF THE INVENTION

[0001] The present invention is related to a lock core, and more particularly to a lock core which have plural lock piece sets embedded therein for cooperating with plural latches so as to form a latching mechanism.

BACKGROUND OF THE INVENTION

[0002] Generally, according to the lock core, the common lock can be classified as pin tumbler lock and plate lock. The pin tumbler lock utilizes various sizes of ball-typed or pillar-typed bolts in the lock core, and each indentation on the key will correspond and match to each different bolts, so that the lock can be opened. In the plate lock, each lock piece set has an indentation, and the indentations are interlocked and simultaneously rejected against one latch element so as to lock the lock core. The examples of conventional pin tumbler lock are R.O.C Patent Application No. 094219454 "Anti-theft lock core structure" and R.O.C Patent Application NO. 094216537 "Anti-theft lock core assembly structure"; and the examples of plate lock are R.O.C Patent Application No. 095206477 "Lock core assembly for door lock" and R.O.C Patent Application No. 094145435 "Anti-theft lock core". However, in the conventional pin tumbler lock or plate lock, there only has one barrier for each bolt or lock piece, and there is no interlocking in each set of bolts or lock pieces, so that the theft can easily open the door through respectively break each barrier. Therefore, the conventional lock core structure still needs to be improved and enhanced.

SUMMARY OF THE INVENTION

[0003] Consequently, the object of the present invention is to provide a lock core structure in which multiple locks are interlocked, so that the lock can not be broken by the theft easily.

[0004] The present invention provides a lock core structure including a housing, a lock core, at least two latch elements and plural lock piece sets. Each lock piece set includes a division plate and a first lock piece and a second lock piece, wherein the first lock piece and the second lock piece are embedded in two sliding tracks on the division plate, and an elastic element is mounted between the first lock piece and the second lock piece for interlocking the first and the second lock pieces. Moreover, the first lock piece and the second lock piece respectively have a first embedding slot and a second embedding slot corresponding to the fixing troughs at the two sides of the division plate, and when the first embedding slot and the second embedding slot are aligned with the fixing troughs, the lock can be opened. Furthermore, because the interlocked structure between the first lock piece and the second lock piece, even the theft tries to

reject any one of the first or the second lock piece, it still difficult to break the lock core.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The foregoing aspects and many of the attendant advantages of this invention will be more readily appreciated as the same becomes better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

Fig. 1A is a decomposition drawing of the present invention;

Fig. 1B is a partial magnification drawing showing a second lock piece;

Fig. 1C is a partial magnification drawing showing a first lock piece;

Fig. 2 is a decomposition drawing showing a partial sectional view of a lock core and the decomposition drawing of a lock piece set;

Fig. 3 is a first sectional view showing the lock core structure;

Fig. 4 is a second sectional view showing the lock core structure;

Fig. 5A is a schematic view showing an initial state of the lock core structure;

Fig. 5B is a schematic view showing an unlocked state of the lock core structure;

Fig. 6A is a first schematic view showing the interlocking between the first and the second lock pieces; and

Fig. 6B is a second schematic view showing the interlocking between the first and the second lock pieces.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0006] Please refer to Figs. 1A and 2, which are decomposition drawings respectively showing a lock core 1 and lock piece set. A lock core structure includes a lock core 1, two latch elements 2 and plural lock piece sets embedded in the lock core 1, wherein the lock core 1 has a space dug for embedding therein plural lock piece sets and also has embedding holes mounted at two sides thereof for positioning the latch elements 2, each of the latch elements 2 further has a bulge 21 mounted thereon, and each of the embedding holes 11 has plural rejecting blocks 111 mounted therein and a latch spring 22 rejected between the latch element 2 and the rejecting block 111. Furthermore, each lock piece set includes a division plate 5, a first lock piece 4, a second lock piece 3 and an elastic element 6 located between the first and the second lock pieces 4, 3, wherein the division plate 5 has a key through hole 52 mounted at the center thereof for passing through a key 8 (shown in Fig. 5B) and a key orientation element 521 mounted around the key through hole 52 for orientating the key, a sliding track 51 respectively mounted at

two sides of the key through hole 52, and a fixing trough 53 respectively located at two sides of the division plate 5 corresponding to the embedding holes 11 of the lock core 1, and the first lock piece 4 and the second lock piece 3 both have two sliding elements 42, 32 for guiding the first lock piece 4 and the second lock piece 3 to move along the sliding tracks 51 on the division plate 5. Besides, the first lock piece 4 has a first key rejecting shaft 41 protrudently mounted at one side thereof near the key through hole 52 so as to correspond to a first embedding slot 43 located at one side of the fixing trough 53, and the second lock piece 3 also has sliding elements 32 for moving along the sliding track of the division plate 5 so as to correspond to a second embedding slot 33 located at one side of the fixing trough 53. In addition, the second lock piece 3 also has a second key rejecting shaft 31 protrudently mounted at one side thereof near the key through hole 52. The first key rejecting shaft 41 and the second key rejecting shaft 31 are respectively mounted in front of the key through hole 52 at the top and the bottom, and a rejecting shaft 34 is further mounted at the lower end of the second lock piece 3 so that an elastic element 6 can be mounted between the rejecting shaft 34 and the first key rejecting shaft 41, and the elastic element 6 is simultaneously rejected at the first key rejecting shaft 41 of the first key plate 4 and the rejecting shaft 34 of the second lock piece 3 so as to form an interlocked structure. Please refer to Figs. 1B and 1C, which are partial enlargements of the first lock piece 4 and the second plate 3. The first key rejecting shaft 41 and the second key rejecting shaft 31 have two inclined planes and approximately have a triangular sectional area, and the first key rejecting shaft 41 and the second key rejecting shaft 31 are mounted in front of the key through hole 52 of the division plate 5 in an opposite direction.

[0007] Please refer to Fig. 3. As shown, the first lock piece 4 and the second lock piece 3 are not shown, and the lock core 1, the latch element 2, the lock latching spring 22 and the lock piece sets are tightly assembled in a housing 7. The housing 7 includes a latching slot 71 for embedding the latch element 2 between the latching slot 7 and the embedding hole 11 of the lock core 1 as in a normal state. The inner edge of the latching slot 71 is formed by plural non-vertical slants so that when the latch element 2 is pushed, it can slide out of the latching slot 71 and move the bulge 21 of the latch element 2 to leave the fixing trough 53 of the division plate 5 by a latching spring 22. Please refer to Fig. 4 which shows a sectional view of the lock core including the first lock piece 4 and the second lock piece 3. The first lock piece 4 and the second lock piece 3 are slid along the sliding track 51 of the division plate 5 via the sliding elements 42, 32, and the first lock piece 4 and the second lock piece 3 are respectively have the first embedding slot 43 and the second embedding slot 33 corresponding to the fixing troughs 53 at the two sides of the division plate 5. When the first embedding slot 43 and the second embedding

slot 33 are aligned with the division plate 5 to form a space for sliding in the latch elements, the turn of the key 8 (shown in Fig. 5B) can force the latch element 2 to slide into the space so as to turn the lock core 1 for unlocking.

[0008] Please refer to Fig. 5A, which shows a locked initial state of the lock core structure. At the initial state, the first lock piece 4 and the second lock piece 3 are rejected by the elastic element 6 so that the first embedding slot 43 and the second embedding slot 33 are not aligned with the fixing trough 53. When an unmatched key 8 (as shown in Fig. 5B) is plugged in for turning the lock core 1, the lock core 1 can not be turned since the latch element 2 which latches the lock core 1 does not have a movement space, so that the locking function is achieved. Further, please refer to Fig. 5B, after a matched key 8 is plugged into the key through hole 52, the grooves on the key 8 will simultaneously reject against the first lock piece 4 and the second lock piece 3, so that the elastic element 6 will be compressed to force the first lock piece 4 and the second lock piece 3 to oppositely move. Then, the first embedding slot 43 and the second embedding slot 33 will simultaneously move and respectively align with the fixing troughs 53 at the two sides of the division plate 5. Therefore, when the lock core 1 is turned, the latch element 2 can slide into the first embedding slot 43, the second embedding slot 33 and the fixing troughs 53 for unlocking.

[0009] Please refer to Figs. 6A and 6B, which are schematic views showing the interaction of the first lock piece 4 and the second lock piece 3. If only the second lock piece 3 is rejected, the second lock piece 3 will move upwardly, and at the same time, the rejecting shaft 34 of the second lock piece 3 will also drive the elastic element 6 to upwardly reject against the first key rejecting shaft 41 of the first lock piece 4, so that the first lock piece 4 will also move upwardly to force the first embedding slot 43 to leave the fixing trough 53 (which is covered in Fig. 6A), and the lock can not be unlocked. In Fig. 6B, if only the first lock piece 4 is rejected, the first key rejecting shaft 41 will push the elastic element 6, and at the same time, the second lock piece 3 will also move downwardly, so that the second embedding slot 33 will leave the fixing trough 53 (which is covered in Fig. 6B). Therefore, this interlocked structure is hard to break and the anti-theft effect can be achieved.

[0010] For enhancing the anti-theft function, plural lock piece sets can be mounted inside a lock core 1, and in each lock piece set, the first key rejecting shaft 41 and the second key rejecting shaft 31 can have different locations for creating the distance therebetween so as to increase the difficulty in unlocking. Moreover, the key orientation element 521 in the division plate 5 can further limit the shape of the key 8, so that through altering the shape, amount and position of the key orientation element 521, the key through hole 52 can block the unmatched key 8. Besides, the first key rejecting shaft 41 and the second rejecting shaft 31 can also have a circle section, and the elastic element 6 can be a spring.

[0011] It is to be understood, however, that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

Claims

1. A lock core structure having plural lock piece sets embedded therein, a key through hole (52) and at least two embedding holes (11) for providing space to at least two latch elements (2) to move therein, the lock core (1), plural lock piece sets and latch element (2) being tightly matched in a housing (7), wherein the lock piece set comprising:
 - a division plate (5) embedded in the lock core (1) and having a key through hole (52) for passing through a key (8), a first and a second sliding tracks (51), and fixing troughs (53) located at the positions corresponding to the embedding slots (11) for sliding therein the latch elements (2);
 - a first lock piece (4) having a sliding element (42) mounted thereon for guiding thereof to slide along the sliding track (51) on the division plate (5), a first key rejecting shaft (41) protrudently mounted at one side thereof near the key through hole (52), and a first embedding slot (43) located at one side thereof corresponding to the fixing trough (53); and
 - a second lock piece (3), mounted on the division plate (5) opposite to the first lock piece (4), having a sliding element (32) mounted thereon for guiding thereof to slide along the sliding track (51) on the division plate (5), a second key rejecting shaft (31) protrudently mounted at one side thereof near the key through hole (52), a second embedding slot (33) located at one side thereof corresponding to the fixing trough (53), and a rejecting shaft (34) for mounting an elastic element (6) between the rejecting shaft (34) and the first key rejecting shaft (41) so as to form an interlocked structure between the first lock piece (4) and the second lock piece (3).
2. The lock core structure as claimed in claim 1, wherein the first embedding slot (43) and the second embedding slot (33) are staggered in a normal state.
3. The lock core structure as claimed in claim 1 or 2, wherein the elastic element (6) is a spring.
4. The lock core structure as claimed in one or more of the claims 1 to 3, wherein the first key rejecting shaft (41) and the second key rejecting shaft (31) in each of plural lock piece sets are staggered.
5. The lock core structure as claimed in one or more of the claims 1 to 4, wherein the first key rejecting shaft (41) and the second key rejecting shaft (31) respectively have a triangular section.
6. The lock core structure as claimed in one or more of the claims 1 to 5, wherein the first key rejecting shaft (41) and the second key rejecting shaft (31) respectively have a circular section.
7. The lock core structure as claimed in one or more of the claims 1 to 6, wherein the first key rejecting shaft (41) and the second key rejecting shaft (31) are staggered at the top and the bottom.
8. The lock core structure as claimed in one or more of the claims 1 to 7, wherein the key through hole (52) of the division plate (5) further comprises at least a key orientation element (521).
9. The lock core structure as claimed in one or more of the claims 1 to 8, wherein the housing (7) has a latching slot (71) for sliding the latch element (2) therein.
10. The lock core structure as claimed in claim 9, wherein the inner wall of the latching slot (71) is formed by non-vertical slants.




Fig. 1A




Fig. 1B




Fig. 1C




Fig. 2




Fig. 3




Fig. 4




Fig. 5A




Fig. 5B




Fig. 6A




Fig. 6B



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 07 10 1043

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	US 3 035 433 A (TESTA FRANK J) 22 May 1962 (1962-05-22) * column 2, line 9 - column 4, line 5; figures 1-8 *	1,8-10	INV. E05B29/06
A	US 3 263 461 A (TARTAGLIA JOHN A) 2 August 1966 (1966-08-02) * column 4, lines 13-43; figures 1-7 *	1	
A	US 3 509 749 A (REGAN JOHN F ET AL) 5 May 1970 (1970-05-05) * figures 1-6 *	1	
A	FR 2 161 473 A (KELLER VOLPER E) 6 July 1973 (1973-07-06) * page 2, line 24 - page 3, line 38; figures 1-4 *	1-4	
A	CH 273 028 A (DASA SOCIETE ANONYME [CH]) 31 January 1951 (1951-01-31) * figures 1-3 *	1	
A	FR 1 296 552 A (BREV NEIMAN S A SOC D EXPL DES) 22 June 1962 (1962-06-22) * figures 1-5 *	1	TECHNICAL FIELDS SEARCHED (IPC) E05B
A	GB 422 093 A (AUTOMATIC MUSICAL INSTR COMPAN) 4 January 1935 (1935-01-04) * figures 1-6 *	1	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 8 May 2007	Examiner Geerts, Arnold
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

2
EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 07 10 1043

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-05-2007

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3035433	A	22-05-1962	NONE	
US 3263461	A	02-08-1966	NONE	
US 3509749	A	05-05-1970	NONE	
FR 2161473	A	06-07-1973	NONE	
CH 273028	A	31-01-1951	NONE	
FR 1296552	A	22-06-1962	NONE	
GB 422093	A	04-01-1935	NONE	

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 094219454 A [0002]
- WO 094216537 A [0002]
- WO 095206477 A [0002]
- WO 094145435 A [0002]