



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 54**

(51) Int Cl.:  
**B60R 11/02** (2006.01) **H01R 13/453** (2006.01)  
**H01R 13/74** (2006.01) **H01R 13/717** (2006.01)

(48) Corrigendum issued on:  
**17.06.2009 Bulletin 2009/25**

(43) Date of publication:  
**10.12.2008 Bulletin 2008/50**

(21) Application number: **07425506.8**

(22) Date of filing: **03.08.2007**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR**  
Designated Extension States:  
**AL BA HR MK RS**

(30) Priority: **08.06.2007 IT TO20070408**

(71) Applicant: **Fiat Group Automobiles S.p.A.**  
**10135 Torino (TO) (IT)**

(72) Inventors:  
• **Tardivo, Michele**  
**10135 Torino (IT)**  
• **Varazi, Giovanni Maria**  
**10135 Torino (IT)**  
• **Mainini, Andrea**  
**10135 Torino (IT)**

(74) Representative: **Bergadano, Mirko et al**  
**Studio Torta S.r.l.**  
**Via Viotti, 9**  
**10121 Torino (IT)**

(54) **A dashboard assembly for a motor vehicle provided with a connector for connecting a portable electronic device**

(57) A dashboard assembly (1) of a motor vehicle includes a dashboard (2) and a connector (5), which is set in a hole of the dashboard (2) and defines a seat (7) which is accessible by opening a hatch (10); the connector has an electrical contact for the 12-V or 24-V electrical supply and at least one electrical contact for transmission of data and is provided with at least one retention hole (22) for withholding a support (14) of a portable electronic device engaging in the seat (7); also provided is a reinforcement system around at least part of the seat (7) for withstanding vibrations and forces exerted, in use, by the support (14).

**FIG. 1**

