



(11) **EP 2 045 138 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
B60R 7/06 (2006.01) B60R 7/04 (2006.01)

(48) Corrigendum issued on:
17.06.2009 Bulletin 2009/25

(43) Date of publication:
08.04.2009 Bulletin 2009/15

(21) Application number: **08017296.8**

(22) Date of filing: **01.10.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR
Designated Extension States:
AL BA MK RS

(30) Priority: **04.10.2007 JP 2007260645**

(71) Applicant: **Honda Motor Co., Ltd.**
Tokyo 107-8556 (JP)

(72) Inventors:
• **Matsui, Toru**
c/o Honda R&D Co., Ltd.
Wako-shi
Saitama 351-0193 (JP)
• **Kamioka, Toshikazu**
c/o Honda R&D Co., Ltd.
Wako-shi
Saitama 351-0193 (JP)

(74) Representative: **Trossin, Hans-Jürgen et al**
Weickmann & Weickmann
Postfach 860 820
81635 München (DE)

(54) **Storage device for vehicle**

(57) A vehicular storage device provided in opposed relation to a passenger seat. A convex part (62, 63), protruding from a rear surface of a lid (16) in a direction opposite from a vehicle occupant, has a deformation allowance part (81) that deforms when an impact is applied to the convex part.

