



(11) **EP 2 045 561 B9**

(12) **CORRECTED EUROPEAN PATENT SPECIFICATION**

(15) Correction information:

Corrected version no 1 (W1 B1)
Corrections, see
Claims EN 1

(51) Int Cl.:

F41A 3/72 ^(2006.01) **F41A 3/26** ^(2006.01)
F41A 3/68 ^(2006.01)

(48) Corrigendum issued on:

25.02.2015 Bulletin 2015/09

(45) Date of publication and mention
of the grant of the patent:

03.12.2014 Bulletin 2014/49

(21) Application number: **08165560.7**

(22) Date of filing: **01.10.2008**

(54) **Firearm with an improved breech bolt assembly**

Feuerwaffe mit einer verbesserten Verschlussbolzenanordnung

Arme dotée d'un ensemble amélioré de verrou de culasse

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR

(30) Priority: **04.10.2007 IT MI20071909**

(43) Date of publication of application:
08.04.2009 Bulletin 2009/15

(73) Proprietor: **FABBRICA D'ARMI PIETRO BERETTA**
S.p.A.
25063 Gardone Val Trompia (BS) (IT)

(72) Inventor: **Zedrosser, Ulrich**
4400, STEYR (AT)

(74) Representative: **Branca, Emanuela et al**
Barzanò & Zanardo Milano S.p.A.
Via Borgonuovo, 10
20121 Milano (IT)

(56) References cited:
EP-A1- 1 645 832 WO-A1-2007/090611
US-A- 3 225 653 US-A- 5 214 233

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 045 561 B9

Description

[0001] The present invention relates to a firearm with an improved breech bolt assembly.

[0002] A breech bolt assembly, comprising a breech bolt-slide and a breech bolt equipped with a locking head, is contained inside a body of a firearm, such as a repeat gun, and can be moved axially with respect to this.

[0003] The breech bolt, in particular, is housed in the slide so as to have a limited rotating and axial translatable movement for the opening of the firing chamber and its closing at the moment of firing.

[0004] To enable the breech bolt to close the firing chamber, it must be equipped with closing guide rails activated by the relative movement between the slide and breech bolt, which takes place at the end of the advance movement of the breech bolt. In particular, during the advance and withdrawal of the breech bolt assembly the relative movement between the breech bolt and slide is prevented, except at the moment of closing and opening, when the breech bolt must also rotate with respect to the slide. This rotation is achieved by means of a cam of the slide engaged with a corresponding cursor of the breech bolt.

[0005] The movement of the breech bolt also has the functions of housing a cartridge in the firing chamber from the magazine and ejecting a cartridge or cartridge case from the firing chamber.

[0006] The loading or reloading procedure of the arm, which is effected by moving the breech bolt along the direction of the barrel, is equally applied in the case of manual, semi-automatic or automatic functioning. In any case, for all the functioning modes mentioned, the loading procedure of the first cartridge must be effected manually. For this reason all firearms with a magazine are equipped with a cocking handle, or reloading lever, produced in different ways.

[0007] EP 1 645 832 discloses a firearm according to the preamble of appended independent claim 1.

[0008] The cocking handle, which is connected to the breech bolt and protrudes from the body of the arm, allows the user to intervene manually on the breech bolt without being able to reach this with his hand.

[0009] According to what is known, the cocking handle is alternatively produced as part of the body, connected to the breech bolt by means of a joint, or it can be directly connected to the breech bolt itself, generally removably to allow the dismantling of the firearm.

[0010] A simple and effective solution of the second type described consists in a cocking handle rigidly connected to the breech bolt protruding outside the body by means of a suitable opening or port. In this case, the port must be sufficiently long, in an axial direction, to allow the necessary movement of the breech bolt for the loading or unloading procedure.

[0011] An objective of the present invention is to provide a firearm with an improved breech bolt assembly which guarantees a correct opening and closing synchro-

nism of the firearm.

[0012] A further objective of the present invention is to produce a firearm with an improved breech bolt assembly which allows an ambidextrous use.

[0013] Another objective of the present invention is to provide a firearm with an improved breech bolt assembly which can be rapidly and simply disassembled without the help of specific tools and in which there are no small-sized loose components.

[0014] These objectives according to the present invention are achieved by producing a firearm with an improved breech bolt assembly as specified in claim 1.

[0015] Further characteristics are indicated in the dependent claims.

[0016] The characteristics and advantages of a firearm with an improved breech bolt assembly according to the present invention will appear more evident from the following illustrative and non-limiting description, referring to the enclosed schematic drawings, wherein:

figure 1 is a perspective view of a firearm equipped with an improved breech bolt assembly according to the invention;

figure 2 is a plan view of the breech bolt assembly according to the invention;

figure 3 shows a section according to the trace III-III of the breech bolt assembly of figure 2;

figure 4 is an exploded view of some details of the breech bolt assembly according to the invention;

figures 5-8 show a sectional view of some of the functioning opening phases of the improved breech bolt assembly according to the invention;

figures 9 and 10 show a sectional view of some of the functional closing phases of the improved breech bolt assembly according to the invention;

figures 11A-13A and 11B-13B show a sectional view of various rotation phases of the cocking handle in the firearm according to the invention.

[0017] With reference to the figures, these show a firearm with an improved breech bolt assembly indicated as a whole with 100.

[0018] The firearm 100, shown for illustrative and non-limiting purposes in figure 1, comprises a breech bolt assembly 10, a barrel 12, a body 14, or outer shell, also equipped on opposite sides with symmetrical openings 15, or ports, for the right or left ejection of a cartridge case, in addition to a magazine 17.

[0019] The breech bolt assembly, shown in figures 2-4, comprises a breech bolt 18 and a breech bolt-holder slide 21, which can be moved together and separately in a direction parallel to the axis 22 of the barrel 12, or axis of the firearm. The breech bolt 18 is equipped, at a front end, with a head 25 which is engaged in a barrel extension 24, indicated for example in figure 5, integral with the barrel 12 for the closing and opening of a firing chamber by rotation.

[0020] The ejection ports of the cartridge cases 15

comprise a slit extension 16 towards the rear end of the opening 15, having a lower height with respect to the port, to allow a cocking handle 23, or reloading lever, to effect its necessary run.

[0021] According to the invention, the cocking handle 23, which allows the user to intervene manually on the breech bolt assembly 10, according to what is shown in figures 2 and 3, is assembled between the breech bolt 18 and the slide 21. In particular, according to the non-limiting example provided, the slide 21 is equipped on both sides close to the cocking handle 23 with seats 21" for coupling with complementary reliefs 123 of the cocking handle 23.

[0022] The cocking handle, when in use, is positioned orthogonally with respect to the axis of the barrel 22 protruding laterally from the body 14 of the firearm 100 through the ports 15 alternating on one side or on the other side, as described and illustrated hereunder.

[0023] During the withdrawal of the breech bolt assembly 10 after the opening phase of the head 25 by rotation and until the closing of the head 25 by rotation, stopping means prevent the relative movement between the breech bolt 18 and slide 21. The stopping means consist of a control pin 28, housed inside a seat 21' of the slide 21 and which can be moved vertically to respectively disengage itself from a control seat 29 in the breech bolt 18, overcoming the force of a specific return spring 30.

[0024] When the breech bolt 18 is closed, the control pin is housed in a second containment seat 31 in the breech bolt 18 in an advanced position with respect to the control seat 29.

[0025] Cam guide rails of the vertical lifting of the control pin 28 are also envisaged, comprising a ramp 32 situated at a rear end of the containment seat 31 and a tilted coupling surface 24' of the barrel extension 24.

[0026] The control pin 28 comprises a main cylindrical body coupled with the seat 21' of the slide and a feeler end 28', for example cylindrical with a smaller diameter, connected to the main body by conical surfaces 28" complementary to a conical hole 23" of the cocking handle 23.

[0027] By pulling the cocking handle transversally with respect to the axis 22, the control pin 28 is raised vertically due to the contact on the complementary conical surfaces. The passage of the cocking handle 23 in a transversal direction with respect to the axis 22 is enabled by the presence of a grooved seat 23' situated in the conical hole 23".

[0028] The return spring 30 is, for example, a lamina spring constrained at a first end to the breech bolt-slide 21 and at the opposite end coupled with a seat 19 on the control pin 28. The lamina spring comprises a "V"-folded portion 30' near the constraining end with the pin 28. The front branch of the folded portion 30' is engaged with the tilted surface 24', or cam, of the barrel extension 24 during the closing phases of the breech bolt.

[0029] The barrel extension 24 is also equipped with a seat 24" for containing the folded portion 30' of the

spring 30 under closed breech bolt conditions.

[0030] Further cam control means of the vertical lifting of the control pin 28, consist in a cam 20, shown for example in figure 5, integral with the body 14 in an upper facing position with respect to the control pin 28, which, in correspondence with a cavity 20', allows the vertical movement of the control pin 28 only within a pre-established range of the relative movement between the slide 21 and the body 14.

[0031] The breech bolt assembly 10, shown in figure 3 in section in an open breech bolt position, also has cam guiding means of the rotation for the closing or opening of the breech bolt which comprise a guiding cursor 26, situated in one piece on the breech bolt 18, which can be moved in engagement with a cam 27 of the slide 21.

[0032] The guiding means of the rotation of the breech bolt 10 are activated by the relative movement between the slide 21 and breech bolt 18.

[0033] The opening of the breech bolt assembly, described on the base of figures 5 to 8, which schematically show the reciprocal movement of the components, begins with the relative withdrawal movement of the breech bolt 18 with respect to the slide 21 (schematized in figure 5 with the arrow F1).

[0034] The control pin 28, which is initially housed in the containment seat 31, is lifted vertically, guided by the ramp 32, until it is disengaged from the breech bolt. The cavity 20' of the cam 20 in the body 14 allows the control pin 28 to have this extracted position. Furthermore, the withdrawal of the slide 21 with respect to the breech bolt 18, due to the cam 27, causes the rotation of the breech bolt 18 itself and therefore the opening (figure 6).

[0035] The further withdrawal of the slide 21 causes the upper end of the control pin 28 to interfere with the cam 20 of the body, which causes the vertical lowering of the pin 28 engaged with the control seat 29 of the breech bolt 18. The action of the return spring 30, loaded by the previous lifting of the pin, also contributes to engage the pin 28 in the control seat 29.

[0036] When the pin 28 is engaged in the control seat 29 (figure 7), the reciprocal movement between the slide 21 and breech bolt 18 is prevented, until the pin 28 is unblocked. In particular, the control seat 29 does not allow the rotation of the breech bolt 18. The withdrawal of the slide 21, according to the arrow F1, consequently also integrally entrains the breech bolt 18 according to the arrow F2.

[0037] The withdrawal of the slide 21 and breech bolt 18 terminates with the possibility of housing a cartridge in the configuration of figure 8.

[0038] The closing phases of the breech bolt assembly, described on the basis of figures 9 and 10, above all provide for the housing of the first cartridge of the magazine 17.

[0039] At the end of the advance movement of the slide 21 and breech bolt 18, according to the arrows F1 and F2 of figure 9, respectively, the control pin 28 is unblocked. The coupling between the front branch of the

"V"-portion 30' of the return spring 30 with the tilted surface 24' of the barrel extension 24, vertically lifts the pin 28 (figure 10), this movement being allowed by the cavity 20' of the cam 20 of the body 14.

[0040] When the breech bolt 18 reaches the end of its run (figure 10), the cam means 26 and 27 guide the rotational-translatory movement between the breech bolt 18 and the slide 21, which is no longer hindered by the control pin 28.

[0041] Under closed conditions of the breech bolt assembly, as shown in figure 5, the control pin 28 is engaged in the containment seat 31.

[0042] For the manual reloading of the firearm, the cocking handle 23, integral with the slide 21 on the right or left side, transmits to this, the advance and/or withdrawal movement described above for the firing phases.

[0043] Figure 2 shows, for illustrative purposes, the cocking handle 23 in the two operating positions, in a continuous line and dashed line.

[0044] Figure 11A and 11B respectively show a raised side view and sectional view according to the marked surface B-B, a breech bolt assembly 10 according to the invention, in which the cocking handle 23 is in an operating position. The cocking handle 23 is kept in a stable position for the rotation through engagement of the reliefs 123 with the complementary seats 21" of the slide 21 (figure 11B).

[0045] In order to rotate the cocking handle 23 by 180° around the pin 28, it is sufficient to open the breech bolt assembly 10 in a more withdrawn position with respect to the cam 20 of the body 14, so that the pin 28 can be lifted vertically without hindrances by moving the cocking handle 23 transversally with respect to the axis of the barrel 22 following a limited run along the arrow T (figure 12B). The control pin 28 is therefore lifted as a result of the coupling with the cocking handle 23 on conical surfaces against the force of the spring 30. The control pin 28 remains in a lifted position resting on the flat upper surface of the cocking handle 23 (figures 12A and 12B).

[0046] The cocking handle 23 is disengaged from the seats 21" of the slide and is free to rotate around the axis of the pin 28 and be positioned, for example, longitudinally with respect to the barrel 12, to allow the extraction of the breech bolt assembly 10 from the body 14 without disassembling any piece (figures 13A and 13B).

When the cocking handle 23 is in a rotation position, the control pin 28 is vertically extracted and protrudes with respect to the slide 21.

[0047] The interference between the pin 28 and cam 20 of the body keeps the breech bolt 18 firmly open during the rotation operations of the cocking handle.

[0048] By continuing the rotation, the cocking handle 23 can be rotated on the opposite side, in a specular position with respect to figures 12A and 12B, and consequently through a transversal passage in the direction of the slide 21, it can be brought back into the stable operating position, which is specular with respect to figures 11A and 11B. The action of the return spring 30

brings the control pin 28 back into engagement on the cocking handle 23 on the coupled conical surfaces.

[0049] This procedure can also be effected with the firearm assembled.

[0050] When the cocking handle 23 is in an operating position, arranged orthogonally with respect to the axis 22 of the barrel 12, this cannot be rotated and has all the advantages of a cocking handle firmly constrained to the breech bolt assembly 10.

[0051] The necessity of lifting the control pin 28 against the force of the spring 30 to rotate the cocking handle, also advantageously allows the movement to be more safely controlled.

[0052] The assembly of the cocking handle 23 on the control pin 28, when the breech bolt is closed, at the end of the advance phase, allows the cocking handle 23 to be situated at the front end of the ejection port 15 of the body 14, i.e. in the normal position of the cocking handle 23.

[0053] Furthermore, this advantageously allows the ejection port of the cartridge cases 15, in any case present, to be used for the passage of the cocking handle 23. It is sufficient, in fact, to envisage the additional slit 16 towards the rear end of the port 15, with a lower height with respect to the port, to allow the cocking handle 23 to effect the whole run necessary.

[0054] This advantageously requires a minimum removal of material from the body and consequently a minimum weakening of the body itself, which is above all equal on opposite sides.

[0055] The firearm with an improved breech bolt assembly, object of the present invention, also has the advantage of allowing a rapid assembly and disassembly without the removal of loose pieces.

[0056] The firearm with an improved breech bolt assembly thus conceived, can undergo numerous modifications and variants, within the scope of the appended claims; furthermore all the details can be substituted by technically equivalent elements. In practice, the materials used, as also the dimensions, can vary according to technical requirements.

Claims

1. A firearm with a breech bolt assembly comprises a barrel (12), a breech bolt assembly (10), a body (14) equipped on opposite sides with ports (15) for the ejection of a cartridge case, in addition to a magazine (17), wherein said breech bolt assembly, which is moveable with respect to said body (14) comprises a breech bolt-holder slide (21), a breech bolt (18) equipped with a rotating locking head (25), cam guide rails (26, 27) configured to guide the relative movement between the breech bolt (18) and slide (21), and also stopping means (28, 29) configured to stop said relative movement, **characterized in that** said stopping means comprise a control pin (28)

which can be moved vertically with respect to a first control seat (29), charged by a return spring (30) applied between said slide (21) and said pin (28), wherein said pin (28) has a cocking handle (23) rotatably applied thereto, for the manual moving of said breech bolt assembly (10).

2. The firearm according to claim 1, **characterized in that** said return spring (30) is a lamina spring constrained to said slide (21) at one end and constrained to said pin (28) at the opposite end.
3. The firearm according to claim 2, **characterized in that** said spring (30) comprises a "V"-folded portion (30') near the constraining end with said pin (28), wherein a front branch of said "V"-folded portion (30') is complementary with a tilted surface, or cam (24') of a barrel extension (24) which guides the vertical lifting of said control pin (28) during the closing of said breech bolt assembly (10).
4. The firearm according to claim 1, **characterized in that** said breech bolt (18) comprises a second containment seat (31) of said control pin (28) adjacent and advanced with respect to said first seat (29).
5. The firearm according to claim 4, **characterized in that** said second seat (31) comprises, at a rear end, a ramp (32), for cam guiding the lifting movement of the control pin (28) during the opening of said breech bolt assembly (10).
6. The firearm according to claim 1, **characterized in that** said control pin (28) is housed inside a complementary seat (21') of the slide (21).
7. The firearm according to claim 6, **characterized in that** said control pin (28) comprises a main body coupled with said seat (21') and a feeler end (28'), connected with the main body by means of conical surfaces (28''), complementary to a conical hole (23'') of said cocking handle (23).
8. The firearm according to claim 1, **characterized in that** said body comprises cam means (20) for controlling the vertical lifting of the pin (28) in an upper facing position with respect to the control pin (28) and equipped with a cavity (20') to allow the vertical movement of the control pin (28) only within a pre-established range of the relative movement between said slide (21) and said body (14).
9. The firearm according to claim 1, **characterized in that** said cocking handle (23) protrudes from said body (14) through said ejection ports (15) and through slit extensions (16) during its run.
10. The firearm according to claim 9, **characterized in**

that said body (14) is symmetrical.

11. The firearm according to claim 7, **characterized in that** said conical hole (23'') comprises, in a transversal direction with respect to the axis (22), a grooved seat (23') which allows the transversal movement of the cocking handle (23), said transversal movement being suitable for vertically lifting the control pin (28).
12. The firearm according to claim 1, **characterized in that** said slide (21) is equipped on both sides near said cocking handle (23), with seats (21'') for a firm coupling with reliefs (123) complementary to said cocking handle (23).
13. The firearm according to claim 12, **characterized in that** said cocking handle (23) can be moved transversally with respect to said axis (22) from an operating position, in which it is firmly constrained to said slide (21) by means of said coupling between seats (21'') and complementary reliefs (123), orthogonally with respect to said axis (22), to a regulation position in which it can be freely rotated by an angle (α) equal to 180°.

Patentansprüche

1. Eine Feuerwaffe mit einer Verschlussbolzenanordnung umfasst einen Lauf (12), eine Verschlussbolzenanordnung (10), einen Körper (14), der auf entgegengesetzten Seiten mit Öffnungen (15) für den Auswurf einer Patronenhülse versehen ist, sowie ein Magazin (17), wobei diese Verschlussbolzenanordnung, die gegenüber dem Körper (14) beweglich ist, einen Verschlussbolzenhalteschlitten (21), einen Verschlussbolzen (18), der mit einem drehbaren Verschlusskopf (25) versehen ist, Nockenführungs-schienen (26, 27), die zum Führen der Relativbewegung zwischen dem Verschlussbolzen (18) und dem Schlitten (21) gestaltet sind, und außerdem Stoppmittel (28, 29), die zum Stoppen dieser Relativbewegung gestaltet sind, umfasst, **dadurch gekennzeichnet, dass** diese Stoppmittel einen Steuerzapfen (28) umfassen, der senkrecht zu einem ersten Steuersitz (29) bewegt werden kann, der von einer Rückstellfeder (30) kraftbeaufschlagt wird, die zwischen dem Schlitten (21) und dem Zapfen (28) angebracht ist, wobei dieser Zapfen (28) einen daran drehbar angebrachten Durchladehebel (23) zum manuellen Bewegen der Verschlussbolzenanordnung (10) aufweist.
2. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** die Rückstellfeder (30) eine Blattfeder ist, die an einem Ende am Schlitten (21) und am entgegengesetzten Ende am Zapfen (28) befestigt ist.

3. Feuerwaffe nach Anspruch 2, **dadurch gekennzeichnet, dass** die Feder (30) einen V-förmig gefalteten Abschnitt (30') nahe dem Ende für die Befestigung am Zapfen (28) aufweist, wobei ein vorderer Zweig dieses V-förmig gefalteten Abschnitts (30') komplementär zu einer schrägen Oberfläche oder einem Nocken (24') einer Laufverlängerung (24) ist, die bzw. der den senkrechten Hub des Steuerzapfens (28) während des Schließens der Verschlussbolzenanordnung (10) führt.
4. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** der Verschlussbolzen (18) einen zweiten Haltesitz (31) des Steuerzapfens (28) umfasst, der neben dem ersten Sitz (29) liegt und ihm gegenüber vorgerückt ist.
5. Feuerwaffe nach Anspruch 4, **dadurch gekennzeichnet, dass** der zweite Sitz (31) an einem hinteren Ende eine Rampe (32) zum nockenartigen Führen der Hubbewegung des Steuerzapfens (28) während des Öffnens der Verschlussbolzenanordnung (10) umfasst.
6. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** der Steuerzapfen (28) in einem komplementären Sitz (21') des Schlittens (21) untergebracht ist.
7. Feuerwaffe nach Anspruch 6, **dadurch gekennzeichnet, dass** der Steuerzapfen (28) einen Hauptkörper, der mit dem Sitz (21') gekoppelt ist, und ein Tastendstück (28') umfasst, das mit dem Hauptkörper über konische Flächen (28'') verbunden ist, die komplementär zu einem konischen Loch (23'') des Durchladehebels (23) sind.
8. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** der Körper ein Nockenmittel (20) zum Steuern des senkrechten Hubs des Zapfens (28) umfasst, das sich in einer dem Steuerzapfen (28) zugewandten oberen Lage befindet und mit einem Hohlraum (20') versehen ist, um die senkrechte Bewegung des Steuerzapfens (28) nur innerhalb eines vorbestimmten Bereichs der Relativbewegung zwischen dem Schlitten (21) und dem Körper (14) zuzulassen.
9. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** der Durchladehebel (23) während seines Laufs durch die Auswurföffnungen (15) und durch Spaltverlängerungen (16) aus dem Körper (14) herausragt.
10. Feuerwaffe nach Anspruch 9, **dadurch gekennzeichnet, dass** der Körper (14) symmetrisch ist.
11. Feuerwaffe nach Anspruch 7, **dadurch gekennzeichnet, dass** das konische Loch (23'') in einer Querrichtung zur Achse (22) eine Nutaufnahme (23') umfasst, welche die Querbewegung des Durchladehebels (23) ermöglicht, wobei diese Querbewegung geeignet ist, den Steuerzapfen (28) senkrecht anzuheben.
12. Feuerwaffe nach Anspruch 1, **dadurch gekennzeichnet, dass** der Schlitten (21) auf beiden Seiten in der Nähe des Durchladehebels (23) mit Aufnahmen (21'') für eine feste Kopplung mit Stufen (123) versehen ist, die komplementär zum Durchladehebel (23) sind.
13. Feuerwaffe nach Anspruch 12, **dadurch gekennzeichnet, dass** der Durchladehebel (23) quer zur Achse (22) aus einer Arbeitsstellung, in der er durch die Kopplung zwischen Aufnahmen (21'') und komplementären Stufen (123) orthogonal zu dieser Achse (22) fest am Schlitten (21) befestigt ist, in eine Einstellstellung bewegt werden kann, in der er frei um einen Winkel (α) von 180° gedreht werden kann.

Revendications

- Arme à feu avec un bloc culasse comprenant un canon (12), un bloc culasse (10), un corps (14) équipé sur des côtés opposés d'orifices (15) pour l'éjection d'une douille de cartouche, en plus d'un chargeur (17), dans laquelle ledit bloc culasse, qui est mobile par rapport audit corps (14), comprend un coulisseau porte-culasse (21), une culasse (18) équipée d'une tête de verrouillage tournante (25), des rails de guidage de came (26, 27) configurés pour guider le mouvement relatif entre la culasse (18) et le coulisseau (21), et également des moyens d'arrêt (28, 29) configurés pour arrêter ledit mouvement relatif, **caractérisée en ce que** lesdits moyens d'arrêt comprennent une goupille de commande (28) qui peut être déplacée verticalement par rapport à un premier siège de commande (29), chargée par un ressort de rappel (30) appliqué entre ledit coulisseau (21) et ladite goupille (28), dans laquelle ladite goupille (28) a un levier d'armement (23) appliqué de manière rotative à celle-ci, pour le déplacement manuel dudit bloc culasse (10).
- Arme à feu selon la revendication 1, **caractérisée en ce que** ledit ressort de rappel (30) est un ressort à lamelle solidaire avec ledit coulisseau (21) à une extrémité et solidaire avec ladite goupille (28) à l'autre extrémité opposée.
- Arme à feu selon la revendication 2, **caractérisée en ce que** ledit ressort (30) comprend une portion pliée en V (30') près de l'extrémité de solidarisation avec ladite goupille (28), dans laquelle une branche


antérieure de ladite portion pliée en V (30') est complémentaire avec une surface inclinée, ou came (24'), d'une extension de canon (24) qui guide la montée verticale de ladite goupille de commande (28) durant la fermeture dudit bloc culasse (10).

4. Arme à feu selon la revendication 1, **caractérisée en ce que** ladite culasse (18) comprend un deuxième siège (31) de confinement de ladite goupille de commande (28), adjacent et avancé par rapport audit premier siège (29). 10
5. Arme à feu selon la revendication 4, **caractérisée en ce que** ledit deuxième siège (31) comprend, à une extrémité postérieure, une rampe (32), pour le guidage à came du mouvement de montée de la goupille de commande (28) durant l'ouverture dudit bloc culasse (10). 15
6. Arme à feu selon la revendication 1, **caractérisée en ce que** ladite goupille de commande (28) est logée à l'intérieur d'un siège complémentaire (21') du coulisseau (21). 20
7. Arme à feu selon la revendication 6, **caractérisée en ce que** ladite goupille de commande (28) comprend un corps principal accouplé avec ledit siège (21') et une extrémité formant palpeur (28'), reliée au corps principal par le biais de surfaces coniques (28"), complémentaires d'un trou conique (23") dudit levier d'armement (23). 25 30
8. Arme à feu selon la revendication 1, **caractérisée en ce que** ledit corps comprend des moyens de came (20) pour commander la montée verticale de la goupille (28) dans une position orientée vers le haut par rapport à la goupille de commande (28) et pourvus d'une cavité (20') pour permettre le mouvement vertical de la goupille de commande (28) seulement dans une plage prédéterminée du mouvement relatif entre ledit coulisseau (21) et ledit corps (14). 35 40
9. Arme à feu selon la revendication 1, **caractérisée en ce que** ledit levier d'armement (23) fait saillie par rapport audit corps (14) à travers lesdits orifices d'éjection (15) et à travers des extensions fendues (16) durant sa course. 45
10. Arme à feu selon la revendication 9, **caractérisée en ce que** ledit corps (14) est symétrique. 50
11. Arme à feu selon la revendication 7, **caractérisée en ce que** ledit trou conique (23") comprend, dans une direction transversale par rapport à l'axe (22), un siège rainuré (23') qui permet le mouvement transversal du levier d'armement (23), ledit mouvement transversal étant adapté pour soulever verticalement la goupille de commande (28). 55

12. Arme à feu selon la revendication 1, **caractérisée en ce que** ledit coulisseau (21) est muni sur les deux côtés, près dudit levier d'armement (23), de sièges (21") pour un accouplement ferme avec des reliefs (123) complémentaires audit levier d'armement (23).

13. Arme à feu selon la revendication 12, **caractérisée en ce que** ledit levier d'armement (23) peut être déplacé transversalement par rapport audit axe (22) d'une position de fonctionnement, dans laquelle il est fermement solidarisé avec ledit coulisseau (21) au moyen dudit accouplement entre des sièges (21") et des reliefs complémentaires (123), orthogonalement par rapport audit axe (22), à une position de réglage dans laquelle il peut être librement tourné d'un angle (α) égal à 180°.

Fig.1






Fig.3




Fig.2

Fig. 4




Fig.5




Fig.6





Fig.7






Fig. 8




Fig.9




Fig. 10




Fig. 11A




Fig. 11B




Fig. 12A




Fig. 12B




Fig. 13A




Fig. 13B

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 1645832 A [0007]