



(11) **EP 2 088 179 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(48) Corrigendum issued on:
07.10.2009 Bulletin 2009/41

(43) Date of publication:
12.08.2009 Bulletin 2009/33

(21) Application number: **07832781.4**

(22) Date of filing: **29.11.2007**

(51) Int Cl.:
C09J 7/02 ^(2006.01) **C09J 123/22** ^(2006.01)
C09J 133/06 ^(2006.01) **C09J 183/07** ^(2006.01)

(86) International application number:
PCT/JP2007/073066

(87) International publication number:
WO 2008/069095 (12.06.2008 Gazette 2008/24)

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE
SI SK TR

(30) Priority: **01.12.2006 JP 2006325348**

(71) Applicant: **Lintec Corporation**
Itabashi-ku
Tokyo
173-0001 (JP)

(72) Inventors:
• **TANAKA, Atsuhiko**
Tokyo 173-0001 (JP)

- **SUZUKI, Tomomi**
Tokyo 173-0001 (JP)
- **HAYAKAWA, Fumio**
Tokyo (JP)
- **KUBOTA, Naoki**
Tokyo (JP)
- **IKEDA, Katsuhiko**
Tokyo
(JP)

(74) Representative: **Gille Hrabal Struck Neidlein Prop**
Roos
Patentanwälte
Brucknerstrasse 20
40593 Düsseldorf (DE)

(54) **RELEASABLE ADHESIVE SHEET**

(57) Provided is a releasable pressure sensitive adhesive sheet, which is mainly used for a coating film for an automobile, and which is applicable to a coating film with insufficient curing immediately after drying. Specifically provided is a releasable pressure sensitive adhesive sheet for a curable coating film, which has a pressure

sensitive adhesive layer on one face of a front substrate, in which a face of the pressure sensitive adhesive layer out of contact with the front substrate has a rolling circle arithmetic mean waviness (Wea) specified in JIS B0610 of 0.30 μm or less.

EP 2 088 179 A8