

(19)



(11)

EP 2 147 133 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
01.12.2010 Bulletin 2010/48

(21) Application number: **08759575.7**

(22) Date of filing: **14.05.2008**

(51) Int Cl.:
C25B 11/02 (2006.01)

(86) International application number:
PCT/EP2008/055887

(87) International publication number:
WO 2008/138945 (20.11.2008 Gazette 2008/47)

(54) **ELECTRODE FOR MEMBRANE ELECTROLYSIS CELLS**

ELEKTRODE FÜR MEMBRANELEKTROLYSEZELLEN

ELECTRODE POUR DES CELLULES D'ÉLECTROLYSE À MEMBRANE

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR**

(30) Priority: **15.05.2007 IT MI20070980**

(43) Date of publication of application:
27.01.2010 Bulletin 2010/04

(73) Proprietor: **Industrie De Nora S.p.A.
20134 Milano (IT)**

(72) Inventors:
• **OTTAVIANI, Angelo**
I-20135 Milan (IT)
• **CARRETTIN, Leonello**
I-20146 Milan (IT)

- **DI FRANCO, Dino Floriano**
Mayfield Village, Ohio 44143 (US)
- **MOJANA, Corrado**
I-23868 Valmadrera (IT)
- **PEREGO, Michele**
I-20135 Milan (IT)

(74) Representative: **Reitstötter - Kinzebach**
Patentanwälte
Sternwartstrasse 4
81679 München (DE)

(56) References cited:
WO-A-2006/084745 DD-A1- 244 769
US-A- 3 361 656 US-A- 3 589 942
US-A- 4 344 832 US-A- 5 676 808

EP 2 147 133 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND

[0001] The invention relates to an electrode for electrochemical applications, in particular to an electrode for membrane electrolysis cells made on a metal support.

[0002] Electrolytic processes carried out in cells separated by ion-exchange membranes are among the most relevant industrial electrochemical applications. Some examples of such applications are the electrolysis of alkali chloride brines (chlor-alkali electrolysis), with particular reference to the electrolysis of sodium chloride brine for the production of chlorine and caustic soda, and the electrolysis of hydrochloric acid solutions.

[0003] In the following description, reference will be made to sodium chloride electrolysis as the most representative example in terms of overall production, but the present invention shall not be understood as limited to such application.

[0004] In membrane chlor-alkali electrolysis, the anodic compartment of the electrolysis cell is separated from the cathodic compartment by means of an ion-exchange membrane. The anodic compartment of the cell is fed with a sodium chloride brine, for instance at a concentration of about 300 g/l; chlorine evolution takes place on the anode surface, at a current density usually not above 4 kA/m², while brine is consequently depleted down to an outlet concentration usually comprised between 200 and 220 g/l. Sodium ions are transported by the electric field across the membrane to the cathodic compartment, where the caustic product is generated at a concentration usually not higher than 33% by weight. The caustic product is then extracted and concentrated by evaporation outside the cell. Hydrogen evolution also takes place on the cathode surface. The need of decreasing the capital investment has led to the design of plants operating at higher current density: in fact, while older plants usually work at 3 kA/m², those of newer construction operate at about 5 kA/m². The current trend in plant design is to further increase such values up to 6 kA/m² or more. The evolution of gas in form of bubbles, whose flow-rate increases at increasing current densities, may cause pressure fluctuations potentially dangerous for the mechanical integrity of the membrane: for this reason, the pressure differential across the two compartments is usually controlled in an accurate fashion and maintained below 3000 Pa, which complicates the cell operation. Moreover, the product gas has the tendency to build-up between the membrane and the electrode surfaces facing the same, increasing the ohmic drop in the contact zone and locally depleting the chloride-ion concentration due to poor electrolyte renewal. Brine dilution favours the local evolution of oxygen with consequent acidification. The combination of these different aspects (chlorine build-up, oxygen build-up, depletion of trapped brine, acidification) accounts for the early deterioration of the membranes, particularly in form of blister generation especially in cor-

respondence of interstitial zones between anode and membrane, leading to voltage increase and electrolysis efficiency decrease. A similar deterioration may also take place in the interstitial zones between membrane and cathode: in this case, liquid stagnation leads to an increase in the caustic product concentration, which may reach a value up to 40-45%. Such a high alkalinity can damage the membrane chemical structure, with consequent voltage increase going along with the onset of localised blistering, as described for the anode side.

[0005] A few measures have been proposed to improve brine circulation near the electrode surface in order to mitigate the problems associated with gas bubble stagnation: US 4,608,144 disclosed an anode surface equipped with vertical parallel channels alternatively directed to brine feed and withdrawal, and further equipped with horizontal channels of lower section reciprocally connecting the feed and withdrawal channels. In this way a forced brine circulation is achieved, somehow preventing the adhesion of chlorine bubbles. US 5,114,547 discloses an anode aimed at promoting brine circulation at the membrane-anode interface in order to obviate the increase in the electrical resistance associated with the depletion of stagnating brine at the interface by means of a structure consisting of vertical channels connected with slanted secondary channels disposed in a herringbone pattern. US 2006/0042935 addresses the same problem by providing an irregular anode surface obtained by sandblasting or acid etching in order to improve the brine supply to the anode. While all of the proposed measures might contribute to some extent to prevent deterioration of ion-exchange membranes in the usual process conditions, they fail to guarantee an optimal functioning in the exasperated process conditions needed to meet the current market requirements aimed at a higher cell productivity.

[0006] It would therefore be desirable to have an electrode for membrane electrolytic cells overcoming the limitations of the prior art, particularly as regards the possibility to operate a membrane electrolysis cell with higher performances in terms of parameters such as membrane lifetime, higher applicable current density, operative voltage, concentration of the caustic product obtained in the cell, degree of brine utilisation or maximum applicable pressure differential.

SUMMARY

[0007] The invention is set out in the accompanying claims.

[0008] One embodiment provides an electrode obtained on a metal substrate having a multiplicity of locally parallel grooves with a depth of 0.005 to 0.02 mm and a pitch - defined as the distance between adjacent grooves - of 0.01 to 0.5 mm.

[0009] By locally parallel grooves it is hereby intended a multiplicity of grooves, of open or closed shape, running in parallel at least in part of their length; the path of the

locally parallel grooves may assume a generally parallel trend across the whole electrode structure, in straight lines or with curvatures of any type. In one embodiment, the electrode surface presents locally parallel grooves having a closed shape and intersecting one another reciprocally.

[0010] The electrode as hereinbefore defined can be advantageous in any electrolytic application, especially for working in direct contact with an ion-exchange membrane; in the case of chlor-alkali electrolysis, the above electrode can be assembled with its grooved surface in direct contact with the membrane, with surprisingly advantageous results both used as the anode and/or as the cathode. The metal substrate may be made of different materials, including but not limited to titanium and titanium alloys for anode application and nickel, nickel alloys and stainless steels for cathode application. The substrate geometry can be of any type: as a non limiting example, the grooved surface can be provided on punched or expanded sheets, meshes and structures comprised of parallel strips optionally rotated along the horizontal axis, also called louvered electrodes.

[0011] The electrode substrate can be provided with a known catalytic coating on its grooved surface: for instance, when use as anode for chlorine evolution in chlor-alkali cells is intended, the electrode substrate may be provided with a coating based on noble metals or oxides thereof. Electrodes obtained on the substrate as hereinbefore defined can be particularly useful in chlor-alkali electrolysis cells, both as anodes for chlorine evolution and as cathodes for hydrogen evolution, especially when assembled with the grooved surface in direct contact with the membrane. In case of straight grooves running parallel across the whole structure, orienting the grooves in the vertical direction can provide an improved circulation of electrolyte and gas-bubble release from the surface. In the case of cells assembled according to the configuration known in the art as zero-gap, wherein both electrodes are in direct contact with the membrane, the inventors observed that manufacturing both the anode and the cathode on grooved substrates as defined made possible to operate at current densities largely exceeding 6 kA/m², up to 10 kA/m², with totally acceptable cell voltages. Life-tests were also carried out with excellent results at anolyte concentrations below 200 g/l (in particular down to 150 g/l), with caustic product concentrations above 33% (in particular up to 37%) and maintaining pressure differentials across the two compartments higher than 3000 Pa (in particular up to 10000 Pa), conditions which normally led to a quick deterioration of the membranes when prior art electrodes were employed.

[0012] Without wishing to be limited by any particular theory, it might be supposed that the electrode obtained on a grooved substrate as defined allows a particularly efficient release of the gas bubbles, also in comparison with grooved electrodes of the prior art, possibly because the densely packed and shallow grooves favour capillary transport phenomena as opposed to an electrolyte cir-

ulation.

[0013] The electrode as defined can be obtained by simple and cheap methods such as a superficial erosion carried out by means of abrasive paper or fabric - optionally in a continuous rolling process - lamellar grinding wheels or grindstones; other techniques include the use of draw-benches or rolling mills, besides more sophisticated technologies such as laser etching or lithographic techniques, according to the selected geometry. The erosion by grindstone for instance can be suitable for obtaining locally parallel grooves of closed shape and intersecting one another, while a lamellar grinding wheel, a draw-bench or a rolling mill can be more suitable for obtaining generally parallel grooves along the whole surface.

[0014] An electrode obtained with the above mentioned techniques can allow a sensible cost reduction compared to other grooved electrodes known in the art and characterised by a much higher groove depth, which cannot be obtained by simple abrasion.

EXAMPLE 1

[0015] Six 1 mm thick and 600 mm x 800 mm wide sheets of titanium grade 1 were degreased and subjected to an erosion treatment with a lamellar grinding wheel, obtaining grooves of 0.2 mm pitch on all samples at various depths; the sheets were expanded according to a known technique, obtaining a rhomboidal-mesh geometry of 10 mm x 5 mm diagonals and 1.6 mm displacement step. Upon completion of the expansion procedure, the grooves measured with a profilometer displayed average depths as reported in table 1:

TABLE 1

Sample ID	Groove depth (mm)
A1	0.003
A2	0.006
A3	0.01
A4	0.02
A5	0.05
A6	0.2

[0016] Similarly, three 1 mm thick and 600 mm x 800 mm wide sheets of nickel were degreased and subjected to the same erosion treatment and subsequent expansion, so as to obtain an identical geometry. Upon completion of the expansion procedure, the grooves measured with a profilometer displayed average depths as reported in table 2:

TABLE 2

Sample ID	Groove depth (mm)
C1	0.002
C2	0.01
C3	0.05

[0017] One sheet of titanium and one of nickel, having the same size as the previous samples, identified as A0 and C0 respectively, were subjected to the same expansion treatment as the above samples, after sandblasting with corundum and subsequent etching in HCl as known in the art; no additional abrasive treatment was effected on these samples.

[0018] All titanium samples were subsequently coated with a ruthenium and titanium oxide-based catalyst for anodic evolution of chlorine, with an overall catalyst loading of 12 g/m². A new check of the groove depth did not show any significant variation introduced by the coating step.

EXAMPLE 2

[0019] All samples prepared in the previous example were cut into 150 mm x 200 mm wide pieces and characterised, coupled in various combinations, in a multiple bench for chlor-alkali electrolysis accelerated lifetime tests. Each station of the multiple bench was equipped with one membrane electrolysis cell suitable for accommodating one anode and one cathode of 1 mm thickness in direct contact with a reference sulphonic/carboxylic double layer membrane (Nafion® 982 produced by DuPont, U.S.A.). The electrode samples of tables 1 and 2 were assembled with vertically oriented grooves. The lifetime test was carried out simultaneously starting-up all cells with the various combinations of anodes and cathodes at process conditions much more severe than the common industrial practice, determining the time of ion-exchange membrane decay, defined as the time required for the cell voltage to increase by 0.5 V with respect to the initial value at the process current density.

[0020] Process conditions were set as follows:

- brine concentration at the anodic compartment outlet: 150 g/l
- concentration by weight of product caustic soda: 37%
- pressure differential across the two compartments: 5000 Pa
- current density: 12 kA/m²

[0021] The results obtained are reported in table 3:

TABLE 3

Test number	Anode	Cathode	Duration (h)
1	A0	C0	514
2	A0	C0	562
3	A0	C2	580
4	A0	C3	565
5	A1	C0	729
6	A2	C0	904
7	A3	C0	1213
8	A4	C0	1417
9	A5	C0	866
10	A6	C0	578
11	A2	C1	940
12	A3	C1	1283
13	A4	C1	1646
14	A5	C1	1108
15	A1	C2	887
16	A2	C2	959
17	A3	C2	1682
18	A4	C2	1704
19	A5	C2	1011
20	A6	C2	622
21	A3	C3	1088
22	A4	C3	1544
23	A3	C1	1305
24	A4	C1	1593

EXAMPLE 3

[0022] An electrolysis cell as in example 2, equipped with an anode sample A4 and a cathode sample C2, and a second analogous electrolysis cell equipped with a non-grooved anode sample A0 and a non-grooved cathode sample C0 were subjected to a lifetime test at process conditions sensibly more severe than the common industrial practice.

[0023] Process conditions were set as follows:

- brine concentration at the anodic compartment outlet: 180 g/l
- concentration by weight of product caustic soda: 35%
- pressure differential across the two compartments: 4000 Pa
- current density: 10 kA/m²

[0024] After about 900 hours of testing, the cell equipped with electrode samples A0 and C0 had to be shut down because the progressive deterioration of the membrane had caused a strong increase in the cell voltage, which attained high values strongly fluctuating in time. The cell disassembly evidenced a general formation of blisters on the surface, with a higher population in correspondence of the brine exhaust outlet nozzle, where an incipient local delamination of the two layers of the membrane could also be observed.

[0025] The cell equipped with anode A4 and cathode C2 was dismantled after 2400 hours of continuous testing at practically constant voltage. Upon disassembling the cell, no particular phenomenon of membrane deterioration was observed.

[0026] The previous description shall not be intended as limiting the invention, which may be practised according to different embodiments without departing from the scopes thereof, and whose extent is solely defined by the appended claims.

[0027] Throughout the description and claims of the present application, the term "comprise" and variations thereof such as "comprising" and "comprises" are not intended to exclude the presence of other elements or additives.

[0028] The discussion of documents, acts, materials, devices, articles and the like is included in this specification solely for the purpose of providing a context for the present invention. It is not suggested or represented that any or all of these matters formed part of the prior art base or were common general knowledge in the field relevant to the present invention before the priority date of each claim of this application.

Claims

1. Electrolysis cell comprising an ion-exchange membrane and at least one electrode in direct contact with said ion-exchange membrane, said electrode comprising a metal substrate having at least one surface equipped with a multiplicity of locally parallel grooves, the depth of said grooves ranging from 0.001 to 0.1 mm and the distance between adjacent grooves ranging from 0.1 to 0.5 mm.
2. The electrolysis cell according to claim 1 wherein said depth of said grooves ranges from 0.005 to 0.02 mm.
3. The electrolysis cell according to claim 1 or 2 wherein said grooves are generally parallel along the whole surface or wherein said locally parallel grooves are intersecting one another.
4. The electrolysis cell according to any one of the preceding claims wherein the material of said electrode substrate is selected from the group consisting of

titanium and alloys thereof, nickel and alloys thereof, stainless steel.

5. The electrolysis cell according to any one of the preceding claims wherein said electrode substrate has a geometry selected from the group consisting of punched or expanded sheets, meshes and louvered structures.
6. The electrolysis cell according to any one of the preceding claims wherein said electrode further comprises a catalytic coating applied to said surface provided with grooves, said catalytic coating preferably comprises noble metals or oxides thereof.
7. The electrolysis cell according to any one of the preceding claims wherein said at least one electrode is assembled with said grooves generally parallel along the whole surface oriented in a mostly vertical direction.
8. Method for manufacturing an electrolysis cell according to any one of claims 1 to 7 comprising the step of forming said multiplicity of grooves on said metal substrate of said electrode by continuous erosion,
9. The method according to claim 8 wherein said erosion is carried out continuously by means of at least one device selected from the group of rollers of abrasive paper or fabric, grindstones and lamellar grinding wheels or wherein said erosion is carried out by means of a draw-bench or a rolling mill.
10. Process of electrolysis of an alkali chloride brine carried out by applying direct electric current in a membrane electrolysis cell according to any one of claims 1 to 7 comprising the step of evolving a gaseous product on the surface of said at least one electrode.
11. The process according to claim 10, wherein said gaseous product is anodically-evolved chlorine or cathodically-evolved hydrogen.
12. The process according to any one of claims 10 to 11 wherein the density of said direct electric current is at least 5 kA/m².
13. The process according to any one of claims 10 to 12 wherein the pressure differential across the membrane of the electrolysis cell is at least 3000 Pa.
14. The process according to any one of claims 10 to 13 wherein the concentration of said brine at the anodic compartment outlet is at most 200 g/l.
15. The process according to any one of claims 10 to 14 wherein a caustic solution at a weight concentration

of at least 33% is produced at the cathodic compartment.

Patentansprüche

1. Elektrolysezelle, umfassend eine Ionenaustauschermembrane und wenigstens eine Elektrode, die in direktem Kontakt mit der Ionenaustauschermembrane steht, wobei die Elektrode ein Metallsubstrat, das wenigstens eine Oberfläche mit einer Vielzahl lokal paralleler Rillen aufweist, umfasst, wobei die Rillen eine Tiefe im Bereich von 0,001 bis 0,1 mm aufweisen und der Abstand benachbarter Rillen im Bereich von 0,1 bis 0,5 mm liegt.
2. Elektrolysezelle nach Anspruch 1, **dadurch gekennzeichnet, dass** die Rillen eine Tiefe im Bereich von 0,005 bis 0,02 mm aufweisen.
3. Elektrolysezelle nach einem der Ansprüche 1 oder 2, **dadurch gekennzeichnet, dass** die Rillen im Wesentlichen parallel über die gesamte Oberfläche angeordnet sind, oder dass die lokal parallelen Rillen sich gegenseitig schneiden.
4. Elektrolysezelle nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, dass** das Material des Elektrodensubstrats ausgewählt ist unter Titan und Legierungen daraus, Nickel und Legierungen daraus, rostfreiem Stahl.
5. Elektrolysezelle nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, dass** das Elektrodensubstrat eine Geometrie, die unter gelochten oder gestreckten Blechen, Geweben und lamellenartigen Strukturen ausgewählt ist, aufweist.
6. Elektrolysezelle nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, dass** die Elektrode zusätzlich eine auf die mit Rillen ausgestattete Oberfläche aufgebrachte, katalytische Beschichtung aufweist, und dass die katalytische Beschichtung vorzugsweise Edelmetalle oder deren Oxide umfasst.
7. Elektrolysezelle nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, dass** die wenigstens eine Elektrode mit den im Wesentlichen über die gesamte Oberfläche parallelen, in einer hauptsächlich vertikalen Richtung ausgerichteten Rillen ausgestattet ist.
8. Verfahren zur Herstellung einer Elektrolysezelle nach einem der Ansprüche 1 bis 7, umfassend einen Schritt, in dem die Vielzahl der Rillen auf dem Metallsubstrat der Elektrode durch kontinuierliche Erosion ausgebildet wird.

5

10

15

20

25

30

35

40

45

50

55

9. Verfahren nach Anspruch 8, **dadurch gekennzeichnet, dass** die Erosion kontinuierlich mittels wenigstens einer Einrichtung, die unter Walzen aus abrasivem Papier oder Fasern, Schleifsteinen und lamellenförmigen Schleifscheiben ausgewählt ist, durchgeführt wird, oder dass die Erosion mittels einer Ziehbank oder eines Walzwerkes durchgeführt wird.

10. Verfahren zur Elektrolyse einer Alkalichlorid-Lauge, ausgeführt durch das Anlegen eines direkten elektrischen Stromes in einer Membranelektrolysezelle nach einem der Ansprüche 1 bis 7, umfassend einen Schritt, in dem sich ein gasförmiges Produkt an der Oberfläche der wenigstens einen Elektrode entwickelt.

11. Verfahren nach Anspruch 10, **dadurch gekennzeichnet, dass** es sich bei dem gasförmigen Produkt um an der Anode gebildetes Chlor oder um an der Kathode gebildeten Wasserstoff handelt.

12. Verfahren nach einem der Ansprüche 10 oder 11, **dadurch gekennzeichnet, dass** die Dichte des direkten elektrischen Stromes mindestens 5 kA/m² beträgt.

13. Verfahren nach einem der Ansprüche 10 bis 12, **dadurch gekennzeichnet, dass** die Druckdifferenz an der Membrane der Elektrolysezelle mindestens 3000 Pa beträgt.

14. Verfahren nach einem der Ansprüche 10 bis 13, **dadurch gekennzeichnet, dass** die Konzentration der Lauge am Auslass des Anodenraums höchstens 200 g/l beträgt.

15. Verfahren nach einem der Ansprüche 10 bis 14, **dadurch gekennzeichnet, dass** eine Laugenlösung mit einer Gewichtskonzentration von wenigstens 33 % im Kathodenraum gebildet wird.

Revendications

1. Cellule d'électrolyse comprenant une membrane échangeuse d'ions et au moins une électrode en contact direct avec ladite membrane échangeuse d'ions, ladite électrode comprenant un substrat métallique qui présente au moins une surface munie de plusieurs rainures localement parallèles, la profondeur desdites rainures étant comprise entre 0,001 et 0,1 mm et la distance entre les rainures adjacentes étant comprise entre 0,1 et 0,5 mm.
2. Cellule d'électrolyse selon la revendication 1, dans laquelle ladite profondeur desdites rainures est comprise entre 0,005 et 0,02 mm.

3. Cellule d'électrolyse selon la revendication 1 ou 2, dans laquelle lesdites rainures sont généralement parallèles le long de toute la surface ou dans laquelle lesdites rainures localement parallèles se coupent entre elles.
4. Cellule d'électrolyse selon l'une quelconque des revendications précédentes, dans laquelle le matériau dudit substrat d'électrode est sélectionné dans le groupe composé du titane et d'alliages de celui-ci, du nickel et d'alliages de celui-ci, et de l'acier inoxydable.
5. Cellule d'électrolyse selon l'une quelconque des revendications précédentes, dans laquelle ledit substrat d'électrode a une géométrie sélectionnée dans le groupe composé de feuilles perforées ou expansées, de grilles et de structures à fentes.
6. Cellule d'électrolyse selon l'une quelconque des revendications précédentes, dans laquelle ladite électrode comprend en outre un revêtement catalytique déposé sur ladite surface munie de rainures, ledit revêtement catalytique comprenant de préférence des métaux nobles ou des oxydes de ceux-ci.
7. Cellule d'électrolyse selon l'une quelconque des revendications précédentes, dans laquelle ladite électrode, au moins au nombre de une, est assemblée avec lesdites rainures, généralement parallèles le long de toute la surface, orientées dans une direction essentiellement verticale.
8. Procédé de fabrication d'une cellule d'électrolyse selon l'une quelconque des revendications 1 à 7, comprenant l'étape consistant à former ladite multiplicité de rainures sur ledit substrat métallique de ladite électrode par érosion continue.
9. Procédé selon la revendication 8, dans lequel ladite érosion est réalisée en continu au moyen d'au moins un dispositif sélectionné dans le groupe de rouleaux de papier ou de tissu abrasif, de meules et de meules à lamelles, ou dans lequel ladite érosion est réalisée au moyen d'un banc d'étirage ou d'un laminoir.
10. Procédé d'électrolyse d'une saumure de chlorure alcalin, réalisé en appliquant un courant électrique continu dans une cellule d'électrolyse à membrane selon l'une quelconque des revendications 1 à 7, comprenant l'étape de dégagement d'un produit gazeux sur la surface de ladite électrode, au moins au nombre de une.
11. Procédé selon la revendication 10, dans lequel ledit produit gazeux est du chlore dégagé au niveau de l'anode ou de l'hydrogène dégagé au niveau de la cathode.
12. Procédé selon l'une des revendications 10 ou 11, dans lequel la densité dudit courant électrique continu est au moins égale à 5 kA/m².
13. Procédé selon l'une quelconque des revendications 10 à 12, dans lequel le différentiel de pression à travers la membrane de la cellule d'électrolyse est au moins égal à 3 000 Pa.
14. Procédé selon l'une quelconque des revendications 10 à 13, dans lequel la concentration de ladite saumure au niveau de la sortie du compartiment anodique est au plus égale à 200 g/l.
15. Procédé selon l'une quelconque des revendications 10 à 14, dans lequel une solution caustique à une concentration en poids au moins égale à 33 % est produite au niveau du compartiment cathodique.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4608144 A [0005]
- US 5114547 A [0005]
- US 20060042935 A [0005]