



(11) **EP 2 148 128 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:
F21S 2/00 (2006.01) **F21V 8/00** (2006.01)
G02B 3/06 (2006.01) **G02B 5/02** (2006.01)
G02B 5/04 (2006.01) **G02F 1/13357** (2006.01)

(48) Corrigendum issued on:
31.03.2010 Bulletin 2010/13

(86) International application number:
PCT/JP2008/051522

(43) Date of publication:
27.01.2010 Bulletin 2010/04

(87) International publication number:
WO 2008/142877 (27.11.2008 Gazette 2008/48)

(21) Application number: **08704269.3**

(22) Date of filing: **31.01.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR

(72) Inventors:
• **KUROMIZU, Yasumori**
Osaka 545-8522 (JP)
• **MOURI, Hirokazu**
Osaka 545-8522 (JP)

(30) Priority: **22.05.2007 JP 2007135049**

(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(74) Representative: **Müller - Hoffmann & Partner**
Patentanwälte
Innere Wiener Strasse 17
81667 München (DE)

(54) **OPTICAL MEMBER, ILLUMINATING DEVICE USING THE SAME, DISPLAY DEVICE, AND TELEVISION RECEIVING DEVICE**

(57) An optical member comprises a diffusion layer (13) diffusing emitted light from light sources (12), a first light collection layer (15), in which first projecting portions (15a) extending in a Y-direction are arranged at intervals (T1), refracting and collecting incident light from the diffusion layer (13), a first reflection layer (14) having first reflective portions (14a) facing boundaries between the adjacent first projecting portions (15a) and reflecting emitted light from the diffusion layer (13), a second light collection layer (17), in which second projecting portions (17a) extending in an X-direction are arranged at intervals (T2), refracting and collecting incident light from the first light collection layer (15), and a second reflection layer (16) having second reflective portions (16a) facing boundaries between the adjacent second projecting portions (17a) and reflecting emitted light from the first light collection layer (15).

FIG.2

