



(11) **EP 2 180 019 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 84**

(51) Int Cl.:  
**C08L 83/02 (2006.01)**

(48) Corrigendum issued on:  
**07.07.2010 Bulletin 2010/27**

(43) Date of publication:  
**28.04.2010 Bulletin 2010/17**

(21) Application number: **09177928.0**

(22) Date of filing: **05.08.2005**

(84) Designated Contracting States:  
**AT DE FR IT**

(30) Priority: **06.08.2004 JP 2004231254**  
**17.03.2005 JP 2005077734**

(62) Document number(s) of the earlier application(s) in  
accordance with Art. 76 EPC:  
**05291679.8 / 1 626 065**

(71) Applicant: **Nippon Shokubai Co., Ltd.**  
**Osaka-shi, Osaka 541-0043 (JP)**

(72) Inventors:  
• **Sugioka, Takuo**  
**Hyogo 662-0011 (JP)**

• **Tsujino, Yasunori**  
**Osaka 567-0085 (JP)**

(74) Representative: **Hart-Davis, Jason et al**  
**Cabinet Beau de Loménie**  
**158, rue de l'Université**  
**75340 Paris Cedex 07 (FR)**

Remarks:

This application was filed on 03-12-2009 as a  
divisional application to the application mentioned  
under INID code 62.

(54) **Resin composition, method of its composition, and cured formulation**

(57) It is an object of the present invention to provide a resin composition which can form cured formulations having various excellent properties such as an insulating property, thermal shock resistance, moldability/formability and strength, and exhibit an excellent appearance in which transparency is enhanced, a resin composition whose cured thin film has excellent flame retardancy, good mechanical property and heat resistance, a dispersing element containing an inorganic microfine particle which can give a flame retardancy to a resin, to which the inorganic microfine particle is added, and can reduce a hygroscopic property to the extent possible, a method for producing the same and a cured formulation obtained by using the resin composition. The present invention

relates to a resin composition comprising a compound having at least one of a glycidyl group and/or an epoxy group and an inorganic microfine particle, a resin composition comprising three components of a phenolic compound, a compound having at least one of a glycidyl group and/or an epoxy group and an inorganic microfine particle, a flame retardant resin composition comprising a polyhydric phenol and an inorganic microfine particle, and a dispersing element containing an inorganic microfine particle obtained by a hydrolysis condensation reaction of alkoxide and/or metal carboxylate in a dispersion medium.

**EP 2 180 019 A8**