

(19)



(11)

EP 2 194 261 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
09.06.2010 Bulletin 2010/23

(51) Int Cl.:
F02M 53/02^(2006.01) F02M 63/00^(2006.01)

(21) Application number: **09174659.4**

(22) Date of filing: **30.10.2009**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

- **Montanari, Gino**
32040-000 Minas Gerais (BR)
- **Aleo, Ricardo**
32040-000 Minas Gerais (BR)
- **Gavioli, Vagner**
32040-000 Minas Gerais (BR)
- **Omori, Akio**
32040-000 Minas Gerais (BR)
- **Barbosa, Alexandre**
32040-000 Minas Gerais (BR)
- **Marques, Rinaldo**
32040-000 Minas Gerais (BR)

(30) Priority: **02.12.2008 BR 08054843**

(71) Applicant: **Magneti Marelli Sistemas Automotivos Indústria e Comércio Ltda.**
Avenida de Emancipação, N° 801 Galpao 4 Jardim Santa Rita de Cassia 13184-654 Hortolandia /SP (BR)

(74) Representative: **Bérogin, Francis et al Cabinet Plasseraud**
52 rue de la Victoire 75440 Paris Cedex 09 (FR)

(72) Inventors:
• **Pontoppidan, Michael**
92700 Colombes (FR)

(54) **Fuel rail equipped with an axial heater device layout for engine cold start operation with ethanol**

(57) The present invention relates to a primary fuel rail (10) of the return-less type equipped with a particular axial heater device layout to increase the heat flux homogeneity in the fuel rail for an Ethanol Cold Start (ECS) system. The fuel rail (10) has one or more heating elements (12a, 12b) inserted therein in such a way that the heating part (100) of each element is oriented along or

parallel to the main symmetry axis of the principal cavity of the said fuel rail (10) and each heating element is composed of two parts, an inactive support part (101) and an active heating part (100) having lengths (L_a, X), which can be individually tuned to obtain a maximum homogeneity of the heat flux along the rail towards the fuel injectors (11a-11d).




FIG. 3a

EP 2 194 261 A1

Description

[0001] The present invention relates to a fuel rail equipped with a particular axial heater device layout to increase the heat flux homogeneity in a primary return-less fuel rail for an Ethanol Cold Start (ECS) system.

Prior art

[0002] It is a well-known fact that when using fuels different from classic gasoline in an Internal Combustion (IC) engine several functions of the engine may be affected. In a modern IC-engine (figure 1), comprising a combustion chamber (1) with a spark ignition device (2), an exhaust (3) and inlet (4) manifold with a gas flow regulating (5) throttle body and an electronically controlled (6) mixture preparation system with Port Fuel Injectors (PFI) (7), a classic gasoline fuel with a typical chemical structure of C_8H_{18} enables a cold start performance, which allows the engine to start and warm-up at temperatures down to approximately $30^{\circ}C$ below zero without use of auxiliary add-on devices. Figure 1 shows a layout of a speed/density (Manifold Absolute Pressure (MAP) and engine speed sensor input), but this layout is not mandatory. The layout can use any kind of strategy as long as it supplies the necessary data to enable the Engine Control Unit (ECU) to compute the relevant data for injector and ignition control.

[0003] In the case of a different low vaporizing fuel for example ethanol (C_2H_5OH) or a mixture between gasoline or ethanol (example: gasohol or E85) the cold start performance is strongly affected by the vaporization and surface tension parameters of the ethanol component, which are notably different from those of a pure gasoline. Fuelling the engine by pure ethanol creates the most difficult situation. In that case the cold start and warm up becomes very delicate below ambient temperatures of about 10° to $12^{\circ}C$.

[0004] The main reason for which not only the cold start but also the warm-up phase is of major interest is that for pollutants control (mainly the HC-content in the exhaust gas) in the time period during which the oxygen-sensor is not functioning (open-loop control strategy) a very precise injector control enables a decrease in unburned HC emission.

[0005] In recent years the presence of the ethanol cold start problem has led to several suggestions of add-on devices, which introduce either a separate high-vaporizing fuel (gasoline) or one or more heating devices, which are not positioned according to the present invention in the normal fuel rail on the upstream side of the fuel injectors. Both approaches have major inconveniences.

[0006] Although functioning well for the cold start itself, the first approach is costly as a separate tank and fuel line for the high-vaporizing fuel must be installed on the vehicle and as the volume of this secondary system is limited (normally under-bonnet location) its capacity to be used during the warm-up period is very limited. The

second type of approach can be used for the cold start, but an approach of this type, which does not follow the particular layout defined by the invention becomes totally unreliable for the warm-up period as the random introduction of a powerful heat source in the fuel-rail on the injector upstream side eventually leads to heat-conditioned cavitations in the liquid fuel.

[0007] Basically a fuel injector is designed to introduce a metered amount of liquid (non compressible) fuel in the intake system. Unfortunately heat-conditioned cavitations introduce gas bubbles into the liquid fuel and thereby change the state of the fluid from non-compressible to compressible. The basic fluid dynamics of compressible fluids is totally different from those of non-compressible fluids and therefore the metering function of the fuel injector designed for liquid fuel is not anymore controllable when a compressible fluid is passing through the metering area inside the injector.

[0008] The applicant has patented a solution, which enables, by a simple mechanical means without complicated electronic feed-back temperature control, to provide an asymptotic temperature stabilization of the fuel inside the fuel rail during the cold start phase (Brazilian Patent Application nr. PI 0705422-0).

Summary of the invention

[0009] The invention adds to the internal volume of a common fuel rail one or more electrically controlled heating elements. The heating elements are located in such a way that their active heating part is oriented along or parallel to the main axis of the fuel rail.

[0010] The distribution of the active heating surface along the rail cavity symmetry axis is favored by this particular axial layout, which increases significantly the homogeneity of the net heat flux in the lateral direction of the cavity and thereby decreases the hot fuel temperature difference between the fuel injectors connected to the rail.

[0011] The present invention presents several different installation layouts of the axial heaters within the perimeter of the fuel rail.

Brief description of the drawings

[0012] The objective of the present invention will be better understood by confronting the joined figures, which are presented as mere examples, which should in no way limit the scope of the invention.

- Figure 1 shows a conventional internal combustion engine with its associated injection system.
- Figure 2 shows the fuel rail with attached fuel injectors and the axial heaters located at each extremity of the rail.
- Figures 3a and 3b show the internal part of the fuel rail with the axial heaters located as well as the detailed layout of each heating element.

- Figures 4a, 4b, 4c, 4d and 4e show axial cuts of several different installation layouts in different fuel rail designs.
- Figure 5 shows a graphical representation of the stabilization versus time of the fuel temperature at each fuel injector (example 4 cylinder engine) by application of the present invention.

Preferred Embodiments

[0013] In conformity with the joined figures, and in particular with reference to figure 2 and figure 3a, the invention adds to the internal volume of a fuel rail one or more electronically controlled heating elements.

[0014] Figure 2 illustrates the principle of the invention. The common fuel rail (10) supplies pressurized fuel to a number of fuel injectors (11a to 11d) and as an example two heating elements (12a and 12b) are located on each side of the fuel rail. Each heating element is a fast acting device with a typical temperature rise- time of $\sim 70^{\circ}\text{C/s}$ (measured in still air at 1 mm from the heater surface). The total number of heating devices will typically absorb approximately 800 W at 10 V supply. The maximum heater temperature should typically be attained after approximately 6 s. The above-indicated numerical values are not limitative.

[0015] Figure 3a shows an example of the internal layout of the system. The active heating parts of the elements (12a and 12b) are located in a position, which is axial or co-axial with respect to the main axis (14) of the fuel rail. The example shows a layout with only one fuel entrance pipe (13), which connects the fuel rail to the fuel delivery pump.

[0016] Figure 3b shows details of the heating elements. An element is composed of a unit, which is axially located in the rail. This unit is divided in two parts, the active heating part (100) of the length L_a (typically between 35 and 70 mm) and an inactive support (101) of a length X (typically between 0 and 35 mm). The axial part is connected to a connector body (102) and an electrical connector (103). To comply with a large number of mounting requirements the connector body (102) and the connector (103) can be positioned at an angle α (between 0 and 90°) with respect to the axial parts (100 and 101). The axial parts (100 and 101) of a heating element can be connected to a mechanical tubular heat dissipater, as suggested by the Brazilian Patent Application nr. PI 0705422-0.

[0017] Figures 4a, 4b, 4c, 4d and 4e show further variants of the installation layout for an axial heating element.

[0018] Figure 4a shows a variant with two fuel inlet pipes (201 and 202), which supply the cold fuel at symmetrical positions in the vicinity of the axial heating elements (12a, 12b). The precise position of the inlet pipes as well as the lengths X and L_a are tuned to provide the maximum equilibrium of heat flux towards the fuel injectors (11a-11d).

[0019] Figure 4b shows a variant by which the effect

of heat flux homogeneity is obtained with only one cold fuel inlet pipe (203), which is connected to a transfer bore (204), located inside the fuel rail (10) with outlets in the vicinity of the heating elements (12a, 12b).

[0020] Figure 4c shows a layout, which adds a separate compartment (300), which enables the introduction of a third co-axial heating element (301) to provide a supplementary heat flux directed towards the center located fuel injectors (11b, 11c). The electrical power output of the three heating elements (12a, 12b, 301) is typically adapted to a total consumption of approximately 800 W at 10 V, but this value is not limitative. Fuel is supplied into the separate compartment (300) through the transfer bores (302) and the heated fuel is supplied to the center fuel injectors (11b, 11c) through the outlet bores (303). To avoid pumping effects, and thereby non homogeneous heat flux distribution, by the intermittent injector duty cycle order the diameter of the transfer bores (302) is typically limited to 50% of that of the outlet bores (303).

[0021] Figure 4d shows a layout in which the rail cavity, by any appropriate mechanical means (400), is divided into two separate left (401) and right (402) hand cavities. Each cavity, equipped with an individual inlet pipe (403) and (404), supplies hot fuel to respectively the left (11a, 11b) and right (11c, 11d) hand injectors. Heat flux distribution oscillations due to the intermittent injector duty cycle order are hereby significantly reduced.

[0022] Figure 4e shows a layout in which is combined only one cold fuel inlet pipe (503), communicating with an internal transfer bore (504), and a rail cavity separated by any appropriate mechanical means (500) in two left (501) and right (502) hand cavities. Each cavity supplies hot fuel to respectively the left (11a, 11b) and right (11c, 11d) hand injectors.

[0023] For convenience the figures 3 to 4e show the different constituent elements such as fuel inlet pipes (13, 201 and 202, 203) and the location of the separate heating compartment (300) in the same plane as the cut of the main fuel rail. However, this is not mandatory as long as the active heating elements all maintain an axial location parallel to or on the fuel rail main axis (14).

[0024] To optimally comply with under-bonnet packaging requirements both the inlet pipes and the separate third heating element compartment can be axially turned clock- or anticlockwise around the fuel rail main axis (14).

Example

[0025] Figure 5 shows a recording of the average temperature evolution of the liquid in the tubes connecting the fuel-rail to the fuel injectors at a cold start event at an ambient temperature of -5°C .

[0026] The recording demonstrates that when all dimensional and orientation parameters are correctly adapted according to the invention the common temperature profile at the fuel injector inlets remains well below the flash-boiling threshold.

[0027] The tests made with the present invention dem-

onstrate clearly that the suggested layout is a very efficient and low cost means to obtain a well controlled heating of the fuel on the upstream side of the fuel injectors without imposing major geometrical changes of existing fuel supply lines or the introduction of a secondary expensive fuel reservoir. 5

and left hand parts each supplying an equal number of fuel injectors with heated fuel.

Claims

1. A fuel rail, which is mounted on an IC-engine with the purpose of improvement of the cold start and warm up phases by usage of low vaporizing fuels such as ethanol, in which is inserted one or more heating elements (12a, 12b) in such a way that the heating part (100) of each element is oriented along or parallel to the main symmetry axis of the principal cavity of the said fuel rail (10) and each heating element is composed of two parts, an inactive support part (101) and an active heating part (100) having lengths (L_a, X), which can be individually tuned to obtain a maximum homogeneity of the heat flux along the rail towards the fuel injectors (11a-11d). 10
2. The fuel rail as in claim 1, in which the electrical body and connector of each heating element can be oriented in-line with the part oriented along or parallel to the rail main symmetry axis or tilted at an arbitrary angle between 1 ° and 90° with respect to the axially oriented part. 15 20 25 30
3. The fuel rail as in claim 1 or 2, in which one or more cold fuel inlet pipe(s) (201, 202, 203, 403, 404, 503) is/are positioned and connected to the rail main cavity in such a way that the cold fuel arrives symmetrically with respect to the heating elements (12a, 12b). 35
4. The fuel rail as in any of claims 1 to 3, in which a center-positioned axial heating element (301) is inserted in a separated cavity being co-axial with the fuel rail main axis to supply with heated fuel the center-connected fuel injectors (11b, 11c). 40
5. The fuel rail as in claim 4, in which the center-positioned cavity communicates with the right and left hand cavities through two inlet bores (302) and with the center-positioned fuel injectors (11b, 11c) through a number of outlet bores (303) equal to the number of center-positioned injectors, and for which the diameter ratio between inlet and outlet bores (302, 303) is equal or less than 0.5. 45 50
6. The fuel rail as in any of claims 1 to 3, in which the fuel rail main cavity having the active heating elements (12a, 12b) axially inserted at each extremity is separated in two non-communicating cavities (401, 402; 501, 502) dividing the main cavity in right 55




FIG. 1




FIG. 2




FIG. 3a




FIG. 3b




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 4e




FIG. 5



EUROPEAN SEARCH REPORT

Application Number
EP 09 17 4659

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	JP 08 338339 A (ISUZU MOTORS LTD) 24 December 1996 (1996-12-24) * abstract; figures 2,3 *	1-3	INV. F02M53/02
X	DE 103 41 708 A1 (MAN B & W DIESEL AG [DE]) 28 April 2005 (2005-04-28) * page 2, paragraphs 0007,0008; figure 1 *	1	ADD. F02M63/00
A	WO 2007/030906 A2 (FIAT AUTOMOVEIS S A MECANICA [BR]; SALES LUIS CARLOS MONTEIRO [BR]) 22 March 2007 (2007-03-22) * page 5, line 31 - page 6, line 9; figure 2 *	1	
A	WO 2006/130938 A1 (BOSCH DO BRASIL [BR]; LEPSCH FERNANDO [BR]; MARRON FERNANDO AUGUSTO [B]) 14 December 2006 (2006-12-14) * page 12, line 28 - page 13, line 8; figure 7 *	1	
A,P	EP 2 071 159 A1 (MAGNETI MARELLI SIST S AUTOMOT [BR]) 17 June 2009 (2009-06-17) * figure 3 *	1	TECHNICAL FIELDS SEARCHED (IPC) F02M
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 18 March 2010	Examiner Etschmann, Georg
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

3
EPO FORM 1503 03.02 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 09 17 4659

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2010

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 8338339	A	24-12-1996	NONE

DE 10341708	A1	28-04-2005	CH 697139 A5 15-05-2008
			CN 1594859 A 16-03-2005
			FI 20041138 A 11-03-2005
			KR 20050026855 A 16-03-2005

WO 2007030906	A2	22-03-2007	AR 055633 A1 29-08-2007
			BR PI0504047 A 22-05-2007
			CN 101375049 A 25-02-2009
			EP 1934467 A2 25-06-2008
			JP 2009508046 T 26-02-2009
			US 2009241915 A1 01-10-2009

WO 2006130938	A1	14-12-2006	AR 053515 A1 09-05-2007
			EP 1888910 A1 20-02-2008
			JP 2008542622 T 27-11-2008
			US 2009133676 A1 28-05-2009

EP 2071159	A1	17-06-2009	NONE

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- BR PI07054220 [0008] [0016]