



(12)

CORRECTED EUROPEAN PATENT APPLICATION

(15) Correction information:

Corrected version no 1 (W1 A3)
 Corrections, see Abstract

(51) Int Cl.:

G06F 3/12 (2006.01)

(48) Corrigendum issued on:

02.12.2015 Bulletin 2015/49

(88) Date of publication A3:

09.01.2013 Bulletin 2013/02

(43) Date of publication A2:

07.07.2010 Bulletin 2010/27

(21) Application number:

10150135.1

(22) Date of filing:

05.01.2010

(84) Designated Contracting States: AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR	(72) Inventor: Kimura, Mitsuo Ohta-ku Tokyo (JP)
(30) Priority: 06.01.2009 JP 2009001108	(74) Representative: Garner, Jonathan Charles Stapleton Canon Europe Ltd European Patent Department 3 The Square Stockley Park Uxbridge, Middlesex UB11 1ET (GB)
(71) Applicant: CANON KABUSHIKI KAISHA Ohta-ku Tokyo 146-8501 (JP)	

(54) Print system, print server, control method thereof, and program

(57) A client terminal (105) transmits a request to a printing apparatus (106) for a registration web page for registering, in a print server (104), a printing apparatus used in a print service provided by the print server. The printing apparatus (106) collects configuration information of the printing apparatus (106) in response to reception of the request, and creates link information which contains the collected configuration information and is used to access the print server (104). The printing apparatus (106) then generates a registration web page containing the created link information, and transmits it to the client terminal (105). The print server (104) receives the configuration information of the printing apparatus (106) transmitted from the client terminal (105) via the registration web page transmitted to the client terminal. The print server (104) creates printing apparatus information which associates the configuration information with user information of the user of the client terminal, and manages it in a storage medium.

FIG. 5

