



(11) **EP 2 213 909 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A2)
Corrections, see
Bibliography INID code(s) 71

(51) Int Cl.:
F16H 61/00 (2006.01)

(48) Corrigendum issued on:
27.10.2010 Bulletin 2010/43

(43) Date of publication:
04.08.2010 Bulletin 2010/31

(21) Application number: **10151374.5**

(22) Date of filing: **22.01.2010**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK SM TR
Designated Extension States:
AL BA RS

(30) Priority: **29.01.2009 JP 2009018783**

(71) Applicants:
• **Hitachi Automotive Systems, Ltd.**
Hitachinaka-shi
Ibaraki 312-8503 (JP)
• **NIDEC TOSOK CORPORATION**
Kanagawa 228-8570 (JP)

(72) Inventors:
• **Shigyo, Toshikazu**
Ibaraki 312-8503 (JP)
• **Odakura, Yasunori**
Ibaraki 312-8503 (JP)

- **Tanabe, Itaru**
Ibaraki 312-8503 (JP)
- **Masuda, Mitsuhiro**
Ibaraki 312-8503 (JP)
- **Kanno, Kiyotaka**
Ibaraki 312-8503 (JP)
- **Yamada, Masaaki**
Kanagawa 228-8570 (JP)
- **Sumiyoshi, Motohiro**
Kanagawa 228-8570 (JP)
- **Takahashi, Kenro**
Kanagawa 228-8570 (JP)
- **Sakagami, Hitoshi**
Kanagawa 228-8570 (JP)

(74) Representative: **MERH-IP**
Matias Erny Reichl Hoffmann
Paul-Heyse-Strasse 29
80336 München (DE)

(54) **Hydraulic control module**

(57) Disclosed is a hydraulic control module that can be downsized. The hydraulic control module includes an upper control valve (3), a lower control valve (4), and a wiring plate (1). The upper and lower control valves (3, 4) each include an oil path having a groove portion. A sandwich structure is employed so that the wiring plate (1) is sandwiched between the upper and lower control

valves (3, 4). The wiring plate (1) has a groove portion or a through-hole (12A1, 12A3) that is in communication with the at least one of the groove portion of the upper control valve (3) and the groove portion of the lower control valve (4).

EP 2 213 909 A8

FIG. 1

