



(11) **EP 2 221 408 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 84**

(51) Int Cl.:  
**D04C 3/48 (2006.01)** *D04C 1/00 (2006.01)*

(48) Corrigendum issued on:  
**09.03.2011 Bulletin 2011/10**

(43) Date of publication:  
**25.08.2010 Bulletin 2010/34**

(21) Application number: **09169279.8**

(22) Date of filing: **02.09.2009**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR**  
**HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL**  
**PT RO SE SI SK SM TR**  
Designated Extension States:  
**AL BA RS**

• **Kabushiki Kaisha Toyota Jidoshokki**  
**Kariya-shi,**  
**Aichi 448-8671 (JP)**

(30) Priority: **03.09.2008 JP 2008226197**

(71) Applicants:  
• **Toyota Jidosha Kabushiki Kaisha**  
**Toyota-shi, Aichi-ken, 471-8571 (JP)**

(72) Inventors:  
• **Inazawa, Koichi**  
**Aichi-ken 471-8571 (JP)**  
• **Hori, Fujio**  
**Aichi-ken 448-8671 (JP)**

(74) Representative: **Albutt, Anthony John**  
**D Young & Co LLP**  
**120 Holborn**  
**London EC1N 2DY (GB)**

(54) **Yarn layer forming apparatus, yarn layer forming method, and method of manufacturing fiber-reinforced member**

(57) A yarn layer forming apparatus (100) includes: an annular braider (30) that supplies braider yarn (S3); annular first supply means (10) that supplies first yarn (S1); annular second supply means (20) that supplies second yarn (S2); and actuating means (40) that moves a mandrel (M). At least one of the first supply means and

the second supply means is rotatable. A layer structure of yarn layers is formed on a peripheral surface of the mandrel (M). The layer structure of yarn layers includes at least yarn arrangement layers formed respectively by the first and second supply means and a woven layer formed by the braider.

**FIG. 1A**

