

(19)



(11)

EP 2 236 593 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

06.10.2010 Bulletin 2010/40

(51) Int Cl.:

C11D 3/08 (2006.01)

C11D 3/10 (2006.01)

(21) Application number: **09275020.7**

(22) Date of filing: **31.03.2009**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK TR**

Designated Extension States:

AL BA RS

(71) Applicant: **Reed, William**

Nokomis, FL 34275 (US)

(72) Inventor: **Reed, William**

Nokomis, FL 34275 (US)

(74) Representative: **Tollett, Ian et al**

Williams Powell

Staple Court

11 Staple Inn Buildings

London, WC1V 7QH (GB)

(54) **Method of Cleaning a Surface**

(57) The application of a gel-like material is disclosed for cleaning a surface having foreign matter thereon, such gel-like material produced by magnetically treating and mixing two solutions, the first solution being comprised of water and sodium bicarbonate and the second solution comprised of water and sodium silicate. The first

solution is passed through a positively charged magnetic field, and the second solution is passed through a negatively charged magnetic field. The two solutions are then mixed together to form a gel.

EP 2 236 593 A1

Description

[0001] The present invention resides in the field of cleaning agents and more particularly relates to the application of a gel used as a degreasing and dirt removal agent.

[0002] U.S. Patent 5,415,900 to Reed discloses a method of delivering a substance into a material mass. This disclosure is specifically directed to the rearrangement of fluid molecules from an agglomerated state to a more linear and organized state. As a result of this linear molecular organization produced by a magnetic influence, the fluid's permeability into a material mass is greatly enhanced, and penetration of the fluid through the surface and periphery of the material mass occurs much more readily than if the fluid's molecular organization had remained in an agglomerated state. The magnetic influence utilized in this disclosure not only makes the fluid more permeable by effecting a linear organization of its molecules, which is a critical feature of the disclosure, but also serves to facilitate the assimilation of such fluids throughout the interior of the material mass. This is accomplished by polarizing two fluids to opposite charges with magnetic fields of different polarities. As a result, the naturally attractive forces between the oppositely charged fluids increases the rate of absorption of the second fluid to be introduced into the material mass and ensures that the absorption of this second fluid is directed throughout the interior of the material mass.

[0003] An additional advantage of the fluid polarization effected by a magnetic influence is that the positive polarity of the fluid molecules will be increased, thereby increasing the spaces between the individual fluid molecules through greater repulsion. As a result of this increased polarity, the fluid molecules are separated to a greater extent so that the molecules are able to penetrate individually rather than collectively into a given material mass, thereby significantly enhancing the permeability of the fluid. In addition, because fluid molecules which are positively charged by a magnetic influence become more separated, chemically reactive agents that are added to the fluids, which serve as carrier vehicles, attain a more uniform distribution amongst the fluid molecules. After the carrier fluids and chemically reactive agents therein are introduced into the material mass, the more uniform dispersion of the chemical agents in the carrier fluids results in an acceleration of the normal reaction time of such chemically reactive agents within the interior of the material mass.

[0004] U. S. Patent No. 5,804,068 to Reed discloses a magnetic fluid treatment device. The object of this disclosure is to provide a device that can effectively polarize a fluid contained therein in order to gradually rearrange its fluid molecules into a more linear, organized and substantially more permeable state.

[0005] According to an aspect of the invention, there is provided a method of cleaning a surface having foreign matter thereon, such as grease, dirt particles, oil and

stains, comprising the steps of:

providing a first solution made by mixing water with sodium bicarbonate;
 providing a second solution made by mixing water with sodium silicate;
 passing said first solution through a positively charged magnetic field;
 passing said second solution through a negatively charged magnetic field;
 mixing equal parts of said first solution and said second solution together to form a mixture;
 allowing said mixture to stand and set, thereby forming a gel;
 introducing said gel onto said surface to be cleaned of said foreign matter;
 surrounding said foreign matter with said gel; and
 removing said gel and surrounded foreign matter from said surface.

[0006] According to another aspect of the invention, there is provided a cleaning agent comprising a mixture of a first solution and a second solution; wherein the first solution is a mixture of water and sodium bicarbonate which has been passed through a positively charged magnetic field; and the second solution is a mixture of water and sodium silicate which has been passed through a negatively charged magnetic field.

[0007] Throughout this description, references to a 'positively charged magnetic field' are references to a magnetic field configured to polarise a solution passing through it such that the solution becomes positively charged, and references to a 'negatively charged magnetic field' are references to a magnetic field configured to polarise a solution passing through it such that the solution becomes negatively charged. In addition, references to 'gallons' are references to US gallons.

[0008] One form of the present invention is directed to the application of a gel produced by combining polarized fluids used to remove grease, dirt and stains. The present invention discloses how the mixture of varying ratios of water to sodium silicate and water to sodium bicarbonate can create a gel having excellent properties in removing grease and oil in a nontoxic manner.

[0009] The present invention is directed towards a magnetically treated sodium silicate and sodium bicarbonate gel. In one embodiment, the gel used as a degreaser and cleaning agent exhibits the following properties:

- a. The ability to emulsify and assimilate to petroleum-based materials;
- b. The ability to remove and clean cooking oils or grease-laden surfaces;
- c. The ability to be completely dissolved in the presence of water;
- d. The ability to eliminate outer stain rings when ap-

plied to previous oil stains in surfaces such as concrete and stone;

e. The ability to lift stains when left overnight on materials such as marble and granite;

f. The ability to be applied on concrete where oils have previously stained the surface, scrubbing the oil stain, being allowed to dry overnight and being removed the following day by application of water, rendering a clean and oil-free surface;

g. The ability to remove and absorb the odors that may be inherently a part of the material to be removed;

h. The material formulation is completely biodegradable and environmentally friendly;

i. The ability to add materials, such as pumice, to create frictional qualities used in hand cleaners;

j. When used with imbibitional beads, the material formulation can be used to clean up oil deposits in environmentally sensitive areas;

k. The ability to be flushed down conventional sewer and waste systems without damage or harm to the environment;

l. The material formulation is non-corrosive to metals;

m. The material formulation can be used on virtually any type of surface; and

n. The ability to remove oxidation from painted surfaces.

[0010] In one embodiment, to produce such gel, a first solution is created by mixing 55 gallons of water with 50 lb. of sodium bicarbonate and passing the resulting mixture through a magnetic device of positive polarity, such as the device taught in U. S. Patent No. 5,804,068, to create a positively charged solution. A second solution is made by mixing 44 gallons of water with 11 gallons of sodium silicate and passing the resulting mixture through a magnetic device of negative polarity, such as the device taught in U. S. Patent No. 5,804,068, to create a negatively charged solution. In another embodiment, the first solution comprises 16lb of sodium bicarbonate with 30 gallons of water and the second solution comprises 30 gallons of water with 1 gallon of sodium silicate. Other, intermediate ratios of components can also be employed. The positively charged first solution is placed in a container with the negatively charged second solution in equal amounts and mixed together and allowed to set to produce a gel material. In one embodiment, however, the first and second solutions are not mixed in equal amounts, but their ratio is varied dependent on the specific design and function of the end product. The initial set time of the combined solution is predicated on the catalyst concentrations, the liquid material temperature and the delivery process. The material is allowed to set and then re-mixed to achieve a smooth, gel-like quality. While these two mixtures will ultimately form a gel when mixed together in an uncharged state, by magnetically activating the two solutions, the resulting gel has the above listed cleaning properties and is more highly struc-

tured to provide for a more uniform assimilation of oil and/or dirt. When distilled quality water with no particulate matter is used, shelf life of the gel is completely stable. Once the two-component material is mixed, it can be containerized and will remain stable for a long period of time. The gel also has the ability to maintain its structure and formation under extreme heat.

[0011] In other embodiments of this invention, varying ratios of water to sodium silicate and of water to sodium bicarbonate can be used to develop the desired gel density, resulting in a desired gel density suitable for removing grease, dirt, stains and oil from all types of surfaces. By removing water from the gel, the resulting hydrate can be re-wet to act as a cleaning agent. Salt water can be used in place of plain water with the formulation to achieve similar cleaning characteristics. The addition of a soap or surfactant to the formulation can be used to convert the gel to a foam-type gel material. The addition of an aggregate, such as pumice, to the gel can impart further cleaning and dirt and oil removal capacity.

[0012] The Occupational Health and Safety Agency (OSHA) and the Environmental Protection Agency (EPA) monitor the application, use, containment and disposal of many solvents and other chemicals used as surface cleaning agents. Many surface cleaning agents and existing cleaning systems have detrimental side effects in their application, both to the user and to the environment. Many types of degreasers and oil-reducing materials are based on the use of chemicals and agents that are toxic in nature and potentially harmful if not used appropriately. Thus it is an object of the present invention to provide a nontoxic, environmentally friendly material for use as a surface cleaner. The mixture of the primary chemicals of sodium bicarbonate and sodium silicate mixed to a highly diluted state with water is considered nontoxic and unregulated by the Department of Transportation (DOT). Each of the primary chemical components is nontoxic and nonhazardous as stated in its respective Material Safety Data Sheet. In one embodiment, the gel starts with a two-component clear liquid that is composed primarily of water. The active ingredients are not regulated by either the DOT or OSHA. When the materials are combined, a reaction occurs that forms a gel-like material with no heat produced. Once the gel is formed, it can later be completely dissolved by introducing water to the gel, causing the gel to return to its liquid state. To dissolve and remove the gel material, water can be either sprayed or added to the material, causing the gel material to liquefy and return to a liquid state. If left exposed to the air with no moisture present, the material will form dendritic crystals and eventually will fully disintegrate.

[0013] In one example, as discussed above, the first solution can be created by mixing 55 gallons of water with 50 lb. of sodium bicarbonate and passing such mixture through a magnetic device of positive polarity (See U. S. Patent No. 5,804,068 to Reed). A second solution can be made by mixing 11 gallons of sodium silicate with 44 gallons of water and passing the mixture through a

negatively charged magnetic field. The two solutions are then mixed together in equal amounts. The resulting mixture sets over time to form a gel. By magnetically activating the two solutions of the mixture, the mixture acquires the aforementioned cleaning and degreasing properties. The gel material encapsulates, emulsifies and dissolves dirt and grease by simple application to the surface. Once the gel material is applied, the surface can be agitated by scrubbing the gel into the soiled area. Once clean, the surface is then rinsed and wiped dry. The cohesive quality of the gel imparts the containment of the materials being removed. As the grease, dirt and oil products are emulsified and absorbed by the gel material, any odors from the material being removed are absorbed, if not eliminated. Since the gel is nontoxic, odorless, colorless and phosphate-free, the material suspended in the gel can be easily collected, making disposal safe and economical.

[0014] To dissolve the gel, when desired, water can be either sprayed onto, or added to, the mixture. The gel then liquefies immediately and is nontoxic and can be removed as a nontoxic liquid would be removed.

[0015] The cleaner can also be further diluted with water to be used as a car wash product.

[0016] An additional sheen-providing ingredient and protectant, such as LXR, can be added to add a sheen to painted surfaces.

[0017] Although the present invention has been described with reference to particular embodiments, it will be apparent to those skilled in the art that variations and modifications can be substituted therefor within the scope of the appended claims.

Claims

1. A method of cleaning a surface having foreign matter thereon, such as grease, dirt particles, oil and stains, comprising the steps of:

providing a first solution made by mixing water with sodium bicarbonate;
 providing a second solution made by mixing water with sodium silicate;
 passing said first solution through a positively charged magnetic field;
 passing said second solution through a negatively charged magnetic field;
 mixing said first solution and said second solution together to form a mixture;
 allowing said mixture to stand and set, thereby forming a gel;
 introducing said gel onto said surface to be cleaned of said foreign matter;
 surrounding said foreign matter with said gel;
 and
 removing said gel and surrounded foreign matter from said surface.

2. The method of claim 1, wherein said first solution and said second solution are mixed in substantially equal parts.

3. The method of Claim 1 or 2 wherein said step of removing said gel and foreign matter from said surface includes the steps of:

collecting said foreign matter surrounded by said gel; and
 rinsing said foreign matter surrounded by said gel with water to liquefy said gel and cause it to run off; and
 recovering said foreign matter for proper disposal.

4. The method of any preceding Claim further including after the step of mixing said first and second solutions, the step of:

adding a surfactant to said mixture to convert said gel to a foam-type gel material.

5. The method of any preceding Claim further including after the step of mixing said first and second solutions, the step of:

adding an aggregate to said mixture.

6. The method of any preceding Claim further including the steps of:

removing water from said gel to form a hydrate; and
 adding water to said hydrate to form a cleaning agent.

7. A cleaning agent comprising a mixture of a first solution and a second solution;
 wherein the first solution is a mixture of water and sodium bicarbonate which has been passed through a positively charged magnetic field; and
 the second solution is a mixture of water and sodium silicate which has been passed through a negatively charged magnetic field.

8. The cleaning agent of claim 7 wherein the first solution and the second solution are mixed in substantially equal amounts.



EUROPEAN SEARCH REPORT

Application Number
EP 09 27 5020

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 6 776 920 B1 (REED WILLIAM C [US]) 17 August 2004 (2004-08-17) * column 1, line 63 - column 2, line 2 * * column 2, line 48 - line 57 * * column 3, line 2 - line 5 * * column 3, line 28 - line 29 * * column 4, line 26 - line 40 * -----	1-8	INV. C11D3/08 C11D3/10
X	US 1 657 147 A (BRAINARD FLORENCE H) 24 January 1928 (1928-01-24) * column 1, line 21 - line 28 * * column 1, line 1 - line 3 * -----	1-8	
			TECHNICAL FIELDS SEARCHED (IPC)
			C11D
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 22 July 2009	Examiner Culmann, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 09 27 5020

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-07-2009

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6776920	B1	17-08-2004	US 7052555 B1	30-05-2006
US 1657147	A	24-01-1928	NONE	

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5415900 A, Reed [0002]
- US 5804068 A, Reed [0004] [0010] [0013]