



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Abstract

(51) Int Cl.:
G02F 1/1337^(2006.01) G02F 1/1343^(2006.01)

(86) International application number:
PCT/JP2008/071971

(48) Corrigendum issued on:
16.03.2011 Bulletin 2011/11

(87) International publication number:
WO 2009/130819 (29.10.2009 Gazette 2009/44)

(43) Date of publication:
29.12.2010 Bulletin 2010/52

(21) Application number: **08874023.8**

(22) Date of filing: **03.12.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR

(30) Priority: **22.04.2008 JP 2008111513**

(71) Applicant: **Sharp Kabushiki Kaisha**
Osaka-shi, Osaka 545-8522 (JP)

(72) Inventors:
• **ASADA, Katsushige**
Osaka-shi
Osaka 545-8522 (JP)
• **YOSHIDA, Masahiro**
Osaka-shi
Osaka 545-8522 (JP)

• **TOMINAGA, Masakatsu**
Osaka-shi
Osaka 545-8522 (JP)
• **FUJIKAWA, Tetsuya**
Osaka-shi
Osaka 545-8522 (JP)
• **MORINAGA, Junichi**
Osaka-shi
Osaka 545-8522 (JP)
• **FUJIHARA, Toshiaki**
Osaka-shi
Osaka 545-8522 (JP)

(74) Representative: **Müller - Hoffmann & Partner**
Patentanwälte
Innere Wiener Strasse 17
81667 München (DE)

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(57) At least either a first substrate or a second substrate has regions corresponding to subpixels (15a, 15b, 15c) and provided with ribs (100a) for controlling how a liquid crystal material is aligned. Scanning signal lines (32) and picture element electrodes (60) are overlapped with each other via an insulating material as seen in plan view. The ribs (100a) and the scanning signal lines (32) are at least partially overlapped with each other as seen in plan view.

