



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71

(51) Int Cl.:
F24H 1/18 (2006.01) **F24H 1/00** (2006.01)
F25B 27/02 (2006.01) **H01M 8/00** (2006.01)
H01M 8/04 (2006.01)

(48) Corrigendum issued on:
29.06.2011 Bulletin 2011/26

(86) International application number:
PCT/JP2010/001002

(43) Date of publication:
02.03.2011 Bulletin 2011/09

(87) International publication number:
WO 2010/109757 (30.09.2010 Gazette 2010/39)

(21) Application number: **10744647.8**

(22) Date of filing: **17.02.2010**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK SM TR

(72) Inventor: **MATSUMOTO, Satoshi**
Osaka-shi, Osaka
540-6207 (JP)

(30) Priority: **24.03.2009 JP 2009071322**

(74) Representative: **Schwabe - Sandmair - Marx**
Patentanwälte
Stuntzstraße 16
81677 München (DE)

(71) Applicant: **Panasonic Corporation**
Kadoma-shi
Osaka 571-8501 (JP)

(54) **FUEL CELL COGENERATION SYSTEM**

(57) An object of the present invention is to provide a highly reliable fuel cell cogeneration system that assures safety during maintenance by a simple structure.

A fuel cell cogeneration system includes: a heat recovery channel (8) in which a first shutoff valve (16), a heat-recovery heat exchanger (4) for recovering exhaust heat developing when a fuel cell (7) generates electricity, a second shutoff valve (17), and a hot water storage tank (1) are sequentially and circularly connected by a heat recovery pipe (3). A heat recovery channel pressure release valve (18) is provided in the heat recovery pipe (3) connecting the first shutoff valve (16), the second shutoff valve (17), and the heat-recovery heat exchanger (4), and is configured to open when internal pressure of the heat recovery pipe (3) closer to the heat-recovery heat exchanger (4) than the first shutoff valve (16) and the second shutoff valve (17) exceeds predetermined pressure.

FIG. 1

