



(11) **EP 2 293 021 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:

Corrected version no 1 (W1 A2)
Corrections, see
Bibliography INID code(s) 72

(51) Int Cl.:

G01D 3/08 (2006.01)

(48) Corrigendum issued on:

11.05.2011 Bulletin 2011/19

(43) Date of publication:

09.03.2011 Bulletin 2011/10

(21) Application number: **10173775.7**

(22) Date of filing: **24.08.2010**

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO SE SI SK SM TR

Designated Extension States:

BA ME RS

- **Tokonaga, Takeshi**
Kanagawa-ken, 224-0012 (JP)
- **Mallmann, Stefan**
74348 Lauffen (DE)
- **Schwarb, Michael**
70825 Korntal (DE)
- **Stapel, Dietmar**
48324 Sendenhorst (DE)
- **Klier, Willy**
Bloomfield Hills, Michigan 48301 (US)
- **Eesmann, Joerg**
48429 Rheine (DE)

(30) Priority: **24.08.2009 US 236409 P**

(71) Applicant: **Robert Bosch GmbH**
70442 Stuttgart (DE)

(72) Inventors:

- **Bechtler, Henrik**
70182 Stuttgart (DE)
- **Bhadange, Ravi**
Farmington, Michigan 48335 (US)
- **Patil, Nachiket**
Farmington Hills, Michigan 48335 (US)

(74) Representative: **Dreiss**
Patentanwälte
Gerokstrasse 1
70188 Stuttgart (DE)

(54) **Good checking for vehicle steering angle sensor**

(57) A controller for determining whether a previously-determined vehicle steering sensor malfunction still exists. The controller includes an electronic, non-volatile memory, and an electronic processing unit connected to the electronic, non-volatile memory. The electronic processing module includes a malfunction monitoring module, a failure handling module, and a signal checking module. The malfunction monitoring module monitors the

operation of at least one vehicle sensor and generates a fault signal when the at least one sensor malfunctions. The failure handling module causes drive cycle information and the fault information to be stored in the electronic, non-volatile memory. The signal checking module performs a signal check on information from the at least one sensor.

EP 2 293 021 A8