



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A2)
Corrections, see
Bibliography INID code(s) 71

(51) Int Cl.:
G06K 19/073 (2006.01)

(48) Corrigendum issued on:
08.06.2011 Bulletin 2011/23

(43) Date of publication:
06.04.2011 Bulletin 2011/14

(21) Application number: **10177829.8**

(22) Date of filing: **21.09.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR
Designated Extension States:
BA ME RS

(71) Applicant: **Ricoh Company Ltd.**
Tokyo 143-8555 (JP)

(72) Inventor: **Kawase, Tsutomu**
Tokyo 143-8555 (JP)

(74) Representative: **Schwabe - Sandmair - Marx**
Patentanwälte
Stuntzstraße 16
81677 München (DE)

(30) Priority: **02.10.2009 JP 2009230205**

(54) **Data input device**

(57) A data input device (SW1, SW2) is configured to include a first RFID tag (74, 75) containing identification data and being able to transmit the identification data to an RFID reader (4) upon receipt of a radio wave from the RFID reader (4), a conductive element (80) which allows the first RFID tag (74, 75) to be incommunicable with the RFID reader (4) when the conductive element (80) is

close to the first RFID tag (74, 75), and an operative element (64) which is configured to support the conductive element (80) and bias the conductive element (80) to a position close to the first RFID tag (74, 75) so that the first RFID tag (74, 75) becomes incommunicable and to return the conductive element (80) against a bias force to a position away from the first RFID tag (74, 75) so that the first RFID tag (74, 75) becomes communicable.

FIG. 1

