

(51) Int Cl.: **C10G 31/06** ^(2006.01) **C10B 55/04** ^(2006.01)

(22) Date of filing: **07.04.2000**

- **Graham, Robert G.**
Nepean, Ontario K2J 2J6 (CA)

(74) Representative: **Thom, Russell
Murgitroyd & Company
Scotland House
165-169 Scotland Street
Glasgow G5 8PL (GB)**

Remarks:
This application was filed on 30-09-2010 as a
divisional application to the application mentioned
under INID code 62.

(72) Inventors:
• **Freel, Barry A.**
Ontario K4P 1E8 (CA)

(57) The present invention is directed to the use of an upgraded liquid feedstock as a product for pipeline transport to permit further processing of the upgraded liquid feedstock elsewhere. The upgraded liquid feedstock is produced from a heavy hydrocarbon feedstock, which is not transportable by pipeline to an offsite location without addition of diluents, by a method for upgrading a heavy hydrocarbon feedstock comprises introducing a particulate heat carrier into an upflow reactor, introducing the heavy hydrocarbon feedstock into the upflow reactor at a location above that of the particulate heat carrier so that a loading ratio of the particulate heat carrier to feedstock is from about 15:1 to about 200:1, allowing the heavy hydrocarbon feedstock to interact with the heat carrier with a residence time of less than about 1 second, to produce a product stream, separating the product stream from the particulate heat carrier, regenerating the particulate heat carrier, and collecting a gaseous and liquid product from the product stream. The upgraded feedstock exhibiting reduced viscosity and increased API gravity.




FIG. 1A




FIG. 1B

Description

[0001] The present invention relates to the rapid thermal processing of viscous oil feedstocks. More specifically, this invention relates to the use of pyrolysis in order to upgrade and reduce the viscosity of these oils.

BACKGROUND OF THE INVENTION

[0002] Heavy oil and bitumen resources are supplementing the decline in the production of conventional light and medium crude oil, and production from these resources is expected to dramatically increase. Pipeline expansion is expected to handle the increase in heavy oil production, however, the heavy oil must be treated in order to permit its transport by pipeline. Presently heavy oil and bitumen crudes are either made transportable by the addition of diluents or they are upgraded to synthetic crude. However, diluted crudes or upgraded synthetic crudes are significantly different from conventional crude oils. As a result, bitumen blends or synthetic crudes are not easily processed in conventional fluid catalytic cracking refineries. Therefore, in either case the refiner must be configured to handle either diluted or upgraded feedstocks.

[0003] Many heavy hydrocarbon feedstocks are also characterized as comprising significant amounts of BS&W (bottom sediment and water). Such feedstocks are not suitable for transportable by pipeline, or upgrading due to the sand, water and corrosive properties of the feedstock. Typically, feedstocks characterized as having less than 0.5 wt. % BS&W are transportable by pipeline, and those comprising greater amount of BS&W require some degree of processing and treatment to reduce the BS&W content prior to transport. Such processing may include storage to let the water and particulates settle, followed by heat treatment to drive off water and other components. However, these manipulations are expensive and time consuming. There is therefore a need within the art for an efficient method for upgrading feedstock comprising a significant BS&W content prior to transport or further processing of the feedstock.

[0004] Heavy oils and bitumens can be upgraded using a range of rapid processes including thermal (e.g. US 4,490,234; US 4,294,686; US 4,161,442), hydrocracking (US 4,252,634) visbreaking (US 4,427,539; US 4,569,753; US 5,413,702) or catalytic cracking (US 5,723,040; US 5,662,868; US 5,296,131; US 4,985,136; US 4,772,378; US 4,668,378, US 4,578,183) procedures. Several of these processes, such as visbreaking or catalytic cracking, utilize either inert or catalytic particulate contact materials within upflow or downflow reactors. Catalytic contact materials are for the most part zeolite based (see for example US 5,723,040; US 5,662,868; US 5,296,131; US 4,985,136; US 4,772,378; US 4,668,378, US 4,578,183; US 4,435,272; US 4,263,128), while visbreaking typically utilizes inert contact material (e.g. US 4,427,539; US 4,569,753), carbonaceous solids (e.g. US 5,413,702), or inert kaolin solids (e.g. US 4,569,753).

[0005] The use of fluid catalytic cracking (FCC), or other, units for the direct processing of bitumen feedstocks is known in the art. However, many compounds present within the crude feedstocks interfere with these process by depositing on the contact material itself. These feedstock contaminants include metals such as vanadium and nickel, coke precursors such as Conradson carbon and asphaltenes, and sulfur, and the deposit of these materials results in the requirement for extensive regeneration of the contact material. This is especially true for contact material employed with FCC processes as efficient cracking and proper temperature control of the process requires contact materials comprising little or no combustible deposit materials or metals that interfere with the catalytic process.

[0006] To reduce contamination of the catalytic material within catalytic cracking units, pretreatment of the feedstock via visbreaking (US 5,413,702; US 4,569,753; US 4,427,539), thermal (US 4,252,634; US 4,161,442) or other processes, typically using FCC-like reactors, operating at temperatures below that required for cracking the feedstock (e.g. US 4,980,045; US 4,818,373 and US 4,263,128;) have been suggested. These systems operate in series with FCC units and function as pre-treaters for FCC. These pretreatment processes are designed to remove contaminant materials from the feedstock, and operate under conditions that mitigate any cracking. This ensures that any upgrading and controlled cracking of the feedstock takes place within the FCC reactor under optimal conditions.

[0007] Several of these processes (e.g. US 4,818,373; US 4,427,539; US 4,311,580; US 4,232,514; US 4,263,128;) have been specifically adapted to process "resids" (i.e. feedstocks produced from the fractional distillation of a whole crude oil) and bottom fractions, in order to optimize recovery from the initial feedstock supply. The disclosed processes for the recovery of resids, or bottom fractions, are physical and involve selective vaporization or fractional distillation of the feedstock with minimal or no chemical change of the feedstock. These process are also combined with metals removal and provide feedstocks suitable for FCC processing. The selective vaporization of the resid takes place under non-cracking conditions, without any reduction in the viscosity of the feedstock components, and ensures that cracking occurs within an FCC reactor under controlled conditions. None of these approaches disclose the upgrading of feedstock within this pretreatment (i.e. metals and coke removal) process. Other processes for the thermal treatment of feedstocks involve hydrogen addition (hydrotreating) which results in some chemical change in the feedstock.

[0008] US 4,294,686 discloses a steam distillation process in the presence of hydrogen for the pretreatment of feedstock for FCC processing. This document also indicates that this process may also be used to reduce the viscosity of the feedstock such that the feedstock may be suitable for transport within a pipeline. However, the use of short residence

time reactors to produce a transportable feedstock is not disclosed.

[0009] There is a need within the art for a rapid and effective upgrading process of a heavy oil or bitumen feedstock that involves a partial chemical upgrade or mild cracking of the feedstock in order to obtain a product characterized in having a reduced viscosity over the starting material. Ideally this process would be able to accommodate feedstocks comprising significant amounts of BS&W. This product would be transportable for further processing and upgrading. Such a process would not involve any catalytic-cracking activity due to the known contamination of catalyst contact materials with components present in heavy oil or bitumen feedstocks. The rapid and effective upgrading process would produce a product characterized in having reduced viscosity, reduced metal content, increased API, and an optimal product yield.

[0010] The present invention is directed to the upgrading of heavy hydrocarbon feedstocks, for example but not limited to heavy oil or bitumen feedstocks, that utilizes a short residence pyrolytic reactor operating under conditions that cracks and chemically upgrades the feedstock. The feedstock used within this process may comprise significant levels of BS&W and still be effectively processed, thereby increasing the efficiency of feedstock handling. The process of the present invention provides for the preparation of a partially upgraded feedstock exhibiting reduced viscosity and increased API gravity. The process described herein selectively removes metals, salts, water and nitrogen from the feedstock, while at the same time maximizes the liquid yield, and minimizing coke and gas production. Furthermore, this process reduces the viscosity of the feedstock to an extent which can permit pipeline transport of the feedstock without addition of diluents. The partially upgraded product optionally permits transport of the feedstock offsite, to locations better equipped to handle refining. Such facilities are typically located at a distance from the point where the crude feedstock is obtained.

SUMMARY OF THE INVENTION

[0011] The present invention relates to the rapid thermal processing of viscous oil feedstocks. More specifically, this invention relates to the use of pyrolysis in order to upgrade and reduce the viscosity of these oils.

[0012] According to the present invention there is provided a method for upgrading a heavy hydrocarbon feedstock comprising:

- i) introducing a particulate heat carrier into an upflow reactor;
- ii) introducing the heavy hydrocarbon feedstock into the upflow reactor at at least one location above that of the particulate heat carrier so that a loading ratio of the particulate heat carrier to feedstock is from about 10:1 to about 200:1;
- iii) allowing the heavy hydrocarbon feedstock to interact with the heat carrier with a residence time of less than about 1 second, to produce a product stream;
- iv) separating the product stream from the particulate heat carrier;
- v) regenerating the particulate heat carrier; and
- vi) collecting a gaseous and liquid product from the product stream, wherein the liquid product exhibits an increased API gravity, a reduced pour point, reduced viscosity and a reduced level of contaminants over that of said feedstock.

[0013] Preferably, the loading ratio of the method as outlined above is from about 20 :1 to about 30:1.

[0014] This invention also includes the method as outlined above wherein the heavy hydrocarbon feedstock is either heavy oil or bitumen. Furthermore, the feedstock is pre-heated prior to its introduction into the upflow reactor.

[0015] The present invention also relates to the method as defined above, wherein the temperature of the upflow reactor is less than 750°C, wherein the residence time is from about 0.5 to about 2 seconds, and wherein the particulate heat carrier is silica sand.

[0016] This invention is also directed to the above method wherein the contaminants, including Conradson carbon (coke), BS&W, nickel and vanadium are removed from the feedstock or deposited onto the heat carrier

[0017] The present invention also includes the method as defined above, wherein said product stream of a first pyrolysis run is separated into a lighter fraction and a heavier fraction, collecting the lighter fraction from the product stream, and recycling the heavier fraction back into the upflow reactor for further processing within a second pyrolysis run to produce a second product stream. Preferably, the further processing includes mixing the heavier fraction with the particulate heat carrier, wherein the temperature of the particulate heat carrier of the second pyrolysis run is at about, or above, that used in the processing of the feedstock within the first pyrolysis run. For example, the temperature of the heat carrier within the first pyrolysis run is from about 300°C to about 590°C, and the temperature of the second pyrolysis run is from about 530°C to about 700°C. The residence time of the second pyrolysis run is the same as, or longer than, the residence time of the first pyrolysis run. Furthermore, the heavier fraction may be added to unprocessed feedstock prior to being introduced into the upflow reactor for the second pyrolysis run.

[0018] The present invention is also directed to an upgraded heavy oil characterized by the following properties:

- i) an API gravity from about 13 to about 23;
- ii) a density from about 0.92 to about 0.98;
- iii) a viscosity at 40°C (cSt) from about 15 to about 300; and
- iv) a reduced Vanadium content of about 60 to about 100 ppm; and
- v) a reduced Nickel content of about 10 to about 50 ppm.

[0019] This invention also embraces an upgraded bitumen characterized by the following properties:

- i) an API gravity from about 10 to about 21;
- ii) a density from about 0.93 to about 1.0;
- iii) a viscosity at 40°C (cSt) from about 15 to about 300; and
- iv) a reduced Vanadium content of about 60 to about 100 ppm; and
- v) a reduced Nickel content of about 10 to about 50 ppm.

[0020] The present invention also pertains to a liquid product characterized in having at least one of the following properties:

- i) less than 50% of the components evolving at temperatures above 538°C during simulated distillation;
- ii) from about 60% to about 95% of the product evolving below 538°C during simulated distillation;
- iii) from about 1.0% to about 10% of the liquid product evolving below 193°C during simulated distillation;
- iv) from about 2 % to about 6 % of the liquid product evolving between 193-232 °C during simulated distillation;
- v) from about 10 % to about 25% of the liquid product evolving between 232-327°C during simulated distillation;
- vi) from about 6 % to about 15 % of the liquid product evolving between 327-360°C during simulated distillation; and
- vii) from about 34.5 % to about 60 % of the liquid product evolving between 360-538°C during simulated distillation.

[0021] This invention also includes an upflow pyrolysis reactor for heavy hydrocarbon feedstock upgrading comprising:

- i) a means for pre-heating the heavy hydrocarbon feedstock;
- ii) at least one injection means at at least one of a plurality of locations along the upflow reactor, the at least one injection means for introducing the heavy hydrocarbon feedstock into the upflow reactor;
- iii) an inlet for introducing a particulate heat carrier, the inlet located below the at least one injection means, the particulate heat carrier present at a loading ratio of at least 10:1;
- iv) a conversion section within the upflow reactor;
- v) a separation means at an outlet of the upflow reactor to separate the gaseous and liquid products from the particulate heat carrier;
- vi) a particulate heat carrier regeneration means;
- vii) a particulate heat carrier recirculation line from the regeneration means to the inlet for supplying the particulate heat carrier to said mixing section;
- viii) a condensing means for cooling and condensing the liquid products;

[0022] The present invention also relates to the upflow reactor as defined above, wherein the plurality of locations, includes locations distributed along the length of said reactor. Furthermore, the upflow reactor may comprise a hot condenser means prior to the condensing means. Preferably, the particulate heat carrier is silica sand, and the loading ratio is from about 20:1 to about 30:1. The upflow reactor as defined above may also comprise a heavy fraction product recirculation means from the hot condensing means to the injection means of the upflow reactor.

[0023] The present invention also pertains to a method for upgrading a heavy hydrocarbon feedstock comprising:

- i) introducing a particulate heat carrier into an upflow reactor;
- ii) introducing a feedstock into the upflow reactor at at least one location above that of the particulate heat carrier so that a loading ratio of the particulate heat carrier to the heavy hydrocarbon feedstock is from about 10:1 to about 200:1;
- iii) allowing the feedstock to interact with the heat carrier with a residence time of less than about 1 second, to produce a product stream;
- iv) separating the product stream from the particulate heat carrier;
- v) regenerating the particulate heat carrier; and
- vi) collecting a gaseous and liquid product from the product stream, wherein the feedstock is obtained from the direct contact between the product stream and a heavy hydrocarbon feedstock, within a condenser.

[0024] The present invention addresses the need within the art for a rapid upgrading process of a heavy oil or bitumen feedstock involving a partial chemical upgrade or mild cracking of the feedstock. This product may, if desired, be transportable for further processing and upgrading. The process as described herein also reduces the levels of contaminants within feedstocks, thereby mitigating contamination of catalytic contact materials with components present in heavy oil or bitumen feedstocks.

[0025] Furthermore, a range of heavy hydrocarbon feedstocks may be processed by the methods as described herein, including feedstocks comprising significant amounts of BS&W. Feedstocks comprising significant BS&W content are non-transportable due to their corrosive properties. Current practices for the treatment of feedstocks to decrease their BS&W content are time consuming and costly, and still require further processing or partial upgrading prior to transport. The methods described herein permit the use of feedstocks having a substantial BS&W component, and produce a liquid product that is partially upgraded and suitable for pipeline or other methods, of transport. The present invention therefore provides for earlier processing of feedstocks and reduces associated costs and processing times.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] These and other features of the invention will become more apparent from the following description in which reference is made to the appended drawings wherein:

FIGURE 1 is a schematic drawing of an embodiment of the present invention relating to a system for the pyrolytic processing of feedstocks.

FIGURE 2 is a schematic drawing of an embodiment of the present invention relating to the feed system for introducing the feedstock to the system for the pyrolytic processing of feedstocks.

FIGURE 3 is a schematic drawing of an embodiment of the present invention relating to the feed system for introducing feedstock into the second stage of a two stage process using the system for the pyrolytic processing of feedstocks as described herein.

FIGURE 4 is a schematic drawing of an embodiment of the present invention relating to the recovery system for obtaining feedstock to be either collected from a primary condenser, or recycled to the second stage of a two stage process using the system for the pyrolytic processing of feedstocks as described herein.

FIGURE 5 is a schematic drawing of an embodiment of the present invention relating to a multi stage system for the pyrolytic processing of feedstocks.

DESCRIPTION OF PREFERRED EMBODIMENT

[0027] The present invention relates to the rapid thermal processing of viscous crude oil feedstocks. More specifically, this invention relates to the use of pyrolysis in order to upgrade and reduce the viscosity of these oils.

[0028] The following description is of a preferred embodiment by way of example only and without limitation to the combination of features necessary for carrying the invention into effect.

[0029] By "feedstock" it is generally meant a heavy hydrocarbon feedstock comprising, but not limited to, heavy oil or bitumens. However, the term "feedstock" may also include other hydrocarbon compounds such as petroleum crude oil, atmospheric tar bottom products, vacuum tar bottoms, coal oils, residual oils, tar sands, shale oil and asphaltic fractions. Furthermore, the feedstock may comprise significant amounts of BS&W (Bottom Sediment and Water), for example, but not limited to, a BS&W content of greater than 0.5% (wt%). Feedstock may also include pre-treated (pre-processed) feedstocks as defined below, however, heavy oil and bitumen are the preferred feedstock. These heavy oil and bitumen feedstocks are typically viscous and difficult to transport. Bitumens typically comprise a large proportion of complex polynuclear hydrocarbons (asphaltenes) that add to the viscosity of this feedstock and some form of pretreatment of this feedstock is required for transport. Such pretreatment typically includes dilution in solvents prior to transport.

[0030] Typically tar-sand derived feedstocks (see Example 1 for an analysis of examples, which are not to be considered limiting, of such feedstocks) are pre-processed prior to upgrading, as described herein, in order to concentrate bitumen. However, pre-processing may also involve methods known within the art, including hot or cold water treatments, or solvent extraction that produces a bitumen-gas oil solution. These pre-processing treatments typically reduce the sand content of bitumen. For example one such water pre-processing treatment involves the formation of a tar-sand containing bitumen- hot water/NaOH slurry, from which the sand is permitted to settle, and more hot water is added to the floating bitumen to dilute out the base and ensure the removal of sand. Cold water processing involves crushing tar-sand in water and floating the bitumen containing tar-sands in fuel oil, then diluting the bitumen with solvent and separating the

bitumen from the sand-water residue. A more complete description of the cold water process is disclosed in US 4,818,373 (which is incorporated by reference). Such pre-processed or pre-treated feedstocks may also be used for further processing as described herein.

[0031] Bitumens may be upgraded using the process of this invention, or other processes such as FCC, visbraking, hydrocracking etc. Pre-treatment of tar sand feedstocks may also include hot or cold water treatments, for example, to partially remove the sand component prior to upgrading the feedstock using the process as described herein, or other upgrading processes including FCC, hydrocracking, coking, visbreaking etc. Therefore, it is to be understood that the term "feedstock" also includes pre-treated feedstocks, including, but not limited to those prepared as described above.

[0032] It is to be understood that lighter feedstocks may also be processed following the method of the invention as described herein. For example, and as described in more detail below, liquid products obtained from a first pyrolytic treatment as described herein, may be further processed by the method of this invention (for example composite recycle and multi stage processing; see Figure 5 and Examples 3 and 4) to obtain a liquid product characterized as having reduced viscosity, a reduced metal (especially nickel, vanadium) and water content, and a greater API. Furthermore, liquid products obtained from other processes as known in the art, for example, but not limited to US 5,662,868; US 4,980,045; US 4,818,373; US 4,569,753; US 4,435,272; US 4,427,538; US 4,427,539; US 4,328,091; US 4,311,580; US 4,243,514; US 4,294,686, may also be used as feedstocks for the process described herein. Therefore, the present invention also contemplates the use of lighter feedstocks including gas oils, vacuum gas oils, topped crudes or pre-processed liquid products, obtained from heavy oils or bitumens. These lighter feedstocks may be treated using the process of the present invention in order to upgrade these feedstocks for further processing using, for example, but not limited to, FCC, visbreaking, or hydrocracking etc, or for transport and further processing.

[0033] The liquid product arising from the process as described herein may be suitable for transport within a pipeline to permit further processing of the feedstock elsewhere. Typically, further processing occurs at a site distant from where the feedstock is obtained. However, it is considered within the scope of the present invention that the liquid product produced using the present method may also be directly input into a unit capable of further upgrading the feedstock, such as, but not limited to, FCC, coking, visbreaking, hydrocracking, or pyrolysis etc. In this capacity, the pyrolytic reactor of the present invention partially upgrades the feedstock while at the same time acts as a pre-treater of the feedstock for further processing, as disclosed in, for example, but not limited to US 5,662,868; US 4,980,045; US 4,818,373; US 4,569,753; US 4,435,272; US 4,427,538; US 4,427,539; US 4,328,091; US 4,311,580; US 4,243,514; US 4,294,686 (all of which are incorporated by reference herein).

[0034] The feedstocks of the present invention are processed using a fast pyrolysis reactor, such as that disclosed in US 5,792,340 (WO91/11499; EP 513,051) involving contact times between the heat carrier and feedstock from about 0.01 to about 2 sec. Other known riser reactors with short residence times may also be employed, for example, but not limited to US 4,427,539, 4,569,753, 4,818,373, 4,243,514 (which are incorporated by reference).

[0035] It is preferred that the heat carrier used within the pyrolysis reactor exhibits low catalytic activity. Such a heat carrier may be an inert particulate solid, preferably sand, for example silica sand. By silica sand it is meant a sand comprising greater than about 80% silica, preferably greater than about 95% silica, and more preferably greater than about 99 % silica. Other components of the silica sand may include, but are not limited to, from about 0.01 % (about 100 ppm) to about 0.04% (400 ppm) iron oxide, preferably about 0.035% (358 ppm); about 0.00037% (3.78 ppm) potassium oxide; about 0.00688% (68.88 ppm) aluminum oxide; about 0.0027 (27.25) magnesium oxide; and about 0.0051 % (51.14 ppm) calcium oxide. It is to be understood that the above composition is an example of a silica sand that can be used as a heat carrier as described herein, however, variations within the proportions of these ingredients within other silica sands may exist and still be suitable for use as a heat carrier. Other known inert particulate heat carriers or contact materials, for example kaolin clays, rutile, low surface area alumina, oxides of magnesium aluminum and calcium as described in US 4,818,373 or US 4,243,514, may also be used.

[0036] Processing of feedstocks using fast pyrolysis results in the production of product vapours and solid byproducts associated with the heat carrier. After removal of the heat carrier from the product stream, the product vapours are condensed to obtain a liquid product and gaseous by-products. For example, which is not to be considered limiting, the liquid product produced from the processing of heavy oil, as described herein, is characterized in having the following properties:

- a boiling point of less than about 600°C, preferably less than about 525°C, and more preferably less than about 500°C;
- an API gravity of at least about 12°, and preferably greater than about 17° (where API gravity = $[141.5/\text{specific gravity}]-131.5$; the higher the API gravity, the lighter the compound);
- greatly reduced metals content, including V and Ni.
- greatly reduced viscosity levels (more than 25 fold lower than that of the feedstock, for example, as determined @ 40°C), and
- yields of liquid product of at least 60 vol%, preferably the yields are greater than about 70 vol%, and more preferably

they are greater than about 80%.

[0037] Following the methods as described herein, a liquid product obtained from processing bitumen feedstock, which is not to be considered limiting, is characterized as having:

- an API gravity from about 10 to about 21;
- a density @ 15°C from about 0.93 to about 1.0;
- greatly reduced metals content, including V and Ni.
- a greatly reduced viscosity of more than 20 fold lower than the feedstock (for example as determined at 40°C), and
- yields of liquid product of at least 60 vol%, preferably the yields are greater than about 75 vol%.

[0038] The high yields and reduced viscosity of the liquid product produced according to this invention may permit the liquid product to be transported by pipeline to refineries for further processing with the addition of little or no diluents. Furthermore, the liquid products exhibit reduced levels of contaminants (e.g. metals and water), with the content of sulphur and nitrogen slightly reduced. Therefore, the liquid product may also be used as a feedstock, either directly, or following transport, for further processing using, for example, FCC, hydrocracking etc.

[0039] Furthermore, the liquid products of the present invention may be characterised using Simulated Distillation (SimDist) analysis, as is commonly known in the art, for example but not limited to ASTM D 5307-97 or HT 750 (NCUT). SimDist analysis, indicates that liquid products obtained following processing of heavy oil or bitumen can be characterized by any one of, or a combination of, the following properties (see Examples 1, 2 and 5):

- having less than 50% of their components evolving at temperatures above 538°C (vacuum resid fraction);
- comprising from about 60% to about 95% of the product evolving below 538°. Preferably, from about 62% to about 85% of the product evolves during SimDist below 538°C (i.e. before the vacuum resid. fraction);
- having from about 1.0% to about 10% of the liquid product evolve below 193°C. Preferably from about 1.2 % to about 6.5% evolves below 193 °C (i.e. before the naphtha/kerosene fraction);
- having from about 2 % to about 6 % of the liquid product evolve between 193-232°C. Preferably from about 2.5% to about 5% evolves between 193-232°C (kerosene fraction);
- having from about 10% to about 25% of the liquid product evolve between 232-327°C. Preferably, from about 13 to about 24% evolves between 232-327°C (diesel fraction);
- having from about 6% to about 15% of the liquid product evolve between 327-360°C. Preferably, from about 6.5 to about 11 % evolves between 327-360°C (light VGO fraction);
- having from about 34.5% to about 60% of the liquid product evolve between 360-538°C. Preferably, from about 35 to about 55% evolves between 360-538°C (Heavy VGO fraction);

[0040] A first method for upgrading a feedstock to obtain liquid products with desired properties involves a one stage process. With reference to Figure 1, briefly, the fast pyrolysis system includes a feed system generally indicated as (10; also see Figures 2 and 3), that injects the feedstock into a reactor (20), a heat carrier separation system that separates the heat carrier from the product vapour (e.g. 100 and 180) and recycles the heat carrier to the reheating/regenerating system (30), a particulate inorganic heat carrier reheating system (30) that reheats and regenerates the heat carrier, and primary (40) and secondary (50) condensers that collect the product. The pre-heated feedstock enters the reactor just below the mixing zone (170) and is contacted by the upward flowing stream of hot inert carrier within a transport fluid, typically a recycle gas supplied by a recycle gas line (210). A through and rapid mixing and conductive heat transfer from the heat carrier to the feedstock takes place in the short residence time conversion section of the reactor. The feedstock may enter the reactor through at least one of several locations along the length of the reactor. The different entry points indicated in Figures 1 and 2 are non-limiting examples of such entry locations. By providing several entry points along the length of the reactor, the length of the residence time within the reactor may be varied. For example, for longer residence times, the feedstock enters the reactor at a location lower down the reactor, while, for shorter residence times, the feedstock enters the reactor at a location higher up the reactor. In all of these cases, the introduced feedstock mixes with the upflowing heat carrier within a mixing zone (170) of the reactor. The product vapours produced during pyrolysis are cooled and collected using a suitable condenser means (40, 50) in order to obtain a liquid product.

[0041] It is to be understood that other fast pyrolysis systems, comprising differences in reactor design, that utilize alternative heat carriers, heat carrier separators, different numbers or size of condensers, or different condensing means, may be used for the preparation of the upgraded product of this invention. For example, which is not to be considered limiting, reactors disclosed in US 4,427,539, 4,569,753, 4,818,373, 4,243,514 (all of which are incorporated by reference) may be modified to operate under the conditions as outlined herein for the production of a chemically upgraded product with an increased API and reduced viscosity.

[0042] Following pyrolysis of the feedstock in the presence of the inert heat carrier, some contaminants present within

the feedstock are deposited onto the inert heat carrier. These contaminants include metals (especially nickel and vanadium), coke, and to some extent nitrogen and sulphur. The inert heat carrier therefore requires regeneration (30) before re-introduction into the reaction stream. The heat carrier may be regenerated via combustion within a fluidized bed at a temperature of about 600 to about 900°C. Furthermore, as required, deposits may also be removed from the heat carrier by an acid treatment, for example as disclosed in US 4,818,373 (which is incorporated by reference). The heated, regenerated, heat-carrier is then re-introduced to the reactor (20) and acts as heat carrier for fast pyrolysis.

[0043] The feed system (10) provides a preheated feedstock to the reactor (20). An example of a feed system which is not to be considered limiting in any manner, is shown in Figure 2, however, other embodiments of the feed system are within the scope of the present invention, for example but not limited to a feed pre-heater unit as shown in Figure 5 (discussed below) and may be optionally used in conjunction with a feed system (10; Figure 5). The feed system (generally shown as 10, Figures 1 and 2) is designed to provide a regulated flow of pre-heated feedstock to the reactor unit (20). The feed system shown in Figure 2 includes a feedstock pre-heating surge tank (110), heated using external band heaters (130) to 80°C, and is associated with a recirculation/transfer pump (120). The feedstock is constantly heated and mixed in this tank at 80°C. The hot feedstock is pumped from the surge tank to a primary feed tank (140), also heated using external band heaters (130), as required. However, it is to be understood that variations on the feed system may also be employed, in order to provide a heated feedstock to the reactor. The primary feed tank (140) may also be fitted with a recirculation/delivery pump (150). Heat traced transfer lines (160) are maintained at about 150°C and pre-heat the feedstock prior to entry into the reactor via an injection nozzle (170). Atomization at the injection nozzle (70) positioned near the mixing zone (170) within reactor (20) may be accomplished by any suitable means. The nozzle arrangement should provide for a homogeneous dispersed flow of material into the reactor. For example, which is not considered limiting in any manner, mechanical pressure using single-phase flow atomization, or a two-phase flow atomization nozzle may be used. With a two phase flow atomization nozzle, pre-heated air, nitrogen or recycled by-product gas may be used as a carrier. Instrumentation is also dispersed throughout this system for precise feedback control (e.g. pressure transmitters, temperature sensors, DC controllers, 3-way valves gas flow metres etc.) of the system.

[0044] Conversion of the feedstock is initiated in the mixing zone (170; e.g. Figure 1) under moderate temperatures (typically less than 750°C) and continues through the conversion section within the reactor unit (20) and connections (e.g. piping, duct work) up until the primary separation system (e.g. 100) where the bulk of the heat carrier is removed from the product vapour stream. The solid heat carrier and solid coke by-product are removed from the product vapour stream in a primary separation unit. Preferably, the product vapour stream is separated from the heat carrier as quickly as possible after exiting from the reactor (20), so that the residence time of the product vapour stream in the presence of the heat carrier is as short as possible.

[0045] The primary separation unit may be any suitable solids separation device, for example but not limited to a cyclone separator, a U-Beam separator, or Rams Horn separator as are known within the art. A cyclone separator is shown diagrammatically in Figures 1, 3 and 4. The solids separator, for example a primary cyclone (100), is preferably fitted with a high-abrasion resistant liner. Any solids that avoid collection in the primary collection system are carried downstream and recovered in a secondary collection system (180). The secondary separation unit may be the same as the primary separation unit, or it may comprise an alternate solids separation device, for example but not limited to a cyclone separator, a 1/4 turn separator, for example a Rams Horn separator, or an impingement separator, as are known within the art. A secondary cyclone separator (180) is graphically represented in Figures 1 and 4, however, other separators may be used as a secondary separator unit.

[0046] The solids that have been removed in the primary and secondary collection systems are transferred to a vessel for regeneration of the heat carrier, for example, but not limited to a direct contact reheater system (30). In a direct contact reheater system (30), the coke and by-product gasses are oxidized to provide processes thermal energy which is directly carried to the solid heat carrier, as well as regenerating the heat carrier. The temperature of the direct contact reheater is maintained independent of the feedstock conversion (reactor) system. However, as indicated above, other methods for the regeneration of the heat carrier may be employed, for example but not limited to, acid treatment.

[0047] The hot product stream from the secondary separation unit is quenched in a primary collection column (or primary condenser, 40; Figure 1). The vapour stream is rapidly cooled from the conversion temperature to less than about 400°C. Preferably the vapour stream is cooled to about 300°C. Product is drawn from the primary column and pumped (220) into product storage tanks. A secondary condenser (50) can be used to collect any material that evades the primary condenser (40). Product drawn from the secondary condenser (50) is also pumped (230) into product storage tanks. The remaining non-condensable gas is compressed in a blower (190) and a portion is returned to the heat carrier regeneration system (30) via line (200), and the remaining gas is returned to the reactor (20) by line (210) and acts as a heat carrier, and transport, medium.

[0048] It is preferred that the reactor used with the process of the present invention is capable of producing high yields of liquid product for example at least greater than 60 vol%, preferably the yield is greater than 70 vol%, and more preferably the yield is greater than 80%, with minimal byproduct production such as coke and gas. Without wishing to limit the scope of the invention in any manner, an example for the suitable conditions for a the pyrolytic treatment of

feedstock, and the production of a liquid product is described in US 5,792,340, which is incorporated herein by reference. This process utilizes sand (silica sand) as the heat carrier, and a reactor temperature ranging from about 480° to about 620°C, loading ratios of heat carrier to feedstock from about 10:1 to about 200:1, and residence times from about 0.35 to about 0.7 sec. Preferably the reactor temperature ranges from about 500° to about 550°C. The preferred loading ratio is from about 15:1 to about 50:1, with a more preferred ratio from about 20:1 to about 30:1. Furthermore, it is to be understood that longer residence times within the reactor, for example up to about 5 sec, may be obtained if desired by introducing the feedstock within the reactor at a position towards the base of the reactor, by increasing the length of the reactor itself, by reducing the velocity of the heat carrier through the reactor (provided that there is sufficient velocity for the product vapour and heat carrier to exit the reactor), or a combination thereof. The preferred residence time is from about 0.5 to about 2sec.

[0049] Without wishing to be bound by theory, it is thought that the chemical upgrading of the feedstock that takes place within the reactor system as described above is in part due to the high loading ratios of feedstock to heat carrier that are used within the method of the present invention. Prior art loading ratios typically ranged from 5:1 to about 12.5:1. However, the loading ratios as described herein, of from about 15:1 to about 200:1, result in a very rapid, ablative and consistent transfer of heat from the heat carrier to the feedstock. The high volume and density of heat carrier within the mixing and conversion zones, ensures that a rapid and even processing temperature is achieved and maintained. In this way the temperatures required for cracking process described herein are easily controlled. This also allows for the use of relatively low temperatures to minimize over cracking, while ensuring that mild cracking of the feedstock is still achieved. Furthermore, with an increased density of heat carrier within the reactor, contaminants and undesired components present in the feedstock and reaction by-products, including metals (e.g. nickel and vanadium), coke, and to some extent nitrogen and sulphur, are readily adsorbed due to the large surface area of heat carrier present. This ensures efficient and optimal removal of contaminants from the feedstock, during the pyrolytic processing of the feedstock. As a larger surface area of heat carrier is employed, the heat carrier itself is not unduly contaminated, and any adsorbed metal or coke and the like is readily stripped during regeneration of the heat carrier. With this system the residence times can be carefully regulated in order to optimize the processing of the feedstock and liquid product yields.

[0050] The liquid product arising from the processing of heavy oil as described herein has significant conversion of the resid fraction when compared to heavy oil or bitumen feedstock. As a result the liquid product of the present invention, produced from the processing of heavy oil is characterized, for example, but which is not to be considered limiting, as having an API gravity of at least about 13 °, and more preferably of at least about 17°. However, as indicated above, higher API gravities may be achieved with a reduction in volume. For example, one liquid product obtained from the processing of heavy oil using the method of the present invention is characterized as having from about 10 to about 15% by volume bottoms, from about 10 to about 15% by volume light ends, with the remainder as middle distillates.

[0051] The viscosity of the liquid product produced from heavy oil is substantially reduced from initial feedstock levels, of from 250 cSt @ 80°C, to product levels of 4.5 to about 10 cSt @ 80°C, or from about 6343 cSt @ 40°C, in the feedstock, to about 15 to about 35 cSt @ 40°C in the liquid product. Following a single stage process, liquid yields of greater than 80 vol% and API gravities of about 17, with viscosity reductions of at least about 25 times that of the feedstock are obtained (@40°C). These viscosity levels are suitable for pipeline transport of the liquid product. Results from Simulated Distillation (SimDist; e.g. ASTM D 5307-97, HT 750, (NCUT)) analysis further reveals substantially different properties between the feedstock and liquid product as produced herein. For heavy oil feedstock, approx. 1 % (wt%) of the feedstock is distilled off below about 232°C (Kerosene fraction), approx. 8.7% from about 232° to about 327°C (Diesel fraction), and 51.5 % evolved above 538°C (Vacuum resid fraction; see Example 1 for complete analysis). SimDist analysis of the liquid product produced as described above may be characterized as having, but is not limited to having, the following properties: approx. 4% (wt%) evolving below about 232°C (Kerosene fraction), approx. 14.2% from about 232° to about 327°C (Diesel fraction), and 37.9% within the vacuum resid fraction (above 538°C). It is to be understood that modifications to these values may arise depending upon the composition of the feedstock used. These results demonstrate that there is a significant alteration in many of the components within the liquid product when compared with the heavy oil feedstock, with a general trend to lower molecular weight components that evolve earlier during SimDist analysis following rapid thermal processing.

[0052] Therefore, the present invention is directed to a liquid product obtained from single stage processing of heavy oil may that may be characterised by at least one of the following properties:

- having less than 50% of their components evolving at temperatures above 538°C (vacuum resid fraction);
- comprising from about 60% to about 95% of the product evolving below 538°. Preferably, from about 60% to about 80% evolves during Simulated Distillation below 538°C (i.e. before the vacuum resid. fraction);
- having from about 1.0 % to about 6 % of the liquid product evolve below 193 °C. Preferably from about 1.2 % to about 5% evolves below 193 °C (i.e. before the naphtha/kerosene fraction);
- having from about 2 % to about 6 % of the liquid product evolve between 193-232°C. Preferably from about 2.8% to about 5% evolves between 193-232°C (diesel fraction);

- having from about 12 % to about 25% of the liquid product evolve between 232-327°C. Preferably, from about 13 to about 18% evolves between 232-327°C (diesel fraction);
- having from about 5% to about 10% of the liquid product evolve between 327-360°C. Preferably, from about 6.0 to about 8.0% evolves between 327-360°C (light VGO fraction);
- having from about 40% to about 60% of the liquid product evolve between 360-538°C. Preferably, from about 30 to about 45% evolves between 360-538°C (Heavy VGO fraction);

[0053] Similarly following the methods as described herein, a liquid product obtained from processing bitumen feedstock following a single stage process, is characterized as having, and which is not to be considered as limiting, an increase in API gravity of at least about 10 (feedstock API is typically about 8.6). Again, higher API gravities may be achieved with a reduction in volume. The product obtained from bitumen is also characterised as having a density from about 0.93 to about 1.0 and a greatly reduced viscosity of at least about 20 fold lower than the feedstock (i.e. from about 15 g/ml to about 60 g/ml at 40°C in the product, v. the feedstock comprising about 1500 g/ml). Yields of liquid product obtained from bitumen are at least 60% by vol, and preferably greater than about 75% by vol. SimDist analysis also demonstrates significantly different properties between the bitumen feedstock and liquid product as produced herein. Highlights from SimDist analysis indicates that for a bitumen feedstock, approx. 1% (wt%) of the feedstock was distilled off below about 232°C (Kerosene fraction), approx. 8.6% from about 232° to about 327°C (Diesel fraction), and 51.2 % evolved above 538°C (Vacuum resid fraction; see Example 2 for complete analysis). SimDist analysis of the liquid product produced from bitumen as described above may be characterized, but is not limited to the following properties: approx. 5.7% (wt%) is evolved below about 232°C (Kerosene fraction), approx. 14.8% from about 232° to about 327°C (Diesel fraction), and 29.9% within the vacuum resid fraction (above 538°C). Again, these results may differ depending upon the feedstock used, however, they demonstrate the significant alteration in many of the components within the liquid product when compared with the bitumen feedstock, and the general trend to lower molecular weight components that evolve earlier during SimDist analysis in the liquid product produced from rapid thermal processing.

[0054] Therefore, the present invention is also directed to a liquid product obtained from single stage processing of bitumen which is characterised by having at least one of the following properties:

- having less than 50% of their components evolving at temperatures above 538°C (vacuum resid fraction);
- comprising from about 60% to about 95% of the product evolving below 538°. Preferably, from about 60% to about 80% evolves during Simulated Distillation below 538°C (i.e. before the vacuum resid. fraction);
- having from about 1.0 % to about 6 % of the liquid product evolve below 193°C. Preferably from about 1.2 % to about 5 % evolves below 193°C (i.e. before the naphtha/kerosene fraction);
- having from about 2 % to about 6 % of the liquid product evolve between 193-232°C. Preferably from about 2.0% to about 5% evolves between 193-232°C (diesel fraction);
- having from about 12 % to about 25% of the liquid product evolve between 232-327°C. Preferably, from about 13 to about 18% evolves between 232-327°C (diesel fraction);
- having from about 5% to about 10 % of the liquid product evolve between 327-360°C. Preferably, from about 6.0 to about 8.0% evolves between 327-360°C (light VGO fraction);
- having from about 40% to about 60% of the liquid product evolve between 360-538°C. Preferably, from about 30 to about 50% evolves between 360-538°C (Heavy VGO fraction);

[0055] The liquid product produced as described herein also exhibits a high degree of stability. Analysis of the liquid product over a 30 day period indicates negligible change in SimDist profile, viscosity, API and density for liquid products produced from either heavy oil or bitumen feedstocks (see Example 1 and 2).

[0056] Because the crack is not as severe, and the residence time short, unwanted reactions that can generate excessive amounts of undesirable aromatics and olefins. Furthermore, it has been found that contaminants such as metals and water are significantly reduced. There is no concentration of contaminants in the liquid product.

[0057] Also as disclosed herein, further processing of the liquid product obtained from the process of heavy oil or bitumen feedstock may take place following the method of this invention. Such further processing may utilize conditions that are very similar to the initial fast pyrolysis treatment of the feedstock, or the conditions may be modified to enhance removal of lighter products (a single-stage process with a mild crack) followed by more severe cracking of the recycled fraction (i.e. a two stage process).

[0058] In the first instance, that of further processing under similar conditions the liquid product from a first pyrolytic treatment is recycled back into the pyrolysis reactor in order to further upgrade the properties of the final product to produce a lighter product. In this arrangement the liquid product from the first round of pyrolysis is used as a feedstock for a second round of pyrolysis after the lighter fraction of the product has been removed from the product stream. Furthermore, a composite recycle may also be carried out where the heavy fraction of the product stream of the first process is fed back (recycled) into the reactor along with the addition of fresh feedstock (e.g. Figure 3, described in more

detail below).

[0059] The second method for upgrading a feedstock to obtain liquid products with desired properties involves a two-stage pyrolytic process (see Figures 2 and 3). This two stage processes comprises a first stage where the feedstock is exposed to conditions that mildly cracks the hydrocarbon components in order to avoid overcracking and excess gas and coke production. An example of these conditions includes, but is not limited to, injecting the feedstock at about 150°C into a hot gas stream comprising the heat carrier at the inlet of the reactor. The feedstock is processed with a residence time less than about one second within the reactor at less than 500°C, for example 300°C. The product, comprising lighter materials (low boilers) is separated (100, and 180, Figure 3), and removed following the first stage in the condensing system (40). The heavier materials (240), separated out at the bottom of the condenser (40) are collected subjected to a more severe crack within the reactor (20) in order to render a liquid product of reduced viscosity and high yield. The conditions utilized in the second stage include, but are not limited to, a processing temperature of about 530° to about 590°C. Product from the second stage is processed and collected as outlined in Figure 1 using a primary and secondary cyclone (100, 180, respectively) and primary and secondary condensers (40 and 50, respectively).

[0060] Following such a two stage process, an example of the product, which is not to be considered limiting, of the first stage (light boilers) is characterized with a yield of about 30 vol%, an API of about 19, and a several fold reduction in viscosity over the initial feedstock. The product of the high boiler fraction, produced following the processing of the recycle fraction in the second stage, is typically characterized with a yield greater than about 75 vol%, and an API gravity of about 12, and a reduced viscosity over the feedstock recycled fraction. SimDist analysis for liquid product produced from heavy oil feedstock is characterized with approx. 7.4% (wt%) of the feedstock was distilled off below about 232°C (Kerosene fraction v. 1.1 % for the feedstock), approx. 18.9% from about 232° to about 327°C (Diesel fraction v. 8.7% for the feedstock), and 21.7 % evolved above 538°C (Vacuum resid fraction v. 51.5% for the feedstock; see Example 1 for complete analysis). SimDist analysis for liquid product produced from bitumen feedstock is characterized with approx. 10.6 % (wt %) of the feedstock was distilled off below about 232°C (Kerosene fraction v. 1.0% for the feedstock), approx. 19.7% from about 232° to about 327°C (Diesel fraction v. 8.6% for the feedstock), and 19.5 % evolved above 538°C (Vacuum resid fraction v. 51.2% for the feedstock; see Example 2 for complete analysis).

[0061] Alternate conditions of a two stage process may include a first stage run where the feedstock is preheated to 150°C and injected into the reactor and processed at about 530° to about 620°C, and with a residence time less than one second within the reactor (see Figure 2). The product is collected using primary and secondary cyclones (100 and 180, respectively, Figures 2 and 4), and the remaining product is transferred to a hot condenser (250). The condensing system (Figure 4) is engineered to selectively recover the heavy asphaltene components using a hot condenser (250) placed before the primary condenser (40). The heavy asphaltenes are collected and returned to the reactor (20) for further processing (i.e. the second stage). The second stage utilizes reactor conditions operating at higher temperatures, or longer residence times, or at higher temperatures and longer residence times (e.g. injection at a lower point in the reactor), than that used in the first stage to optimize the liquid product. Furthermore, a portion of the product stream may be recycled to extinction following this method.

[0062] Yet another modification of the composite and two stage processing systems, termed "multi-stage" processing, comprises introducing the primary feedstock (raw feed) into the primary condenser (see figure 5) via line 280, and using the primary feedstock to rapidly cool the product vapours within the primary condenser. Product drawn from the primary condenser, is then recycled to the reactor via line 270 for combined "first stage" and "second stage" processing (i.e. recycled processing). The recycled feedstock is exposed to conditions that mildly crack the hydrocarbon components in order to avoid overcracking and excess gas and coke production. An example of these conditions includes, but is not limited to, injecting the feedstock at about 150°C into a hot gas stream comprise the heat carrier at the inlet of the reactor. The feedstock is processed with a residence time of less than about two seconds within the reactor at a temperature of between about 500 °C to about 600 °C. Preferably, the residence time is from about 0.8 to about 1.3 sec., and the reactor temperature is from about 520° to about 580°C The product, comprising lighter materials (low boilers) is separated (100, and 180, Figure 5), and removed in the condensing system (40). The heavier materials (240), separated out at the bottom of the condenser (40) are collected and reintroduced into the reactor (20) via line 270. Product gasses that exit the primary condenser (40) enter the secondary condenser (50) where a liquid product of reduced viscosity and high yield (300) is collected (see Example % for run analysis using this method). With multi-stage processing, the feedstock is recycled through the reactor in order to produce a product that can be collected from the second condenser, thereby upgrading and optimizing the properties of the liquid product.

[0063] Alternate feeds systems may also be used as required for one, two, composite or multi stage processing. For example, in the system outlined Figure 5, the feedstock (primary feedstock or raw feed) is obtained from the feed system (10), and is transported within line (280; which may be heated as previously described) to a primary condenser (40). The primary product obtained from the primary condenser may also be recycled back to the reactor (20) within a primary product recycle line (270). The primary product recycle line may be heated if required, and may also comprise a pre-heater unit (290) as shown in Figure 5, to re-heat the recycled feedstock to desired temperature for introduction within the reactor (20).

[0064] Following the recycle process as outlined above and graphically represented in Figure 5, product with yields of greater than 60, and preferably above 75 % (wt%), and with the following characteristics, which are not to be considered limiting in any manner, may be produced from either bitumen or heavy oil feedstocks: an API from about 14 to about 19; viscosity of from about 20 to about 100 (cSt @40°C); and a low metals content (see Example 5).

[0065] From SimDist analysis, liquid products obtained following multi-stage processing of heavy oil can be characterized by comprising at least one of the following properties:

- having less than 50 % of their components evolving at temperatures above 538°C (vacuum resid fraction);
- comprising from about 60% to about 95% of the product evolving below 538°. Preferably, from about 70% to about 90%, and more preferably from about 75 to about 87% of the product evolves during Simulated Distillation below 538°C (i.e. before the vacuum resid. fraction) ;
- having from about 1.0% to about 6 % of the liquid product evolve below 193°C. Preferably from about 1.2 % to about 5%, and more preferably from about 1.3% to about 4.8% evolves below 193 °C (i.e. before the naphtha/kerosene fraction);
- having from about 2 % to about 6 % of the liquid product evolve between 193-232°C. Preferably from about 2.8% to about 5% evolves between 193-232°C (diesel fraction);
- having from about 15 % to about 25% of the liquid product evolve between 232-327°C. Preferably, from about 18.9 to about 23.1% evolves between 232-327°C (diesel fraction);
- having from about 8% to about 15 % of the liquid product evolve between 327-360 °C. Preferably, from about 8.8 to about 10.8% evolves between 327-360°C (light VGO fraction);
- having from about 40% to about 60% of the liquid product evolve between 360-538°C. Preferably, from about 42 to about 55% evolves between 360-538°C (Heavy VGO fraction);

[0066] The liquid product obtained from multi-stage processing of bitumen may be characterized as having at least one of the following properties:

- having less than 50% of their components evolving at temperatures above 538°C (vacuum resid fraction);
- comprising from about 60% to about 95% of the product evolving below 538°. Preferably, from about 60 % to about 85 % evolves during Simulated Distillation below 538°C (i.e. before the vacuum resid. fraction);
- having from about 1.0% to about 8% of the liquid product evolve below 193°C. Preferably from about 1.5% to about 7% evolves below 193°C (i.e. before the naphtha/kerosene fraction);
- having from about 2 % to about 6 % of the liquid product evolve between 193-232°C. Preferably from about 2.5% to about 5% evolves between 193-232°C (diesel fraction);
- having from about 12 % to about 25% of the liquid product evolve between 232-327°C. Preferably, from about 15 to about 20% evolves between 232-327°C (diesel fraction);
- having from about 5% to about 12 % of the liquid product evolve between 327-360°C. Preferably, from about 6.0 to about 10.0% evolves between 327-360°C (light VGO fraction);
- having from about 40% to about 60% of the liquid product evolve between 360-538°C. Preferably, from about 35 to about 50% evolves between 360-538°C (Heavy VGO fraction);

[0067] Collectively these results show that a substantial proportion of the components with low volatility in either of the feedstocks have been converted to components of higher volatility (light naphtha, kerosene and diesel) in the liquid product. These results demonstrate that the liquid product are substantially upgraded, and exhibits properties suitable for transport.

[0068] The above description is not intended to limit the claimed invention in any manner, furthermore, the discussed combination of features might not be absolutely necessary for the inventive solution.

[0069] The present invention will be further illustrated in the following examples. However it is to be understood that these examples are for illustrative purposes only, and should not be used to limit the scope of the present invention in any manner.

Example 1: Heavy Oil (Single Stage)

[0070] Pyrolytic processing of Saskatchewan Heavy Oil and Athabasca Bitumen (see Table 1) were carried out over a range of temperatures using a pyrolysis reactor as described in US 5,792,340.

Table 1: Characteristics of heavy oil and bitumen feedstocks

Compound	Heavy Oil ¹⁾	Bitumen ²⁾
Carbon (wt%)	84.27	83.31
Hydrogen (wt%)	10.51	10.31
Nitrogen (wt%)	< 0.5	< 0.5
Sulphur (st%)	3.6	4.8
Ash (wt%)	0.02	0.02
Vanadium (ppm)	127	204
Nickel (ppm)	nd	82
Water content (wt%)	0.8	0.19
Gravity API°	11.0	8.6
Viscosity @ 40°C (cSt)	6343	30380
Viscosity @ 60°C (cSt)	892.8	1268.0
Viscosity @ 80°C (cSt)	243.4	593.0
Aromaticity (C13 NMR)	0.31	0.35
1) Saskatchewan Heavy Oil		
2) Athabasca Bitumen (neat)		

[0071] Briefly the conditions of processing include a reactor temperature from about 500° to about 620°C. Loading ratios for particulate heat carrier (silica sand) to feedstock of from about 20:1 to about 30:1 and residence times from about 0.35 to about 0.7 sec. These conditions are outlined in more detail below (Table 2).

Table 2: Single stage processing of Saskatchewan Heavy Oil

Crack Temp °C	Viscosity @ 40°C (cSt)	Yield wt%	Density @ 15° g/ml	API°	Yield Vol%
620	4.6 ¹⁾	71.5	0.977	13.3	72.7
592	15.2 ¹⁾	74.5	0.970	14.4	76.2
590	20.2	70.8	0.975	13.6	72.1
590	31.6	75.8	0.977	13.3	77.1
560	10.0 ¹⁾	79.9 ²⁾	0.963	15.4	82.3 ²⁾
560	10.0 ¹⁾	83.0 ³⁾	0.963	16.2 ³⁾	86.3 ³⁾
550	20.8	78.5	0.973	14.0	80.3
550 ⁴⁾	15.7	59.8 ²⁾	0.956	16.5	61.5 ²⁾
550 ⁴⁾	15.7	62.0 ³⁾	0.956	18.3 ^{2,3)}	65.1 ³⁾
530	32.2	80.9 ²⁾	0.962	15.7	82.8 ²⁾
530	32.2	83.8 ³⁾	0.962	16.6 ³⁾	87.1 ³⁾

1) Viscosity @ 80°C

2) Yields do not include overhead condensing

3) Estimated yields and API with overhead condensing

4) Not all of the liquids were captured in this trial.

[0072] The liquid products of the runs at 620°C, 592°C and 560°C were analysed for metals, water and sulphur content. These results are shown in Table 3. Nickel, Vanadium and water levels were reduced 72, 69 and 87%, respectively, while sulphur and nitrogen remained the same or were marginally reduced. No metals were concentrated in the liquid product.

Table 3: Metal Analysis of Liquid Products (ppm)¹⁾

Component	Saskatchewan Heavy Oil	Run @ 620°C	Run @ 592°C	Run @ 560°C
Aluminum	< 1	< 1	11	< 1
Iron	< 1	2	4	< 1
Nickel	44	10	12	9
Zinc	2	< 1	2	1

(continued)

Component	Saskatchewan Heavy Oil	Run @ 620°C	Run @ 592°C	Run @ 560°C
Calcium	4	2	3	1
Magnesium	3	1	2	< 1
Boron	21	42	27	< 1
Sodium	6	5	5	4
Silicon	1	10	140	4
Vanadium	127	39	43	39
Potassium	7	7	< 1	4
Water(wt%)	0.78	0.19	0.06	.10
Sulphur (wt%)	3.6	3.5	3.9	3.5
1) Copper, tin, chromium, lead, cadmium, titanium, molybdenum, barium and manganese all showed less than 1 ppm in feedstock and liquid products.				

[0073] The gas yields for two runs are presented in Table 4.

Table 4: Gas analysis of Pyrolysis runs		
Gas (wt%)	Run @620°C	Run @ 560°C
Total Gas Yield	11.8	7.2
Ethylene	27.0	16.6
Ethane	8.2	16.4
Propylene	30.0	15.4
Methane	24.0	21.0

[0074] The pour point of the feedstock improved and was reduced from 32°F to about -54°F. The Conradson carbon reduced from 12. wt% to about 6.6 wt%.

[0075] Based on the analysis of these runs, higher API values and product yields were obtained for crack temperatures of about 530 to about 560°C. At these temperatures, API gravities of 14 to 18.3, product yields of from about 80 to about 87 vol%, and viscosities of from about 15 to about 35 cSt (@40°C) or about 10 cST (@80°C) were obtained (the yields from the 550°C run are not included in this range as the liquid yield capture was not optimized during this run). These liquid products reflect a significant degree of upgrading, and exhibit qualities suitable for pipeline transport.

[0076] Simulated distillation (SimDist) analysis of feedstock and liquid product obtained from several separate runs is present in Table 5. SimDist analysis followed the protocol outlined in ASTM D 5307-97, which reports the residue as anything with a boiling point higher than 538°C. Other methods for SimDist may also be used, for example HT 750 (NCUT; which includes boiling point distribution through to 750°C). These results indicate that over 50 % of the components within the feedstock evolve at temperatures above 538°C. These are high molecular weight components with low volatility. Conversely, in the liquid product, the majority of the components, approx 62.1 % of the product are more volatile and evolve below 538°C.

Table 5: SimDist analysis of feedstock and liquid product after single stage processing (Reactor temp 538°C)

Fraction	Temp (°C)	Feedstock	R245
Light Naphtha	< 71	0.0	0.5
Light/med Naphtha	71-100	0.0	0.3
Med Naphtha	100-166	0.0	1.4
Naphtha/Kerosene	166-193	0.1	1.0
Kerosene	193-232	1.0	2.8
Diesel	232-327	8.7	14.2
Light VGO	327-360	5.2	6.5
Heavy VGO	360-538	33.5	35.2
Vacuum Resid.	> 538	51.5	37.9

[0077] The feedstock can be further characterized with approx. 0.1 % of its components evolving below 193°C (naphtha/kerosene fraction), v. approx. 6% for the liquid product. The diesel fraction also demonstrates significant differences between the feedstock and liquid product with 8.7% and 14.2 % evolving at this temperature range (232-327 °C), respectively. Collectively these results show that a substantial proportion of the components with low volatility in the feedstock have been converted to components of higher volatility (light naphtha, kerosene and diesel) in the liquid product.

[0078] Stability of the liquid product was also determined over a 30 day period (Table 6). No significant change in the viscosity, API or density of the liquid product was observed over a 30 day period.

Table 6: Stability of liquid products after single stage processing

Fraction	Time=0	7 days	14 days	30days
Density @ 15.6°C (g/cm ³)	0.9592	0.9590	0.9597	0.9597
API (deg. API)	15.9	15.9	15.8	15.8
Viscosity @40°C (cSt)	79.7	81.2	81.2	83.2

Example 2 Bitumen (single stage)

[0079] Several runs using Athabasca Bitumen were conducted using the pyrolysis reactor described in US 5,792,340. The conditions of processing included a reactor temperature from 520° to about 590°C. Loading ratios for particulate heat carrier to feedstock of from about 20:1 to about 30:1, and residence times from about 0.35 to about 1.2 sec. These conditions, and the resulting liquid products are outlined in more detail below (Table 7).

Table 7: Single Stage Processing with Undiluted Athabasca Bitumen

Crack Temp	Viscosity @ 40°C (cSt)	Yield wt%	Density @ 15°C	Metals V (ppm)*	Metals Ni (ppm)**	API
519°C	205	81.0	nd	nd	nd	13.0
525°C	201	74.4	0.979	88	24	12.9
528°C	278	82.7	nd	nd	nd	12.6
545 °C	151	77.4	0.987	74	27	11.8
590°C	25.6	74.6	0.983	nd	nd	12.4

* feedstock V 209 ppm

** feedstock Ni 86 ppm

[0080] These results indicate that undiluted bitumen may be processed according to the method of this invention to produce a liquid product with reduced viscosity from greater than 1300 cSt (@40°C) to about 25.6 - 200 cSt (@40°C) (depending on the run conditions; see also Tables 8 and 9), with yields of over 75 % to about 85%, and an improvement in the product API from 8.6 to about 12-13. Again, as per Example 1, the liquid product exhibits substantial upgrading of the feedstock. SimDist analysis, and other properties of the liquid product are presented in Table 8, and stability studies in Table 9.

Table 8: Properties and SimDist analysis of feedstock and liquid product after single stage processing (Reactor temp. 545°C).

Fraction	Temp (°C)	Feedstock	R239	
			14 days	30 days
Density @15.5°C	-		0.9871	0.9876
API	-		11.7	11.6
Viscosity @40°C	-		162.3	169.4
Light Naphtha	< 71	0.0	0.2	0.1
Light/med Naphtha	71-100	0.0	0.2	0.2
Med Naphtha	100-166	0.0	1.5	1.4
Naphtha/Kerosene	166-193	0.1	1.0	1.0
Kerosene	193-232	0.9	3.1	3.0
Diesel	232-327	8.6	15.8	14.8
Light VGO	327-360	5.2	7.9	7.6

(continued)

Fraction	Temp (°C)	Feedstock	R239	
			14 days	30 days
Heavy VGO	360-538	34.0	43.9	42.0
Vacuum Resid.	538	51.2	26.4	29.9

Table 9: Stability of liquid products after single stage processing (reactor temperature 525°C)

Fraction	Temp (°C)	Feedstock	day 0	R232		
				7 days	14 days	30days
Density @ 15.6°C*	-	1.0095	0.979	0.980	0.981	0.981
API	-	8.5	12.9	12.7	12.6	12.6
Viscosity @40°C**	-	30380	201.1	213.9	214.0	218.5
Light Naphtha	< 71	0.0	0.1	0.1	0.1	0.1
Light/med Naphtha	71-100	0.0	0.1	0.1	0.1	0.1
Med Naphtha	100-166	0.0	1.5	1.5	1.5	1.4
Naphtha/Kerosene	166-193	0.1	1.0	1.0	1.0	1.1
Kerosene	193-232	1.0	2.6	2.6	2.6	2.7
Diesel	232-327	8.7	14.1	14.1	14.3	14.3
Light VGO	327-360	5.2	7.3	7.3	7.4	7.4
Heavy VGO	360-538	33.5	41.3	41.3	41.7	42.1
Vacuum Resid.	> 538	51.5	32.0	32.0	31.2	30.8

*g./cm³
**cSt

[0081] The slight variations in the values presented in the stability studies (Table 9 and other stability studies disclosed herein) are within the error of the test methods employed, and are acceptable within the art. These results demonstrate that the liquid products are stable.

[0082] These results indicate that over 50% of the components within the feedstock evolve at temperatures above 538°C (vacuum resid fraction). This fraction is characterized by high molecular weight components with low volatility. Conversely, over several runs, the liquid product is characterized as comprising approx 68 to 74 % of the product that are more volatile and evolve below 538°C. The feedstock can be further characterized with approx. 0.1 % of its components evolving below 193 °C (naphtha/kerosene fraction), v. approx. 2.7 to 2.9% for the liquid product. The diesel fraction also demonstrates significant differences between the feedstock and liquid product with 8.7% (feedstock) and 14.1 to 15.8% (liquid product) evolving at this temperature range (232-327°C). Collectively these results show that a substantial proportion of the components with low volatility in the feedstock have been converted to components of higher volatility (light naphtha, kerosene and diesel) in the liquid product. These results demonstrate that the liquid product is substantially upgraded, and exhibits properties suitable for transport.

Example 3: Composite/recycle of feedstock

[0083] The pyrolysis reactor as described in US 5,792,340 may be configured so that the recovery condensers direct the liquid products into the feed line to the reactor (see Figures 3 and 4).

[0084] The conditions of processing included a reactor temperature ranging from about 530° to about 590°C. Loading ratios for particulate heat carrier to feedstock for the initial and recycle run of about 30:1, and residence times from about 0.35 to about 0.7 sec were used. These conditions are outlined in more detail below (Table 10). Following pyrolysis of the feedstock, the lighter fraction was removed and collected using a hot condenser placed before the primary condenser (see Figure 4), while the heavier fraction of the liquid product was recycled back to the reactor for further processing (also see Figure 3). In this arrangement, the recycle stream (260) comprising heavy fractions was mixed with new feedstock (270) resulting in a composite feedstock (240) which was then processed using the same conditions as with the initial run within the pyrolysis reactor.

Table 10: Composite/Recycle operation using Saskatchewan Heavy Crude Oil and Undiluted Athabasca Bitumen

Feedstock	Crack Temp °C	Yield Vol %	API°	Recycle ⁴⁾ Yield vol%	Recycle ⁴⁾ API°
Heavy Oil	590	77.1 ¹⁾	13.3	68.6	17.1
	560	86.3 ²⁾	16.2	78.1	21.1
	550	50.1 ¹⁾	14.0	71.6	17.8
	550	65.1 ^{2,3)}	18.3	56.4	22.9
	530	87.1 ²⁾	16.6	78.9	21.0
Bitumen	590	75.2 ²⁾	12.4	67.0	16.0

1) Yield and API gravity include overhead condensing (actual)

2) Yield and API gravity include overhead condensing (estimated)

3) Not all of the liquid was recovered in this run

4) These values represent the total recovery of product following the recycle run, and presume the removal of approximately 10% heavy fraction which is recycled to extinction. This is therefore a conservative estimate of yield as some of the heavy fraction will produce lighter components that enter the product stream, since not all of the heavy fraction will end up as coke.

[0085] The API gravity increased from 11.0 in the heavy oil feedstock to about 13 to about 18.5 after the first treatment cycle, and further increases to about 17 to about 23 after a second recycle treatment. A similar increase in API is observed for bitumen having a API of about 8.6 in the feedstock, which increase to about 12.4 after the first run and to 16 following the recycle run. With the increase in API, there is an associated increase in yield from about 77 to about 87 % after the first run, to about 67 to about 79 % following the recycle run. Therefore associated with the production of a lighter product, there is a decrease in liquid yield. However, an upgraded lighter product may be desired for transport, and recycling of liquid product achieves such a product.

Example 4: Two-Stage treatment of Heavy Oil

[0086] Heavy oil or bitumen feedstock may also be processed using a two-stage pyrolytic process which comprises a first stage where the feedstock is exposed to conditions that mildly crack the hydrocarbon components in order to avoid overcracking and excess gas and coke production. Lighter materials are removed following the processing in the first stage, and the remaining heavier materials are subjected to a more severe crack at a higher temperature. The conditions of processing within the first stage include a reactor temperature ranging from about 510 to about 530°C (data for 515°C given below), while in the second stage, a temperature from about 590° to about 800°C (data for 590°C presented in table 11) was employed. The loading ratios for particulate heat carrier to feedstock range of about 30:1, and residence times from about 0.35 to about 0.7 sec for both stages. These conditions are outlined in more detail below (Table 11).

Table 11: Two-Stage Runs of Saskatchewan Heavy Oil

Crack Temp. °C	Viscosity @ 80°C (cSt)	Yield wt%	Density @ 15°C g/ml	API°	Yield Vol% ¹⁾
515	5.3	29.8	0.943	18.6	31.4
590	52.6	78.9	0.990	11.4	78.1
515 & 590	nd	nd	nd	13.9	86.6

"nd" means not determined

1)Light condensable materials were not captured. Therefore these values are conservative estimates.

[0087] These results indicate that a mild initial crack which avoids overcracking light materials to gas and coke, followed by a more severe crack of the heavier materials produces a liquid product characterized with an increased API, while still exhibiting good product yields.

[0088] Other runs using a two stage processes, involved injecting the feedstock at about 150°C into a hot gas stream maintained at about 515°C and entering the reactor at about 300°C (processing temperature). The product, comprising lighter materials (low boilers) was separated and removed following the first stage in the condensing system. The heavier materials, separated out at the bottom of the cyclone were collected subjected to a more severe crack within the reactor in order to render a liquid product of reduced viscosity and high yield. The conditions utilized in the second stage were

a processing temperature of between about 530° to about 590°C. Product from the second stage was processed and collected.

[0089] Following such a two stage process the product of the first stage (light boilers) is characterized with a yield of about 30 vol%, an API of about 19, and a several fold reduction in viscosity over the initial feedstock. The product of the high boiling point fraction, produced following the processing of the recycle fraction in the second stage, is typically characterized with a yield greater than about 75 vol % , and an API gravity of about 12, and a reduced viscosity over the feedstock recycled fraction.

Example 5: "Multi-Stage" treatment of Heavy Oil and Bitumen, using Feedstock for Quenching within Primary Condenser.

[0090] Heavy oil or bitumen feedstock may also be processed using a "Multi-stage" pyrolytic process as outlined in Figure 5. In this system, the pyrolysis reactor described in US 5,792,340 is configured so that the primary recovery condenser directs the liquid product into the feed line back to the reactor, and feedstock is introduced into the system at the primary condenser where it quenches the product vapours produced during pyrolysis.

[0091] The conditions of processing included a reactor temperature ranging from about 530° to about 590°C. Loading ratios for particulate heat carrier to feedstock for the initial and recycle run of from about 20:1 to about 30:1, and residence times from about 0.35 to about 1.2 sec were used. These conditions are outlined in more detail below (Table 12). Following pyrolysis of the feedstock, the lighter fraction is forwarded to the secondary condenser while the heavier fraction of the liquid product obtained from the primary condenser is recycled back to the reactor for further processing (Figure 5).

Table 12: Characterization of the liquid product obtained following Multi-Stage processing of Saskatchewan Heavy Oil and Bitumen

Crack Temp. °C	Viscosity @ 40°C (cSt)	Yield wt%	Density @ 15.6°C g/ml	API°	Yield Vol% ¹⁾
Heavy Oil					
543	80	62.6	0.9592	15.9	64.9
557	24	58.9	0.9446	18.2	62.1
561	53	70.9	0.9568	16.8	74.0
Bitumen					
538	40	61.4	0.9718	14.0	71.1

[0092] The liquid products produced from multi-stage processing of feedstock exhibit properties suitable for transport with greatly reduced viscosity down from 6343 cSt (@40°C) for heavy oil and 30380 cSt (@40°C) for bitumen. Similarly, the API increased from 11 (heavy oil) to from 15.9 to 18.2, and from 8.6 (bitumen) to 14.7. Furthermore, yields for heavy oil under these reaction conditions are from 59 to 68 % for heavy oil, and 82 % for bitumen.

Table 13: Properties and SimDist of liquid products prepared from Heavy Oil using the multi- stage Process (for feedstock properties see Tables 1 and 5).

Fraction	Temp (°C)	R241*		R242**	R244***
		Day 0	Day 30	Day 30	
Density @ 15.6°C	-	0.9592	0.9597	0.9465	0.9591
API	-	15.9	15.8	17.8	15.9
Viscosity @40°C	-	79.7	83.2	25.0	49.1
Light Naphtha	< 71	0.0	0.2	0.3	0.3
Light/med Naphtha	71-100	0.0	0.1	0.2	0.3
Med Naphtha	100-166	0.1	0.4	2.5	1.8
Naphtha/ Kerosene	166-193	0.6	0.6	1.8	1.5
Kerosene	193-232	2.8	2.5	5.0	3.5

(continued)

Fraction	Temp (°C)	Day 0	R241*	R242**	R244***
			Day 30	Day 30	
Diesel	232-327	21.8	21.0	23.1	18.9
Light VGO	327-360	10.8	10.2	9.9	8.8
Heavy VGO	360-538	51.1	45.0	44.9	43.2
Vacuum	> 538	12.7	20.0	12.3	21.7
Resid.					

* reactor temp. 543°C

** reactor temp. 557°C

*** reactor temp. 561 °C

[0093] Under these run conditions the API increased from 11 to about 15.9 to 17.8. Product yields of 62.6 (wt%; R241), 58.9 (wt%; R242) and 70.9 (wt%; R244) were achieved along with greatly reduced viscosity levels. These liquid products have been substantially upgraded over the feedstock and exhibit properties suitable for pipeline transport.

[0094] SimDist results indicate that over 50 % of the components within the feedstock evolve at temperatures above 538°C (vacuum resid fraction), while the liquid product is characterized as comprising approx 78 to 87 % of the product that are more volatile and evolve below 538°C. The feedstock can be further characterized with approx. 0.1 % of its components evolving below 193 °C (naphtha/kerosene fraction), v. approx. 1.3 to 4.8 % for the liquid product. The kerosene and diesel fractions also demonstrates significant differences between the feedstock and liquid product with 1% of the feedstock fraction evolving between 193-232°C v. 2.8 to 5% for the liquid product, and with 8.7% (feedstock) and 18.9 to 23.1 % (liquid product) evolving at this temperature range (232-327°C; diesel). Collectively these results show that a substantial proportion of the components with low volatility in the feedstock have been converted to components of higher volatility (light naphtha, kerosene and diesel) in the liquid product. These results demonstrate that the liquid product is substantially upgraded, and exhibits properties suitable for transport.

Table 14: Properties and SimDist of liquid products prepared from Bitumen following "Two Stage" processing (reactor temp. 538°C; for feedstock properties see Tables 1, 8 and 9).

Fraction	Temp (°C)	R243
Density @ 15.6°C	-	0.9737
API	-	13.7
Viscosity @40°C	-	45.4
Light Naphtha	<71	0.3
Light/med Naphtha	71-100	0.4
Med Naphtha	100-166	3.6
Naphtha/Kerosne	166-193	1.9
Kerosene	193-232	4.4
Diesel	232-327	19.7
Light VGO	327-360	9.1
Heavy VGO	360-538	41.1
Vacuum Resid.	538	19.5

[0095] Under these run conditions the API increased from 8.6 to about 14. A product yield of 68.4 (wt%) was obtained along with greatly reduced viscosity levels (from 30380 cSt @40°C in the feedstock, to approx. 45 cSt in the liquid product).

[0096] Simulated distillation analysis demonstrates that over 50% of the components within the feedstock evolve at temperatures above 538°C (vacuum resid fraction) while 80.5% of the liquid product evolves below 538°C. The feedstock can be further characterized with approx. 0.1 % of its components evolving below 193 °C (naphtha/kerosene fraction), v. 6.2 % for the liquid product. The diesel fraction also demonstrates significant differences between the feedstock and liquid product with 8.7% (feedstock) and 19.7% (liquid product) evolving at this temperature range (232-327°C). Collectively these results show that a substantial proportion of the components with low volatility in the feedstock have been converted to components of higher volatility (light naphtha, kerosene and diesel) in the liquid product. These results demonstrate that the liquid product is substantially upgraded, and exhibits properties suitable for transport.

[0097] All citations are herein incorporated by reference.

[0098] The present invention has been described with regard to preferred embodiments. However, it will be obvious

to persons skilled in the art that a number of variations and modifications can be made without departing from the scope of the invention as described herein.

[0099] The present application is a divisional application based on earlier European Application No 00916713.1 which was in turn derived from PCT Application No PCT/CA00/00369. The following clauses, which correspond to the claims of that earlier Application as filed, form part of the present disclosure and in particular form further aspects of the invention, whether or not they appear in the present claims.

(A) A method for upgrading a heavy hydrocarbon feedstock comprising:

i) providing a particulate heat carrier into an upflow reactor;

ii) introducing said heavy hydrocarbon feedstock into said upflow reactor at at least one location above that of the particulate heat carrier so that a loading ratio of said particulate heat carrier to said heavy hydrocarbon feedstock is from about 10: 1 to about 200: 1;

iii) allowing said heavy hydrocarbon feedstock to interact with said heat carrier with a residence time of less than about 5 seconds, to produce a product stream;

iv) separating said product stream from said particulate heat carrier;

v) regenerating said particulate heat carrier; and

vi) collecting a gaseous and liquid product from said product stream, wherein said liquid product exhibits an increased API gravity, a reduced pour point, reduced viscosity and a reduced level of contaminants over that of said feedstock.

(B) The method of clause (A), wherein in said step of introducing (step ii)), said loading ratio is from about 20: 1 to about 30: 1.

(C) The method of clause (A), wherein in said step of introducing (step ii)), said heavy hydrocarbon feedstock is either heavy oil or bitumen.

(D) The method of clause (A), wherein in said step of introducing (step ii)), said feedstock is pre-heated prior to its introduction into said upflow reactor.

(E) The method of clause (A), wherein in said step of introducing (step ii)), the temperature of said upflow reactor is less than 750°C, and wherein said residence time is from about 0.5 to about 2.0 seconds.

(F) The method of clause A, wherein in said step of providing (step i)), said particulate heat carrier is silica sand.

(G) The method of clause (A), wherein said contaminants are deposited onto said heat carrier, said contaminants including Conradson carbon and metals.

(H) The method of clause (G), wherein said metals include nickel and vanadium.

(I) The method of clause (A), wherein said contaminants include bottom sediments and water (BS&W).

(J) The method of clause (A), wherein, in said step of allowing (step iii)), said product stream of a first pyrolysis run is separated into a lighter fraction and a heavier fraction, collecting said lighter fraction from said product stream, and recycling said heavier fraction back into said upflow reactor for further processing within a second pyrolysis run to produce a second product stream.

(K) The method of clause (J), wherein said further processing includes mixing said heavier fraction with said particulate heat carrier, wherein said particulate heat carrier of said second pyrolysis run is at a temperature at about, or above, that used in the processing of said feedstock within said first pyrolysis run.

(L) The method of clause (K), wherein said heavier fraction is added to unprocessed feedstock prior to being introduced into said upflow reactor for said second pyrolysis run.

(M) The method of clause (L), wherein the temperature of said heat carrier within said first pyrolysis run is from about 300°C to about 590°C, and the temperature of said second pyrolysis run is from about 530°C to about 700°C, and wherein said residence time of said second pyrolysis run is the same as, or longer than, the residence time of said first pyrolysis run.

(N) The method of clause (J), wherein said particulate heat carrier is separated from second product stream, and a second product is collected from said second product stream.

(O) The method of clause (J), wherein said product stream of said first pyrolysis run is treated within a hot condenser prior to recovery of said light fraction and said heavy fraction.

(P) An upgraded heavy oil characterized by the following properties:

- i) an API gravity from about 13 to about 23;
- ii) a density at 15°C from about 0.92 g/ml to about 0.98 g/ml;
- iii) a viscosity at 40°C, cSt, from about 15 to about 300;
- iv) a reduced Vanadium content of about 60 to about 100 ppm; and
- v) a reduced Nickel content of about 10 to about 50 ppm.

(Q) An upgraded bitumen characterized by the following properties:

- i) an API gravity from about 10 to about 21;
- ii) a density at 15°C from about 0.93 g/ml to about 1.0 g/ml;
- iii) a viscosity at 40°C, cSt, from about 15 to about 300;
- iv) a reduced Vanadium content of about 60 to about 100 ppm; and
- v) a reduced Nickel content of about 10 to about 50 ppm.

(R) An upgraded heavy oil produced by the method of clause (A).

(S) An upgraded bitumen produced by the method of clause (A).

(T) An upgraded heavy oil produced by the method of clause (J).

(U) An upgraded bitumen produced by the method of clause (J).

(V) An upflow pyrolysis reactor for heavy hydrocarbon feedstock upgrading comprising:

- i) a means for pre-heating said heavy hydrocarbon feedstock;
- ii) at least one injection means at at least one of a plurality of locations along said upflow reactor, said at least one injection means for introducing said heavy hydrocarbon feedstock into said upflow reactor;
- iii) an inlet for introducing a particulate heat carrier, said inlet located below said at least one injection means, said particulate heat carrier present at a loading ratio of at least 10: 1;
- iv) a conversion section within said upflow reactor;
- v) a separation means at an outlet of said upflow reactor to separate the gaseous and liquid products from said particulate heat carrier;

vi) a particulate heat carrier regeneration means;

vii) a particulate heat carrier recirculation line from said regeneration means to said inlet for supplying said particulate heat carrier to said mixing section;

viii) a condensing means for cooling and condensing said liquid products.

(W) The upflow reactor of clause (V), wherein said plurality of locations includes locations distributed along the length of said reactor.

(X) The upflow reactor of clause (W), further comprising a hot condenser means prior to said condensing means.

(Y) The upflow reactor of clause (W), wherein said particulate heat carrier is silica sand, and said loading ratio is from about 20: 1 to about 30: 1.

(Z) The upflow reactor of clause (X), further comprising a heavy fraction product recirculation means from said hot condensing means to said injection means of said upflow reactor.

(AA) A liquid product characterized in having at least one of the following properties:

i) less than 50% of the components evolving at temperatures above 538°C during simulated distillation;

ii) from about 60% to about 95% of the product evolving below 538° during simulated distillation;

iii) from about 1.0% to about 10% of the liquid product evolve below 193°C during simulated distillation;

iv) from about 2% to about 6% of the liquid product evolve between 193- 232°C during simulated distillation;

v) from about 10% to about 25% of the liquid product evolve between 232-327°C during simulated distillation;

vi) from about 6 % to about 15 % of the liquid product evolve between 327- 360°C during simulated distillation; and

vii) from about 34.5% to about 60% of the liquid product evolve between 360-538°C during simulated distillation.

(BB) A method for upgrading a heavy hydrocarbon feedstock comprising:

i) introducing a particulate heat carrier into an upflow reactor;

ii) introducing a feedstock into said upflow reactor at at least one location above that of the particulate heat carrier so that a loading ratio of said particulate heat carrier to said heavy hydrocarbon feedstock is from about 10: 1 to about 200: 1;

iii) allowing said feedstock to interact with said heat carrier with a residence time of less than about 1 second, to produce a product stream;

iv) separating said product stream from said particulate heat carrier;

v) regenerating said particulate heat carrier; and

vi) collecting a gaseous and liquid product from said product stream, wherein said feedstock is obtained from the direct contact between said product stream and a heavy hydrocarbon feedstock within a condenser.

(CC) An upgraded heavy oil produced by the method of clause (BB).

(DD) An upgraded bitumen produced by the method of clause (BB).

Claims

1. A use of an upgraded liquid feedstock as a product for pipeline transport to permit further processing of the upgraded liquid feedstock elsewhere, the upgraded liquid feedstock produced from a heavy hydrocarbon feedstock which is not transportable by pipeline to an offsite location without addition of diluents by a method comprising:
 - i) providing a particulate heat carrier into an upflow reactor;
 - ii) introducing said heavy hydrocarbon feedstock in a preheated state into said upflow reactor at at least one location above that of the particulate heat carrier so that a loading ratio of said particulate heat carrier to said heavy hydrocarbon feedstock is from about 10:1 to about 200:1;
 - iii) allowing said heavy hydrocarbon feedstock to interact with said heat carrier with a residence time of less than about 5 seconds, to produce a product stream;
 - iv) separating said product stream from said particulate heat carrier;
 - v) regenerating said particulate heat carrier;
 - vi) collecting said upgraded liquid feedstock from said product stream, wherein said upgraded liquid feedstock exhibits an increased API gravity, a reduced pour point, reduced viscosity and a reduced level of contaminants over that of said heavy hydrocarbon feedstock.
2. The use of claim 1, wherein in said step of introducing (step ii)), said loading ratio is from about 20:1 to about 30:1.
3. The use of claim 1, wherein in said step of introducing (step ii)), said heavy hydrocarbon feedstock is a heavy oil or a bitumen.
4. The use of claim 1, wherein the temperature of the upflow reactor is less than 750°C, and wherein said residence time of the heavy hydrocarbon feedstock is from about 0.5 to about 2.0 seconds.
5. The use of claim 1, wherein in said step of providing (step i)), said particulate heat carrier is silica sand.
6. The use of claim 1, wherein said contaminants are deposited onto said heat carrier, said contaminants including Conradson carbon and metals.
7. The use of claim 6, wherein said metals include nickel and vanadium.
8. The use of claim 1, wherein said contaminants include bottom sediments and water (BS&W).
9. The use according to claim 1, wherein, in said step of allowing (step iii)), said product stream of a first pyrolysis run is separated into a lighter fraction and a heavier fraction, collecting said lighter fraction from said product stream, and recycling said heavier fraction back into said upflow reactor for further processing within a second pyrolysis run to produce a second product stream.
10. The use according to claim 9 wherein said further processing includes mixing said heavier fraction with said particulate heat carrier, wherein said particulate heat carrier of said second pyrolysis run is at a temperature at about, or above, that used in the processing of said feedstock within said first pyrolysis run.
11. The use according to claim 10, wherein said heavier fraction is added to unprocessed feedstock prior to being introduced into said upflow reactor for said second pyrolysis run.
12. The use according to claim 11, wherein the temperature of said heat carrier within said first pyrolysis run is from about 300°C to about 590°C, and the temperature of said second pyrolysis run is from about 530°C to about 700°C, and wherein said residence time of said second pyrolysis run is the same as, or longer than, the residence time of said first pyrolysis run.
13. The use according to claim 9, wherein said particulate heat carrier is separated from second product stream, and a second product is collected from said second product stream.
14. The use according to claim 9, wherein said product stream of said first pyrolysis run is treated within a hot condenser prior to recovery of said light fraction and said heavy fraction.

15. The use according to claim 1, wherein the upgraded feedstock is **characterized by** the following properties:

- i) an API gravity from about 13 to about 23;
- ii) a density at 15°C from about 0.92 g/ml to about 0.98 g/ml;
- iii) a viscosity at 40°C, cSt, from about 15 to about 300;
- iv) a reduced Vanadium content of about 60 to about 100 ppm; and
- v) a reduced Nickel content of about 10 to about 50 ppm.




FIG. 1A




FIG. 1B





FIG. 2







FIG. 4



LEGEND	
MARK	DESCRIPTION
A	PRIMARY (1°) FEED
B	SAND TO REACTOR
C	SAND TO REACTOR
D	FLUE GAS
E	PRIMARY (1°) PRODUCT
F	SECONDARY (2°) PRODUCT
G	DEMISTER PRODUCT
H	FILTER PRODUCT
I	ENHANCED RECOVERY UNIT (ERU) PRODUCT
J	PRODUCT GAS
K	REACTOR FEED
L	MINI-CONDENSER LIQUID
M	MINI-CONDENSER GAS
N	HOT DEMISTER
PL	PRODUCT LIQUID
FS	FRESH SAND
RH	REHEATER SAND

FIG. 5B



EUROPEAN SEARCH REPORT

Application Number
EP 10 18 4110

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 5 807 478 A (MYERS RONALD DAMIAN [CA] ET AL) 15 September 1998 (1998-09-15) * abstract * * column 1, line 24 - line 26 * * claims; examples; table 2 * -----	1-15	INV. C10G31/06 C10B55/04
X	US 5 104 516 A (DE BRUIJN THEO J W [CA] ET AL) 14 April 1992 (1992-04-14) * abstract * * column 1, line 26 - line 35 * * column 4, line 20 - column 6, line 35 * * claims; examples * -----	1-15	
X	US 4 153 540 A (GORRING ROBERT L ET AL) 8 May 1979 (1979-05-08) * abstract * * column 2, line 7 - line 30 * * column 3, line 34 - line 45; claims; examples * -----	1-15	
X	US 4 080 285 A (MCKINNEY JOEL DREXLER ET AL) 21 March 1978 (1978-03-21) * abstract; claims 1,5,6,8,9 * * column 1, line 4 - line 7 * * column 1, line 67 - column 2, line 15 * * column 3, line 55 - line 58 * * column 4, line 25 - column 5, line 11 * * column 6, line 22 - line 54 * * column 10, line 26 - column 11, line 12 * * example 1 * -----	1-15	TECHNICAL FIELDS SEARCHED (IPC) C10G C10B
A	GB 2 117 394 A (ENGELHARD CORP) 12 October 1983 (1983-10-12) * abstract; claims 1,13-19; figures * * page 3, line 106 - page 4, line 9 * * page 4, line 77 - line 97 * ----- -/--	1-15	
1 The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 11 April 2011	Examiner Nazario, Luis
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03 82 (P04C01)



EUROPEAN SEARCH REPORT

Application Number
EP 10 18 4110

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	W0 91/11499 A1 (ENSYN ENG ASS [CA]) 8 August 1991 (1991-08-08) * abstract * * claims 1, 5, 8, 11, 12, 21-23; figures * -----	1-15	
T	"Oil, Oil Refining" In: "Ullmann's Encyclopedia of Industrial Chemistry", 1991, VCH, XP002632273, ISBN: 3-527-20118-1 vol. A18, page 97, * right-hand column, paragraph 2 * -----		
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 11 April 2011	Examiner Nazario, Luis
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 18 4110

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-04-2011

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5807478	A	15-09-1998	NONE		
US 5104516	A	14-04-1992	CA	2012071 A1	13-09-1991
US 4153540	A	08-05-1979	NONE		
US 4080285	A	21-03-1978	NONE		
GB 2117394	A	12-10-1983	NONE		
WO 9111499	A1	08-08-1991	AU	7070191 A	21-08-1991
			CA	2009021 A1	31-07-1991
			CS	9100223 A3	15-04-1992
			DE	69106347 D1	09-02-1995
			DE	69106347 T2	11-05-1995
			DK	0513051 T3	18-04-1995
			EP	0513051 A1	19-11-1992
			ES	2065674 T3	16-02-1995
			FI	923434 A	30-07-1992
			PL	168638 B1	29-03-1996

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4490234 A [0004]
- US 4294686 A [0004] [0008] [0032] [0033]
- US 4161442 A [0004] [0006]
- US 4252634 A [0004] [0006]
- US 4427539 A [0004] [0006] [0007] [0032] [0033] [0034] [0041]
- US 4569753 A [0004] [0006] [0032] [0033] [0034] [0041]
- US 5413702 A [0004] [0006]
- US 5723040 A [0004]
- US 5662868 A [0004] [0032] [0033]
- US 5296131 A [0004]
- US 4985136 A [0004]
- US 4772378 A [0004]
- US 4668378 A [0004]
- US 4578183 A [0004]
- US 4435272 A [0004] [0032] [0033]
- US 4263128 A [0004] [0006] [0007]
- US 4980045 A [0006] [0032] [0033]
- US 4818373 A [0006] [0007] [0030] [0032] [0033] [0034] [0035] [0041] [0042]
- US 4311580 A [0007] [0032] [0033]
- US 4232514 A [0007]
- US 4427538 A [0032] [0033]
- US 4328091 A [0032] [0033]
- US 4243514 A [0032] [0033] [0034] [0035] [0041]
- US 5792340 A [0034] [0048] [0070] [0079] [0083] [0090]
- WO 9111499 A [0034]
- EP 513051 A [0034]
- EP 00916713 A [0099]
- CA 0000369 W [0099]