



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**24.08.2011 Bulletin 2011/34**

(51) Int Cl.:  
**B60R 16/02 (2006.01) H02G 3/22 (2006.01)**

(21) Application number: **10014667.9**

(22) Date of filing: **16.11.2010**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**

(72) Inventor: **Fujita, Tetsuya**  
**Yokkaichi-City**  
**Mie 510-8503 (JP)**

(74) Representative: **Müller-Boré & Partner**  
**Patentanwälte**  
**Grafinger Straße 2**  
**81671 München (DE)**

(30) Priority: **15.02.2010 JP 2010030511**


(71) Applicant: **Sumitomo Wiring Systems, Ltd.**  
**Yokkaichi-shi, Mie 510-8503 (JP)**

(54) **Grommet for wire harness and wire harness provided therewith**

(57) In a grommet (10) fitted around a wire harness wired in a vehicle, and mounted in a through hole (21) of a vehicle body panel (20), a radially outward extending portion (12) is provided on an outer peripheral surface at an end of a small diameter cylinder portion (11), in which the wire harness is tightly inserted. A large diameter cylinder portion (13) is connected to an outer peripheral end of the radially outward extending portion (12). An annular vehicle body engaging recessed portion (14) is provided in an outer peripheral surface of the large diameter cylinder portion (13). An annular stretchable portion (15) is provided at a portion connecting the small diameter cylinder portion (11) to the radially outward extending portion (12).

tion (12). The stretchable portion (15) extends in a direction same as a direction that the large diameter cylinder portion (13) extends and is then folded backward, to form a U-shape. A step (S) is provided on an inner peripheral surface at a boundary position between the small diameter cylinder portion (11) and the stretchable portion (15), such that a thickness (T2) of the stretchable portion (15) is thinner than a thickness (T1) of the small diameter cylinder portion (11). An annular rib (18) is provided on an outer peripheral surface of the boundary position. Radially extending restoring ribs (16) are provided on a convex side surface of the stretchable portion circumferentially spaced in-between.

**FIG.2A**



## Description

### 1. Field of the Invention

**[0001]** The present invention is related to a grommet for a wire harness and to a wire harness provided therewith, in particular, to a grommet, into which a wire harness to be wired in an automobile is inserted and which is mounted in a through hole of a vehicle body panel, having an improved following deformability and a restoring force after deformation of the grommet.

### 2. Description of Related Art

**[0002]** Conventionally, when a wire harness wired in an automobile is inserted into a through hole of a vehicle body panel, a grommet, into which the wire harness is inserted, is mounted in the through hole of the vehicle body panel, and thus, the grommet protects a portion of the wire harness W/H passing through the through hole, and prevents water and dust from entering.

**[0003]** Fig. 5 shows an example of a known grommet. The grommet 1 shown in Fig. 5 has a small diameter cylinder portion 2, in which a wire harness W/H is tightly inserted, and a large diameter cylinder portion 4, in which an annular recessed portion 5 to be engaged with a through hole of a vehicle body panel (not shown), is provided. The small diameter cylinder portion 2 and the large diameter cylinder portion 4 are connected in an axial direction via a radially outward extending portion 3. A stretchable portion 6, which has a U-shaped cross-section and extends toward the large diameter cylinder portion 4 side in parallel to the axial direction, is provided at a portion where the radially outward extending portion 3 is connected to the small diameter cylinder portion 2. After the wire harness W/H is inserted into the grommet, an adhesive tape 8 for fixing the wire harness is wound around a portion from an outer peripheral surface of the wire harness, which is pulled out from the small diameter cylinder portion 2, to an outer peripheral surface of the small diameter cylinder portion 2, to fix them to each other.

**[0004]** When the grommet 1 is mounted into the through hole of the vehicle body, the grommet is pushed into the through hole, receives a pulling external force, and further receives a twisting or skewing external force. However, as shown in Figs. 6A, 6B and 6C, the stretchable portion 6 follows the external force by compressing, stretching and bending, thereby absorbing the external force. Thus, the stretchable portion 6 prevents the large diameter cylinder portion 4 having the annular recessed portion 5 from receiving the external force. Accordingly, the annular recessed portion 5 is not separated from the through hole, and a gap between the through hole and the annular recessed portion 5 is not generated.

**[0005]** However, since the stretchable portion 6 is required to have a flexible deformability, the thickness of the stretchable portion 6 is thin and a restoring force after

the deformation is weak. In particular, the grommet 1 is difficult to be restored after stretching or compressing deformation in the axial direction of the grommet 1. Therefore, the wiring path of the harness may be changed thereby. Further, the wire harness may interfere with other components, or a working space may be reduced due to the change in the wiring path.

**[0006]** In view of the above circumstances, Japanese Patent Application Publication No. 11-63313 discloses a grommet 100 as shown in Figs. 7A and 7B. The grommet 100 has a small diameter cylinder portion 101, into which a wire harness 110 is tightly inserted, and a large diameter cylinder portion 103, in which an annular recessed portion 104 to be engaged with a through hole 109 of a vehicle body panel 108 is provided. The small diameter cylinder portion 101 and the large diameter cylinder portion 103 are connected via a circumferential wall portion 102. A stretchable portion 105, which extends toward the large diameter cylinder portion 103 side in parallel with an axial direction of the grommet 100, is provided at a portion where the circumferential wall portion 102 is connected to the small diameter cylinder portion 101. Reinforcing ribs 107 are provided in a concave portion 106 of the stretchable portion 105 on the small diameter cylinder portion 101 side, to connect between two side wall inner surfaces of the concave portion 106.

**[0007]** According to the grommet 100, a restoring force of the stretchable portion 105 after deformation is expected to be increased by the reinforcing ribs 107. However, the reinforcing ribs 107 restrict a stretching-and-compressing deformation of the stretchable portion 105 in the axial direction. Therefore, when the grommet 100 is inserted into the through hole 109, following deformability of the grommet 100 is reduced, and the insertion force into the through hole is not reduced. Further, a holding force to maintain the grommet 100 in the through hole is likely to be reduced.

**[0008]** Further, in the grommet shown in Fig. 5, when the deformation amount of the stretchable portion 6 increases, the adhesive tape 8 for fixing the wire harness, which is wound around a portion from the outer peripheral surface of the small diameter cylinder portion 2 to the outer peripheral surface of the wire harness W/H, is likely to be detached from an end portion, as shown in Fig. 6D. When the adhesive tape 8 is once detached, even if the stretchable portion 6 is restored to its original shape, the tape still remains detached, and the fixing force is weakened. Therefore, the positional displacement may occur in the mounting positions of the wire harness and the grommet. Further, when the operator grasps the grommet, the adhesive surface of the detached tape may stick to the operator's hand, and the detached tape may be completely separated from the grommet.

**[0009]** In view of the above-described circumstances, it is an object of the present invention to provide a grommet for a wire harness and a wire harness provided therewith, having a following deformability with respect to a push-in force or a pulling force applied to the grommet

when the grommet is mounted in a through hole of a vehicle body, and particularly in which a restoring force after the following deformation is improved, such that the grommet is mounted in and held by the through hole in a right posture.

**[0010]** This object is solved according to the invention by the features of the independent claims. Preferred embodiments of the invention are subject of the dependent claims.

**[0011]** According to the invention, there is provided a grommet configured to be fitted around a wire harness and to be mounted in a through hole of a vehicle body panel, the grommet comprising:

- a small diameter tubular portion in which the wire harness is to be tightly inserted;
- a large diameter tubular portion connected to the small diameter tubular portion via a radially outward extending portion;
- a vehicle body engaging recessed portion provided in an outer peripheral surface of the large diameter tubular portion;
- a stretchable portion provided at a portion connecting the small diameter tubular portion to the radially outward extending portion;
- at least one step provided at a boundary position between an inner peripheral surface of the small diameter tubular portion and a convex side surface of the stretchable portion, such that a thickness of the stretchable portion is thinner than a thickness of the small diameter tubular portion,
- at least one annular rib provided on an outer peripheral surface of the boundary position; and
- one or more restoring ribs provided on the convex side surface of the stretchable portion.

**[0012]** Accordingly, the stretchable portion can have an excellent stretching-and-compressing deformability in an axial direction, in addition to a radial direction of the grommet. Further, the one or more restoring ribs make the stretchable portion partially thicker, thereby increasing a restoring force of the stretchable portion after the deformation. Accordingly the grommet has an excellent following deformability with respect to the pulling, pushing and/or bending performed during a mounting operation of the grommet into the through hole e.g. in the vehicle body, or the like. Thus, a mounting operability of the grommet into the through hole e.g. in the vehicle body can be improved. At the same time, the stretchable portion substantially does not remain in the stretched or compressed state after the following deformation, and is quickly restored towards or to the original shape. Accordingly, the wire harness is prevented from interfering with the other components mounted on the vehicle due to the change in the path of the wire harness. Further, reduction in a work space is also prevented.

**[0013]** According to a preferred embodiment of the invention, the stretchable portion substantially extending

in a direction same as a direction in which the large diameter tubular portion extends and then being folded backward to substantially have a V- or U-shape.

**[0014]** Preferably, a plurality of restoring ribs are provided radially extending on the convex side surface of the stretchable portion circumferentially spaced in-between.

**[0015]** According to a further preferred embodiment of the invention, there is further provided a grommet which is fitted around a wire harness wired in a vehicle, mounted in a through hole of a vehicle body panel, and molded with a rubber or an elastomer. The grommet includes: a small diameter cylinder portion, in which the wire harness is tightly inserted; a radially outward extending portion provided on an outer peripheral surface at an end of the small diameter cylinder portion; a large diameter cylinder portion connected to an outer peripheral end of the radially outward extending portion; an annular vehicle body engaging recessed portion provided in an outer peripheral surface of the large diameter cylinder portion; and an annular stretchable portion provided at a portion connecting the small diameter cylinder portion to the radially outward extending portion. The stretchable portion extends in a direction same as a direction in which the large diameter cylinder portion extends and is then folded backward, to form a U-shape. A step is provided at a boundary position between an inner peripheral surface of the small diameter cylinder portion and a convex side surface of the stretchable portion, such that a thickness of the stretchable portion is thinner than a thickness of the small diameter cylinder portion. An annular rib is provided on an outer peripheral surface of the boundary position. Radially extending restoring ribs are provided on the convex side surface of the stretchable portion circumferentially spaced in-between.

**[0016]** Thus, the restoring ribs are provided on the convex side surface that extends in a hollow portion surrounded by the large diameter cylinder portion, instead of on the outer surface of the concave portion side of the stretchable portion being folded backward in U-shape. Therefore, the stretchable portion can have an excellent stretching-and-compressing deformability in an axial direction, in addition to a radial direction of the grommet. Further, the restoring ribs make the stretchable portion partially thicker, thereby increasing a restoring force of the stretchable portion after the deformation. Accordingly the grommet has an excellent following deformability with respect to the pulling, pushing and bending performed during a mounting operation of the grommet into the through hole in the vehicle body, or the like. Thus, a mounting operability of the grommet into the through hole in the vehicle body can be improved. At the same time, the stretchable portion does not remain in the stretched or compressed state after the following deformation, and is quickly restored to the original shape. Accordingly, the wire harness is prevented from interfering with the other components mounted on the vehicle due to the change in the path of the wire harness. Further, reduction in a

work space is also prevented.

**[0017]** Further, at the boundary position between the thick small diameter cylinder portion and the thin stretchable portion, the step is provided in the inner periphery, and the annular rib is provided on the outer periphery. Thus, rigidity of the boundary position is increased both from inside and outside. As a result when the stretchable portion is pushed in, resistance is generated at the boundary position, and thereby a push-in amount of the stretchable portion can be restricted. Further, since the width of the annular rib provided on the outer periphery should be flipped at once without stopping, this width also generates resistance. Moreover, the annular rib on the outer periphery particularly protects an end portion of the adhesive tape for fixing the wire harness, which is wound around an area from the outer periphery of the small diameter cylinder portion to the outer periphery of the wire harness. Accordingly, even if the stretchable portion is pushed in, the tape is prevented from being detached, since the adhesive tape does not extend to the stretchable portion.

**[0018]** As described above, the thickness of the stretchable portion may preferably be thinner than the thickness of the small diameter cylinder portion. The extending height of the restoring rib may preferably be a height that the restoring rib does not extend inwardly to exceed the inner peripheral surface of the small diameter tubular or cylinder portion. The thickness of the outer peripheral portion of the radially outward extending portion and the large diameter tubular or cylinder portion may preferably be between double and quadruple the thickness of the stretchable portion.

**[0019]** Thus, since the extending height of the restoring rib is set to a height that the restoring rib does not extend to exceed the inner peripheral surface of the small diameter cylinder portion, the wire harness can be more easily inserted into the small diameter cylinder portion and the interference between the restoring ribs and the wire harness can be prevented.

**[0020]** Further, since the thickness of the stretchable portion is thinner than the thickness of the small diameter tubular or cylinder portion, the stretchable portion has an excellent following deformability. In addition, since the thickness of the outer peripheral portion of the radially outward extending portion and the large diameter tubular or cylinder portion, which are positioned around the vehicle body engaging recessed portion, is approximately between double and quadruple the thickness of the stretchable portion, it is possible to achieve a good balance between the following deformability and an excellent mounting force to the through hole.

**[0021]** When the thickness of the outer peripheral portion of the radially outward extending portion and the large diameter tubular or cylinder portion is less than double of the thickness of the stretchable portion, the thickness of the stretchable portion is too thick and the stretching-and-compressing deformability decreases, or the thicker portion is too thin and the mounting force to the

through hole decreases. On the other hand, when the thickness of the outer peripheral portion of the radially outward extending portion and the large diameter cylinder portion is more than quadruple the thickness of the stretchable portion, the thickness of the stretchable portion is too thin and the restoring force of the restoring rib does not function sufficiently, or the thicker portion is thicker than necessary and the cost and weight of the grommet are likely to increase.

**[0022]** An area of the restoring ribs may be approximately 5 to 25% of a circular projected area, which is formed by projecting the convex side surface of the stretchable portion from a front. By setting the area of the restoring ribs approximately within this range, the stretchable portion can have both the stretching deformability and the restoring force in a balanced manner. The sum of the thickness of the stretchable portion and a thickness of the restoring rib may be substantially equal to the thickness of the small diameter tubular portion. The thickness of the stretchable portion may be set to be equal to or slightly thinner than the thickness of the small diameter tubular portion. A thickness of a portion adjacent to the vehicle body engaging recessed portion may be set substantially within the range from double to quadruple a thickness of the stretchable portion. Each restoring rib may preferably have a width of about 1 mm - 9mm, and the number of restoring ribs may preferably be between 3 and 16. Further, the width of the annular rib, provided on the outer peripheral surface of the boundary between the stretchable portion and the small diameter cylinder portion, may preferably be 1 mm - 6mm.

**[0023]** As described above, the grommet according to a preferred embodiment of the present invention has the stretchable portion having a V- or U-shape cross-section provided at a portion where the small diameter cylinder portion is connected to the radially outward extending portion, and the radially extending restoring ribs provided on the convex side surface of the stretchable portion circumferentially spaced in-between. Accordingly, the restoring force after deformation can be improved without reducing the deformability of the stretchable portion.

**[0024]** Therefore, even when an external force, such as pulling, push-in, bending, or the like, is applied to the grommet during the operation of mounting the grommet into a through hole in the vehicle body, the following deformation of the stretchable portion prevents the vehicle body engaging portion from being deformed, and an excellent mounting force to the through hole can be provided. In addition, the stretchable portion does not remain in a stretched or compressed state, and is immediately restored by the restoring ribs. Accordingly, the wire harness is prevented from changing its path, and from interfering with the other components mounted on the vehicle thereby. Further, a reduction in a work space is also prevented.

**[0025]** Further, at the boundary position between the small diameter cylinder portion and the stretchable portion, a step and an annular rib are respectively provided

on the inner surface side and on the outer surface side, to increase the rigidity at the boundary position. Therefore, the push-in amount of the stretchable portion can be restricted, and the adhesive tape for fixing the wire harness, which is wound around the area from the outer peripheral surface of the small diameter cylinder portion to the outer peripheral surface of the wire harness, is prevented from being detached from the end portion.

**[0026]** According to the invention, there is further provided a wire harness having a plurality of wires around which a grommet according to the invention or a preferred embodiment thereof is fitted.

**[0027]** The present invention is further described in the detailed description which follows, in reference to the noted plurality of drawings by way of non-limiting examples of exemplary embodiments of the present invention, in which like reference numerals represent similar parts throughout the several views of the drawings. It should be understood that even though embodiments are separately described, single features thereof may be combined to additional embodiments.

Figs. 1A, 1B and 1C show a grommet according to an embodiment of the present invention, in which, Fig. 1A is a side elevational view, Fig. 1B is a front elevational view, and Fig. 1C is a perspective view; Fig. 2A is a cross-sectional view of the grommet taken along the line II-II of Fig. 1B;

Fig. 2B is an enlarged cross-sectional view illustrating a main portion of Fig. 2A;

Fig. 3A, 3B and 3C show stretching-and-compressing deformation of the grommet, when the grommet is being mounted in the through hole of a vehicle body, in which Fig. 3A is a cross-sectional view showing a state when the grommet is pushed in, Fig. 3B is a cross-sectional view showing a state when the grommet is pulled, and Fig. 3C is a cross-sectional view showing a state when the grommet is pressed; Fig. 4 is an enlarged cross-sectional view illustrating a main portion of a modified embodiment of the present invention;

Fig. 5 is a cross-sectional view illustrating a conventional grommet;

Figs. 6A-6D illustrate deformation of the grommet shown in Fig. 5, in which Fig. 6A is a cross-sectional view illustrating a state when the grommet is pushed in; Fig. 6B is a cross-sectional view illustrating a state when the grommet is pulled; Fig. 6C is a cross sectional view illustrating a state when the grommet is bent; and Fig. 6D is a view illustrating a state when an adhesive tape for fixing the wire harness is detached from the grommet; and

Figs. 7A and 7B illustrate another conventional grommet, in which Fig. 7A is a side elevational view (partial cross-sectional view); and Fig. 7B is a front elevational view.

**[0028]** The particulars shown herein are by way of ex-

ample and for purposes of illustrative discussion of the embodiments of the present invention only and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the present invention. In this regard, no attempt is made to show structural details of the present invention in more detail than is necessary for the fundamental understanding of the present invention, the description is taken with the drawings making apparent to those skilled in the art how the forms of the present invention may be embodied in practice.

**[0029]** Embodiments of the present invention will be described hereinafter with respect to the drawings. Figs. 1-3 illustrate a grommet 10 according to an embodiment of the present invention. The grommet 10 is or is to be fitted around a wire harness 25 to be at least partly inserted into a through hole 21 provided e.g. in a vehicle body panel 20 of an automobile, and is mounted in the through hole 21.

**[0030]** As shown in Figs. 1A-1C and Fig. 2A, the grommet 10 includes a small diameter cylinder or tubular portion 11, into which the wire harness 25 is to be tightly inserted; a radially outward extending portion 12, which extends from an outer peripheral surface at an end of the small diameter cylinder portion 11; a large diameter cylinder or tubular portion 13, which extends from an outer peripheral end of the radially outward extending portion 12. The small diameter cylinder portion 11, the radially outward extending portion 12 and the large diameter cylinder portion 13 are connected in an axial direction A, and are integrally or unitarily formed of any suitable elastic material, such as a rubber or an elastomer. An annular vehicle body engaging recessed portion 14, which engages with a rim or portion of the through hole 21, is provided in an outer peripheral surface of the large diameter cylinder portion 13.

**[0031]** An annular stretchable or deformable portion 15 is provided at a portion connecting the small diameter cylinder portion 11 to the radially outward extending portion 12. The stretchable portion 15 extends toward the large diameter cylinder portion 13 side substantially in parallel with the axial direction A, and is folded backward to substantially form a V- or U-shape. Further, the stretchable portion 15 continues in a circumferential direction to bulge annularly. As shown in Fig. 2B, a step or protruding portion S is provided at a boundary position between an inner peripheral surface of the small diameter cylinder portion 11 and a convex side surface 15a of the stretchable portion 15. Thickness T2 of the stretchable portion 15 particularly is thinner than thickness T1 of the small diameter cylinder portion 11. Further, an annular rib 18 particularly is provided on an entire outer periphery of the boundary position between the small diameter cylinder portion 11 and the concave side surface 15b of the stretchable portion 15. Width W2 of the annular rib may be any suitable size, such as about 1mm - 4mm. In addition, one or more (e.g. eight) restoring ribs 16 are provided to extend from a convex side surface 15a of the

stretchable portion 15 particularly substantially equiangularly. Each restoring rib 16 radially particularly extends the substantially entire length of the convex side surface 15a in the radial direction and is curved into a U-shape.

[0032] As shown in Fig. 1B, the annular stretchable portion 15 particularly has an inner diameter D1 of about 18 mm and an outer diameter D2 of about 75mm. On the other hand, width W1 of the restoring rib 16 is such as 2 mm. Accordingly, the total area of the restoring rib 16 particularly is about 8.5% of the total area of the convex side surface 15a of the stretchable portion 15, in a frontal projected area.

[0033] Further as shown in Fig. 2B, thickness (extending height) T4 of the restoring rib 16 extending from the stretchable portion 15 particularly is set such that an extending end 16a of the restoring rib 16 does not exceed an inner peripheral surface 11 a of the small diameter cylinder portion 11. In other words, total thickness T3, which is a sum of T2 and T4, particularly is substantially equal to the thickness T1 of the small diameter cylinder portion 11.

[0034] Thickness T5 of the outer peripheral portion of the radial outward extending portion 12 and the large diameter cylinder portion 13 particularly is set within a range approximately between double to quadruple the thickness T2 of the stretchable portion 15.

[0035] Thus, the grommet 10 as constructed above has the restoring ribs 16 on the convex side surface 15a of the stretchable portion 15, instead of on the concave side surface 15b. Therefore, restoring force after deformation can be improved without impairing (or reducing) stretching-and-compressing deformability of the stretchable portion 15. Further, the thickness T2 of the stretchable portion 15 particularly is set to be equal to or slightly thinner than the thickness T1 of the small diameter cylinder portion 11, and/or the projected area of the restoring ribs 16 particularly is set to be 8.5%, i.e., within the range approximately between 5% and 25% of the total projected area of the convex side surface 15a of the stretchable portion 15. Therefore, it is possible to achieve a good balance between the stretching-and-compressing deformability and the restoring force of the stretchable portion 15.

[0036] While the small diameter cylinder portion 11 of the grommet 10 is being expanded by an expanding jig (not shown), the wire harness 25 is to be at least partly inserted into the grommet 10 substantially along the axis thereof. After the insertion, an adhesive tape 19 for fixing the wire harness particularly is wound around a portion from an outer peripheral surface of the small diameter cylinder portion 11 to an outer peripheral surface of the wire harness 25, which is pulled out from an end of the small diameter cylinder portion 11, to fix the wire harness 25 to the grommet 10. An end of the adhesive tape 19 particularly reaches the position of the annular rib 18.

[0037] When the wire harness 25 is wired in the vehicle body and the wire harness 25 is at least partly inserted in the through hole of the vehicle body 20, the grommet

10, attached to the wire harness 25, is pressed into and pulled out of the through hole, to mount the grommet 10 in the through hole 21 of the vehicle body. At this time, the grommet 10 receives an external force in a pressing direction as shown in Fig. 3A, as well as an external force in a pulling direction as shown in Fig. 3B. When the grommet 10 receives such an external force, as shown in Figs. 3A and 3B, the stretchable portion 15 can be compressed or stretched to absorb such external forces. Further, even when the similar external forces are applied to the grommet 10 after the grommet 10 is mounted on the vehicle body, the stretchable portion 15 can be similarly deformed to absorb the external force. Therefore, it is possible to prevent the external forces from being applied to the large diameter cylinder portion 13, and thus to prevent disengagement of the vehicle body engaging recessed portion 14 from the through hole 21, formation of a gap between the vehicle body engaging recessed portion 14 and the through hole 21, or the like. In addition, when the grommet 10 stops receiving the external forces, the restoring ribs 16 start functioning and thus the stretchable portion 15 is (particularly immediately) restored toward or to its original state particularly without remaining in a compressed state or stretched state. Therefore, the wire harness 25 is prevented from changing its path or interfering with other components mounted on the vehicle thereby. Further, a reduction in a work space is also prevented.

[0038] In particular, as shown in Fig. 3C, the boundary position between the stretchable portion 15 and the small diameter cylinder portion 11 is reinforced both from inside and outside by providing the step S on the inner surface and the annular rib 18 on the outer surface at the boundary position. Therefore, even if the force to push the stretchable portion 15 into the hollow portion in the large diameter cylinder portion 13 is increased, the boundary position resists a force to deform the small diameter cylinder portion 11. Thus, an end portion of the small diameter cylinder portion 11, where the annular rib 18 is provided, is not deformed to bend outwardly. Accordingly, the adhesive tape 19 for fixing the wire harness, which is wound around the outer peripheral surface of the small diameter cylinder portion 11 up to the position of the annular rib 18, is securely prevented from being detached from the end. As a result, the adhesive tape 19 can maintain the grommet 10 and the wire harness 25 being fixed to each other without causing a positional displacement.

[0039] Further, the thickness T5 of the outer peripheral portion of the radially outward extending portion 12 and the large diameter cylinder portion 13, i.e., the thickness of a portion adjacent to the vehicle body engaging recessed portion 14, particularly is set substantially within the range from double to quadruple the thickness T2 of the stretchable portion 15. Accordingly, the grommet 10 provides an excellent followability to the deformation caused e.g. by a harness handling operation, or the like, and a strong mounting force to the through hole 21 in a balanced manner.

**[0040]** Further, the extending ends 16a of the restoring ribs 16 particularly do not extend inwardly to exceed the inner peripheral surface 11 a of the small diameter cylinder portion 11. Therefore, the interference between the wire harness 25, which is inserted into the small diameter cylinder portion 11, and the restoring ribs 16 can be avoided.

**[0041]** As shown in a modified embodiment in Fig. 4, the thickness T3, which is a sum of the thickness T2 of the stretchable portion 15 and the thickness T4 of the restoring rib 16, may be thinner than the thickness T1 of the small diameter cylinder portion 11. In this case, the extending end 16a of the restoring rib 16 is indented outwardly from the inner peripheral surface 11 a of the small diameter cylinder portion 11, so as to form a step.

**[0042]** Accordingly, in a grommet to be fitted around a wire harness wired in a vehicle, and to be mounted in or to a through hole of a vehicle body panel, a radially outward extending portion is provided on an outer peripheral surface at an end of a small diameter cylinder or tubular portion, in which the wire harness is to be tightly inserted. A large diameter cylinder portion is connected to an outer peripheral end of the radially outward extending portion. An annular vehicle body engaging recessed portion is provided in an outer peripheral surface of the large diameter cylinder portion. An annular stretchable portion is provided at a portion connecting the small diameter cylinder portion to the radially outward extending portion. The stretchable portion extends in a direction substantially same as a direction that the large diameter cylinder portion extends and is then folded backward, to form a U-shape. A step is provided on an inner peripheral surface at a boundary position between the small diameter cylinder portion and the stretchable portion, such that a thickness of the stretchable portion is thinner than a thickness of the small diameter cylinder portion. An annular rib is provided on an outer peripheral surface of the boundary position. One or more substantially radially extending restoring ribs are provided on a convex side surface of the stretchable portion circumferentially spaced in-between.

present invention has been described with reference to exemplary embodiments, it is understood that the words which have been used herein are words of description and illustration, rather than words of limitation. Changes may be made, within the purview of the appended claims, as presently stated and as amended, without departing from the scope and spirit of the present invention in its aspects. Although the present invention has been described herein with reference to particular structures, materials and embodiments, the present invention is not intended to be limited to the particulars disclosed herein; rather, the present invention extends to all functionally equivalent structures, methods and uses, such as are within the scope of the appended claims.

**[0043]** The present invention is not limited to the above described embodiments, and various variations and modifications may be possible without departing from the

scope of the present invention.

## Claims

1. A grommet (10) configured to be fitted around a wire harness (25) and to be mounted in a through hole (21) of a vehicle body panel (20), the grommet (10) comprising:

a small diameter tubular portion (11) in which the wire harness (25) is to be tightly inserted;  
a large diameter tubular portion (13) connected to the small diameter tubular portion (11) via a radially outward extending portion (12);  
a vehicle body engaging recessed portion (14) provided in an outer peripheral surface of the large diameter tubular portion (13);  
a stretchable portion (15) provided at a portion connecting the small diameter tubular portion (11) to the radially outward extending portion (12);  
at least one step (S) provided at a boundary position between an inner peripheral surface of the small diameter tubular portion (11) and a convex side surface of the stretchable portion (15), such that a thickness (T2) of the stretchable portion (15) is thinner than a thickness (T1) of the small diameter tubular portion (11),  
at least one annular rib (18) provided on an outer peripheral surface of the boundary position; and  
one or more restoring ribs (16) provided on the convex side surface of the stretchable portion (15).

2. The grommet for the wire harness according to claim 1, wherein the stretchable portion (15) substantially extending in a direction same as a direction in which the large diameter tubular portion (13) extends and then being folded backward to substantially have a V- or U-shape.
3. The grommet for the wire harness according to any one of the preceding claims, wherein a plurality of restoring ribs (16) are provided radially extending on the convex side surface of the stretchable portion (15) circumferentially spaced in-between.
4. The grommet for the wire harness according to any one of the preceding claims, wherein an extending height of the restoring ribs (16) is set such that the restoring ribs (16) do not exceed the inner peripheral surface of the small tubular cylinder portion (11).
5. The grommet for the wire harness according to any one of the preceding claims, wherein a thickness (T5) of an outer peripheral portion of the radially outward extending portion (12) and the large diameter

tubular portion (13) is set between double and quadruple the thickness (T2) of the stretchable portion (15).

6. The grommet for the wire harness according to any one of the preceding claims, wherein an area of the restoring ribs (16) approximately is 5 to 25% of a circular projected area, which is formed by projecting the convex side surface (15a) of the stretchable portion (15) from a front view. 5  
10
  
7. The grommet for the wire harness according to any one of the preceding claims, wherein the sum of the thickness (T2) of the stretchable portion (15) and a thickness (T4) of the restoring rib (16) is substantially equal to the thickness (T1) of the small diameter tubular portion (11). 15
  
8. The grommet for the wire harness according to any one of the preceding claims, wherein the thickness (T2) of the stretchable portion (15) is set to be equal to or slightly thinner than the thickness (T1) of the small diameter tubular portion (11). 20
  
9. The grommet for the wire harness according to any one of the preceding claims, wherein a thickness of a portion adjacent to the vehicle body engaging recessed portion (14) is set substantially within the range from double to quadruple a thickness (T2) of the stretchable portion (15). 25  
30
  
10. The grommet for the wire harness according to any one of the preceding claims, wherein each restoring rib (16) has a width of about 1 mm - 9mm and/or the number of restoring ribs (16) is between 3 and 16. 35
  
11. The grommet for the wire harness according to any one of the preceding claims, wherein a width of the annular rib (18) approximately is 1 mm - 6mm. 40
  
12. A wire harness (25) having a plurality of wires around which a grommet (10) according to any one of the preceding claims is fitted. 45

50

55

60



FIG.1A




FIG.1B




FIG.1C




FIG.2A




FIG.2B




FIG.3A




FIG.3B




FIG.3C




FIG.4




FIG.5  
PRIOR ART




FIG.6A  
PRIOR ART




FIG.6B  
PRIOR ART




FIG.6C  
PRIOR ART




FIG.6D  
PRIOR ART




FIG.7A  
PRIOR ART





FIG.7B  
PRIOR ART





## EUROPEAN SEARCH REPORT

Application Number  
EP 10 01 4667

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	EP 1 468 877 A1 (SUMITOMO WIRING SYSTEMS [JP]) 20 October 2004 (2004-10-20) * the whole document *	1	INV. B60R16/02 H02G3/22
A	US 2003/014924 A1 (NAKAMURA MAMIKO [JP]) 23 January 2003 (2003-01-23) * figure 1 *	1	
A	WO 2009/096036 A1 (SUMITOMO WIRING SYSTEMS [JP]; OKUHARA TAKASHI [JP]; SAKATA TSUTOMU [JP]) 6 August 2009 (2009-08-06) * the whole document *	1-12	
A,D	JP 11 063313 A (YAZAKI CORP) 5 March 1999 (1999-03-05) * the whole document *	1-12	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (IPC)
			B60R H02G
Place of search		Date of completion of the search	Examiner
Berlin		30 May 2011	Tamme, H
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

1  
EPO FORM 1503 03 82 (P04C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 01 4667

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-05-2011

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1468877	A1	20-10-2004	CN 1551251 A	01-12-2004
			JP 4036135 B2	23-01-2008
			JP 2004320951 A	11-11-2004
			US 2004206538 A1	21-10-2004
-----				
US 2003014924	A1	23-01-2003	CN 1397457 A	19-02-2003
			DE 10232712 A1	06-03-2003
			JP 2003032854 A	31-01-2003
-----				
WO 2009096036	A1	06-08-2009	AU 2008349287 A1	06-08-2009
			CN 101932477 A	29-12-2010
			EP 2248703 A1	10-11-2010
			US 2011011625 A1	20-01-2011
-----				
JP 11063313	A	05-03-1999	JP 3570660 B2	29-09-2004
-----				

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- JP 11063313 A [0006]