



(11) **EP 2 395 147 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
14.12.2011 Bulletin 2011/50

(21) Application number: **10162405.4**

(22) Date of filing: **10.05.2010**

(51) Int Cl.:
D21C 9/00 *(2006.01)* **D21C 9/10** *(2006.01)*
D21C 9/16 *(2006.01)* **D21D 1/02** *(2006.01)*
D21D 1/20 *(2006.01)* **D21D 1/30** *(2006.01)*
D21D 1/34 *(2006.01)*

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO SE SI SK SM TR**
Designated Extension States:
BA ME RS

(71) Applicant: **Unilever PLC, A Company Registered
in England and
Wales under Company no. 41424
London, Greater London EC4Y 0DY (GB)**

(72) Inventor: **The designation of the inventor has not
yet been filed**

(74) Representative: **McNab, Donald C. et al
Marks & Clerk LLP
Glasgow Office
120 Bothwell Street,
Glasgow G2 7JS (GB)**

(54) **Freeness of paper products**

(57) The present invention provides for the optimisation of conditions for treating pulp with a catalyst and hydrogen peroxide to produce a Freeness value (SR) in a web produced from the treated pulp such that the en-

ergy required in mechanical agitation of the pulp is reduced.

EP 2 395 147 A1

DescriptionFIELD OF INVENTION

5 **[0001]** The present invention relates to a new refining process for paper pulp.

BACKGROUND OF THE INVENTION

10 **[0002]** Pulp for making paper, tissues, board or related products may be obtained from cellulose from wood and other sources (e.g., hemp, straw, cotton). The vast majority of the raw material is wood pulp, which can be either softwood or hardwood raw material. Softwood fibres come from needle-bearing conifer trees such as pine, spruce, alpine fir, Douglas fir. Hardwood fibres are derived from deciduous trees of various types, such as birch, eucalyptus, and acacia. Mechanical pulp contains most of the original lignin, whilst in chemical pulp most of the lignin has been removed.

15 **[0003]** Among the distinguishing differences between softwood (SW) and hardwood (HW) fibres are the length of the individual cellulosic fibres of the wood, the coarseness of the fibres and the stiffness/collapsibility of the fibres.

[0004] Hardwood and softwood must be subjected to specific mechanical treatments (refining) for converting the wood into a fibrous slurry employed in the formation of a paper web. The fibres of cellulose pulp suspensions are mechanically treated to change the fibres properties. The cellulose pulp suspension is processed into a product having increased tensile/tear strength properties, increased freeness (Shopper-Riegler) values, increased fines, and improved paper/tissue making properties over that of the initial cellulose pulp suspension. Increased freeness values lead to decreased dewatering capabilities for paper/tissue making, which increases the energy required to dry the paper and it will slow down the speed of paper making. On the other hand, too low freeness yields paper/tissues that are not strong enough. Refining is of importance to the properties of both chemical and mechanical pulp. Apart from the dewatering, it should also be noted that the energy consumption during the refining process is high.

25 **[0005]** A chemical process to modulate the cellulosic fibres by treatment of fibres by iron salts and hydrogen peroxide has been disclosed in WO 2005/028744; treatment of Kraft softwood pulp leads to fibre properties reminiscent to hardwood fibres.

[0006] WO 2004/022842 discloses a reduced energy process for refining mechanical pulp after treatment with a pectinase enzyme to produce pulp with certain freeness properties.

30 **[0007]** EP 0458397 discloses the use manganese 1,4,7-Trimethyl-1,4,7-triazacyclononane (Me₃-TACN) complexes as bleaching and oxidation catalysts and use for textile and pulp bleaching processes.

[0008] United States Application 2001/0025695A1, Patt et al, discloses the use of PF₆⁻ salts of 1,2,-bis-(4,7,-dimethyl-1,4,7,-triazacyclonon-1-yl)-ethane and Me₃-TACN (Me₄-DTNE) for wood-pulp delignification and bleaching.

35 **[0009]** WO 2007/125517 discloses the use of 1,2,-bis-(4,7,-dimethyl-1,4,7,-triazacyclonon-1-yl)-ethane and Me₃-TACN (Me₄-DTNE) with buffer and sequestrants for bleaching of cellulosic substrates.

[0010] WO 2008/086937 discloses the use of 1,2,-bis-(4,7,-dimethyl-1,4,7,-triazacyclonon-1-yl)-ethane and Me₃-TACN (Me₄-DTNE) for bleaching of cellulosic substrates whilst keeping the pH constant.

[0011] It would be desirable to provide a method that permits a paper/tissue producer to use a refining process with a lower level of freeness that yields the same pulp strength properties as conventionally provided by mechanical means.

SUMMARY OF THE INVENTION


40 **[0012]** We have found that treating cellulosic fibers using a preformed transition metal complex of azacyclic molecules and hydrogen peroxide, improves the effect of refining of these fibers. Treatment can be either done before, during or after the refining process. The improved refining properties can be observed by increased tensile strength properties at the same mechanical energy input and same Shopper-Riegler value (SR).

[0013] The present invention may be applied to chemical and mechanical pulp, including recycling pulp, for production of paper, tissue or board.


50 **[0014]** We have found that energy consumption and time of reaching a cellulose pulp suspension that may be further processed to a web having improved freeness may be reduced by the action of a manganese catalyst together with hydrogen peroxide.

[0015] In one aspect the present invention provides a method for the treatment of a cellulose pulp suspension comprising (i) the step of subjecting cellulose pulp fibres to an aqueous solution of a manganese transition metal catalyst and hydrogen peroxide at pH from 6 to 13 and (ii) subjecting the pulp to a refining process until a Shopper Riegler (SR) value of from 10 to 90° is reached and the resultant pulp is processed into paper, tissue or board, wherein the manganese transition metal catalyst is present at a concentration from 0.0001 to 1 kg/tonne oven-dry pulp and the hydrogen peroxide is present at a concentration from 0.1 to 100 kg/tonne oven-dry pulp, the manganese transition metal catalyst is preformed and a mononuclear Mn(II), Mn(III), Mn(IV) or dinuclear Mn(II)Mn(II), Mn(II)Mn(III), Mn(III)Mn(III), Mn(III)Mn(IV) or Mn(IV)

Mn(IV) transition metal catalyst, the ligand of the transition metal catalyst of formula (I):



wherein:



p is 3;

R is independently selected from: hydrogen, C1-C6-alkyl, C2OH, C1 COOH, and pyridin-2-ylmethyl or one of R is linked to the N of another Q from another ring via an ethylene bridge;

25 R1, R2, R3, and R4 are independently selected from: H, C1-C4-alkyl, and C1-C4-alkylhydroxy.

[0016] The Freeness value (SR) is a standard measurement as measured by Shopper Riegler method for Drainability NORM EN ISO 5267-1; the Freeness value (SR) as used herein has been measured by this method.

30 [0017] The concentration of the catalyst and hydrogen peroxide will have an effect upon the time of refining treatment of the pulp that is required as will the ratio of the mass of pulp to amount of actives used. In this regard, to optimise the conditions the variables of concentration of actives, temperature, pH and time are variables that may be changed.

[0018] It is preferred that the treatment time of the pulp with the catalyst and hydrogen peroxide is from 1 min to 4 h, more preferred 5 min to 3 h, and most preferred 10 min to 2 h. Further, it is preferred that the temperature of the process using the catalyst and hydrogen peroxide is from 30 to 95 °C and more preferably between 40 to 90 °C. The pH of the process using the catalyst and hydrogen peroxide is preferably between pH 8 and 12.

35 [0019] It will be appreciated that the amount of transition metal catalyst/hydrogen peroxide required per tonne of pulp (oven dry) is essentially that of a molar ratios but within the industry it is normal to express amounts in weight. In this regard, the range of transition metal catalyst required per tonne of pulp (oven dry) is in the range from 0.0001 to 1 kg per tonne of pulp (oven dry) which equates approximately to 0.1 to 1500 mmol/tonne pulp (oven dry). The hydrogen peroxide (100%) per tonne of pulp (oven dry) is in the range from 0.1 to 100 kg, more preferably 0.5 to 50 kg, most preferably 1 to 30 kg.

[0020] The molar ratio of transition metal catalyst: hydrogen peroxide is preferably in the range from 1:100 to 1:10000.

40 [0021] With the above in mind it is then routine for a technician skilled in the art to determine the conditions by trial and error to produce the Freeness value (SR) and apply the conditions to obtain and optimise the pulp having the desired Freeness value (SR) to a web industrially.

DETAILED DESCRIPTION OF THE INVENTION

50 [0022] Pulp to produce paper or board grades is fed to a paper machine where it is formed as a paper web and the water is removed from it by pressing and drying. Pressing the sheet removes the water by force. Once the water is forced from the sheet, felt is used to collect the water. When making paper by hand, a blotter sheet is used. Pulp for the manufacturing of tissue or kitchen towel grades is dewatered and dried without pressing, to maintain the appropriate absorbancy and smoothness properties.

55 [0023] Drying involves using air and or heat to remove water from the paper sheet. In the earliest days of papermaking this was done by hanging the paper sheets like laundry. In more modern times, various forms of heated drying mechanisms are used. On the paper machine, the most common is the steam-heated can dryer. These dryers can heat to temperatures above 200°F (93°C) and are used in long sequences of more than 40 cans. The heat produced by these can easily dry the paper to less than 6% moisture.

[0024] Specific procedures exist to produce tissue paper. Reference is made to Paper and Board Grades, Book 18, chapter 4, by the Finnish Paper Engineers' Association and TAPPI (2000).

[0025] We have found that treating a cellulose pulp suspension with a manganese transition metal catalyst and hydrogen peroxide changes the extent to which the pulp reacts to a mechanical refining process, as measured by its freeness value (Shopper-Riegler - SR), to produce a web made from the cellulose pulp suspension. Treatment by the manganese catalyst can be either done before the mechanical refining, during, or after the mechanical refining process.

[0026] The ratio between tensile strength and freeness is improved, i.e., either an increased strength at the same freeness value or same strength at a lower freeness value. By monitoring the conditions of treatment optimum freeness value of a final product is obtained. Further, increased bulk at the same refining can be achieved, particularly important for tissue paper.

[0027] We have found that treating a cellulose pulp suspension and monitoring the variables of concentration and time permits an optimum freeness value for different periods of time.

[0028] The term oven dry pulp is one where pulp has been dried at 100-105 °C to yield a constant weight. Reference is made to TAPPI-test T240 om-93 (1993).

REFINING

[0029] Different types of equipment are frequently used to mechanically treat the cellulosic pulp. Beaters, including Hollander beaters, have been used in many mills, but have now largely replaced by conical and disk refiners, which can operate in continuous processes. Conical refiners are of the shallow angle refiners (Jordan), medium angle refiners (Conflo) and wide angle refiners (Claffin). The group disk refiners comprises three types, single disc, double disc multi-disc refiners.

[0030] Refining can be done at low consistency (2-6%), medium consistency (10-20%) or high consistency (30-35%). Depending on the requirements of the end product, different choices for optimal consistency processing can be made. Reference is made to Paper and Board Grades, Papermaking Part 1. Stock Preparation and Wet End, Book 18, chapter 4, by the Finnish Paper Engineers' Association and TAPPI (2000).

[0031] Processes can be either batch-wise or in a continuous manner, the latter being often preferred due to cost reasons and easier control of quality.

[0032] In many cases different types of wood pulp are mixed, such as softwood and hardwood pulp. One of those or both may be refined independently. Often, more refiners are employed in series, to enhance the benefits/energy requirements, to treat the pulp.

[0033] Refining may take place for chemical pulp, mechanical pulp and recycle pulp, all objects of the current invention.

[0034] Depending on the application, different levels of refining can be done. For tissue and kitchen towel grades, a low refining is carried out, to ensure a good bulk, softness, absorbancy and brightness. A low refining is beneficial for above properties, but negatively impacts the strength properties. Therefore, often wet-and/or dry-strength agents are added. Shopper-Riegler values of between 10 and 30° are often obtained, after refining.

[0035] For printing and writing paper, printability and machine runnability are key parameters. The paper must be clean and bright, have the appropriate smoothness, compressibility, ink-penetration capabilities and sufficient strength for the printing operations. A minimum opacity is another important feature. Therefore, these papers need good refining control to develop the internal bond strength and to obtain the right level of smoothness and formation for its end use. Bleached board grades, used a.o. for packaging frozen foods and liquids, and for paper plates and cups, need good stiffness and bulk with proper smoothness and printability. Also internal bond, creasability and dimensional stability are important factors. Therefore sufficient refining to get these properties will also be needed (without decreasing the bulk and stiffness too much). Shopper-Riegler values after refining of between 15 and 50° are often needed for these applications.

[0036] Dense papers need significant amount of refining, depending on the particular product needs. Release-base papers, glassine, and greaseproof paper all require extensive refining to get the desired balance of strength and appearance properties. Especially if the objective is to make transparent papers, considerable energy requirements are needed for the refining processes. SR values as high 90° can be needed.

[0037] Mechanical pulp needs often refining to produce the paper or board materials exhibiting the appropriate physical properties. Shopper-Riegler values of between 20 and 80° are often reached when refining mechanical pulp.

[0038] The extent of refining can be monitored on-line. Energy input is the most important parameter to determine the extent of refining. Control systems exist to on-line monitor the refining process and adjust energy input according the requirements. Probes to monitor the refiner load, temperature changes, flow/consistency, drainage/freeness (SR), etc. Main process variables include temperature, pH, consistency, additives, pretreatments, production rate, and applied energy.

[0039] Treatment of cellulosic fibers by manganese catalyst and hydrogen peroxide

[0040] Application of the manganese catalyst and hydrogen peroxide to treat the cellulosic fibers can be done at

different stages during the fiber treatment/paper making process. This can be either before the mechanical refining process, during the mechanical refining process or after the mechanical refining process.

5 [0041] Typically pulp that has been bleached in one or more delignification and bleaching stage, chemical pulp, can be used to treat further to produce tissue, paper or board. However, within the scope of this invention, also lignin-containing pulp (mechanical pulp) or recycled wood pulp can be used. For integrated mills a wet pulp slurry is brought into the paper mill. When paper producers obtain pulp from other mills, the pulp sheets are first put into a chest and disintegrated to obtain a diluted pulp slurry, which can be further processed.

10 [0042] In the pulp mills, chemical pulp is commonly bleached by hydrogen peroxide and/or other bleaching processes using for example ozone or chlorine dioxide. Mechanical and recycle pulp are often bleached with hydrogen peroxide to increase brightness of the pulp. During one or more of these bleaching stages, hydrogen peroxide together with the manganese catalyst can be employed to obtain cellulose that can be treated in the refining process. The manganese catalyst and hydrogen peroxide can be added during different stages in the pulp mill.

15 [0043] In a pulp mixer, chemicals are added to the pulp, which is then mixed very thoroughly. Within the scope of this invention, catalyst and hydrogen peroxide could be added to the pulp mixer to achieve treatment of the pulp. This can be done in low consistency mixers (continuous stirred mixers, tower mixers, dynamic mixers or static mixers), medium consistency mixers (peg mixers, high shear mixers) or high consistency mixers, including Kneader and disc-type mixers. In a steam mixer, steam is added to the pulp to increase the temperature of the pulp. The catalyst and hydrogen peroxide may also be added to the pulp in the steam mixer.

20 [0044] Reference is made to Pulp Bleaching, Principle and Practice, C.W. Dence, D.W. Reeve ed., Tappi, Atlanta, 1996).

25 [0045] After adding the pulp bleaching chemicals in the mixers, the bulk of the pulp bleaching takes place in the pulp bleaching tower, after which the pulp is washed. As bleaching processes are generally slow (2-4 h are typical), the bleaching towers tend to be large. However, also smaller pulp retention pipes are sometimes employed to allow certain bleaching or treatment reactions to occur. As the processes are generally continuous, the pulp is either moving slowly upwards (upflow tower), downwards (downflow tower), or a combination thereof (upflow-downflow tower). Within the scope of this invention, the treatment by the catalyst and hydrogen peroxide, may be much shorter, allowing relatively small treatment towers.

30 [0046] In a pulp washer usually the pulp treated with chemicals in a previous stage of the treatment process are washed out. For example, acidic chlorine dioxide is washed with NaOH solution, to remove alkaline-soluble lignin residues and make the pulp ready for the next stage. Within the scope this invention, the manganese catalyst and hydrogen peroxide could be added into an (additional) mixer, making use of its fast reaction kinetics to treat the pulp with the catalyst.

35 [0047] A pulp storage tower is designed to store pulp to process further after a period of time. Usually such storage tower can be found before the processes where the pulp bleaching stages are taken place or after the final bleaching stage, before e.g. transporting to the paper mill. Catalyst and hydrogen peroxide can be added together with the pulp entering this storage tower, allowing a slow treatment process of the pulp.

[0048] A pulper is used to dilute waste paper (deinked pulp) and to add alkaline and hydrogen peroxide for bleaching of deinked pulp. The manganese catalyst could be added in this pulper to allow the treatment of deinked pulp by the catalyst.

40 [0049] Also the manganese catalyst and hydrogen peroxide can be added to the cellulosic pulp before the refining process in the paper mill, such as in the pulper, high density pulp chest, pulp latency chest, pulp mixing chest or pulp levelling chests. The pulper and high density chest are commonly used to prepare dry raw material, half stuff and recycle paper into a pumpable state by addition of water and then mixing with water. In the pulp mixing chest, two or more different types of pulp, optionally refined, are mixed and stored for further processing, such as softwood and hardwood pulp. In levelling chests the consistency of wood pulp is lowered to desired levels.

45 [0050] Mechanical pulp is often treated in latency chests to treat the fibers that are distorted (kinked, curled, or twisted). Typically mechanical pulp is diluted to 1-2% consistency, heated to 70-90 °C, agitated for at least 20 minutes, after which it is further processed. Pulp stock chests are, similarly to the pulp storage described above, used to store the wood pulp. Also the other above-mentioned chests are often used to store the wood pulp and ensure a constant flow of pulp to be treated in the subsequent processes. The wood pulp may be shipped from pulp bleaching mills or it may have been produced on site (integrated mill).

50 [0051] Alternatively the catalyst/hydrogen peroxide can be added just before the pulp refiner and be allowed to react with the cellulose during the refining process. Due to heat evolution during refining, the additional energy requirement to obtain an optimal treatment effect by the catalyst will be reduced or absent. Different refining equipment can be used, which includes beaters; Hollander beaters; shallow-angle conical refiners; medium-angle conical refiners; wide-angle conical refiners; single-disc refiners; double-disc refiners; multi-disc refiners. Reference is made to Paper and Board Grades, Papermaking Part 1. Stock Preparation and Wet End, Book 18, chapter 4, by the Finnish Paper Engineers' Association and TAPPI (2000) and C.F. Baker, Tappi Journal, 78, 147, 1995.

[0052] Finally, the catalyst/hydrogen peroxide may be added after the mechanical refining stage, in for example in the pulp blend chest (where the different wood pulp sources are mixed) or pulp stock chest. For example mechanical pulp may be treated this way.

5 TRANSITION METAL CATALYST

[0053] The manganese transition metal catalyst used may be non-deliquescent by using counter ions such as PF_6^- or ClO_4^- , it is preferred for industrial substrates that the transition metal complex is water soluble. It is preferred that the preformed transition metal is in the form of a salt such that it has a water solubility of at least 50 g/l at 20 °C. Preferred salts are those of chloride, acetate, sulphate, and nitrate. These salts are described in WO 2006/125517.

[0054] Preferably, R1, R2, R3, and R4 are independently selected from: H and Me. Most preferably, the catalyst is derived from a ligand selected from the group consisting 1,4,7-Trimethyl-1,4,7-triazacyclononane ($\text{Me}_3\text{-TACN}$) and 1,2-bis-(4,7-dimethyl-1,4,7-triazacyclonon-1-yl)-ethane ($\text{Me}_4\text{-DTNE}$).

[0055] The preformed transition metal catalyst salt is preferably a dinuclear Mn(III) or Mn(IV) complex with at least one O^{2-} bridge.

[0056] The level of application of the manganese catalysts can vary depending on the application, but will be typically between 0.0005 and 0.2 kg/t oven-dry pulp (o.d.p.).

20 HYDROGEN PEROXIDE

[0057] The hydrogen peroxide is provided as an aqueous solution per se, or as peroxy salts, such as, percarbonate, etc. However, for cost reasons liquid hydrogen peroxide is preferred. A preferred level of hydrogen peroxide applied is: 0.1 kg/t to 100 kg/t oven dry pulp (o.d.p.), more preferable 0.3 to 50 kg/t o.d.p. and most preferred 0.5 to 25 kg/t o.d.p.

[0058] The reagents are preferably provided in an alkali medium, optimally between pH 8 and 13, the alkalinity of which is preferably provided by sodium hydroxide or sodium carbonate.

[0059] The temperature of the treatment process is preferably between 30°C and 95°C and more preferably between 40°C and 90°C.

[0060] The time of the treatment with the catalyst and hydrogen peroxide is between 1 minute and 4 hours, more preferably between 5 minutes and 3 hours, and most preferably between 10 minutes and 2 hours.

30 SEQUESTRANT

[0061] Many sequestrants are suitable for use with the present invention. Suitable sequestrants include ethylenediamine tetra-acetate (EDTA), the polyphosphonates such as Dequest™ and non-phosphate stabilisers such as EDDS (ethylene diamine di-succinic acid).

[0062] The sequestrant used in the treatment step with manganese catalyst and hydrogen peroxide is preferably a aminocarboxylate sequestrant or mixtures thereof. The following are preferred examples of aminocarboxylate sequestrants: ethylenediaminetetraacetic acid (EDTA), N-hydroxyethylenediaminetetraacetic acid (HEDTA), iminodisuccinic acid (IDS), nitrilotriacetic acid (NTA), N-hydroxyethylaminodiacetic acid, diethylenetriaminepentaacetic acid (DTPA), methylglycinediacetic acid (MGDA), and alanine-N,N-diacetic acid. A most preferred aminocarboxylate sequestrant is diethylenetriaminepentaacetic acid (DTPA).

[0063] Phosphonate sequestrants may also be used; a preferred phosphonate sequestrant is Dequest 2066 (Diethylenetriamine Penta(methylene phosphonic acid sodium salt)).

[0064] The most preferred concentration of the sequestrant used in the method is 0.01 to 50 kg/ton oven dry pulp in the solution containing the manganese catalyst and hydrogen peroxide, most preferably 0.03 to 20 kg/ton oven dry pulp.

EXPERIMENTAL

[0065] Experiment 1: Treatment of softwood pulp with hydrogen peroxide with and without $[\text{Mn}_2(-\text{O})_3(\text{Me}_3\text{TACN})_2](\text{CH}_3\text{COO})_2$ at pH 11.0 ($\text{Me}_3\text{-TACN}$ = 1,4,7-Trimethyl-1,4,7-triazacyclononane).

[0066] $[\text{Mn}_2(-\text{O})_3(\text{Me}_3\text{TACN})_2](\text{CH}_3\text{COO})_2$ (as 3.5% aqueous solution) was obtained as disclosed elsewhere (WO2006/125517).

[0067] Softwood pulp with a starting ISO-brightness of 49.9 was treated as follows: To a 1 L polyethylene (PE) bottle containing 250 g of oven-dry pulp was added 10 kg/odtp H_2O_2 (odtp=oven-dry ton pulp - equals to 29.4 mM H_2O_2) and 7.2 kg/odtp NaOH (equals to 18 mM NaOH). Depending on the experiments 0.04 kg/odtp $[\text{Mn}_2(-\text{O})_3(\text{Me}_3\text{TACN})_2](\text{CH}_3\text{COO})_2$ (equals to 6.5 μM $[\text{Mn}_2(-\text{O})_3(\text{Me}_3\text{TACN})_2](\text{CH}_3\text{COO})_2$) was added and 1.0 kg/odtp DTPA (Diethylenetriaminepenta-acetic acid, pentasodium salt) - (ex Akzo Nobel; trade name Dissolvine D50; purity is 50%). The pH-value was pH 11.0 (measured at 20°C).

EP 2 395 147 A1

Note 1: This softwood pulp has been delignified in a O₂-delignification step, and partly further bleached by a ClO₂ step.

Note 2: In practice, pulp was used that contained 35.6% dry matter and 64.4% water (35.6% dry content). Therefore 702.3 g of 'wet' pulp was used for each experiment.

Note 3: All experiments were carried out at 10% consistency.

5

[0068] The PE bottles are put in a pre-heated water bath (62.5°C) for 1 hour and are shaken throughout the bleaching process. Subsequently the pulp mixture is filtrated through a Buchner funnel and washed with copious amounts of demineralised water. Using the filtrate, the H₂O₂ consumption is measured. The following analyses are carried out on the bleached pulp: kappa number, brightness and intrinsic viscosity.

10 **[0069]** The results of the experiments are given in Table 1.

Table 1 Results of treatment of softwood pulp using [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂, [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ and DTPA and no [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ at pH 11.0 at 60°C for 60 minutes.

15

N°	Sample	Brightness (ISO %)	Intr. Visc. (ml/g)	Kappa #	H ₂ O ₂ consumption (kg/odtp)
U	Untreated (raw)	49.9	764	8.33	
P1	Blank (no catalyst)	67.4	753	4.27	7.5
P2	0.04 kg/odtp [Mn ₂ (-O) ₃ (Me ₃ TACN) ₂](CH ₃ COO) ₂ and 1 kg/odtp DTPA	68.1	701	4.11	7.8
P3	0.04 kg/odtp [Mn ₂ (-O) ₃ (Me ₃ TACN) ₂](CH ₃ COO) ₂	66.8	698	4.17	9.6

20

25

30

[0070] The results gathered in Table 1 show that the addition of [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ has some effect on the bleaching and kappa value and a clear effect on viscosity (degree of cellulose polymerization) of softwood pulp.

35

[0071] The treated pulp was desintegrated (DIN EN ISO 5263-1; 2004-12), beaten (PFI-mill) (ÖNORM EN ISO 5264-2; 2003-05) and the drainability (Schopper-Riegler method, ÖNORM EN ISO 5267-1; 2000-10) was tested.

[0072] Laboratory handsheets were prepared by the Rapid-Köthen method (ÖNORM EN ISO 5269-2; 2005-04) and conditioning of the samples, NC 23/50 was carried out (DIN EN 20187; 1993-11). The following tests were conducted using the handsheets: grammage (DIN EN ISO 536; 1996-08), thickness, bulk and density (DIN EN ISO 534; 2005-05), air permeance (Bendtsen, ISO 5636/3; 1992-09), tensile force, stretch at break, tensile strength, tensile index, TEA and elastic modulus (DIN EN ISO 1924-2; 2009-05), internal bond strength (z-direction, TAPPI 541 om-05; 2005), tearing resistance, tear index (ÖNORM EN 21974; 1994-09).

40

[0073] The results are given in the following tables.

45

Table 2 Results of beating and drainability of bleached softwood pulp using [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ (P1), [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ and DTPA (P2) and no [Mn₂(-O)₃(Me₃TACN)₂](CH₃COO)₂ (P3) at pH 11.0 at 60°C for 60 minutes.

50

Sample Drainability	P1 [SR]	P2 [SR]	P3 [SR]
Unbeaten	14.0	13.8	14.0
PFI 2000 Revolutions	15.9	16.2	16.9
PFI 5000 Revolutions	24.1	24.3	23.2
PFI 7000 Revolutions	32.7	32.8	32.9
PFI 9000 Revolutions	41.6	46.5	45.5

55

[0074] The results gathered in Table 2 show that the pulp samples treated with the catalyst and hydrogen peroxide exhibit similar SR values till 7000 revolutions as the reference, whilst increase SR values are obtained when the pulp is refined at 9000 revolutions.

Table 3 Strength and tear values of handsheets prepared using pulp refined at 5000 revolutions


Sample		P1 5000rev	P2 5000rev	P3 5000rev
Grammage	[g/m ²]	80.2	81.0	80.2
Thickness	[μm]	111	112	113
Density	[g/cm ³]	0.724	0.725	0.711
Bulk	[cm ³ /g]	1.380	1.380	1.407
Air permeance (Bendtsen)	[ml/min]	429	435	560
Tensile force	[N]	101	111	108
Stretch at break	[%]	2.96	2.89	2.89
Tensile strength	[kN/m]	6.74	7.42	7.21
Tensile index	[Nm/g]	84.1	91.6	89.9
TEA	[J/m ²]	136	144	141
Elastic modulus	[GPa]	6.33	6.92	6.76
Internal bond strength	[N/cm ²]	82.6	81.5	84.1
Tearing resistance	[mN]	877	827	814
Tear index	[mN.m ² /g]	10.9	10.2	10.2

[0075] The results gathered in Table 3 show that the pulp samples treated with the catalyst and hydrogen peroxide and then refined at 5000 revolutions in the PFI mill, show increased tensile strength, tensile energy absorption (TEA) and tensile index values, decreased tearing resistance and tear index, whilst the other parameters are largely unaffected by the treatment using the catalyst and hydrogen peroxide. A slight enhanced of these tensile strength properties when the catalyst was employed in combination with DTPA.

Claims

1. A method for the treatment of a cellulose pulp suspension comprising (i) the step of subjecting cellulose pulp fibres to an aqueous solution of a manganese transition metal catalyst and hydrogen peroxide at pH from 6 to 13 and (ii) subjecting the pulp to a refining process until a Shopper Riegler (SR) value of from 10 to 90° is reached and the resultant pulp is processed into paper, tissue or board, wherein the manganese transition metal catalyst is present at a concentration from 0.0001 to 1 kg/tonne oven-dry pulp and the hydrogen peroxide is present at a concentration from 0.1 to 100 kg/tonne oven-dry pulp, the manganese transition metal catalyst is preformed and a mononuclear Mn(II), Mn(III), Mn(IV) or dinuclear Mn(II)Mn(II), Mn(II)Mn(III), Mn(III)Mn(III), Mn(III)Mn(IV) or Mn(IV)Mn(IV) transition metal catalyst, the ligand of the transition metal catalyst of formula (I):


5



10

wherein:

15



20

p is 3;

R is independently selected from: hydrogen, C1-C6-alkyl, C2OH, C1COOH, and pyridin-2-ylmethyl or one of R is linked to the N of another Q from another ring via an ethylene bridge;

R1, R2, R3, and R4 are independently selected from: H, C1-C4-alkyl, and C1-C4-alkylhydroxy.

25

2. A method according to claim 1, wherein R is independently selected from:

hydrogen, CH3, C2H5, CH2CH2OH and CH2COOH.

30

3. A method according to claim 1 or 2, wherein R, R1, R2, R3, and R4 are independently selected from: H and Me.

4. A method according to claim 1, wherein the catalyst is derived from a ligand selected from 1,4,7-trimethyl-1,4,7-triazacyclononane (Me₃-TACN) and 1,2-bis-(4,7-dimethyl-1,4,7-triazacyclonon-1-yl)-ethane (Me₄-DTNE).

35

5. A method according to any one of the preceding claims, wherein the pulp is subjected to a refining process until a Shopper Riegler (SR) value of from 10 to 30° is reached, to produce tissue paper.

6. A method according to any one of claims 1 to 4, wherein the pulp is subjected to a refining process until a Shopper Riegler (SR) value of from 15 to 50° is reached, to produce printing and writing paper.

40

7. A method according to any one of claims 1 to 4, wherein the pulp is subjected to a refining process until a Shopper Riegler (SR) value of from 50 to 90° is reached, to produce tracing and transparent paper.

8. A method according to any one of claims 1 to 4, wherein mechanical pulp is subjected to a refining process until a Shopper Riegler (SR) value of from 20 to 80° is reached.

45

9. A method according to any one of the preceding claims, wherein the catalyst and hydrogen peroxide is added to the pulp in a device selected from: a pulper; a high density pulp chest; a pulp washer; a pulp latency chest; a pulp levelling chest; a pulp mixing chest; a pulp refiner; a pulp dilution tank; and, a pulp stock chest.

50

10. A method according to claim 9, wherein the pulp refiner is selected from:

beaters; Hollander beaters; shallow-angle conical refiners; medium-angle conical refiners; wide-angle conical refiners; single-disc refiners; double-disc refiners; and, multi-disc refiners.

55

11. A method according to any one of the preceding claims, wherein the catalyst and hydrogen peroxide is added to the pulp during one of the bleaching stages for chemical, mechanical or recycle pulp treatment.

12. A method according to claim 11, wherein the catalyst and hydrogen peroxide is added to the pulp in a device selected

EP 2 395 147 A1

from a pulp mixer; a pulp bleaching tower; a pulp retention pipe; a pulp washer; a pulp storage tower; a steam mixer; and a pulper.

5 **13.** A method according to any one of the preceding claims, wherein the solution containing the catalyst and hydrogen peroxide comprises from 0.01 to 50 kg/ton oven dry pulp of an organic sequestrant, the sequestrant selected from: an aminophosphonate sequestrant and a carboxylate sequestrant.

14. A method according to claim 13, wherein the sequestrant is selected from:

10 Dequest 2066 (Diethylenetriamine Penta(methylene phosphonic acid sodium salt)), MGDA(methylglycindi-
acetate), GLDA (glutamic acid diacetate), IDS (iminodissuccinate), EDDS (ethylenediaminedisuccinate), EDTA
(ethylenediamine-tetraacetate), and DTPA (diethylenetriaminepentaacetate).

15 **15.** A method according to any one of the preceding claims, wherein the energy input into the refining treatment is monitored and based upon the energy input threshold pulp is processed into paper, tissue or board.

20

25

30

35

40

45

50

55



EUROPEAN SEARCH REPORT

Application Number
EP 10 16 2405

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
Y	US 2002/066542 A1 (JAKOB HARALD [DE] ET AL) 6 June 2002 (2002-06-06) * paragraph [0010]; claims 1-26 * -----	1-15	INV. D21C9/00 D21C9/10 D21C9/16
Y,D	US 2001/025695 A1 (THE FIRM OF KARL F ROSS) 4 October 2001 (2001-10-04) * claims 1-3,21 * -----	1-15	D21D1/02 D21D1/20 D21D1/30 D21D1/34
X,D	WO 2006/125517 A1 (UNILEVER PLC) 30 November 2006 (2006-11-30)	1-15	
Y	* page 6, line 10 - line 18; claims 1-25 * -----	1-15	
Y	EP 2 103 735 A1 (UNILEVER PLC [GB]) 23 September 2009 (2009-09-23) * claims 1-13 * -----	1-15	
Y,D	WO 2008/086937 A2 (UNILEVER PLC) 24 July 2008 (2008-07-24) * claims 1-13 * -----	1-15	
A	US 2004/198626 A1 (REINHARDT GERD [DE] ET AL) 7 October 2004 (2004-10-07) * claims 1-10 * -----	1-15	TECHNICAL FIELDS SEARCHED (IPC) D21C D21D
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 29 July 2010	Examiner Ponsaud, Philippe
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

1
EPO FORM 1503 03.82 (F04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 10 16 2405

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-07-2010

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002066542 A1	06-06-2002	BR 0104611 A	04-06-2002
		CA 2359162 A1	17-04-2002
		DE 10051317 A1	18-04-2002
		EP 1199402 A2	24-04-2002
		KR 20020030731 A	25-04-2002
		NO 20015027 A	18-04-2002
		ZA 200108492 A	06-06-2002
US 2001025695 A1	04-10-2001	BR 9709108 A	03-08-1999
		CA 2255588 A1	27-11-1997
		CN 1225698 A	11-08-1999
		DE 19620241 A1	27-11-1997
		WO 9744520 A1	27-11-1997
		EP 0900300 A1	10-03-1999
		JP 2000510914 T	22-08-2000
WO 2006125517 A1	30-11-2006	AR 056367 A1	10-10-2007
		AU 2006251406 A1	30-11-2006
		BR PI0610466 A2	22-06-2010
		CA 2608440 A1	30-11-2006
		CN 101253292 A	27-08-2008
		US 2009205143 A1	20-08-2009
		ZA 200710210 A	25-02-2009
EP 2103735 A1	23-09-2009	NONE	
WO 2008086937 A2	24-07-2008	AR 064890 A1	06-05-2009
		AU 2007344425 A1	24-07-2008
		CA 2670743 A1	24-07-2008
		CL 1052008 A1	05-09-2008
		CN 101589191 A	25-11-2009
		EP 2104765 A2	30-09-2009
		US 2010101029 A1	29-04-2010
US 2004198626 A1	07-10-2004	DE 10304131 A1	05-08-2004
		EP 1445305 A1	11-08-2004
		ES 2273103 T3	01-05-2007
		JP 2004238623 A	26-08-2004

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2005028744 A [0005]
- WO 2004022842 A [0006]
- EP 0458397 A [0007]
- US 20010025695 A1, Patt [0008]
- WO 2007125517 A [0009]
- WO 2008086937 A [0010]
- WO 2006125517 A [0053] [0066]

Non-patent literature cited in the description

- Paper and Board Grades, Book 18. Finnish Paper Engineers' Association and TAPPI. 2000 [0024]
- Paper and Board Grades, Papermaking Part 1. Stock Preparation and Wet End, Book 18. Finnish Paper Engineers' Association and TAPPI. 2000 [0030] [0051]
- Pulp Bleaching, Principle and Practice. 1996 [0044]
- C.F. BAKER. *Tappi Journal*, 1995, vol. 78, 147 [0051]