



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
01.02.2012 Bulletin 2012/05

(51) Int Cl.:
G01D 4/00 (2006.01)

(21) Application number: **11176038.5**

(22) Date of filing: **29.07.2011**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **Curt, Walter**
Harrisonburg, VA Virginia 22801 (US)
• **Mullins, Christopher**
Penn Laird, VA Virginia 22846 (US)

(30) Priority: **29.07.2010 US 369045 P**

(74) Representative: **Kastel, Stefan et al**
Flügel Preissner Kastel Schober
Nymphenburger Strasse 20a
80335 München (DE)

(71) Applicant: **Power Monitors, Inc.**
Mount Crawford, Virginia 22841 (US)

(54) **Method and apparatus for a demand management monitoring system**

(57) A demand management monitoring system including a remote measurement device including a micro-processor for calculating RMS voltage data from digital

samples and a wireless communications device, and a server system including a database configured to store the RMS voltage data from the remote measurement device.




FIG. 1

Description

RELATED APPLICATIONS

[0001] This application claims priority to U.S. Provisional Application S.N. 61/369,045, filed July 29, 2010, for METHOD AND APPARATUS FOR A DEMAND MANAGEMENT MONITORING SYSTEM.

BACKGROUND

[0002] Increased demand on the electric distribution grid increases the need for more careful management of system voltage, especially with regards to peak demand. Over a 24 hour period, the peak power consumed may be much higher than the average power. Since transformers, wire, and other infrastructure may be sized for the highest power, not the average power, increases in peak demand require equipment capable of handling that peak demand, such as larger transformers and so on. Conversely, reducing the peak demand allows utilities to postpone the upsizing of infrastructure in the face of rising total demand. Utilities may purchase power at much higher rates during times of peak demand, due to typical contract agreements. Reducing power consumption during times of peak demand may have larger financial benefit than reducing consumption at other times. Flattening the demand curve may have multiple benefits for utilities, and may reduce the need for extra generation as loading increases.

[0003] One technique for reducing demand is Conservation Voltage Regulation (CVR). With CVR, the distribution system voltage is reduced during times of peak demand. Resistive loads may consume less power when the voltage is reduced. Power consumption may be proportional to the square of the voltage for many loads, so a 1% reduction in voltage can produce a larger than 1% change in power consumption. Reductions of between 2% and 10% of total power have been achieved with CVR techniques.

[0004] To implement CVR, utilities may need much finer control over the distribution system voltage, and the voltage delivered to customers. To accomplish this, devices may be required both to adjust and measure the distribution line voltage at many strategic locations. Voltage measurements may be required for two reasons. First, actual voltage levels may be needed as part of a closed-loop feedback system, so a centralized Demand Management System can make decisions about how to adjust voltage regulators and other management devices. These voltage readings may typically be used in conjunction with system models and historical patterns, and after suitable calculations, commands may be sent to voltage regulators, capacitor banks, and so on. Second, voltage measurements may be needed to insure that regulatory voltage limits are not crossed. For example, as part of a CVR system, the voltage is typically lowered during times of peak demand, leaving much less safety

margin. Regulatory limits dictate how low a voltage is allowed, and monitoring may be required to insure that these limits are met. These limits are applied at the point of delivery to customers, which may typically be the service entrance or revenue meter location.

[0005] Traditional sensors may be too slow for real-time systems, for example, those based on slow power line carrier systems, or many Automated Meter Reading (AMR) systems, or too bulky and expensive for widespread or residential deployment. Existing cellular radio solutions may not be practical for use in residential locations, due to the size and obtrusiveness of the hardware. In addition, existing systems have limited, or no, provision for storing and analyzing historical voltage data.

SUMMARY

[0006] In various embodiments, a system, method, and apparatus are provided for demand management monitoring in a power distribution system.

[0007] In one embodiment, a demand management monitoring system includes a remote measurement device where the remote measurement device includes a microprocessor configured to calculate RMS voltage data from digital samples and a wireless communications device, and a server system which includes a database configured to store the RMS voltage data from the remote measurement device.

[0008] Additional features and advantages are described herein, and will be apparent from, the following Detailed Description and the figures.

[0009] Several aspects and/or advantageous embodiments of the invention are given in the following clauses:

[0010] Clause 1: An apparatus for a demand management monitoring system comprising:

at least one remote measurement device, the remote measurement device comprising a microprocessor configured to calculate RMS voltage data from digital samples and a wireless communications device.

[0011] Clause 2: The apparatus of clause 1, wherein the remote measurement device further comprises:

a voltage input configured to receive a line voltage from a powerline;
a voltage reducer configured to reduce a voltage of the line voltage; and
an analog to digital (A/D) converter configured to convert the line voltage to the digital samples.

[0012] Clause 3: The apparatus of any of the preceding clauses, especially clause 2, wherein the voltage reducer comprises a transformer.

[0013] Clause 4: The apparatus of any of the preceding clauses, especially clause 2, wherein the voltage reducer comprises a pulse-withstanding divider resistor network.

[0014] Clause 5: The apparatus of any of the preceding

clauses, especially clause 1, wherein the remote measurement device further comprises a low power wireless communications device configured to receive data from external sensors.

[0015] Clause 6: The apparatus of any of the preceding clauses, especially clause 2, wherein the remote measurement device further comprises a signal conditioning circuit configured to receive the line voltage from the voltage reducer and condition the line voltage.

[0016] Clause 7: The apparatus of any of the preceding clauses, especially clause 1, wherein the remote measurement device is contained in a standard meter base adapter.

[0017] Clause 8: The apparatus of any of the preceding clauses, especially clause 1, wherein the wireless communication device is adapted to communicate directly with an external utility system.

[0018] Clause 9: The apparatus of any of the preceding clauses, especially clause 8, wherein the external utility system is a SCADA system using at least one of a DNP3 interface, IEC 61850 interface, and another standard SCADA protocol interface.

[0019] Clause 10. An apparatus for a demand management monitoring system comprising:

a server system comprising a database configured to store the RMS voltage data from at least one remote measurement device and a listening process configured to receive data comprising the RMS voltage data and other data from the remote measurement devices through a network.

[0020] Clause 10a: An apparatus as indicated any of the clauses 1 to 9 the apparatus being an apparatus for a demand management monitoring system comprising:

a server system comprising a database configured to store the RMS voltage data from at least one remote measurement device and a listening process configured to receive data comprising the RMS voltage data and other data from the remote measurement devices through a network.

[0021] Clause 11: The apparatus of any of the preceding clauses, especially clause 10, wherein the server system further comprises:

a dataset preprocessor configured to decimate and chunk the RMS voltage data.

[0022] Clause 12: The apparatus of any of the preceding clauses, especially clause 10, wherein the server system further comprises:

an alarm process configured to search the other data for alert and event messages.

[0023] Clause 13: The apparatus of any of the preceding

clauses, especially clause 10, wherein the server system further comprises:

an email and SMS alert process configured to distribute email and SMS alerts based on the alert and event messages in the other data.

[0024] Clause 14. The apparatus of any of the preceding clauses, especially clause 10, wherein the server system further comprises:

a web server configured to display the RMS voltage data and the other data on a web page.

[0025] Clause 15: The apparatus of any of the preceding clauses, especially clause 10, wherein the server system further comprises:

a dataset process configured to access the RMS voltage data and other data in the database and prepare the RMS voltage data and other data for display on a web page.

[0026] Clause 16. The apparatus of any of the preceding clauses, especially clause 10, wherein the server system further comprises:

an external interface configured to access the RMS voltage data and other data in the database and transmit the RMS voltage data and other data to a requesting external utility system.

[0027] Clause 17. The apparatus of any of the preceding clauses, especially clause 10, wherein the other data includes environmental data.

[0028] Clause 18. A method for a remote measurement device in a demand management monitoring system comprising:

receiving a line voltage;
reducing a voltage of the line voltage;
calculating an RMS voltage of the line voltage; and
transmitting the RMS voltage.

[0029] Clause 18a: A method for operating a remote measurement device in a demand management monitoring system, comprising:

receiving a line voltage;
reducing a voltage of the line voltage;
calculating an RMS voltage of the line voltage; and
transmitting the RMS voltage.

[0030] Clause 19: The method of any of the preceding clauses, especially clause 18, further comprising:

conditioning the line voltage.

[0031] Clause 20: The method of any of the preceding clauses, especially clause 18, further comprising:

receiving environmental data from at least one external sensor; and
transmitting the environmental data.

[0032] Clause 21: The method of any of the preceding clauses, especially clause 18, further comprising:

detecting an event or alarm condition; and
transmitting an alarm or even message.

[0033] Clause 22: The method of any of the preceding clauses, especially clause 18, wherein the RMS voltage is transmitted to a server system.

[0034] Clause 23: The method of any of the preceding clauses, especially clause 18, wherein the RMS voltage is transmitted to an external utility system.

[0035] Clause 24: A method for a server system in a demand management monitoring system comprising:

receiving data comprising RMS voltage data;
checking the data for alarm or event messages; and
inserting the data into a database.

[0036] Clause 24a: A method for operating a server system in a demand management monitoring system comprising:

receiving data comprising RMS voltage data;
checking the data for alarm or event messages; and
inserting the data into a database.

[0037] Clause 25: The method of any of the preceding clauses, especially clause 24, further comprising:

transmitting at least one of an email and an SMS alert when an alarm or event message is found in the data.

[0038] Clause 26: The method of any of the preceding clauses, especially clause 24, further comprising:

preprocessing that data before inserting the data into the database, wherein the preprocessing comprises at least one of decimating the data and chunking the data.

[0039] Clause 27: The method of any of the preceding clauses, especially clause 24, further comprising:

receiving a request for a portion of the data;
retrieving the portion of the data from the database;
processing the portion of the data for display; and
displaying the portion of the data on a web page.

[0040] Clause 28: The method of any of the preceding

clauses, especially clause 27, wherein processing the data comprises at least one of converting the data into a graph and converting the data into a chart.

[0041] Clause 29: The method of any of the preceding clauses, especially clause 24, further comprising:

receiving a request for a portion of the data from an external utility system;
retrieving the portion of the data from the database;
and
transmitting the portion of the data to the external utility system.

Clause 30: The method of any of the preceding clauses, especially clause 24, further comprising:

[0042] displaying a map on a web page, wherein the map comprises at least one marker indicating the location of at least one remote measurement device;
retrieving a portion of the data related to the at least one remote measurement device from the database; and
displaying the portion of the data on the web page.

[0043] Clause 31: The method of any of the preceding clauses, especially clause 24, further comprising:

receiving an instruction for at least one remote measurement device through a web page; and
transmitting the instruction to the at least one remote measurement device.

[0044] Clause 32: The method of any of the preceding clauses, especially clause 24, wherein the data further comprises environmental data.

BRIEF DESCRIPTION OF THE FIGURES

[0045] Fig. 1 depicts an exemplary overview diagram of system for demand management monitoring in a power distribution system;

[0046] Fig. 2 depicts exemplary diagram of system for demand management monitoring in a power distribution system including multiple remote measurement devices;

[0047] Fig. 3 depicts an exemplary diagram of a remote measurement device;

[0048] Fig. 4 depicts an exemplary diagram of a server system;

[0049] Fig. 5 depicts an exemplary web front end;

[0050] Fig. 6 depicts an exemplary procedure for operating a remote measurement device;

[0051] Fig. 7 depicts an exemplary procedure for receiving data from a remote measurement device at a server system;

[0052] Fig. 8 depicts an exemplary procedure for operating a web server on the server system; and

[0053] Fig. 9 depicts an exemplary procedure for operating an external interface on the server system.

DETAILED DESCRIPTION

[0054] In various embodiments as illustrated in Figs. 1-9, a remote measurement device measures voltage levels and ancillary data at a location in a power distribution system and transmits the data to a server system to be stored in a database and made accessible through a web front end and an external interface.

[0055] Fig. 1 depicts an exemplary overview diagram of system for demand management monitoring in a power distribution system. The system may include a remote measurement device 101 and a server system 107. The remote measurement device 101 may be installed in a power distribution system, and may receive voltage from a powerline 103 through a voltage input 102. The remote measurement device 101 may use a wireless communications device 104 to communicate, using wireless signals 105, with the server system 107, through a network 106. The network 106 may be, for example, the Internet. A computing device 108 and an external utility system 109 may access the server system 107, for example, through the network 106.

[0056] Fig. 2 depicts exemplary diagram of system for demand management monitoring in a power distribution system including multiple remote measurement devices. Multiple remote measurement devices 101 may be installed at strategic locations in a power distribution system. The server system 107 may receive data from, and send data to, any of the remote measurement devices 101. Data received from the remote measurement devices 101, such as, for example, voltage readings, including RMS voltage, may be stored by the server system 107, for example, in a database.

[0057] Fig. 3 depicts an exemplary diagram of a remote measurement device. The remote measurement device 101 may include the voltage input 102 for the powerline 103, a voltage reducer 301, a signal conditioning circuit 302, an Analog to Digital (A/D) convertor 303, a microprocessor 304, a wireless communications device 104, and a low power wireless communications device 306. The remote measurement device 101 may be contained in a small size and form factor, such as, for example, in a standard meter base adapter. This may allow the remote measurement device 101 to be placed between a residential meter base and revenue meter, without installing a large amount of hardware. Installing the remote measurement device 101 in a revenue meter may make it easier to perform voltage measurements required to ensure compliance with regulatory voltage limits, as the voltage drop in the service drop from the pole to the meter base must be included in the measurements.

[0058] The voltage reducer 301 may be any suitable device for reducing the voltage received by the voltage input 102 from the powerline 103. For example, the voltage reducer 301 may be a resistive divider circuit. The signal conditioning circuit 302 may be any suitable device for conditioning the reduced voltage signal from the voltage reducer 301. For example, the voltage reducer 301

may be a low-pass filter.

[0059] The A/D convertor 303 may be any suitable device for digitizing an analog signal. The A/D converter 303 may receive the voltage signal and convert the voltage signal into a digital signal including digital samples, using any suitable sample rate. The digital signal from the A/D converter 303 may be sent to the microprocessor 304.

[0060] The microprocessor 304 may be any suitable device for performing computation on received data. For example, the microprocessor 304 may be a low-voltage CPU, an FPGA, a DSP, or any other high-speed programmable logic device. The microprocessor 304 may read A/D values from the digital signal, and compute RMS voltage from the raw data. The microprocessor 304 may also be capable of direct waveform sampling, enabling the computation of harmonics, waveform capture, flicker, and other PQ metrics.

[0061] Alternatively, the remote measurement device 101 may use an energy monitoring integrated circuit (IC), which may be used generally in revenue metering applications. The RMS voltage may be read directly from the energy monitoring IC.

[0062] The wireless communications device 104 may be any suitable device for wireless communication and data transmission, including, for example, a digital cellular modem or a Wi-Fi device using any suitable wireless protocol. The wireless communications device 104 may be connected to the microprocessor 304, and may send data to and receive data from the server system 107, through, for example, the network 106. The microprocessor 304 may be a separate processor from the wireless communications device 104, or the microprocessor 104 may be embedded in the wireless communications device 104 and act as both a processor for the wireless communications device 104 and an RMS processor, reading voltage data directly.

[0063] The remote measurement device 101 may also include hardware capable of current measurements, such as, for example, Rogowski coil transducers with hardware or software integration.

[0064] The low power wireless communications device 306 may be any suitable device for wireless communication and data transmission, including, for example, RF, Wi-Fi or Bluetooth devices. The low power wireless communications 306 may wirelessly communicate with various external sensors 305, using, for example, a low power wireless protocol. The low power wireless communications device 306 may be part of, or separate from, the wireless communications device 104.

[0065] The external sensors 305 may be any suitable devices for measuring various environmental qualities that may be correlated to power consumption. The external sensors may be located remotely from the remote measurement device 101, and may measure, for example, temperature, humidity, pressure, wind speed, wind direction, and solar load. The external sensors 305 may be battery powered, or may use energy harvesting meth-

ods for power. In addition to environmental measurements, the external sensors 305 may perform additional voltage and current measurements of other electrical nodes. Data gathered by the external sensors 305 may be transmitted to the remote measurement device 101 through wireless signals 307 received by the low power wireless communications device 306.

[0066] The remote measurement device 101 may connect to the server system 107 at power up. At periodic intervals, the remote measurement device 101 may send status messages to the server system 107. At other intervals, the remote measurement device 101 may send stripchart interval data for various measured quantities, such as, for example, RMS voltage over a certain averaging period, to the server system 107. The measurements may be checked, for example, every second, for alarm or event conditions. If the remote measurement device 101 detects an alarm or event condition, an alarm or event notification may be sent to the server system 107. Alarm conditions may be based on crossing high or low voltage thresholds, including effects of hysteresis and minimum period past threshold. Events that trigger an event notification may include loss of power, loss of cellular signal, and so on. Optionally, the remote measurement device 101 may enter a "burst mode", where fast real-time updates may be sent for a preprogrammed amount of time. The remote measurement device 101 may be able to synchronize with a time server, such as those hosted by NIST.

[0067] The remote measurement device 101 may be capable of 3-phase measurements. In this case, the remote measurement device 101 may include three voltage inputs 102 and, optionally, three current inputs. The compression scheme used by the remote measurement device 101 when transmitting RMS voltage and other data may take advantage of correlations among the voltage and current channels. The remote measurement device 101 may also measure power and other parameters derived from voltage and current readings, and use further correlations among these readers when compressing the data.

[0068] The server system 107 may group three individual single-phase, i.e., one channel, remote measurement devices 101. This logical grouping of three of the remote measurement devices 101 may be used to emulate a 3-phase remote measurement device 101. The individual RMS voltage data from the three remote measurement devices 101 may be used to compute 3-phase voltage unbalance, and other 3-phase parameters, for storage in the database 401. The three remote measurement devices 101 may be installed on separate phases, but on the same distribution circuit, so they are electrically "close" together.

[0069] Fig. 4 depicts an exemplary diagram of a server system. The server system 107 may be any suitable combination of hardware and software, and may include a database 401, a listening process 402, a dataset preprocessor 403, an alarm process 404, an email and SMS

alert process 405, a web server 406, an external interface 407, and a dataset process 408. For example the server system 107 may be a combination of specialized server computing hardware and software. The server system 107 may be connected to the network 106, which may be, for example, the Internet.

[0070] The database 401 may be any suitable combination of hardware and software for implementing a database. The database 401 may be implemented on the same hardware as the rest of the server system 107, or may be implemented on separate hardware connected to the server system 107. The database 401 may store the data sent to the server system 107 from the remote measurement devices 101. The data may be stored database 401 in chunks, which may be, for example, 240 to 1800 data points long. The data may be chunked in the remote measurement device 101, for example, by the microprocessor 304, and received and stored in the database 401 with that chunk size, or a process on the server system 107, for example, the dataset preprocessor 403, may accumulate incoming data, and resize the chunks to the desired chunk size. Chunking the incoming data from the remote measurement devices 101 may allow for increased database performance by avoiding performing an insert operation on the database 401 for each received data point. The chunks may be stored with a timestamp and chunk length.

[0071] The database 401 may also store the data as decimated stripchart data. For example, if a graph of one year's worth of stripchart data, including one-second averages, is desired, a large number of points may be returned: $86400 \times 365 = 31$ million points. If this is graphed on a normal sized display, such as, for example, a 1024 pixel wide graph, each pixel column in the x-axis may have over 30,000 points, and thus each point may not be visible. Instead of returning all 31 million points, it may suffice to just return two sets of reduced-resolution traces. In this case, a decimation factor of 4096 may be used, resulting in two traces of 7500 points. Each of those "points" may cover 4096 actual stripchart points. One trace may be a time series of the maximum values of each set of 4096 points, and one trace may be the minimum values. These two traces may be sent to the requesting application, and graphed. The graph may be rendered by drawing a line from the 1st point's maximum value, to that point's minimum value, then to the next point's maximum value, at most one pixel over on the x-axis, and so on. This graph would may be visually identical to graphing the original 31 million point dataset, and may still show the absolute maximum and minimum values, no matter how far out the graph is zoomed. If a user zooms in on the graph, a new decimated stripchart may be returned. If the requested points are small enough, a different decimation level may be used, or none at all.

[0072] One decimation strategy may be, for example, to use factors of 16. The raw chunked data may be stored normally in the database 401. The data may then be decimated by a factor of 16, and the maximum/minimum val-

ues may be stored. For example, for every 16 points in a chunk, a maximum value and minimum value may be stored. These values may also be stored in chunks in the database 401. The decimated data may then be further decimated by a factor of 16, and so on. For example, as many as 8 levels of 16x decimation may be required. When a stripchart request is received, a start time and end time may be received. A process on the server system 107, such as, for example, the dataset process 408, may compute the appropriate decimation level such that a suitable number of points are returned. The number of points returned may be large enough so that the graph of maximum/minimum values may be visually identical to the full dataset plot, but no larger, which may minimize the amount of data transferred.

[0073] The decimated stripcharts may be computed as the data is received by the server system 107, for example, by the dataset preprocessor 403, and then sent to the database 401 in real-time, or an offline batch process may retrieve the raw data from the database 401, decimate it, and store it back in the database 401. Alternatively, the data may be stored in the database 401 without decimation, and decimation may be performed as necessary when data is requested from the database 401. This may allow the sending of the smaller sets of data provided by decimation, without having to maintain a decimated database 401.

[0074] Usage logs may be kept, which may be used to identify which graphs and reports are most likely to be accessed. Graphs and reports identified as likely to be accessed later may be pre-rendered by an offline batch processor.

[0075] The listening process 402 may be any suitable combination of hardware and software, such as, for example, back-end software running on a general purpose CPU in the server system 107. The listening process 402 may receive the data sent from the remote measurement devices 101, and may parse the incoming data packets and, if necessary, decompress stripchart and other data. The listening process 402 may pass the incoming data to the dataset preprocessor 403 and the alarm process 404.

[0076] The dataset preprocessor 403 may be any suitable combination of hardware and software. The dataset preprocessor 403 may receive data from the listening process 402, and may perform point chunking, and decimation, as described above, and may insert the data into the database 401 in any suitable manner. For example, data may be inserted into the database 401 directly after being processed through the dataset preprocessor 403, or raw and decimated stripchart buffers may be kept in memory, and when the desired chunk size reached, written to the database 401.

[0077] The alarm process 404 may be any suitable combination of hardware and software for detecting alarm conditions, and may be separate from the database 401, or may be implemented within the database 401 using database triggers and stored procedures. The

alarm process 404 may receive raw data from the listening process 402, and may parse the data looking for alarm and event messages from the remote measurement devices 101. If the alarm process 404 finds an alarm trigger condition in the data, the database 401 may be queried for what action to take. The alarm process 404 may also cache the alarm status of each remote measurement device 101, the latest status values, and the latest real-time analog readings. These cached values may be used to feed the web server 406, to avoid excessive queries to the database 401.

[0078] The email and SMS alert process 405 may be any suitable combination of hardware and software for transmitting alert communications from the server system 107. The email and SMS alert process may be triggered by the alarm process 404, and may optionally include querying the database 401 to determine the correct distribution list for a specific alarm condition. The email and SMS alert process 405 may send out alerts, for example, using email and SMS messages, when notified of an alarm condition or event message by the alarm process 404. Email alerts may be formatted, and may include text or graphical data displays, and URLs which load web content.

[0079] The dataset process 408 may be any suitable combination of hardware and software for retrieving and processing data from the database 401. When a stripchart request is received from, for example, the web server 406, the dataset process 408 may query the database 401 for the necessary chunks needed to build the desired stripchart data. The dataset process 408 may retrieve the chunks, and reconstruct the data for the desired interval using the chunked data. The dataset process 408 may also be used to generate reports and graphs using the retrieved data.

[0080] The web server 406 may be any suitable combination of hardware and software for hosting a web page. The web server 406 may host a web front-end, such as, for example, a web page accessible through the Internet, which may act as a user interface for the demand management monitoring system. The web server 406 may be accessible over the network 106 to any suitable computing device 108, such as, for example, a personal computer or smartphone. The web server 406 may be able to retrieve data as necessary from the database 401, for example, using the dataset process 408, and may be able to communicate with the remote measurement devices 101, allowing the remote measurement devices 101 to be controlled through the computing device 108.

[0081] Fig. 5 depicts an exemplary web front-end. The web front-end may be a web page 502, displayed in a web browser window 501. The web browser window 501 may be part of any suitable web browsing software. The web page 502 may include a map 503, with markers, such as, for example, the marker 505, locating the remote measurement devices 101. Information about the remote measurement devices 101, such as, for example, current alarm status, serial number, name, current readings, and

current environmental measurements, may be displayed using graphical icons and indicators on the web page 502, for example, in information sidebar 504. Information may also be displayed in any other suitable manner, for example, in a pop-up window or on a separate screen after selecting the marker 505 for one of the remote measurement devices 101 on the map 503. The information displayed and the manner in which the information is displayed may be settable by users, with the specific parameters pulled from the database 401. For example, clicking on the marker 505 may pop up a display window showing real time readings. The user may click to start "burst mode", which may causes the web server 406 to send a request to the remote measurement device 101 to start sending real-time updates. In this mode, the web page 502 may display continuous real-time readings, while burst mode lasts.

[0082] The locations of the remote measurement devices 101 may be entered manually, for example, by dragging the markers 505 on the map 503, acquired from an on-board GPS, or computed from cell tower location information gathered from the remote measurement devices 101.

[0083] The map 503 may also be integrated with other geographic information or overlays. This may include weather or environmental overlays, such as, for example, temperature, humidity, and so on, acquired from the remote measurement devices 101 or from other weather sources, GIS asset data from electric utilities, such as, for example, pole locations, substation locations, and so on, or any other suitable overlays. These overlays may be configured by the user.

[0084] The web page 502 may be used to request the generation of reports, such as, for example, basic HTML reports. Using the web page 502, the user may request a report, which may cause the web server 406 to invoke a process on the server system 107, such as, for example, the dataset process 408, which may query the database 401 for the values needed for the specific report, render it in HTML, and display the report to the user on the web page 502. Optionally, the report may be rendered as a PDF, Excel spreadsheet, or any other suitable format. The look and feel of the report may be customized, for example, with a company logo, header, footer, and so on, by the user. Users may also create reports by writing suitable code, with knowledge of the database schema used by the database 401. Reports may also be created with a graphical wizard or a drag and drop scheme.

[0085] Graphs of any time series data in the database 401 may be displayed on the web page 502. A process on the server system 107, such as, for example, the dataset process 408, may be invoked by, for example, an AJAX call, and may access the stripchart data, including dechunking and appropriate decimation, from the database 401 and return the data as a JSON object to the web browser 501. Javascript code in the web browser 501 may then render the graph on a canvas object for

display on the web page 502. Flash, JAVA, or PC client code implementations may also be used.

[0086] Graphs may be customized, including customized trace colors and properties, annotations, markers, and so on. Stripchart information from one of the remote measurement devices 101 can be added or removed from the graph dynamically, for example, by dragging the marker 505 for the remote measurement device 101 from the map to the graph, or by dragging a trace for the remote measurement device 101 back off the graph. A custom view or annotated graph may be saved in the database 401 for later recall, or saved as a URL which may be bookmarked, or sent to other users.

[0087] The external interface 407 may be any suitable combination of hardware and software for interfacing with the external utility systems 109. For example, the external interface 407 may include a DNP3 interface to an electric utility SCADA system. The external interface 407 may act as a DNP3 gateway, and may respond to DNP3 polls and requests by returned the appropriate data from the database 401, duplicating the responses the remote measurement devices 101 would have sent if the remote measurement devices 101 implemented the DNP3 protocol. If an alarm or event is received from the remote measurement devices 101 by the server system 107, a corresponding unsolicited message may be sent through the external interface 107 to the external utility system 109, for example, using DNP3 to send a message to a SCADA system. The external interface 107 may emulate the performance of a system where the remote measurement devices 101 had direct links to the external utility system 109, such as, for example, DNP3 links directly to a SCADA system.

[0088] Alternatively, the remote measurement device 101 may interface directly with the external utility system 109, for example, using DNP3 or any other suitable protocol, while simultaneously interfacing with the server system 107. The remote measurement device 101 may send compressed block data to the server system 107, and also send telemetry data to the external utility system 109, for example, through the SCADA system, as requested by the SCADA master controller. The remote measurement device 101 may be able to send alerts and alarm conditions through either interface. The remote measurement device 101 may also only interface with the external utility system 109, and there may be no server system 107.

[0089] Fig. 6 depicts an exemplary procedure for operating a remote measurement device. In block 601, a line voltage may be received from a powerline. For example, the powerline 103 may be connected to the voltage input 102 of the remote measurement device 101.

[0090] In block 602, the voltage of the line voltage may be reduced. For example, the front end device 101 may have a voltage reducer 301, such as a transformer or a pulse-withstanding divider resistor, connected to the voltage input 102. The line voltage may pass through the voltage reducer 301 and end up with a reduced voltage.

[0091] In block 603, the line voltage may be subject to signal conditioning. After being reduced in voltage, the line voltage may be conditioned in any suitable manner by the signal conditioning circuit 302. For example, the line voltage may be run through a low-pass filter.

[0092] In block 604, the line voltage may be converted into digital samples. For example, the remote measurement device 101 may have the A/D converter 303 connected to the signal conditioning circuit 302. After the voltage of the line voltage has been reduced and conditioned, the line voltage may be digitized by the A/D converter 303 and output as a digital signal with digital samples.

[0093] In block 605, the RMS voltage of the line voltage may be calculated based on the digital samples of the line voltage. For example, after the A/D converter 303 converts the line voltage to digital sample, the digital samples may be fed into the microprocessor 304. The microprocessor 304 may use any suitable algorithm for calculating RMS voltage based on the digital samples. The microprocessor 304 may also receive other data, for example, from the external sensors 305, which may be used in the calculation of RMS voltage, or may be packaged along with the RMS voltage data for transmission to the server system 107. Alert or event messages may also be generated by the microprocessor 304, as appropriate, and sent along with the RMS voltage and other data.

[0094] In block 606, the RMS voltage and other data may be transmitted to a server system. For example, the microprocessor 304 may send the RMS voltage and other data to the wireless communications device 104. The wireless communications device 104 may communicate with the network 106 with wireless signal 105. The RMS voltage and other data may be routed through the network 106 to the server system 107, where the data may be received by, for example, the listening process 402. The RMS voltage and other data may be compressed, and may be sent using a low data rate telemetry plan. For example, the RMS voltage and other data may be compressed a compression rate of up to 30:1 using differential and arithmetic compression techniques. The compression algorithm and chunk size of the data may be adjustable, in order to allow for fine-tuning of the system to keep the data transfer as small as possible.

[0095] Fig. 7 depicts an exemplary procedure for receiving data from a remote measurement device at a server system. In block 701, data from a remote measurement device may be received. For example, data, including RMS voltage and other data, sent from the remote measurement device 101 may be routed through the network 106 to the server system 107. The listening process 402 may receive the data.

[0096] In block 702, the data may be checked for alarm and event messages. For example, the listening process 402 may send the data to the alarm process 404, and the alarm process 404 may determine if the data includes any alarm or event messages.

[0097] In block 703, if an alert or event message is

detected in the data, flow proceeds to block 704, otherwise flow proceeds to block 705.

[0098] In block 704, an alert may be sent out. For example, if the alarm process 404 determines that the data includes an alert or event message, the alarm process 404 may trigger the email and SMS alert process 405, which may transmit an alert. The alert may be transmitted by email, SMS, or using any other suitable manner of communication. The email and SMS alert process 405 may check the database 401 to determine what kind of message to transmit based on the alert or event message that was found in the data.

[0099] In block 705, the data may be preprocessed. For example, the listening process 402 may send the data to the dataset preprocessor 403, where the data may be decimated and chunked, as described above. Any other preprocessing may also be preformed, such as, for example, correlating the RMS voltage data with the other data, including, for example, data from the external sensors 305.

[0100] In block 706, the data may be inserted a database. For example, after the data has been preprocessed by the dataset preprocessor 403, the processed data may be inserted in the database 401 for long term storage and retrieval.

[0101] Fig. 8 depicts an exemplary procedure for operating a web server on the server system. In block 801, a web server on a server system may receive a request from a computing device. For example, a user using the computing device 108 may use the web browser 501 to navigate to the web page 502, which may display the map 503 and data on the remote measurement devices 101. The request from the computing device 108 for the web page 502 and the data displayed on the web page 502 may be transmitted through the network 106 to the server system 107, where the web server 406 may receive the request.

[0102] In block 802, data may be retrieved from a database in response to the request for data. For example, the web server 406 may invoke the dataset process 408, which may retrieve the requested data from the database 401.

[0103] In block 803, the data may be processed. For example, the dataset process 408 may process the data, for example, by decimating data that has not already been decimated, and converting the data into a report or graph suitable for display on the web page 502. The web server 407 may also process the data, for example, correlating the data with the marker 505 for the appropriate remote measurement device 101 on the map 503.

[0104] In block 804, the data may be displayed on the web page. For example, the data may be displayed on the web page 502 in the web browser 503, so that the user may view and interact with the data on the computing device 108. Displaying the data may include displaying the map 502, displaying the information sidebar 504, displaying the data in pop-up windows, or in graph or report form.

[0105] Fig. 9 depicts an exemplary procedure for operating an external interface on the server system. In block 901, an external interface on a server system may receive a request from an external utility system. For example, the external utility system 109 may request data from the remote measurement devices 101. The request may be routed through the network 106 to the server system 107, where it may be received by the external interface 407.

[0106] In block 902, the requested data may be retrieved. For example, the external interface 407 may retrieve the data requested by the external utility system 109 from the database 401. The external interface 407 may not process the data, so that the data will appear to the external utility system 109 as if it came directly from the remote measurement devices 101, instead of from the server system 107, rendering the server system 107 transparent to the external utility system 109.

[0107] In block 903, the data may be sent to the external interface. For example, the external interface 407 may transmit the data retrieved from the database 401 to the external utility system 109. The data may appear to the external utility system 109 to have been transmitted directly from the remote measurement devices 101.

[0108] As used herein, a "computer" or "computer system" may be, for example and without limitation, either alone or in combination, a personal computer (PC), server-based computer, main frame, server, microcomputer, minicomputer, laptop, personal data assistant (PDA), cellular phone, pager, processor, including wireless and/or wire line varieties thereof, and/or any other computerized device capable of configuration for receiving, storing and/or processing data for standalone application and/or over a networked medium or media. Examples of communication media that can be employed include, without limitation, wireless data networks, wire line networks, and/or a variety of networked media.

[0109] Computers and computer systems described herein may include operatively associated computer-readable media such as memory for storing software applications used in obtaining, processing, storing and/or communicating data. It can be appreciated that such memory can be internal, external, remote or local with respect to its operatively associated computer or computer system. Memory may also include any means for storing software or other instructions including, for example and without limitation, a hard disk, an optical disk, floppy disk, DVD, compact disc, memory stick, ROM (read only memory), RAM (random access memory), PROM (programmable ROM), EEPROM (extended erasable PROM), and/or other like computer-readable media.

[0110] In general, computer-readable media may include any medium capable of being a carrier for an electronic signal representative of data stored, communicated or processed in accordance with embodiments of the present invention. Where applicable, method steps described herein may be embodied or executed as instruc-

tions stored on a computer-readable medium or media.

[0111] It is to be understood that the figures and descriptions of the present invention have been simplified to illustrate elements that are relevant for a clear understanding of the present invention, while eliminating, for purposes of clarity, other elements. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable. However, because such elements are well known in the art, and because they do not facilitate a better understanding of the present invention, a discussion of such elements is not provided herein. It should be appreciated that the figures are presented for illustrative purposes and not as construction drawings. Omitted details and modifications or alternative embodiments are within the purview of persons of ordinary skill in the art.

[0112] It can be appreciated that, in certain aspects of the present invention, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to provide an element or structure or to perform a given function or functions. Except where such substitution would not be operative to practice certain embodiments of the present invention, such substitution is considered within the scope of the present invention.

[0113] The examples presented herein are intended to illustrate potential and specific implementations of the present invention. It can be appreciated that the examples are intended primarily for purposes of illustration of the invention for those skilled in the art. The diagrams depicted herein are provided by way of example. There may be variations to these diagrams or the operations described herein without departing from the spirit of the invention. For instance, in certain cases, method steps or operations may be performed or executed in differing order, or operations may be added, deleted or modified.

[0114] Furthermore, whereas particular embodiments of the invention have been described herein for the purpose of illustrating the invention and not for the purpose of limiting the same, it will be appreciated by those of ordinary skill in the art that numerous variations of the details, materials and arrangement of elements, steps, structures, and/or parts may be made within the principle and scope of the invention without departing from the invention as described in the following claims.

Claims

1. An apparatus for a demand management monitoring system comprising:
 - i) at least one remote measurement device (101), the remote measurement device (101) comprising a microprocessor (304) configured to calculate RMS voltage data from digital samples and a wireless communications device (104) and/or

- ii) a server system (107) comprising a database (401) configured to store the RMS voltage data from at least one remote measurement device (101) and a listening process (402) configured to receive data comprising the RMS voltage data and other data from the remote measurement devices (101) through a network (106). 5
2. The apparatus of claim 1, wherein the remote measurement device (101) further comprises: 10
- a voltage input (102) configured to receive a line voltage from a powerline (103);
a voltage reducer (301) configured to reduce a voltage of the line voltage; and 15
an analog to digital [A/D] converter (303) configured to convert the line voltage to the digital samples.
3. The apparatus of claim 2, wherein the voltage reducer (301) comprises a transformer and/or a pulse-withstanding divider resistor network. 20
4. The apparatus of any of the claims 2 or 3, wherein the remote measurement device further comprises a signal conditioning circuit configured to receive the line voltage from the voltage reducer and condition the line voltage. 25
5. The apparatus of any of the preceding claims further **characterized by** at least one of the following features a) to d): 30
- a) that the remote measurement device (101) further comprises a low power wireless communications (306) device configured to receive data from external sensors (305); and/or 35
b) that the remote measurement device (101) is contained in a standard meter base adapter and/or 40
c) that the wireless communication device (104) is adapted to communicate directly with an external utility system and/or
d) that the external utility system is a SCADA system using at least one of a DNP3 interface, IEC 61850 interface, and another standard SCADA protocol interface. 45
6. The apparatus of any of the preceding claims, wherein the server system further comprises at least one of the following elements 6.1 to 6.6: 50
- 6.1 a dataset preprocessor (403) configured to decimate and chunk the RMS voltage data;
6.2 an alarm process (404) configured to search the other data for alert and event messages;
6.3 an email and SMS alert process (405) configured to distribute email and SMS alerts based 55
- on the alert and event messages in the other data;
6.4 a web server (406) configured to display the RMS voltage data and the other data on a web page (502);
6.5 a dataset process (408) configured to access the RMS voltage data and other data in the database and prepare the RMS voltage data and other data for display on a web page (502); and/or
6.6 an external interface (407) configured to access the RMS voltage data and other data in the database and transmit the RMS voltage data and other data to a requesting external utility system.
7. The apparatus of any of the preceding claims, wherein the other data includes environmental data.
8. A method for a remote measurement device (101) in a demand management monitoring system comprising:
- receiving (601) a line voltage;
reducing (602) a voltage of the line voltage;
calculating (605) an RMS voltage of the line voltage; and
transmitting (606) the RMS voltage.
9. The method of claim 8, further comprising at least one of the following steps 9.1 to 9.3:
- 9.1 conditioning (603) the line voltage;
9.2 receiving environmental data from at least one external sensor (305); transmitting the environmental data;
9.3 detecting (703) an event or alarm condition; and/or transmitting (704) an alarm or event message.
10. The method of any of the claims 8 or 9 wherein the RMS voltage is transmitted to a server system (107) and/or to an external utility system.
11. A method for a server system (107) in a demand management monitoring system comprising:
- receiving (701) data comprising RMS voltage data;
checking (702) the data for alarm or event messages; and
inserting (706) the data into a database.
12. The method of claim 11 further comprising at least one of the following steps 12.1 to 12.6:
- 12.1 I transmitting (704) at least one of an email and an SMS alert when an alarm or event mes-

sage is found in the data;

12.2 preprocessing (705) that data before inserting (706) the data into the database, wherein the preprocessing (705) comprises at least one of decimating the data and chunking the data; 5

12.3 receiving (801) a request for a portion of the data, retrieving (802) the portion of the data from the database, processing (803) the portion of the data for display, and displaying (804) the portion of the data on a web page; 10

12.4 receiving (901) a request for a portion of the data from an external utility system, retrieving (902) the portion of the data from the database and transmitting (903) the portion of the data to the external utility system; 15

12.5 displaying (804) a map (503) on a web page (502), wherein the map (503) comprises at least one marker indicating the location of at least one remote measurement device (101), retrieving a portion of the data related to the at least one remote measurement device (101) from the database, and displaying the portion of the data on the web page (502); and/or 20

12.6 receiving an instruction for at least one remote measurement device through a web page (502), and transmitting the instruction to the at least one remote measurement device (101). 25

13. The method of claim 12, wherein processing (803) the data in step 12.3 comprises at least one of converting the data into a graph and converting the data into a chart. 30

14. The method of any of the claims 11 to 13, wherein the data further comprises environmental data. 35

15. A combination of a method according to any of the claims 8 to 10 with a method according to any of the claims 11 to 14. 40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 61369045 A [0001]