



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**22.02.2012 Bulletin 2012/08**

(51) Int Cl.:  
**G01S 5/10 (2006.01) G01S 5/14 (2006.01)**

(21) Application number: **11174476.9**

(22) Date of filing: **19.07.2011**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**

(72) Inventor: **Rieger III, Charles**  
**Potomac, MD 20854 (US)**


(74) Representative: **Pelly, Jason Charles**  
**Boult Wade Tennant**  
**Verulam Gardens**  
**70 Gray's Inn Road**  
**London WC1X 8BT (GB)**

(30) Priority: **17.08.2010 US 857808**

(71) Applicant: **Navteq North America, LLC**  
**Chicago, Illinois 60606 (US)**

(54) **Location-determining system for radio clients within local-area spaces**

(57) Systems, devices, features, and/or methods for determining a location of a mobile device are disclosed. A method may include (a) receiving, into a mobile device, a common RF signal on a common carrier frequency, wherein the common RF signal includes a respective RF signal output by each of three or more transmitters on a common time basis in a round-robin manner, and wherein each of the three or more transmitters is positioned at a known location, (b) capturing data representing the common RF signal, (c) based on the captured data, discriminating between each respective RF signal that forms the received common RF signal, (d) determining a relative phase shift of each respective RF signal, and (e) determining the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.



**FIG. 2**

## Description

### BACKGROUND OF THE INVENTION

**[0001]** One emerging area of wireless communications is the provision of services based on a location of a mobile device. These location-based services may take various forms. For example, a location-based service may provide a user of the mobile device with a weather or traffic report relevant to the user's location. As another example, a location-based service may provide the user with a list of services or establishments (e.g., restaurants, parks, theatres, etc.) in the user's vicinity. As still another example, a location-based service may provide the user with an advertisement or coupon relevant to a product in the user's vicinity.

**[0002]** To facilitate the provision of location-based services to a user of a mobile device, a location-based service provider accurately determines and/or tracks the location of the mobile device. Various technologies currently exist to determine and/or track the location of a mobile device, the most prevalent of which are Global Positioning System (GPS) technologies and cellular network technologies. However, these technologies have drawbacks regarding accurate determination and/or tracking of a mobile device location, such as in an indoor environment. Accordingly, an improved location-determination system that is capable of accurately determining and/or tracking the location of a mobile device, such as, for example, in an indoor environment, is desirable.

### SUMMARY OF THE INVENTION

**[0003]** According to one aspect, a method of determining a location of a mobile device is provided. For example, the method may include (a) receiving, into a mobile device, a common RF signal on a common carrier frequency, wherein the common RF signal includes a respective RF signal output by each of three or more transmitters on a common time basis in a round-robin manner, and wherein each of the three or more transmitters is positioned at a known location, (b) capturing data representing the common RF signal, (c) based on the captured data, discriminating between each respective RF signal that forms the received common RF signal, (d) determining a relative phase shift of each respective RF signal, and (e) determining the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.

**[0004]** According to an aspect of the invention, there is provided a method of determining a location of a mobile device, the method comprising: receiving, into a mobile device, a common RF signal on a common carrier frequency, wherein the common RF signal includes a respective RF signal output by each of three or more transmitters on a common time basis in a round-robin manner, and wherein each of the three or more transmitters is positioned at a known location; capturing data represent-

ing the common RF signal; based on the captured data, discriminating between each respective RF signal that forms the received common RF signal; determining a relative phase shift of each respective RF signal; and determining the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.

**[0005]** In some embodiments, the common RF signal comprises repeating periods of timeslots, wherein each period of timeslots includes at least one timeslot occupied by a respective signal segment output by each of the three or more transmitters in a round-robin manner. Each period of timeslots may further include at least one unoccupied timeslot that distinguishes the period of timeslots from an adjacent period of timeslots. Each respective signal segment may comprise an integral number of cycles of a periodic signal. Each respective signal segment may comprise a header segment and an identifier segment that uniquely identifies one of the three or more transmitters.

**[0006]** In some embodiments, capturing the data representing the common RF signal comprises capturing a timestamp of each zero-crossing of the common RF signal.

**[0007]** In some embodiments, capturing the data representing the common RF signal comprises capturing a timestamp of each edge of the common RF signal.

**[0008]** In some embodiments, discriminating between each respective RF signal that forms the received common RF signal comprises identifying which of the respective RF signals was output by which of the three or more transmitters.

**[0009]** In some embodiments, determining the location comprises the mobile device determining the location, and the method further comprises: the mobile device reporting the determined location to a server.

**[0010]** In some embodiments, the method further comprises the mobile device reporting the captured data to a server, determining the relative phase shift of each respective RF signal comprises the server determining the relative phase shift of each respective RF signal, and determining the location comprises the server determining the location.

**[0011]** In some embodiments, the location of the mobile device comprises one or both of a local coordinate and a geographic coordinate.

**[0012]** According to an aspect of the invention, there is provided a method of determining a location of a mobile device, the method comprising: three or more transmitters each outputting a respective radio frequency (RF) signal on a common time basis and a common carrier frequency in a round-robin manner, wherein the three or more transmitters are each positioned at a known location; receiving, via a mobile device, data representing a common RF signal on the common carrier frequency, wherein the common RF signal includes the respective RF signal output by each of the three or more transmitters; based on the received data, discriminating between

each respective RF signal that forms the received common RF signal; determining a relative phase shift of each respective RF signal; and determining the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.

**[0013]** In some embodiments, the method further comprises using a common signal source (CSS) to drive the three or more transmitters to each output a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner.

**[0014]** In some embodiments, the three or more transmitters each outputting a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner comprises: the three or more transmitters each periodically outputting a segment of a common drive signal from the CSS on a common time basis and a common carrier frequency in a round-robin manner. Each segment of the common drive signal may comprise an integral number of cycles of a periodic signal. Each segment of the common drive signal may comprise a header segment and an identifier segment that uniquely identifies one of the three or more transmitters.

**[0015]** In some embodiments, capturing the data representing the common RF signal comprises capturing a timestamp of each zero-crossing of the common RF signal.

**[0016]** In some embodiments, capturing the data representing the common RF signal comprises capturing a timestamp of each edge of the common RF signal.

**[0017]** In some embodiments, discriminating between each respective RF signal that forms the received common RF signal comprises identifying which of the respective RF signals was output by which of the three or more transmitters.

**[0018]** According to an aspect of the invention, there is provided a system configured to determine a location of a mobile device, the system comprising: three or more transmitters each configured to output a respective radio frequency (RF) signal on a common time basis and a common carrier frequency in a round-robin manner, wherein the three or more transmitters are each positioned at a known location; and a mobile device configured to (a) receive a common RF signal on the common carrier frequency, wherein the common RF signal includes the respective RF signal output by each of the three or more transmitters, (b) capture data representing the common RF signal, (c) based on the captured data, discriminate between each respective RF signal that forms the received common RF signal, (d) determine a relative phase shift of each respective RF signal, and (e) determine the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.

**[0019]** In some embodiments, the system further comprises: a common signal source (CSS) coupled to each of the three or more transmitters via a respective link and configured to drive the three or more transmitters to out-

put a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner; and a server configured to store a determined location of the mobile device.

**[0020]** According to an aspect of the invention, there is provided a system configured to determine a location of a mobile device, the system comprising: a common signal source (CSS); and three or more transmitters coupled to the CSS via a respective link, wherein each of the three or more transmitters are positioned at a known location, wherein the CSS is configured to drive the three or more transmitters to output a respective radio frequency (RF) signal on a common time basis and a common carrier frequency in a round-robin manner, and wherein the three or more transmitters are configured to output a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner, and wherein data representing a common RF signal on the common carrier frequency is received via a mobile device, wherein the common RF signal includes the respective RF signal output by each of the three or more transmitters, wherein, based on the received data, each respective RF signal that forms the received common RF signal is discriminated, wherein a relative phase shift of each respective RF signal is determined, and wherein the location of the mobile device is determined based on the determined relative phase shifts and the known locations of the three or more transmitters.

**[0021]** The present invention is defined by the following claims, and nothing in this section should be taken as a limitation on those claims. Further aspects and advantages of the invention are discussed below in conjunction with the preferred embodiments.

## BRIEF DESCRIPTION OF THE DRAWINGS

### **[0022]**

Figure 1 is a simplified block diagram of exemplary communication system configured to determine a location of a mobile device within an indoor environment;

Figure 2 is a simplified flow chart of an exemplary method 30 for determining a location of a mobile device within an indoor environment;

Figure 3 (a) illustrates a portion of a common drive signal generated by the central signal source (CSS) in the system of Figure 1, according to an example of a first embodiment;

Figure 3(b) illustrates a portion of a respective timeslot assignment signal for each of the transmitters in the system of Figure 1, according to an example of the first embodiment;

Figure 3(c) illustrates a portion of respective radio frequency (RF) signal output by each of the transmitters in the system of Figure 1, according to an example of the first embodiment;

Figure 3(d) illustrates a portion of a common RF sig-

nal received by the mobile device in the system of Figure 1, according to an example of the first embodiment;

Figure 4(a) illustrates a portion of a common drive signal generated by the CSS in the system of Figure 1, according to an example of a second embodiment; Figure 4(b) illustrates a portion of a respective timeslot assignment signal for each of the transmitters in the system of Figure 1, according to an example of the second embodiment;

Figure 4(c) illustrates a portion of respective RF signal output by each of the transmitters in the system of Figure 1, according to an example of the second embodiment;

Figure 4(d) illustrates a portion of a common RF signal received by the mobile device in the system of Figure 1, according to an example of the second embodiment; and

Figure 5 illustrates a portion of the respective RF signals generated by the CSS in the system of Figure 1, according to an example of a third embodiment.

## DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

### I. Exemplary Location-Determination System

**[0023]** Figure 1 is a simplified block diagram of exemplary communication system 10 configured to determine a location of a mobile device within an indoor environment 22. As shown, communication system 10 may include a common signal source (CSS) 12 coupled to transmitters 14<sub>A</sub>-14<sub>D</sub> via links 16<sub>A</sub>-16<sub>D</sub>, a mobile device 18, and a central server 20. Other configurations may be provided as well.

**[0024]** It should be understood that the arrangements described herein are set forth for purposes of example only. As such, those skilled in the art will appreciate that other arrangements and other elements (e.g., components, interfaces, functions, orders of functions, etc.) can be used instead, some elements may be added, and/or some elements may be omitted altogether. Further, those skilled in the art will appreciate that many of the elements described herein are functional elements that may be implemented as discrete or distributed components or in conjunction with other components, and in any suitable combination and location. Still further, various functions described herein as being performed by one or more entities may be carried out by hardware, firmware and/or software. For instance, various functions may be carried out by a processor executing a set of program instructions written in any suitable programming language (e.g., C, C++, Java, etc.) and stored in memory.

**[0025]** CSS 12 may be any device configured to drive each of transmitters 14<sub>A</sub>-14<sub>D</sub> to output a respective radio frequency (RF) signal on a common time basis (i.e., CSS 12 may drive each of transmitters 14<sub>A</sub>-14<sub>D</sub> such that act as slave clocks that are coordinated with a master clock,

and thus output respective RF signals that are synchronized according to the master clock). CSS 12 may include various components that enable it to perform this function. For instance, CSS 12 may include a high-precision master clock (e.g., a 300 MHz clock), one or more signal generators (e.g., a square wave generator, a sinusoidal wave generator, etc.), and one or more line drivers (e.g., differential line drivers). Additionally, in some embodiments, CSS 12 may include delay circuitry. Other configurations of CSS 12 are possible as well.

**[0026]** Each of transmitters 14<sub>A</sub>-14<sub>D</sub> maybe any device configured to be driven by CSS 12 to output a respective RF signal on a common time basis. Each of transmitters 14<sub>A</sub>-14<sub>D</sub> may include various components that enable the transmitter to perform this function. For instance, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may include a line receiver (e.g., a differential line receiver), an amplifier, and an antenna. Additionally, in some embodiments, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may include a modulator. Other configurations of transmitters 14<sub>A</sub>-14<sub>D</sub> are possible as well.

**[0027]** In the embodiments described herein, transmitters 14<sub>A</sub>-14<sub>D</sub> are positioned at fixed locations within indoor environment 22. For example, transmitters 14<sub>A</sub>-14<sub>D</sub> may be affixed to or embedded in walls, ceilings, and/or floors within the indoor environment 22. Other examples are possible as well. Each of transmitters 14<sub>A</sub>-14<sub>D</sub> may thus have a known location within indoor environment 22 (e.g., a local coordinate). Further, in some embodiments, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may have a known location within a global environment (e.g., a geographic coordinate) as well.

**[0028]** Each of links 16<sub>A</sub>-16<sub>D</sub> may be any wired and/or wireless link configured to carry one or more signals from CSS 12 to one of transmitters 14<sub>A</sub>-14<sub>D</sub>. For instance, each of links 16<sub>A</sub>-16<sub>D</sub> may include a first cable (e.g., a twisted-pair copper cable) configured to carry a first signal from CSS 12 to one of transmitters 14<sub>A</sub>-14<sub>D</sub>. Additionally, in some embodiments, each of links 16<sub>A</sub>-16<sub>D</sub> may include a second cable (e.g., a twisted-pair copper cable) configured to carry a second signal from CSS 12 to one of transmitters 14<sub>A</sub>-14<sub>D</sub>. Each of links 16<sub>A</sub>-16<sub>D</sub> may take other forms as well.

**[0029]** In the embodiments described herein, each of links 16<sub>A</sub>-16<sub>D</sub> will have defined transmission properties, such as length and propagation speed. For instance, links 16<sub>A</sub>-16<sub>D</sub> may all have the same defined transmission properties. Alternatively, links 16<sub>A</sub>-16<sub>D</sub> may have different defined transmission properties. In either case, CSS 12 may use the defined transmission properties of links 16<sub>A</sub>-16<sub>D</sub> to ensure that all transmitters 14<sub>A</sub>-14<sub>D</sub> are being driven on a common time basis.

**[0030]** Mobile device 18 may be any device configured to receive and process RF signals from transmitters 14<sub>A</sub>-14<sub>D</sub> and send wireless communications to central server 20. The mobile device 18 is a personal navigation device ("PND"), a portable navigation device, a cellular telephone, a mobile phone, a personal digital assistant

("PDA"), a watch, a camera, a computer, and/or any other mobile device. Mobile device 18 may include various components that enable it to perform the recited functions. For instance, mobile device 18 may include a microprocessor, an RF receiver (e.g., an amplitude modulation (AM) receiver, a phase-shift keying (PSK) receiver/demodulator, etc.), and a wireless transceiver (e.g., an 802.11 chipset). Further, in some embodiments, mobile device 18 may include timestamping circuitry, such as an edge detector configured to detect a rising/falling edge or a zero-crossing (e.g., high-speed comparator), a high-frequency timestamping clock configured to define a master time base (e.g., a 300 MHz cyclical 32-bit counter), and a timestamp latch configured to generate an interrupt signal when each new edge is captured). Further yet, in other embodiments, mobile device 18 may include an analog-to-digital (A/D) converter configured to capture signal strength samples and generate interrupts at a predefined rate (e.g., 50 MHz). As examples, mobile device 18 may take the form of a cell phone, a personal navigation device (PND), or a tag. Other configurations of mobile device 18 are possible as well.

**[0031]** Central server 20 may be any device configured to receive and store data regarding a location of mobile device 18 (as well as other mobile devices) within indoor environment 22. Central server 20 may include various components that enable it to perform these functions. For instance, central server 20 may include a processor, data storage, and a wireless transceiver (e.g., an 802.11 card). Other configurations of central server 20 are possible as well.

## II. Exemplary Location-Determination Method

**[0032]** Figure 2 is a simplified flow chart of an exemplary method 30 for determining a location of a mobile device within an indoor environment. Fewer or more steps may be provided. For purposes of illustration, exemplary method 30 will be described with reference to communication system 10 determining a location of mobile device 18 within indoor environment 22, but it should be understood that exemplary method 30 may be applicable to other systems as well. In one example, one or more steps of exemplary method 30 may be embodied as program instructions stored on a non-transitory computer-readable medium and executable by a processor.

**[0033]** As shown in Figure 2, exemplary method 30 begins at step 32 with CSS 12 driving each of transmitters 14<sub>A</sub>-14<sub>D</sub> to output a respective RF signal on a common time basis. In turn, at step 34, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a respective RF signal on a common time basis.

**[0034]** At step 36, mobile device 18 may be receiving a respective RF signal from each of transmitters 14<sub>A</sub>-14<sub>D</sub>. In turn, at step 38, mobile device 18 may capture data representing the respective RF signals. At step 40, mobile device 18 may also optionally report the captured data representing the respective RF signals to central

server 20.

**[0035]** At step 42, based on the captured data representing the respective RF signals, mobile device 18 and/or central server 20 may discriminate between the respective RF signals and thereby identify which respective RF signal was output by which of transmitters 14<sub>A</sub>-14<sub>D</sub>. In turn, at step 44, mobile device 18 and/or central server 20 may calculate a phase shift value of each respective RF signal. At step 46, mobile device 18 and/or central server 20 may then use the calculated phase shift values and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub> to determine a location of mobile device 18 (e.g., a location coordinate and perhaps a geographic coordinate).

**[0036]** At step 48, if mobile device 18 determines its location, mobile device 18 may also report the determined location to central server 20. At step 50, central server 20 may then store the determined location of mobile device 18 for future reference.

**[0037]** Advantageously, the exemplary location-determination method may enable communication system 10 to accurately determine and/or track the location of mobile device 18. In turn, a location-based service provider may use the determined location of mobile device 18 to provide a user of mobile device 18 with location-based services. For example, if mobile device 18 is located in a store (e.g., a retail store or a grocery store) in which locations are being monitored by communication system 10, a location-based service provider may be able to provide a user of mobile device 18 with an advertisement or coupon relevant to a product in the user's vicinity. Many other examples are possible as well.

## III. Embodiments of the Exemplary Location-Determination Method

**[0038]** Embodiments of exemplary method 30 will now be described. As above, for purposes of illustration, the embodiments of exemplary method 30 will be described with reference to communication system 10 determining a location of mobile device 18 within indoor environment 22, but it should be understood that exemplary method 30 may be applicable to other systems as well.

### a. First Embodiment

**[0039]** A first embodiment of exemplary method 30 begins at step 32 with CSS 12 driving each of transmitters 14<sub>A</sub>-14<sub>D</sub> to output a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner. For instance, CSS 12 may be generating a common drive signal that has repeating periods of timeslots, each having at least one timeslot assigned to each of transmitters 14<sub>A</sub>-14<sub>D</sub> in a round-robin manner and at least one unassigned timeslot. Each timeslot may be occupied by a respective signal segment of the common drive signal. The arrangement of these timeslot periods may take various forms, and may be a known sys-

tem parameter. In one example, as shown in Figure 3(a), each period of timeslots of the common drive signal may be arranged to have a first timeslot assigned to transmitter 14<sub>A</sub>, a second timeslot assigned to transmitter 14<sub>B</sub>, a third timeslot assigned to transmitter 14<sub>C</sub>, a fourth timeslot assigned to transmitter 14<sub>D</sub>, and a fifth timeslot that is unassigned. Other examples are possible as well.

**[0040]** Each signal segment may take various forms. For example, each signal segment may take the form of an integral number of cycles (e.g., 64 cycles) of a periodic waveform having a common frequency, such as a sinusoidal wave having a frequency in the long-wave or medium-wave band range (e.g., 148.5 KHz to 283.5 KHz or 520 KHz to 1710 KHz) or a square wave having a frequency in the baseband range (e.g., 5 KHz to 20 KHz). In this respect, CSS 12 may generate the common drive signal as a continuous waveform. Other examples are possible as well.

**[0041]** To communicate the timeslot assignments to transmitters 14<sub>A</sub>-14<sub>D</sub>, CSS 12 may additionally be generating for each of transmitters 14<sub>A</sub>-14<sub>D</sub> a respective timeslot assignment signal that identifies which timeslots in the common drive signal are assigned to the transmitter. Each such timeslot assignment signal may take various forms. For example, as shown in Figure 3(b), each timeslot assignment signal may take the form of a bit sequence, with each "1" bit identifying the timeslot in the parallel common drive signal as being assigned to the transmitter and each "0" bit identifying the timeslot in the parallel common drive signal as being assigned to a different transmitter. Other examples are possible as well.

**[0042]** CSS 12 may then be outputting to each of transmitters 14<sub>A</sub>-14<sub>D</sub> the common drive signal and a respective timeslot assignment signal. In this respect, CSS 12 may be delaying the output of the common drive signal and a respective timeslot assignment signal to at least one of transmitters 14<sub>A</sub>-14<sub>D</sub>, to ensure that all of transmitters 14<sub>A</sub>-14<sub>D</sub> receive these signals on a common time basis. For instance, CSS 12 may be delaying the output of these signals to each of transmitters 14<sub>A</sub>-14<sub>D</sub> in an amount that is inversely proportional to the length of the transmitter's link (e.g., zero or minimum delay for the longest link and maximum delay for the shortest link). Other examples are possible as well. As a result of CSS 12 outputting to each of transmitters 14<sub>A</sub>-14<sub>D</sub> the common drive signal and a respective timeslot assignment signal, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may then be receiving the common drive signal and a respective timeslot assignment signal on a common time basis.

**[0043]** At step 34, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner (i.e., only one of transmitters 14<sub>A</sub>-14<sub>D</sub> is outputting an RF signal at any one time). For instance, as shown in Figure 3(c), each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a segment of the received common drive signal during each of its assigned timeslots as an unmodulated or modulated RF signal on the common carrier frequency.

In this respect, as shown, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may stop transmitting before the end of each assigned timeslot, to ensure that its output does not overlap with another transmitter's output. Alternatively, however, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may transmit during the entire duration of each assigned timeslot. In either case, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may enable its power during each of its assigned timeslots (as identified by the timeslot assignment signal) and disable its power during any other timeslot (as identified by the timeslot assignment signal). Other examples are possible as well.

**[0044]** At step 36, mobile device 18 may be receiving a common RF signal on the common carrier frequency that includes a respective RF signal from each of transmitters 14<sub>A</sub>-14<sub>D</sub>. For instance, mobile device 18 may be receiving a common RF signal on the common carrier frequency that includes repeating periods of timeslots, each having (a) at least one timeslot occupied by a respective signal segment received from each of transmitters 14<sub>A</sub>-14<sub>D</sub> in a round-robin manner and (b) at least one unoccupied timeslot. For example, as shown in Figure 3(d), each period of timeslots of the received common RF signal may have a first timeslot occupied by a signal segment received from transmitter 14<sub>A</sub>, a second timeslot occupied by a signal segment received from transmitter 14<sub>B</sub>, a third timeslot occupied by a signal segment received from transmitter 14<sub>C</sub>, a fourth timeslot occupied by a signal segment received from transmitter 14<sub>D</sub>, and a fifth timeslot that is unoccupied. Further, as shown, the respective signal segments from each of transmitters 14<sub>A</sub>-14<sub>D</sub> may have a phase shift relative to one another due to the differences in transmission times (and thus distances) between each of transmitters 14<sub>A</sub>-14<sub>D</sub> and mobile device 18. (While Figure 3(d) depicts the timeslots of the received common RF signal as being defined based on the signal segment received from transmitter 14<sub>A</sub>, it should be understood that the timeslots may alternatively be defined based on a signal segment received from one of transmitters 14<sub>B</sub>-14<sub>D</sub>.) Other examples are possible as well.

**[0045]** At step 38, mobile device 18 may capture data representing the received common RF signal. For instance, mobile receiver 18 may capture a timestamp of each zero-crossing of the received common RF signal (e.g., for a sinusoidal wave). Alternatively, mobile device 18 may capture a timestamp of each rising and/or falling edge of the received RF signals (e.g., for a square wave). Other examples are possible as well. At step 40, mobile device 18 may also optionally report the captured data representing the received common RF signal to central server 20.

**[0046]** At step 42, based on the captured data representing the received common RF signal, mobile device 18 and/or central server 20 may discriminate between each respective RF signal that forms the received common RF signal. For instance, based on the captured data representing the received common RF signal, mobile device 18 and/or central server 20 may first identify a times-

lot of the received common RF signal that is unoccupied (e.g., a time period with a minimal number of captured data points). In turn, mobile device 18 and/or central server 20 may identify a beginning of a new period of timeslots immediately following the unoccupied timeslot (e.g., a first captured data point after the time period with no timestamps). Based on the known arrangement of timeslot periods, mobile device 18 and/or central server 20 may then discriminate between each respective timeslot in the new period of timeslots and thereby discriminate between each respective signal segment in the new period of timeslots. Further, based on the known arrangement of timeslot periods, mobile device 18 and/or central server 20 may identify which respective signal segment was output by which of transmitters 14<sub>A</sub>-14<sub>D</sub>. Mobile device 18 and/or central server 20 may repeat this process to discriminate between each respective timeslot (and each respective signal segment) in each period of timeslots in the received common RF signal. Other examples are possible as well.

**[0047]** After discriminating between each respective timeslot and respective signal segment in the common drive signal, mobile device 18 and/or central server 20 may process the data representing the signal segment in each respective timeslot to align the time base of mobile device 18 with the common time base of transmitters 14<sub>A</sub>-14<sub>D</sub>. For example, mobile device 18 and/or central server 20 may (a) slot the captured data points into modulus buckets, (b) identify the captured data points falling into the most popular modulus, and (c) perform a least squares fit on the identified captured data points to generate an accurate time base. Other examples are possible as well.

**[0048]** At step 44, after discriminating between each respective RF signal that forms the received common RF signal, mobile device 18 and/or central server 20 may determine a relative phase shift value of each respective RF signal. For instance, in each period of timeslots, mobile device 18 and/or central server 20 may first identify one or more captured data points representing each respective signal segment. Further, mobile device 18 and/or central server 20 may define one signal segment in the period as a reference signal segment having a relative phase shift value of 0. For each given segment in the period other than the reference segment, mobile device 18 and/or central server 20 may then (a) calculate a first time difference between the given segment and the reference segment and (b) calculate a second time difference between the given segment's timeslot and the reference segment's timeslot (e.g., based on the known duration of timeslots). In turn, mobile device 18 and/or central server 20 may calculate the relative phase shift of the given segment with respect to the reference segment as the time difference between the first and second calculated time differences. As mentioned above, Figure 3(d) illustrates the relative phase shift of the respective signal segment received from each of transmitters 14<sub>B</sub>-14<sub>D</sub> with respect to the signal segment received from

transmitter 14<sub>A</sub>.

**[0049]** At step 46, after determining a relative phase shift value of each respective RF signal, mobile device 18 and/or central server 20 may use the relative phase shift values and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub> to determine a location of mobile device 18. For instance, based on the relative phase shift values, mobile device 18 and/or central server 20 may first calculate the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> using any technique now known or later developed. In turn, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub>, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 using any technique now known or later developed (e.g., multilateration). For example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within indoor environment 22, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the indoor environment (e.g., local coordinates). As another example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within a global environment, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the global environment (e.g., geographic coordinates). Other examples are possible as well.

**[0050]** At step 48, if mobile device 18 determines its location, mobile device 18 may also report the determined location to central server 20. At step 50, central server 20 may then store the determined location of mobile device 18 for future reference.

#### b. Second Embodiment

**[0051]** A second embodiment of exemplary method 30 begins at step 32 with CSS 12 driving each of transmitters 14<sub>A</sub>-14<sub>D</sub> to output a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner. For instance, CSS 12 may be generating a common drive signal that has repeating periods of timeslots, each having at least one timeslot assigned to each of transmitters 14<sub>A</sub>-14<sub>D</sub> in a round-robin manner. Each timeslot may be occupied by a respective signal segment of the common drive signal that includes a header segment and an identifier segment that uniquely identifies the assigned transmitter. The arrangement of the timeslot periods may also have various forms and may be a known system parameter. In one example, as shown in Figure 4(a), each period of timeslots of the common drive signal may be arranged to have a first timeslot assigned to transmitter 14<sub>A</sub>, a second timeslot assigned to transmitter 14<sub>B</sub>, a third timeslot assigned to transmitter 14<sub>C</sub>, and a fourth timeslot assigned to transmitter 14<sub>D</sub>. Other examples are possible as well.

**[0052]** Each header segment may take various forms. For example, each header segment in the sequence may take the form of an integral number of cycles of a square wave having a frequency in the baseband range (e.g., 5 KHz to 20 KHz). Other examples are possible as well. Each identifier segment in the sequence may also take various forms. For example, each identifier segment may take the form of a bit pattern in which each "1" bit is represented by plurality of cycles (e.g., 5) of a square wave having a frequency in an increased baseband range (e.g., 20 KHz to 100 KHz range) and each "0" bit is represented by a null signal. Other examples are possible as well.

**[0053]** As in the first embodiment, to communicate the timeslot assignments to transmitters 14<sub>A</sub>-14<sub>D</sub>, CSS 12 may additionally be generating for each of transmitters 14<sub>A</sub>-14<sub>D</sub> a respective timeslot assignment signal that identifies which timeslots in the common drive signal are assigned to the transmitter. Each such timeslot assignment signal may take various forms. For example, as shown in Figure 4(b), each timeslot assignment signal may take the form of a bit sequence, with each "1" bit identifying the timeslot in the parallel common drive signal as being assigned to the transmitter and each "0" bit identifying the timeslot in the parallel common drive signal as being assigned to a different transmitter. Other examples are possible as well.

**[0054]** CSS 12 may then be outputting to each of transmitters 14<sub>A</sub>-14<sub>D</sub> the common drive signal and a respective timeslot assignment signal. In this respect, as in the first embodiment, CSS 12 may be delaying the output of the common drive signal and a respective timeslot assignment signal to at least one of transmitters 14<sub>A</sub>-14<sub>D</sub>, to ensure that all of transmitters 14<sub>A</sub>-14<sub>D</sub> receive these signals on a common time basis. For instance, CSS 12 may be delaying the output of these signals to each of transmitters 14<sub>A</sub>-14<sub>D</sub> in an amount that is inversely proportional to the length of the transmitter's link (e.g., zero or minimum delay for the longest link and maximum delay for the shortest link). Other examples are possible as well. As a result of CSS 12 outputting to each of transmitters 14<sub>A</sub>-14<sub>D</sub> the common drive signal and a respective timeslot assignment signal, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may then be receiving the common drive signal and a respective timeslot assignment signal on a common time basis.

**[0055]** At step 34, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a respective RF signal on a common time basis and a common carrier frequency in a round-robin manner (i.e., only one of transmitters 14<sub>A</sub>-14<sub>D</sub> is outputting an RF signal at any one time). For instance, as shown in Figure 4(c), each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a header and identifier segment of the received common drive signal during each of its assigned timeslots as an unmodulated or modulated RF signal on the common carrier frequency. In this respect, as shown, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may transmit during the entire duration of each assigned timeslot. Alternatively,

however, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may stop transmitting before the end of each assigned timeslot, to ensure that the transmitter's output does not overlap with another transmitter's output. In either case, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may enable its power during each of its assigned timeslots (as identified by the timeslot assignment signal) and disable its power during any other timeslot (as identified by the timeslot assignment signal). Other examples are possible as well.

**[0056]** At step 36, mobile device 18 may be receiving a common RF signal on the common carrier frequency that includes a respective RF signal from each of transmitters 14<sub>A</sub>-14<sub>D</sub>. For instance, mobile device 18 may be receiving a common RF signal on the common carrier frequency that includes repeating periods of timeslots, each having at least one timeslot occupied by a respective header and identifier segment received from each of transmitters 14<sub>A</sub>-14<sub>D</sub> in a round-robin manner. For example, as shown in Figure 4(d), each period of timeslots of the received common RF signal may have a first timeslot occupied by a header and identifier segment received from transmitter 14<sub>A</sub>, a second timeslot occupied by a header and identifier segment received from transmitter 14<sub>B</sub>, a third timeslot occupied by a header and identifier segment received from transmitter 14<sub>C</sub>, and a fourth timeslot occupied by a header and identifier segment received from transmitter 14<sub>D</sub>. Further, as shown, the respective signal segments from each of transmitters 14<sub>A</sub>-14<sub>D</sub> may have a phase shift relative to one another due to the differences in transmission times (and thus distances) between each of transmitters 14<sub>A</sub>-14<sub>D</sub> and mobile device 18. (While Figure 4(d) depicts the timeslots of the received common RF signal as being defined based on the signal segment received from transmitter 14<sub>A</sub>, it should be understood that the timeslots may alternatively be defined based on a signal segment received from one of transmitters 14<sub>B</sub>-14<sub>D</sub>.) Other examples are possible as well.

**[0057]** At step 38, mobile device 18 may capture data representing the received common RF signal. For instance, mobile device 18 may capture a timestamp of each rising and/or falling edge of the header and identifier segments. Other examples are possible as well. At step 40, mobile device 18 may also optionally report the captured data representing the received common RF signal to central server 20.

**[0058]** At step 42, based on the captured data representing the received common RF signal, mobile device 18 and/or central server 20 may discriminate between each respective RF signal that forms the received common RF signal. For instance, based on the captured data representing the received common RF signal, mobile device 18 and/or central server 20 may first identify the identifier segments of the received common RF signal. Mobile device 18 and/or central server 20 perform this identification in various manners. In one example, mobile device 18 and/or central server 20 may search for segments of the common drive signal that take the form of a bit pattern



in which each "1" bit is represented by plurality of cycles (e.g., 5) of a square wave having a frequency in an increased baseband range (e.g., 20 KHz to 100 KHz range) and each "0" bit is represented by a null signal. These segments may appear to mobile device 18 and/or central server 20 as time periods with a large number of captured data points. Other examples are possible as well. Based on these identifier segments and the known arrangement of timeslots, mobile device 18 and/or central server 20 may then discriminate between each respective timeslot in the common drive signal and thereby discriminate between each respective signal segment received in the common drive signal.

**[0059]** After discriminating between each respective timeslot and respective signal segment in the common drive signal, mobile device 18 and/or central server 20 may process the data representing the header segment in each respective timeslot to align the time base of mobile device 18 with the common time base of transmitters 14<sub>A</sub>-14<sub>D</sub>. For example, mobile device 18 and/or central server 20 may (a) slot the captured data points into modulus buckets, (b) identify the captured data points falling into the most popular modulus, and (c) perform a least squares fit on the identified captured data points to generate an accurate time base. Other examples are possible as well. In turn, mobile device 18 and/or central server 20 may use the aligned time base of mobile device 18 to accurately determine the pattern of the identifier segment in each respective signal segment, and thus identify which respective signal segment was output by which of transmitters 14<sub>A</sub>-14<sub>D</sub>. Other examples are possible as well.

**[0060]** At step 44, after discriminating between each respective RF signal that forms the received common RF signal, mobile device 18 and/or central server 20 may determine a relative phase shift value of each respective RF signal. For instance, in each period of timeslots, mobile device 18 and/or central server 20 may first identify one or more captured data points representing each respective identifier segment (e.g., a timestamp of a first rising edge of each identifier segment). Mobile device 18 and/or central server 20 may then define one identifier segment in the period as a reference identifier segment having a relative phase shift value of 0. For each given identifier segment in the period other than the reference identifier segment, mobile device 18 and/or central server 20 may then (a) calculate a first time difference between the given identifier segment and the reference identifier segment and (b) calculate a second time difference between the given identifier segment's timeslot and the reference identifier segment's timeslot (e.g., based on the known duration of timeslots). In turn, mobile device 18 and/or central server 20 may calculate the relative phase shift of the given identifier segment (and thus the given signal segment) with respect to the reference identifier segment (and thus the reference signal segment) as the time difference between the first and second calculated time differences. As mentioned above, Figure 4(d) illus-

trates the relative phase shift of the respective signal segment received from each of transmitters 14<sub>B</sub>-14<sub>D</sub> with respect to the signal segment received from transmitter 14<sub>A</sub>.

**[0061]** At step 46, after determining a relative phase shift value of each respective RF signal, mobile device 18 and/or central server 20 may use the relative phase shift values and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub> to determine a location of mobile device 18. For instance, based on the relative phase shift values, mobile device 18 and/or central server 20 may first calculate the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> using any technique now known or later developed. In turn, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub>, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 using any technique now known or later developed (e.g., multilateration). For example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within indoor environment 22, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the indoor environment (e.g., local coordinates). As another example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within a global environment, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the global environment (e.g., geographic coordinates). Other examples are possible as well.

**[0062]** At step 48, if mobile device 18 determines its location, mobile device 18 may also report the determined location to central server 20. At step 50, central server 20 may then store the determined location of mobile device 18 for future reference.

#### C. Third Embodiment

**[0063]** A third embodiment of exemplary method 30 begins at step 32 with CSS 12 driving each of transmitters 14<sub>A</sub>-14<sub>D</sub> to output a respective RF signal on a common time basis and a different carrier frequency. For instance, CSS 12 may be generating a separate drive signal for each of transmitters 14<sub>A</sub>-14<sub>D</sub>, with each drive signal having a different frequency. Each separate drive signals may take various forms. For example, each separate drive signal may be a sinusoidal wave having a frequency in the long-wave band range (e.g., 148.5 KHz to 283.5 KHz). Other examples are possible as well. CSS 12 will preferably select the different frequencies such that each separate drive signal includes an integral number of cycles during a commonly-defined duration. For example, as shown in Figure 5, CSS 12 may generate separate drive signals having frequencies of 250, 225, 200, and 175 KHz respectively, such that each separate drive sig-

nal includes an integral number of cycles (10, 9, 8, and 7 respectively) during a 40 microsecond window. Other examples are possible as well.

**[0064]** CSS 12 may then be outputting a separate drive signal to each of transmitters 14<sub>A</sub>-14<sub>D</sub>. In this respect, CSS 12 may be delaying the output of the separate drive signal to at least one of transmitters 14<sub>A</sub>-14<sub>D</sub>, to ensure that all of transmitters 14<sub>A</sub>-14<sub>D</sub> receive these signals on a common time basis. For instance, CSS 12 may be delaying the output of the separate drive signal to each of transmitters 14<sub>A</sub>-14<sub>D</sub> in an amount that is inversely proportional to the length of the transmitter's link (e.g., zero or minimum delay for the longest link and maximum delay for the shortest link). Other examples are possible as well. As a result of CSS 12 outputting a separate drive signal to each of transmitters 14<sub>A</sub>-14<sub>D</sub>, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may then be receiving the a separate drive signal on a common time basis.

**[0065]** At step 34, each of transmitters 14<sub>A</sub>-14<sub>D</sub> may be outputting a respective RF signal on a common time basis and a different frequency. For instance, each of transmitters 14<sub>A</sub>-14<sub>D</sub> maybe outputting its separate drive signal as an unmodulated or modulated RF signal on a respective carrier frequency. Other examples are possible as well.

**[0066]** At step 36, mobile device 18 maybe receiving a respective RF signal from each of transmitters 14<sub>A</sub>-14<sub>D</sub> on a different carrier frequency. For example, mobile device 18 may receive a first RF signal from transmitter 14<sub>A</sub> on a first frequency, a second RF signal from transmitters 14<sub>B</sub> on a second frequency, a third RF signal from transmitter 14<sub>C</sub> on a third frequency, and a fourth RF signal from transmitter 14<sub>D</sub> on a fourth frequency. Other examples are possible as well.

**[0067]** At step 38, mobile device 18 may capture data representing the respective RF signal from each of transmitters 14<sub>A</sub>-14<sub>D</sub>. For instance, mobile receiver 18 may simultaneously capture a signal strength value of each respective RF signal at a given sampling rate (e.g., 50 MHz) during a given duration (e.g., a 44 microsecond window). Other examples are possible as well. At step 40, mobile device 18 may also optionally report the captured data representing the received common RF signal to central server 20.

**[0068]** At step 42, mobile device 18 and/or central server 20 may discriminate between each respective RF signal based on the respective carrier frequency of each respective RF signal. In turn, at step 44, mobile device 18 and/or central server 20 may determine a relative phase shift value of each respective RF signal. For instance, mobile device 18 and/or central server 20 may first fit sine waves to the data representing each respective RF signal (e.g., using a sliding correlator algorithm). Mobile device 18 and/or central server 20 may then define one respective RF signal as a reference signal having a relative phase shift value of 0. (Mobile device 18 and/or central server 20 may also use the reference signal to align the time base of mobile device 18 with the common

time base of transmitters 14<sub>A</sub>-14<sub>D</sub>). For each respective RF signal other than the reference signal, mobile device 18 and/or central server 20 may then calculate a first phase difference between the respective RF signal and the reference signal and (b) calculate a second phase difference between the respective RF signal's carrier frequency and the reference signal's carrier frequency. In turn, mobile device 18 and/or central server 20 may calculate the relative phase shift of the respective RF signal with respect to the reference signal as the difference between the first and second calculated phase differences. Other examples are possible as well.

**[0069]** At step 46, after determining a relative phase shift value of each respective RF signal, mobile device 18 and/or central server 20 may use the relative phase shift values and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub> to determine a location of mobile device 18. For instance, based on the relative phase shift values, mobile device 18 and/or central server 20 may first calculate the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> using any technique now known or later developed. In turn, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location(s) of each of transmitters 14<sub>A</sub>-14<sub>D</sub>, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 using any technique now known or later developed (e.g., multilateration). For example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within indoor environment 22, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the indoor environment (e.g., local coordinates). As another example, based on the absolute distances between mobile device 18 and each of transmitters 14<sub>A</sub>-14<sub>D</sub> and the known location of each of transmitters 14<sub>A</sub>-14<sub>D</sub> within a global environment, mobile device 18 and/or central server 20 may calculate the location of the mobile device 18 within the global environment (e.g., geographic coordinates). Other examples are possible as well.

**[0070]** At step 48, if mobile device 18 determines its location, mobile device 18 may also report the determined location to central server 20. At step 50, central server 20 may then store the determined location of mobile device 18 for future reference.

#### IV. Alternatives

**[0071]** The systems and methods described above are directed to determining a location of a mobile device within an indoor environment. It should be understood, however, that the techniques described herein are not limited to any particular environment, and are thus equally applicable to determining a location of a mobile device in an outdoor or other environment.

**[0072]** The logic, data, software, or instructions for implementing the systems, processes, methods and/or

techniques discussed above are provided on computer-readable storage media or memories or other tangible media, such as a cache, buffer, RAM, removable media, hard drive, other computer readable storage media, or any other tangible media. The tangible media include various types of volatile and nonvolatile storage media. The functions, acts, steps, or tasks illustrated in the figures or described herein are executed in response to one or more sets of logic or computer-executable instructions stored in or on computer readable storage media. The functions, acts or tasks are independent of the particular type of instructions set, storage media, processor or processing strategy and may be performed by software, hardware, integrated circuits, firmware, micro code and the like, operating alone or in combination. Likewise, processing strategies may include multiprocessing, multitasking, parallel processing and the like. In one embodiment, the instructions are stored on a removable media device for reading by local or remote systems. In other embodiments, the logic or instructions are stored in a remote location for transfer through a computer network or over telephone lines. In yet other embodiments, the logic or instructions are stored within a given computer, central processing unit ("CPU"), and/or graphics processing unit ("GPU") or system.

**[0073]** It is intended that the foregoing detailed description be regarded as illustrative rather than limiting and that it is understood that the following claims including all equivalents are intended to define the scope of the invention.

## Claims

1. A method of determining a location of a mobile device, the method comprising:

receiving, into a mobile device, a common RF signal on a common carrier frequency, wherein the common RF signal includes a respective RF signal output by each of three or more transmitters on a common time basis in a round-robin manner, and wherein each of the three or more transmitters is positioned at a known location;  
capturing data representing the common RF signal;  
based on the captured data, discriminating between each respective RF signal that forms the received common RF signal;  
determining a relative phase shift of each respective RF signal; and  
determining the location of the mobile device based on the determined relative phase shifts and the known locations of the three or more transmitters.

2. The method of claim 1, wherein the common RF sig-

nal comprises repeating periods of timeslots, and wherein each period of timeslots includes at least one timeslot occupied by a respective signal segment output by each of the three or more transmitters in a round-robin manner.

3. The method of claim 2, wherein each period of timeslots further includes at least one unoccupied timeslot that distinguishes the period of timeslots from an adjacent period of timeslots.
4. The method of claim 2, wherein each respective signal segment comprises an integral number of cycles of a periodic signal.
5. The method of claim 2, wherein each respective signal segment comprises a header segment and an identifier segment that uniquely identifies one of the three or more transmitters.
6. The method of claim 1, wherein capturing the data representing the common RF signal comprises capturing a timestamp of each zero-crossing of the common RF signal.
7. The method of claim 1, wherein capturing the data representing the common RF signal comprises capturing a timestamp of each edge of the common RF signal.
8. The method of claim 1, wherein discriminating between each respective RF signal that forms the received common RF signal comprises identifying which of the respective RF signals was output by which of the three or more transmitters.
9. The method of claim 1, wherein determining the location comprises the mobile device determining the location, the method further comprising:  
the mobile device reporting the determined location to a server.
10. The method of claim 1, further comprising the mobile device reporting the captured data to a server, wherein determining the relative phase shift of each respective RF signal comprises the server determining the relative phase shift of each respective RF signal, and wherein determining the location comprises the server determining the location.
11. The method of claim 1, wherein the location of the mobile device comprises one or both of a local coordinate and a geographic coordinate.
12. A system configured to determine a location of a mobile device, the system comprising:

a common signal source (CSS); and  
three or more transmitters coupled to the CSS  
via a respective link, wherein each of the three  
or more transmitters are positioned at a known  
location, wherein the CSS is configured to drive  
the three or more transmitters to output a re-  
spective radio frequency (RF) signal on a com-  
mon time basis and a common carrier frequency  
in a round-robin manner, and wherein the three  
or more transmitters are configured to output a  
respective RF signal on a common time basis  
and a common carrier frequency in a round-robin  
manner, and  
wherein data representing a common RF signal  
on the common carrier frequency is received via  
a mobile device, wherein the common RF signal  
includes the respective RF signal output by each  
of the three or more transmitters, wherein, based  
on the received data, each respective RF signal  
that forms the received common RF signal is  
discriminated, wherein a relative phase shift of  
each respective RF signal is determined, and  
wherein the location of the mobile device is de-  
termined based on the determined relative  
phase shifts and the known locations of the three  
or more transmitters.

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3(a)




FIG. 3(b)




FIG. 3(c)




FIG. 3(d)






FIG. 4(a)




FIG. 4(b)




FIG. 4(c)





FIG. 4(d)



**FIG. 5**



## EUROPEAN SEARCH REPORT

Application Number  
EP 11 17 4476

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 3 150 372 A (GROTH JR EDWARD J) 22 September 1964 (1964-09-22) * column 2, line 39 - line 45 * * column 2, line 49 - line 51 * * column 3, line 5 - line 10 * * column 3, line 15 - line 20 * * column 3, line 29 - line 31 * * figure 1 * -----	1-12	INV. G01S5/10 G01S5/14
			TECHNICAL FIELDS SEARCHED (IPC)
			G01S
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 9 November 2011	Examiner Renaudie, Cécile
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

2

EPO FORM 1503 03.02 (P04C01)

09-11-2011

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3150372 A	22-09-1964	GB 893401 A	11-04-1962
-----			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82