



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 30

(51) Int Cl.:
H04L 29/08 (2006.01)

(48) Corrigendum issued on:
01.08.2012 Bulletin 2012/31

(43) Date of publication:
02.05.2012 Bulletin 2012/18

(21) Application number: **12000284.5**

(22) Date of filing: **05.12.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

(30) Priority: **06.12.2007 US 952074**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
08170883.6 / 2 075 991

(71) Applicant: **Wyse Technology Inc.**
San Jose, CA 95134-1803 (US)

(72) Inventors:
• **Barreto, Daniel Ernesto**
San Francisco
CA 94114 (US)

• **Niranjanmurthy, Jayadev Marulappa**
Bangalore
PIN 560038
Karnataka (IN)
• **Wang, Shishuang**
100035 Beijing (CN)
• **Seetharamaiah, Sriranga**
Karnataka
PIN 570023 (US)

(74) Representative: **Müller-Boré & Partner**
Patentanwälte
Grafinger Straße 2
81671 München (DE)

Remarks:

This application was filed on 18-01-2012 as a divisional application to the application mentioned under INID code 62.

(54) **Local device redirection**

(57) The present application relates to a system (180) and a method for utilizing a device (120) of a remote system (110). The system (180) for utilizing a device (120) of a remote system (110) may comprise: an agent (170) configured to communicate with a remote access module (175), the remote access module (175) configured to establish a remote access connection (140) between a system (180) and a remote system (110), the agent (170) configured to provide socket connection information to the remote access module (175) to allow a local device (120) of the remote system (110) to be redirected to the system (180), the agent (175) configured to provide over a socket connection (150) to the remote system (110) at

least one device transaction designated for the local device (120) of the remote system (110), wherein the local device (120) is remote from the system (180).

Figure 1

