



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
29.08.2012 Bulletin 2012/35

(51) Int Cl.:
H01H 83/14 (2006.01) H01H 69/01 (2006.01)

(21) Application number: **12151239.6**

(22) Date of filing: **16.01.2012**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(71) Applicant: **LSIS Co., Ltd.**
Dongan-gu, Anyang-si
Gyeonggi-do 431-080 (KR)

(72) Inventor: **Ham, Seung Jin**
361-300 Chungbuk (KR)

(30) Priority: **25.02.2011 KR 20110016865**


(74) Representative: **Melin Granberg, Linda**
Groth & Co KB
P.O. Box 6107
102 32 Stockholm (SE)

(54) **Circuit breaker**

(57) A circuit breaker is disclosed, wherein the circuit breaker according to an exemplary embodiment of the present disclosure includes a permanent magnet (100)

rotatably hinged to a yoke (200), and wherein the permanent magnet is changed in magnetic path direction thereof by rotation to set up a sensitivity current, whereby a defect ratio of product is minimized.

FIG. 4



Description

[0001] This application claims the benefit of earlier filing date and right of priority to Korean Patent Application No.10-2011-0016865, filed on February 25, 2011, the contents of which is hereby incorporated by reference in their entirety.

BACKGROUND OF THE DISCLOSURE

Field

[0002] The present disclosure relates to a circuit breaker, and more particularly to a circuit breaker configured to be installed at a wiring.

Background

[0003] Generally, a circuit breaker is a power device for detecting an abnormal current to automatically break the circuit, thereby protecting life, an electrical load device, and a circuit from an accident current in a power supply circuit between the power source and the load, when the abnormal current such as an over current, an electric shortage current, or the like is generated in the circuit. The circuit breaker is compulsorily installed on a wiring at a house and a factory, for example.

[0004] The circuit breaker may be categorized into two types based on operation method, that is, an electronic circuit breaker that operates using a leakage detecting chip, and a circuit breaker in which a trip coil is directly connected to a secondary winding of a ZCT (Zero-phase Current Transformer), where the latter is largely used.

[0005] FIG.1 is a lateral view illustrating a trip coil assembly of a circuit breaker according to prior art, and FIG.2 is a perspective view illustrating a trip coil assembly of a circuit breaker according to prior art.

[0006] The trip coil assembly according to the conventional circuit breaker includes a permanent magnet (10), a yoke (20) forming a magnetic path of a magnetic field induced by the permanent magnet (10), a bracket (30) mounted on the yoke (20) to fix the yoke (20) to the permanent magnet (10), a lever (40) contacted to one side of the yoke (20) to release a connection with a mechanism of the circuit breaker, a trip coil (50) directly connected to a secondary winding of a ZCT, and a spring (60) mounted on the bracket (30) and connected to the lever (40) to provide elasticity to the lever (40).

[0007] Now, operation of the conventional circuit breaker will be described.

[0008] A current in proportion to a leakage current flows in the trip coil (50) connected to the secondary winding of the ZCT when a leakage occurs, a magnetic field formed by the permanent magnet (10) is offset by an AC magnetic field generated thereby, and the lever (40) is activated the moment the magnetic field is offset to activate the circuit breaker in response to operation of a device connected to the mechanism.

[0009] The circuit breaker thus described is such that the energy of the permanent magnet (10) is very small, because the magnetic field of the permanent magnet (10) is offset by using a current of several milliampere flowing in the secondary winding of the ZCT in case a leakage occurs. Generally, the force by the conventional permanent magnet (i.e., the energy) is obtained by multiplication by coercivity (Hc) and residual magnetic flux density (Br), which is BH characteristic.

[0010] In case products are mass-manufactured corresponding to respectively different sensitivity currents, for example, in case the sensitivity currents are 30mA, 100mA and 300mA, an energy intensity of a permanent magnet with a sensitivity current of 300mA is generally greater than that of a permanent magnet with a sensitivity current of 30mA.

[0011] A demagnetization method is representatively used for setting up an energy intensity of a permanent magnet. The demagnetization method is a method in which an AC current-flowing electronic magnet is made to approach a vicinity of an assembled RCCB (Residual-Current Circuit Breaker) to demagnetize the intensity of the permanent magnet assembled inside the RCCB.

[0012] However, the demagnetization method thus described is disadvantageously problematic in that a desired sensitivity current value can be obtained only through several repeated performances of demagnetization, because an accurate demagnetization is not obtainable by a one-time process, and a remagnetization process must be added for over-magnetized products caused by erroneous operation of an operator, thereby complicating the work and lengthening the work time.

SUMMARY

[0013] The present disclosure has been made to solve the foregoing problems of the prior art and therefore an object of certain embodiments of the present invention is to provide a circuit breaker configured to minimize a defect ratio of a product, to simplify work processes and to remarkably reduce working hours by changing a magnetic path (magnetization) direction of a permanent magnet assembled on a yoke of a trip coil to perform a sensitivity set-up of the permanent magnet.

[0014] In one general aspect of the present disclosure, there is provided a circuit breaker, comprising: a yoke forming a magnetic path of magnetic field; a trip coil mounted at a bottom surface of the yoke and directly connected to a secondary winding of a ZCT (Zero-phase Current Transformer); a lever arranged at one side of the yoke to trip a mechanism of the circuit breaker; a spring connected to the lever to provide an elasticity to the lever; and a permanent magnet rotatably hinged to the other side of the yoke, wherein the permanent magnet is changed in magnetic path direction by the rotation to set up a sensitivity current.

[0015] The circuit breaker according to the present disclosure is advantageous in that defect ratio of product is

minimized by allowing a yoke to include a rotatably-hinged permanent magnet, and changing a magnetic path direction by rotation of the permanent magnet to set up a sensitivity current.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The accompanying drawings, which are included to provide a further understanding of the disclosure and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the disclosure and together with the description serve to explain the principle of the disclosure. In the drawings:

FIG. 1 is a lateral view illustrating a trip coil assembly of a circuit breaker according to prior art;
 FIG. 2 is a perspective view illustrating a trip coil assembly of a circuit breaker according to prior art;
 FIG. 3 is a perspective view illustrating an interior of a trip coil assembly in a circuit breaker according to an exemplary embodiment of the present disclosure;
 FIG. 4 is a partially cutaway perspective view of a trip coil assembly in a circuit breaker according to an exemplary embodiment of the present disclosure;
 FIG. 5 is a perspective view illustrating a trip coil assembly in a circuit breaker according to an exemplary embodiment of the present disclosure;
 FIG. 6 is a schematic view illustrating a simplified permanent magnet, a simplified yoke and a simplified lever according to an exemplary embodiment of the present disclosure;
 FIG. 7 is a graph illustrating a change of magnetic field advancing direction based on magnetization direction of a permanent magnet according to an exemplary embodiment of the present disclosure;
 FIG. 8 is a schematic view illustrating a yoke based on a magnetization direction of a permanent magnet and an intensity distribution of a magnetic field flowing in a lever according to an exemplary embodiment of the present disclosure; and
 FIG. 9 is a table showing an intensity change of a force of a lever based on a magnetization direction of a permanent magnet according to an exemplary embodiment of the present disclosure.

DETAILED DESCRIPTION

[0017] The disclosed embodiments and advantages thereof are best understood by referring to FIGS. 1-9 of the drawings, like numerals being used for like and corresponding parts of the various drawings. Other features and advantages of the disclosed embodiments will be or will become apparent to one of ordinary skill in the art upon examination of the following figures and detailed description. It is intended that all such additional features and advantages be included within the scope of the disclosed embodiments, and protected by the accompanying drawings. Further, the illustrated figures are only ex-

emplary and not intended to assert or imply any limitation with regard to the environment, architecture, or process in which different embodiments may be implemented. Accordingly, the described aspect is intended to embrace all such alterations, modifications, and variations that fall within the scope and novel idea of the present invention.

[0018] Meanwhile, the terminology used herein is for the purpose of describing particular implementations only and is not intended to be limiting of the present disclosure. The terms "first," "second," and the like, herein do not denote any order, quantity, or importance, but rather are used to distinguish one element from another. For example, a second constituent element may be denoted as a first constituent element without departing from the scope and spirit of the present disclosure, and similarly, a first constituent element may be denoted as a second constituent element.

[0019] As used herein, the terms "a" and "an" herein do not denote a limitation of quantity, but rather denote the presence of at least one of the referenced item. That is, as used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[0020] It will be understood that when an element is referred to as being "connected" or "coupled" to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being "directly connected" or "directly coupled" to another element, there are no intervening elements present.

[0021] It will be further understood that the terms "comprises" and/or "comprising," or "includes" and/or "including" when used in this specification, specify the presence of stated features, regions, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components, and/or groups thereof.

[0022] Also, "exemplary" is merely meant to mean an example, rather than the best. It is also to be appreciated that features, layers and/or elements depicted herein are illustrated with particular dimensions and/or orientations relative to one another for purposes of simplicity and ease of understanding, and that the actual dimensions and/or orientations may differ substantially from that illustrated.

[0023] That is, in the drawings, the size and relative sizes of layers, regions and/or other elements may be exaggerated or reduced for clarity. Like numbers refer to like elements throughout and explanations that duplicate one another will be omitted.

[0024] Now, a circuit breaker according to an exemplary embodiment of the present disclosure will be described in detail with reference to the accompanying drawings.

[0025] FIG. 3 is a perspective view illustrating an interior of a trip coil assembly in a circuit breaker according to an exemplary embodiment of the present disclosure, FIG. 4 is a partially cutaway perspective view of a trip coil

assembly in a circuit breaker according to an exemplary embodiment of the present disclosure, and FIG.5 is a perspective view illustrating a trip coil assembly in a circuit breaker according to an exemplary embodiment of the present disclosure.

[0026] A circuit breaker according to an exemplary embodiment of the present disclosure includes a permanent magnet (100), a yoke (200) rotatably hinged to the permanent magnet (100) to form a magnetic path of magnetic field formed by the permanent magnet, a trip coil (300) mounted at the yoke (200) to be directly connected to a secondary winding of a ZCT (Zero-phase Current Transformer), a lever (400) arranged at one side of the yoke (200) to trip a mechanism of the circuit breaker, and a spring (500) connected to the lever (400) to provide an elasticity to the lever (400).

[0027] The permanent magnet (100) takes a round shape having a predetermined thickness, one lateral surface of one side of the permanent magnet (100) being rotatably hinged to the yoke (200) and one lateral surface of the other side of the permanent magnet (100) having a tool insertion groove (110) for rotating the permanent magnet (100) using a separate tool to change a magnetization direction (magnetic path direction) of the permanent magnet (100).

[0028] In one non-limiting example, the tool insertion groove (110) takes a straight shape, and may be used with a flat-head screwdriver for changing the magnetization direction. However, the tool is not limited to the flat-head screwdriver, and any type of screwdriver may be used.

[0029] The yoke (200) is secured at an upper surface thereof with a bracket (210) using a rivet (220), rotatably mounted at a lateral surface thereof with the permanent magnet (100), mounted at a bottom surface with the trip coil (300) and arranged at an opposite side of the lateral surface arranged with the permanent magnet (100) with the lever (400). The bracket (210) is secured at one side to a distal end of the spring (500), and rotatably supported at the other side by the lever (400).

[0030] Furthermore, the lever (400) is rotatably supported by the bracket (210), and trips the circuit breaker by being rotated by elasticity of the spring (500), in a case a current flows to the trip coil (300) to offset the magnetic field formed by the permanent magnet (100).

[0031] An external side of the yoke (200) is mounted with a molded case (600) for preventing foreign objects such as dust from entering the yoke (200), and a lateral surface formed with the permanent magnet (100) is arranged with a cover (610) secured to the case (600) to wrap the permanent magnet.

[0032] The cover (610) is provided with a tool path (620) through which a tool passes whereby the tool can be inserted into the insertion groove (110) of the permanent magnet (100).

[0033] The circuit breaker according to the exemplary embodiment of the present disclosure is advantageous in that working hours setting up a sensitivity current of

the permanent magnet (100) can be drastically reduced, and product defect caused by over-demagnetization or insufficient demagnetization can be prevented by rotating the permanent magnet (100) to change magnetization direction (magnetic path direction) of the permanent magnet (100) and to set up a sensitivity current.

[0034] Next, a setting method of sensitivity current in response to rotation of a permanent magnet will be described.

[0035] FIG.6 is a schematic view illustrating a simplified permanent magnet, a simplified yoke and a simplified lever according to an exemplary embodiment of the present disclosure, and FIG.7 is a graph illustrating a change of magnetic field advancing direction based on magnetization direction of a permanent magnet according to an exemplary embodiment of the present disclosure.

[0036] Referring to FIG.6, in a case a magnetization direction of the permanent magnet is an X axis while position of the permanent magnet (100) is set up by an X axis, a Y axis, and a Z axis, θ is 90° , and θ is 0° in a case the magnetization direction of the permanent magnet is Y axis. The magnetic path direction of the permanent magnet varies depending on position of the permanent magnet.

[0037] That is, in a case θ is 0° , the magnetic path direction of the permanent magnet is distributed as shown in A to be horizontal with Y axis, and in a case a tool is inserted into the tool insertion groove (110) of the permanent magnet (100) to rotate the permanent magnet (100) to a predetermined degree to make θ 30° , the magnetic path direction of the permanent magnet (100) is distributed as shown in B to form an angle with Y axis at 30° .

[0038] In a case the permanent magnet (100) is rotated to make θ 45° , the magnetic path direction of the permanent magnet (100) is distributed as shown in C to form an angle with Y axis at 45° . In a case the permanent magnet (100) is rotated to make θ 60° , the magnetic path direction of the permanent magnet (100) is distributed as shown in D to form an angle with Y axis at 60° . In a case the permanent magnet (100) is rotated to make θ 90° , the magnetic path direction of the permanent magnet (100) is distributed as shown in E to form an angle with Y axis at 90° .

[0039] As noted above, the magnetic path directions are changed depending on rotational angle of the permanent magnet, and intensity of the permanent magnet applied to the lever (400) is changed, as the magnetic path direction of the permanent magnet is changed.

[0040] That is, as shown in FIG. 8, if the intensity of force of the permanent magnet applied to the lever is measured in response to change in θ value, it can be noticed that magnetic field flowing in the yoke (200) and the lever (400) is least distributed in a case θ is 0° , distribution of magnetic field flowing in the yoke (200) and the lever (400) gradually increases as θ the value increases, and distribution of magnetic field flowing in the yoke

(200) and the lever (400) becomes maximum when θ is 90° .

[0041] Furthermore, as illustrated in FIG. 9, it can be noted that the intensity of force acting on the lever gradually increases as the θ value increases when the intensity of force acting on the lever is measured in response to the change of the θ value.

[0042] As apparent from the foregoing, the circuit breaker according to the present disclosure has an industrial applicability in that a defect ratio of a product can be minimized and work processes can be simplified because of enablement of sensitivity current set-up in a permanent magnet by rotating the permanent magnet to change the magnetic path (magnetization) direction of a permanent magnet.

[0043] Although the present disclosure has been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure.

[0044] More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

Claims

1. A circuit breaker in which a secondary winding of a ZCT(Zero-phase Current Transformer) is directly connected to a trip coil, the circuit breaker **characterized by**: a yoke forming a magnetic path of magnetic field; the trip coil mounted at a bottom surface of the yoke; a lever arranged at one side of the yoke to trip a mechanism of the circuit breaker; a spring connected to the lever to provide an elasticity to the lever; and a permanent magnet rotatably hinged to the other side of the yoke, wherein the rotation of the permanent magnet changes magnetic path direction to set up a sensitivity current.
2. The circuit breaker of claim 1, **characterized in that** an upper surface of the yoke is secured by a bracket and one side of the bracket rotatably supports the lever.
3. The circuit breaker of claim 2, **characterized in that** the other side of the bracket is secured by one side of the spring.
4. The circuit breaker of claims 1 to 3, **characterized in that** the permanent magnet is rotatably hinged to a lateral surface of the other side of the yoke.

5. The circuit breaker of claims 1 to 4, **characterized in that** the permanent magnet has a tool insertion groove in a predetermined shape.

6. The circuit breaker of claims 1 to 5, further **characterized by** a cover wrapping the permanent magnet.

7. The circuit breaker of claim 6, **characterized in that** the cover is provided with a tool path.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

θ	Force[N]
90°	0.114
60°	0.088
45°	0.06
30°	0.032
0°	0.002



EUROPEAN SEARCH REPORT

Application Number
EP 12 15 1239

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	WO 79/00105 A1 (GATH N) 8 March 1979 (1979-03-08) * abstract; figure 4 * -----	1-7	INV. H01H83/14 H01H69/01
A	US 3 806 845 A (ZUBATY M ET AL) 23 April 1974 (1974-04-23) * column 4, lines 27-29 * -----	1	
			TECHNICAL FIELDS SEARCHED (IPC)
			H01H
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 29 May 2012	Examiner Simonini, Stefano
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

2

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 12 15 1239

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-05-2012

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 7900105	A1	08-03-1979	DE 2860745 D1 10-09-1981
			EP 0006894 A1 23-01-1980
			IT 1098158 B 07-09-1985
			JP 54053275 A 26-04-1979
			LU 78012 A1 09-04-1979
			WO 7900105 A1 08-03-1979

US 3806845	A	23-04-1974	NONE

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 1020110016865 [0001]